

18/03/2019Ansible Playbooks

ANSIBLE PLAYBOOKS

- Ansible Introduction
- Ansible Concepts
- ➔ Ansible Playbooks
- Plugins & Dynamic inventories
- Playbooks Advanced
- Ansible Roles
- AWX / Ansible Tower Overview

©2019 edc-4it B.V.

1

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

PLAYBOOK INTRODUCTION

©c) 2019 edc-4it B.V.

2.1

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

yaml

A PLAYBOOK IS TYPICALLY a
yaml FILE
SLIDE DECK

©c) 2019 edc-4it B.V.

2.2

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

A BOOK WITH PLAYS

EACH PLAY CONSISTS OF TASKS


©c) 2019 edc-4it B.V.

2.3

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

PLAY STRUCTURE



The diagram illustrates the structure of an Ansible play. On the left, a blue box labeled 'inventory' has a dashed arrow pointing to a stack of colored boxes representing the play's components: 'name' (green), 'hosts' (blue), 'users' (orange), 'variables' (cyan), 'tasks' (yellow), and 'handlers' (magenta). To the right of the 'tasks' and 'handlers' boxes are two green boxes labeled 'module', with arrows pointing from the 'tasks' and 'handlers' boxes to them respectively.

©c) 2019 edc-4it B.V.

2.4

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

BREAKDOWN OF SECTIONS

EXAMPLE

```
---  
- name: Configure Apache httpd  
  hosts: tv-series-web-servers  
  become: true  
  tasks:  
    - name: ensure https is at the latest version  
      package:  
        name: httpd  
        state: present  
    ...  
  - name: ensure apache is running  
    service:  
      name: httpd  
      state: started
```

©c) 2019 edc-4it B.V.

2.5

©c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

MULTIPLE PLAYS

```
---  
- name: Configure Apache httpd  
  hosts: tv-series-web-servers  
  become: true  
  tasks:  
  ...  
- name: Configure Postgres  
  hosts: tv-series-db-servers  
  become: true  
  become_user: postgres  
  tasks:  
  ...
```

2.6

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

HOSTS

3.1

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

EXAMPLE

```
---  
- hosts: db-servers  
  ...
```

Will be ordered by *inventory*

3.2

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

SETTING ORDERING

```
---  
- hosts: db-servers  
  order:  
  ...  
    inventory, reverse_inventory, sorted, reverse_sorted, shuffle
```

3.3

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

GATHERING FACTS

```
---  
- hosts: db-servers  
  gather_facts: false  
  ...
```

By default *true/yes*

3.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

TASKS

4.1

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

A Play contains one or more tasks

a named call to a module
with arguments

4.2

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

TASK LIST

- in order
- one-at-a-time for all machines
- then proceed to next task

This behaviour can be changed through strategies (explained later)

4.3

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

Failures

machines with failed tasks
are taken out of rotation

Errors can be managed (explained later)

4.4

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

EXAMPLE

```
tasks:
- name: Ensure docker is installed
  package:
    name: {{docker_package_name}}
- name: make sure docker is restarted and enabled
  service:
    name: docker
    state: restarted
    enabled: true
```

4.5

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

MODULES OVERVIEW

5.1

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

categories

- Cloud modules
- Clustering modules
- Commands modules
- Crypto modules
- Database modules
- Files modules
- Identity modules
- Inventory modules
- Messaging modules
- Monitoring modules
- Net Tools modules
- Network modules
- Notification modules
- Packaging modules
- Remote Management modules
- Source Control modules
- Storage modules
- System modules
- Utilities modules
- Web Infrastructure modules
- Windows modules

5.2

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

GETTING HELP on a
module
ANSIBLE-DOC

\$ ansible-doc ...

5.3

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command

```
- name: Ensure the database is initialised
command: "/usr/bin/initdb -u scott -encoding UTF-8 -n recipesdb"
args:
  chdir: /var/db/
  creates: /var/db/recipesdb # to make this task idempotent
```

uses *Free Form* syntax for the
command (and hence the args)

5.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

SHELL
runs in a SHELL (/bin/sh)

```
- name: Ensure security tokens are removed
shell: "$HOME/cleanup.sh"
args:
  removes: /etc/credentials/
```

Also uses *freeform*

5.5

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

INSTALLING SOFTWARE
calls yum, DNF, apt, ...

```
- name: Ensure docker is installed
package:
  name: {{docker_package_name}}
  state: present # (set to absent to uninstall)
```

Also available: [apt](#), [yum](#), [yumdnf](#) ...

5.6

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

INSTALLING SOFTWARE
using a LIST

```
- name: Ensure docker is installed
package:
  name:
    - docker
    - docker-compose
  state: present
```

5.7

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

service module

```
- name: make sure docker is running and enabled
service:
  name: docker
  state: started
  enabled: true
```

Uses `ansible_service_mgr` fact (systemd, systemctl, service, ...)

5.8

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

Non OS Package Modules

- bower
- bundler
- composer
- cpanm
- easy_install
- gems
- maven_artifact
- npm/yarn
- pear
- pip

5. 9

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

FILE MODULES

overview

- archive
- blockinfile
- copy
- fetch
- file
- find
- ini_file
- lineinfile
- patch
- replacein
- stat
- synchronize
- tempfile
- template
- unarchive
- xml
- ...

5. 10

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

COPY FILES/DIRECTORIES

```
- name: ensure index page is there
copy:
  src: resources/index.html
  dest: /var/www/html
  owner: www
  group: www
  mode: 0644
```

5. 11

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

ENSURING LINES IN FILES

```
tasks:
- lineinfile:
  path: /etc/httpd/conf/httpd.conf
  regexp: '^#Listen '
  line: 'Listen 8080'
- lineinfile:
  path: /etc/sudoers
  state: absent
  regexp: '^%wheel
```

5. 12

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

BLOCK IN FILES

```
- name: Ensure proxy set for npm
blockinfile:
  path: "{{ ansible_env.HOME }}/.npmrc"
  block: |
    proxy={{proxy_address}}
    https-proxy={{proxy_address}}
  marker: '# (mark) proxy settings'
  create: yes
  insertbefore: BOF
```

Often in conjunction with yaml [literal style](#) multi-line scalar (|)

5. 13

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

creating users/groups

```
tasks:
- name: Ensure the jboss group exists
  group:
    name: postgres
    state: present
- name: Ensure jboss user is available
  user:
    name: jboss
    group: jboss
    home: /opt/jboss/
    password: 14415186a0c9969c0229p7yee7j0p4k40kq00W01dsewfc41u0Qp0h111110u0_0ue70y0h0u00_0d070u0u00000000_0hu1100ue0701
    append: true
```

Password needs to be salted (see next slide)

5. 14

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

PASSWORD

Hashing

```
$ mkpasswd --method=sha-512
Password:
$6$789Wac0ggFv0s2p7ykwVj02pakk806rG6NDt8awvK41uKqr8h1z18YuK.qxw7EzYXkmoNG.u32U3tzccKDDHQLj2hiibdaq7Yj1
```

or use PYTHON (example is PYTHON3)

```
$ python -c 'import crypt,getpass; \
print(crypt.crypt(getpass.getpass(), \
crypt.mksalt(crypt.METHOD_SHA512))) '
```

For python make sure `passlib` is installed

5.15

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

IDENTITY & PRIVILEGE

escalation

6.1

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

overview

key	description
remote_user	SSH user
become	set to <code>yes</code> to escalate privilege
become_user	which user to <i>become</i> (root)
become_method	su, sudo, pbrun, ...
become_flags	parameters to the <code>become_method</code>

might be used in conjunction with `--ask-become-pass`

6.2

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

EXAMPLE

```
---
- hosts: webservers
  remote_user: admin
  become: yes
  become_user: www
```

6.3

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

can also be set on

TASKS

```
---
- hosts: webservers
  tasks:
    - service:
      name: nginx
      state: started
      become: yes
      become_method: sudo
```

6.4

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

DEFAULTS are set using

ansible.cfg

ini	env	default
become	ANSIBLE_BECOME	false
become_ask_pass	ANSIBLE_BECOME_ASK_PASS	false
become_flags	ANSIBLE_BECOME_FLAGS	' '
become_method	ANSIBLE_BECOME_METHOD	sudo
become_user	ANSIBLE_BECOME_USER	root

[`privilege_escalation`] section

6.5

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line OPTIONS

- --ask-become-pass,-K
- --become,-b
- --become-method=
- --become-user=

6.6

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

VARIABLES & FACTS IN PLAYBOOKS

7.1

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

VARIABLES IN PLAYBOOK

example (reCAP)

```
---
- hosts: all
  user: vagrant
  vars:
    host: proxy01.example.com
    port_no: 8443
    proxy_address: http://{{host}}:{{port_no}}
  tasks:
    - name: Ensure proxy set in .npmrc
      blockinfile:
        path: "/home/vagrant/.npmrc"
        block: |
          proxy={{proxy_address}}
          https-proxy={{proxy_address}}
      ...
```

7.2

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

external FILE

```
hosts: ...
vars_files:
  - vars/myvars.yaml
```

vars/myvars.yaml:

```
host: proxy01.example.com
port_no: 8443
proxy_address: http://{{host}}:{{port_no}}
```

7.3

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
...

```

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
...
$ ansible-playbook -e "env=localhost" playbook.yml
```

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
vars:
  port_no: 8443
...

$ ansible-playbook -e "env=localhost" playbook.yml
```

Can also use yaml/json

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
vars:
  port_no: 8443
...

$ ansible-playbook -e "env=localhost" playbook.yml
$ ansible-playbook -e "env=localhost"
-e "port_no=8080" playbook.yml
```

Can also use yaml/json

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
vars:
  port_no: 8443
...

$ ansible-playbook -e "env=localhost" playbook.yml
$ ansible-playbook -e "env=localhost"
-e "port_no=8080" playbook.yml
$ ansible-playbook -e "-e '{{ env: test-machines }}'" playbook.yml
```

Can also use yaml/json

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

command line

-e/--extra-vars

```
- hosts: "{{ { env } }}"
vars:
  port_no: 8443
...

$ ansible-playbook -e "env=localhost" playbook.yml
$ ansible-playbook -e "env=localhost"
-e "port_no=8080" playbook.yml
$ ansible-playbook -e "-e '{{ env: test-machines }}'" playbook.yml
$ ansible-playbook -e "@my-vars.json" playbook.yml
```

Can also use yaml/json

7.4

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

PROMPTING

```
- hosts: localhost
vars:
  proxy: http://{{username}}:{{password}}@{{host}}:{{port_no}}
...
vars_prompt:
- name: username
  prompt: "proxy username"
  private: no
- name: password
  prompt: "proxy password"
  private: yes
```

7.5

(c) 2019 edc-4it B.V.

18/03/2019Ansible Playbooks

REGISTER VARIABLES

```
tasks:
- command: /usr/sbin/ip route list 10.0.2.0/24
  register: routeValue
- debug:
  var: routeValue
```

7.6

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

SETTING FACTS

USING set_fact

```
tasks:
- command: whoami
  register: woami_result
- set_fact:
    user: "{{woami_result.stdout}}"
```

7.7

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

set_fact USING Jinja2 FUNCTIONS

```
tasks:
- command: /usr/sbin/ip route list 10.0.2.0/24
  register: route_result
- set_fact:
    route_ip: "{{route_result.stdout.split()[8]}}"
```

7.8

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

TROUBLESHOOTING

8.1

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

CHECK SYNTAX

--syntax-check

```
$ ansible-playbook --syntax-check test.yml
```

8.2

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

CHECK mode

-C/ --check

```
$ ansible-playbook --check mybook.yml
```

Like a *dry-mode*

8.3

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

DIFF

(TOGETHER WITH CHECK-MODE)

```
$ ansible-playbook --check --diff mybook.yml
```

...

8.4

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

DIFF

(TOGETHER WITH CHECK-MODE)

```
$ ansible-playbook --check --diff mybook.yml
```

```
...
TASK [Configure the server] *****
--- before: /etc/nginx/conf.d/server.conf (content)
+++ after:  /etc/nginx/conf.d/server.conf (content)
@@ -0,0 +1,6 @@
+# BEGIN ANSIBLE MANAGED BLOCK
+server {
+    listen 80;
+    location / {
+    }
+}
+# END ANSIBLE MANAGED BLOCK
```

8.4

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

VERBOSE MODE

```
$ ansible-playbook my-book.yaml --verbose
```

-v / --verbose, -vvv, -vvvv

8.5

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

DEBUG MODULE

```
- tasks:
- name: Initialise the database
  shell: initdb
  register: result
- debug:
  var: result
  verbosity: 3 # for -vvv, 0 by default
```

Or use msg with Jinja2 templates

8.6

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

STEPPING

one-STEP-at-a-TIME

```
$ ansible-playbook mybook.yaml --step
```

PLAY [mybook] task: TASK: Gathering Facts
(N) o / (y) es / (c) ontinue:

At the same time open a ssh connection to investigate

8.7

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

STEPPING

one-STEP-at-a-TIME

```
$ ansible-playbook mybook.yaml --step
```

PLAY [mybook] task: TASK: Gathering Facts
(N) o / (y) es / (c) ontinue: y

At the same time open a ssh connection to investigate

8.7

(c) 2019 edc-4it B.V.

18/03/2019

Ansible Playbooks

STEPPING

one-STEP-at-a-TIME

```
$ ansible-playbook mybook.yaml --step
```

PLAY [mybook] task: TASK: Gathering Facts
(N) o / (y) es / (c) ontinue: y
ok: [db-servers]
Perform task: TASK: Ensure database is installed
(N) o / (y) es / (c) ontinue: l

At the same time open a ssh connection to investigate

8.7

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

Make error messages easier to read

```
ANSIBLE_STDOUT_CALLBACK=yaml ansible-playbook mybook.yaml
```

Can also be set in `ansible.cfg` (`stdout_callback`)

More on this later

8.8

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

LAB 3

PLAYBOOKS

9

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

HANDLERS

10.1

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

PROBLEM

- certain tasks require an action afterwards
- tasks are idempotent
- so how do we know if we need to perform the action?
- what if many tasks require the same action (e.g., reload a service?)

10.2

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

HANDLERS

- Called zero or one time
- only when notified one or more times
- at the end of the block
- in the order they are defined

10.3

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

DEFINING HANDLERS

```
tasks:
- name: restart redis service
  service:
    name: redis
    state: restarted
- name: restart docker service
  service:
    name: docker
    state: restarted
```

10.4

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

TRIGGERING HANDLERS BY THEIR *name*

```
tasks:
- name: configure redis authentication
  ...
  notify: restart redis service
- name: enable redis store
  ...
  notify: restart redis service
handlers:
...
```

10.5

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

TRIGGERING HANDLERS USING *listen*

```
tasks:
- name: configure redis authentication
  ...
  notify: RESTART_REDIS
handlers:
- name: restart redis service
  service:
    name: redis
    state: restarted
  listen: RESTART_REDIS
```

Decouples from handler's name

10.6

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

TRIGGERING MULTIPLE HANDLERS;

```
tasks:
- name: configure redis authentication
  ...
  notify: RESTART_REDIS
handlers:
- name: restart redis service
  ...
  listen: RESTART_REDIS
- name: restart redis proxy
  ...
  listen: RESTART_REDIS
```

10.7

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

TRIGGERING ALL HANDLERS BEFORE BLOCK-END USING a *meta* statement

```
tasks:
- name: ...
  ...
- name: ...
  ...
- meta: flush_handlers
```

Triggers all notified handlers inside block so far

10.8

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

LAB 4 HANDLERS

11

(c) 2019 edc-4it B.V.

18/03/2019 Ansible Playbooks

DONE!

- [Ansible Introduction](#)
- [Ansible Concepts](#)
- [Ansible Playbooks](#)
- ➔ [Plugins & Dynamic inventories](#)
- [Playbooks Advanced](#)
- [Ansible Roles](#)
- [AWX / Ansible Tower Overview](#)

12

(c) 2019 edc-4it B.V.