Robi Teletalk 5:23 M

... / ahmedullah378.github.io

Code Issues Pull requests Actions Projects Wiki More

← Cloud Scanner

new_photo #12

Summary

Triggered via repository dispatch now

ahmedullah378 new_photo 6af2ec5

Status	Total duration	Artifacts
Failure	15s	–

scanner.yml

on: repository_dispatch

scan 12s

Annotations

1 error and 1 warning

scan

```
Process completed with exit code 1.
```

scan

```
Node.js 20 actions are deprecated. The following actions are running on Node.js 20 and may not work as expected: actions/checkout@v4. Actions will be forced to run with Node.js 24 by default starting June 2nd, 2026. Node.js 20 will be removed from the runner on September 16th, 2026. Please check if updated versions of these actions are available that support Node.js 24. To opt into Node.js 24 now, set the FORCE_JAVASCRIPT_ACTIONS_TO_NODE24=true environment variable on the runner or in your workflow file. Once Node.js 24 becomes the default, you can temporarily opt out by setting ACTIONS_ALLOW_USE_UNSECURE_NODE_VERSION=true. For more information see: https://github.blog/changelog/2025-09-19-deprecation-of-node-20-on-github-actions-runners/
```

Show less

Robi Teletalk 5:19 M

/ ahmedullah378.github.io

Code Issues Pull requests Actions Projects Wiki More

← Cloud Scanner

new_photo #11

Summary

Triggered via repository dispatch 1 minute ago

ahmedullah378 new_photo 69e77a7

Status	Total duration	Artifacts
Failure	21s	–

scanner.yml

on: repository_dispatch

scan 11s

Annotations

1 error and 1 warning

scan

```
Process completed with exit code 1.
```

scan

```
Node.js 20 actions are deprecated. The following actions are running on Node.js 20 and may not work as expected: actions/checkout@v4. Actions will be forced to run with Node.js 24 by default starting June 2nd, 2026. Node.js 20 will be removed from the runner on September 16th, 2026. Please check if updated versions of these actions are available that support Node.js 24. To opt into Node.js 24 now, set the FORCE_JAVASCRIPT_ACTIONS_TO_NODE24=true environment variable on the runner or in your workflow file. Once Node.js 24 becomes the default, you can temporarily opt out by setting ACTIONS_ALLOW_USE_UNSECURE_NODE_VERSION=true. For more information see: https://github.blog/changelog/2025-09-19-deprecation-of-node-20-on-github-actions-runners/
```

Show less

```
print("Checking Slack for documents...")
response = client.conversations_history(channel="C0B0LFFAHM5")

for msg in response["messages"]:
    if "files" in msg:
        file_info = msg["files"][0]
        print(f"Found: {file_info['name']}")
        trigger_github(file_info['url_private'], msg.get('user', 'Ahmed'))
        break
# ... (keep your tokens and imports)

def trigger_github(file_urls, user):
    url = "https://api.github.com/repos/ahmedullah378/ahmedullah378.github.io/dispatches"
    headers = {"Authorization": f"token {GITHUB_TOKEN}"}
    # Join all URLs into one string separated by commas
    payload = {
        "event_type": "new_photo",
        "client_payload": {"file_url": ",".join(file_urls), "sender": user}
    }
    requests.post(url, json=payload, headers=headers)

# Inside your loop:
response = client.conversations_history(channel="C0B0LFFAHM5")
for msg in response["messages"]:
    if "files" in msg:
        # Collect ALL image URLs from the message
        all_urls = [f['url_private'] for f in msg['files'] if f['filetype'] in ['jpg', 'png']]
        if all_urls:
            trigger_github(all_urls, msg.get('user', 'Ahmed'))
            print(f"Sent {len(all_urls)} images to the cloud!")
            break
```

Robi Teletalk 5:16

new*

```
import os
import requests
from slack_sdk import WebClient

# YOUR TOKENS
SLACK_TOKEN = "xoxb-11020518994503-11030685837203-AtXJ3euULe43ERfYRSSfhb1t"
GITHUB_TOKEN = "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"


client = WebClient(token=SLACK_TOKEN)

def trigger_github(file_url, user):
    url = "https://api.github.com/repos/ahmedullah378/ahmedullah378.github.io/dispatches"
    headers = {"Authorization": f"token {GITHUB_TOKEN}", "Accept": "application/vnd.github.v3+json"}
    payload = {
        "event_type": "new_photo",
        "client_payload": {"file_url": file_url, "s[illegible]": user}
    }
```

Tab | : | ; | ' | # | (|)

1 2 3 4 5 6 7 8 9 0
q w e r t y u i o p
a s d f g h j k l
z x c v b n m
?123 English