

# Sentiment Analysis using Word Vectors

ATJ, NSB

## Abstract

### What is Sentiment Analysis?

Sentiment Analysis is the task of extracting the favorable or unfavorable inclination of a person towards a subject or topic. For example, we could analyze twitter feeds to predict or assess the stock market trends, the favorability of a presidential nominee during elections, or how good a movie is based on the volume of the tweets and their content. It can be used to get user opinions on the products the user purchased based on the star ratings and reviews submitted through online portals like amazon.com which can be used by product manufacturers to identify how well their product is received by the majority of users. This kind of feedback is invaluable and very crucial in many cases.

### Some common classifiers

Sentiment Analysis is a text categorization problem in Natural Language Processing (NLP) that is often addressed by using a multinomial naive Bayes classifier or a Support Vector Machine (SVM) classifier. A Naive Bayes classifier makes several assumptions like representing a document as a bag of words in which the position of words does not matter. It also assumes that the words are conditionally independent given the class to which they belong. This is implicitly errant when it comes to sentiment analysis because it ignores the possibility of negated reviews like negated positive reviews which become negative and negated negative which might become positive. An SVM classifier tries to minimize a hinge loss function and combined with a regularization parameter, for a binary classification, it learns the equation of a separating line the classes. All the data points falling on one side of the line are classified with that label.

It learns the weights or coefficients of the line through training. Other classifiers which share a similar decision boundary are Gaussian naive Bayes , Logistic Regression etc. KNN is a non-parametric classifier that stores every training sample in memory, gets better with increase in the number of data samples and suffers from the famous curse of dimensionality. Decision trees and random forests which use multitudes of them averaged build a binary tree with each node as a feature value decision point. Neural networks provide good improvement in the accuracies of NLP classifiers, most of which is through the usage of word vectors as features over the regular one hot encoding or bag of words. LDA and LSA are two most commonly used techniques to generate word vectors.

Latent Dirichlet Allocation(LDA; [Blei et al., 2003]) is a probabilistic document model that assumes each document is a mixture of latent topics. This models the topics directly than the words and is less efficient. The result is a wordtopic matrix in which the rows are taken to represent word meanings or word vectors. Latent Semantic Analysis (LSA) is a

vector space model which explicitly learns semantic word vectors by applying singular value decomposition (SVD) to factor a term-document co-occurrence matrix. While LSA captures the semantic relationships between words, it doesn't capture the sentimental proximities or differences. For example, "wonderful", "delightful" and "awful", "ghastly" all seem to have similar semantic proximity or representation.

## Scope of the Project

In this project, we hope to evaluate different word and document vector representations for sentiment and subjectivity analysis. Sentiment determines polarity of a document while subjectivity says if the author is subjective or objective in his opinion. We plan to compare document vectors such as bag of words (unigram) count frequency, bag of words(unigram) presence/absence representation, bigram word dependencies, and word vectors learnt from LDA, LSA, word2vec, neural network, assign strong\_pos/weak\_pos / strong\_neg / weak\_neg / neutral tag to each word in a document and using them with classifiers such as Naive Bayes, KNN, Decision Trees, SVM, Ensemble/Boosting classifiers over the three data sets we mention below. We hope to build different pipelines with stages of preprocessing, feature extraction, classifier training, hyper parameter selection and come up with the best that performs across all the data sets. We plan to reach the existing accuracy levels of classification using the respective vector representations and try to improve if possible.

## Dataset

We will be employing the sentiment polarity v2.0 dataset and the subjectivity dataset provided by ([Pang and Lee, 2004]) which are available online at <http://www.cs.cornell.edu/People/pabo/movie-review-data/>. We will also use the Large Movie Review Dataset v1.0 made available by [Maas et al., 2011]. The polarity dataset v2.0 ([Pang and Lee, 2004]) consists of 2,000 positive and negative labelled movie reviews, and the subjectivity dataset ([Pang and Lee, 2004]) contains 5000 objective and 5000 subjective sentences. The Large Movie Dataset v1.0 [Maas et al., 2011] contains 50,000 reviews split evenly into 25k train and 25k test sets. Table 1 gives the classification accuracies that [Maas et al., 2011] obtained on the three datasets and classification accuracies reported by others [Sadeghian and Sharafat, ].

We don't plan on doing any human annotation. We plan to use the data sets available as are.

Features	PL04	IMDB Dataset	Subjectivity
Bag of Words	85.45	87.80	87.77
LDA	66.70	67.42	66.65
LSA	84.55	83.96	82.82
Semantic Only	87.10	87.30	86.65
Bag of Words SVM [Pang and Lee, 2004]	87.15	N/A	90.00

Table 1: Classification accuracies reported by [Maas et al., 2011] and others for different word representations.

## References

- [Blei et al., 2003] Blei, D. M., Ng, A. Y., and Jordan, M. I. (2003). Latent dirichlet allocation. *Journal of machine Learning research*, 3(Jan):993–1022.
- [Maas et al., 2011] Maas, A. L., Daly, R. E., Pham, P. T., Huang, D., Ng, A. Y., and Potts, C. (2011). Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies-Volume 1*, pages 142–150. Association for Computational Linguistics.
- [Pang and Lee, 2004] Pang, B. and Lee, L. (2004). A sentimental education: Sentiment analysis using subjectivity summarization based on minimum cuts. In *Proceedings of the 42nd annual meeting on Association for Computational Linguistics*, page 271. Association for Computational Linguistics.
- [Sadeghian and Sharafat, ] Sadeghian, A. and Sharafat, A. R. Bag of words meets bags of popcorn.