

KNMID API Documentation

Overview

The KNMID API facilitates secure interaction with PACI-KNMID, enabling the retrieval of user personal information. All API endpoints require authentication via a Bearer token for secure access.

When making requests, replace {parameter} placeholders with actual values. Ensure that the Bearer token is included in the Authorization header of all requests:

1. Initiate Authentication Request

This endpoint generates an access token and a unique requestID for user authentication. The token must be included in subsequent API calls as a Bearer token.

Method: POST

URL: <https://knmid.media.gov.kw/api/InitiatePushRequest>

Content Type: application/json

Request Body

```
{
  "username": "*****",
  "password": "*****",
  "civilid": "282082102788"
}
```

Response

Success (200 OK)

```
{
  "error": false,
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "civilID": "282082102788",
  "requestID": "MOINFO-KNMID-XXXXX-XXXXX"
}
```

Failure (200 OK - Authentication Error)

```
{
  "error": true,
  "status": "Fail",
  "message": "Civil ID is invalid. Kindly check."
}
```

Note:

The authentication process initiated by the first API requires user authorization within a maximum time limit of 5 minutes. Therefore, the second API is required to make repeated calls for up to 5 minutes to check for the availability of the authentication result.

2. Retrieve User Details

This endpoint retrieves user details based on the civilID and requestID obtained from the authentication step. To use this method, you need to make a POST request over HTTPS. When making the API call, include the generated token in the authorization option as a Bearer Token.

Method: POST

URL: <https://knmid.media.gov.kw/api/GetDetails>

Content Type: application/json

Request Body

```
{
  "civilid": "282082102788",
  "requestID": "MOINFO-KNMID-XXXXX-XXXXX"
}
```

Response

Success (200 OK - Authenticated User)

```
{
  "error": false,
  "requestId": "MOINFO-KNMID-XXXXX-XXXXX",
  "requestStatus": "Completed",
  "resultCode": "1",
  "messageEn": "Success",
  "messageAR": "نجاح",
  "fullNameEn": "XXXXX ",
  "fullNameAr": "XXXXX ",
  "nationalityEn": "Kuwait",
  "nationalityAr": "الكويت",
  "birthDate": "xxxx-xx-xx",
  "gender": "M",
  "mobileNumber": "xxxxxxxx",
  "emailAddress": "example@example.com",
  "cardExpiryDate": "xxxx-xx-xx"
}
```

Failure (200 OK - Authentication Declined)

```
{
  "error": true,
  "requestId": "MOINFO-KNMID-XXXXX-XXXXX",
  "civilID": "284111801481",
  "resultCode": "4",
  "messageEn": "Declined",
  "messageAR": "مرفوض"
}
```

Result Codes & Descriptions

Result Code	Description	Action Required
1	Authenticated	Proceed with API calls
2	Certificate Revoked	Contact support
3	Failed to Verify	Check request parameters
4	Declined	User authentication denied
5	Certificate Expired	Renew certificate
6	General Error	Contact support

Security Considerations

- Always use HTTPS for API communication.
- Store authentication tokens securely.
- Ensure that authentication is completed within 5 minutes.

Troubleshooting

Issue	Cause	Solution
Invalid Token	Token is expired or incorrect	Re-authenticate and obtain a new token
Civil ID Not Found	Incorrect Civil ID provided	Verify Civil ID before sending request
Authentication Timeout	Request not completed within 5 minutes	Retry the authentication request