
CENG443 Heterogeneous Parallel Programming

Introduction to CUDA

3 Ways to Accelerate Applications



Libraries

Ease of use: Using libraries enables GPU acceleration without in-depth knowledge of GPU programming

"Drop-in": Many GPU-accelerated libraries follow standard APIs, thus enabling acceleration with minimal code changes

Quality: Libraries offer high-quality implementations of functions encountered in a broad range of applications

GPU Accelerated Libraries

Linear Algebra FFT, BLAS, SPARSE, Matrix









Numerical & Math RAND, Statistics









Data Struct. & AI Sort, Scan, Zero Sum







Visual Processing Image & Video







Vector Addition in Thrust

```
#include <thrust/device vector.h>
#include <thrust/transform.h>
#include <thrust/functional.h>
#include <iostream>
int main (void)
 thrust::device vector<float> X(3);
 thrust::device vector<float> Y(3);
 thrust::device vector<float> Z(3);
 X[0] = 10; X[1] = 20; X[2] = 30;
 Y[0] = 15; Y[1] = 35; Y[2] = 10;
  thrust::transform(X.begin(), X.end(),
                    Y.begin(),
                    Z.begin(),
                    thrust::plus<float>());
 for (size t i = 0; i < Z.size(); i++)</pre>
    std::cout << "Z[" << i << "] = " << Z[i] << "\n";
 return 0;
```

Compiler Directives

Ease of use: Compiler takes care of details of parallelism management and data movement

Portable: The code is generic, not specific to any type of hardware and can be deployed into multiple languages

Uncertain: Performance of code can vary across compiler versions

OpenACC

Compiler directives for C, C++, and FORTRAN

```
#pragma acc parallel loop copyin(input1[0:inputLength],input2[0:inputLength]),
copyout(output[0:inputLength])
for(i = 0; i < inputLength; ++i) {
    output[i] = input1[i] + input2[i];
}</pre>
```


Programming Languages

Performance: Programmer has best control of parallelism and data movement


Flexible: The computation does not need to fit into a limited set of library patterns or directive types

Verbose: The programmer often needs to express more details

GPU Programming Languages




CUDA C




CUDA Programming

CUDA (Compute Unified Device Architecture) Integrated host+device app C program


Serial or modestly parallel parts in host C code Highly parallel parts in device SPMD kernel C code



CUDA C Program Compilation



CUDA C Program Execution



Vector Addition - Traditional C Code

```
// Compute vector sum C = A + B
void vecAdd(float *h_A, float *h_B, float *h_C, int n)
    int i;
    for (i = 0; i < n; i++) h_C[i] = h_A[i] + h_B[i];
int main()
    // Memory allocation for h_A, h_B, and h_C
  // I/O to read h_A and h_B, N elements
    vecAdd(h_A, h_B, h_C, N);
```

Heterogeneous Computing

Setup inputs on the host (CPU-accessible memory)
Allocate memory for outputs on the GPU
Allocate memory for outputs on the GPU
Copy inputs from host to GPU
Start GPU kernel (function that executed on gpu)
Copy output from GPU to host

vecAdd CUDA Host Code


```
Part 1
#include <cuda.h>
void vecAdd(float* A, float* B, float* C, int n)
                                                Host memory
                                                                 Device memory
 int size = n* sizeof(float);
                                                                     GPU
                                                  CPU
 float *d A *d B, *d C:
                                                                    (Part 2)
1. // Allocate device memory for A, B, and C
  // copy A and B to device memory
                                                            Part 3
2. // Kernel launch code - to have the device
  // to perform the actual vector addition
3. // copy C from the device memory
  // Free device vectors
```

Partial Overview of CUDA Memories

Device code can:

R/W per-thread registers

R/W all-shared global memory



Host code can:

Transfer data to/from per grid global memory

CUDA Device Memory API functions

cudaMalloc()


Allocates an object in the device global memory

Two parameters

Address of a pointer to the allocated object Size of allocated object in terms of bytes

cudaError_t cudaMalloc (void ** devPtr,

size_t size)



CUDA Device Memory API functions


cudaFree()

Frees object from device global memory

One parameter

Pointer to freed object

cudaError t cudaFree(void* devPtr)



Vector Addition Host Code

```
void vecAdd(float *h A, float *h B, float *h C, int n)
  int size = n * sizeof(float); float *d A, *d B, *d C;
  cudaMalloc((void **) &d_A, size);
  //transfer data to device
   cudaMalloc((void **) &d_B, size);
  //transfer data to device
   cudaMalloc((void **) &d_C, size);
   // Kernel invocation code – to be shown later
  //get data from device
   cudaFree(d_A); cudaFree(d_B); cudaFree (d_C);
```

Host-Device Data Transfer API functions

cudaMemcpy()

memory data transfer


Requires four parameters

Pointer to destination

Pointer to source

Number of bytes copied

Type/Direction of transfer



Transfer to device is asynchronous

Host-Device Data Transfer API functions

cudaMemcpy()

kind is one of cudaMemcpyHostToHost, cudaMemcpyHostToDevice, cudaMemcpyDeviceToHost, or cudaMemcpyDeviceToDevice

Calling cudaMemcpy() with dst and src pointers that do not match the direction of the copy results in an undefined behavior

Vector Addition Host Code

```
void vecAdd(float *h A, float *h B, float *h C, int n)
  int size = n * sizeof(float); float *d A, *d B, *d C;
  cudaMalloc((void **) &d A, size);
  cudaMemcpy(d_A, h_A, size, cudaMemcpyHostToDevice);
   cudaMalloc((void **) &d B, size);
   cudaMemcpy(d_B, h_B, size, cudaMemcpyHostToDevice);
   cudaMalloc((void **) &d C, size);
  // Kernel invocation code – to be shown later
   cudaMemcpy(h_C, d_C, size, cudaMemcpyDeviceToHost);
   cudaFree(d A); cudaFree(d B); cudaFree (d C);
```

Error Check

```
cudaError_t err = cudaMalloc((void **) &d_A, size);

if (err != cudaSuccess) {
   printf("%s in %s at line %d\n", cudaGetErrorString(err), __FILE__,
   __LINE__);
   exit(EXIT_FAILURE);
}

-For brevity, we will omit this!
```

Kernel Function

Our "parallel" function
Given to each thread
Simple implementation:


```
__global__ void
cudaAddVectorsKernel(float * a, float * b, float * c) {
    //Decide an index somehow
    c[index] = a[index] + b[index];
}
```

Arrays of Parallel Threads


A CUDA kernel is executed by a grid (array) of threads

All threads in a grid run the same kernel code (Single Program Multiple Data)

Each thread has indexes that it uses to compute memory addresses and make control decisions



Thread Blocks: Scalable Cooperation




Divide thread array into multiple blocks

Threads within a block cooperate via shared memory, atomic operations and barrier synchronization

Threads in different blocks do not interact

Kernel, Block, Thread



Vector Addition Kernel Function - Device Code

```
// Compute vector sum C = A + B

// Each thread performs one pair-wise addition

__global__

void vecAddKernel(float* A, float* B, float* C, int n)

{
   int i = threadIdx.x+blockDim.x*blockIdx.x;
   if(i<n) C[i] = A[i] + B[i];
}</pre>
```

Vector Addition Kernel Function - Device Code

```
// Compute vector sum C = A + B

// each thread calculates two (adjacent) output elements of a vector addition

__global__

void vecAddKernel(float* A, float* B, float* C, int n)

{
   int i = (threadIdx.x+blockDim.x*blockIdx.x)*2;
   if(i<n) C[i] = A[i] + B[i];
}</pre>
```

CUDA C Keywords for Function Declarations

	Executed on the:	Only callable from the:
device float DeviceFunc()	device	device
global void KernelFunc()	device	host
host float HostFunc()	host	host

__global__ defines a kernel function

Each "__" consists of two underscore characters

A kernel function must return void

device and _host_ can be used together

host is optional if used alone

Indexing

Each thread uses indices to decide what data to work on


blockldx: 1D, 2D, or 3D (CUDA 4.0)

threadIdx: 1D, 2D, or 3D

Simplifies memory addressing when processing multidimensional data

Image processing

Solving PDEs on volumes



Vector Addition Kernel Launch - Host Code

```
void vecAdd(float* h_A, float* h_B, float* h_C, int n)
{
   // d_A, d_B, d_C allocations and copies omitted
   // Run ceil(n/256.0) blocks of 256 threads each
   vecAddKernel<<<ceil(n/256.0), 256>>>(d_A, d_B, d_C, n);
}
```

More on Kernel Launch - Host Code

```
void vecAdd(float* h_A, float* h_B, float* h_C, int n)
{
   dim3 DimGrid(ceil(n/256.0), 1, 1);
   dim3 DimBlock(256, 1, 1);
   vecAddKernel<<<DimGrid, DimBlock>>>(d_A, d_B, d_C, n);
}
```

Vector Addition with 8000 Elements

Each thread calculates one output element


Thread block size is 1024 threads

The programmer configures the kernel launch to have a minimal number of thread blocks to cover all output elements

How many threads will be in the grid?

```
ceil(8000/1024) * 1024 = 8 * 1024 = 8192
(the minimal multiple of 1024 to cover 8000 is 1024*8 = 8192)
```

Kernel Execution



Important CUDA Syntax Extensions

Declaration specifiers

__global__ void foo(...); // kernel entry point (runs on GPU)

Syntax for kernel launch

foo<<<500, 128>>>(...); // 500 thread blocks, 128 threads each

Built in variables for thread identification

dim3 threadIdx; dim3 blockIdx; dim3 blockDim;

Example: Original C Code

```
void saxpy serial(int n, float a, float *x, float *y)
   for (int i = 0; i < n; ++i)
   y[i] = a*x[i] + y[i];
int main()
   // omitted: allocate and initialize memory
    saxpy serial(n, 2.0, x, y); // Invoke serial SAXPY kernel
  // omitted: using result
```

CUDA Code

```
global void saxpy(int n, float a, float *x, float *y) {
     int i = blockldx.x*blockDim.x + threadIdx.x:
     if(i<n) y[i]=a*x[i]+y[i];
}
int main() {
    // omitted: allocate and initialize memory
     int nblocks = (n + 255) / 256;
     cudaMalloc((void**) &d x, n);
    cudaMalloc((void**) &d y, n);
     cudaMemcpy(d x,h x,n*sizeof(float),cudaMemcpyHostToDevice);
     cudaMemcpy(d y,h y,n*sizeof(float),cudaMemcpyHostToDevice);
     saxpy < < nblocks, 256 >> > (n, 2.0, d x, d y);
     cudaMemcpy(h y,d y,n*sizeof(float),cudaMemcpyDeviceToHost);
    // omitted: using result
}
```