SetTimer — Exercise Routine Interval Timer

A modular, client-side Progressive Web App (PWA) for building and running custom interval workout routines. Designed to be hosted directly on GitHub Pages.

Compartmentalized Module Structure

- `index.html` — Application layout for Edit Mode and Run Mode (with top Volume Slide Bars, App Icon links, and PWA Manifest)
- `styles.css` — Styling for Edit Mode cards, Drag & Drop indicators, Volume Slide Bars, and Full-Screen Run Mode color states
- `storage.js` — `localStorage` persistence for saving, auto-loading, creating, and deleting exercise routines and sound volume preferences
- `dragdrop.js` — HTML5 drag-and-drop and button reordering for activities
- `excel.js` — SheetJS (`.xlsx`) and `.csv` export/import module for backing up and restoring all routines
- `timer.js` — Interval state machine, high-precision countdown engine, and Web Audio API sound cues with adjustable volume (`0%`–`100%`)
- `app.js` — Main UI controller connecting Edit Mode, Run Mode, Volume Slide Bars, and Service Worker registration
- `manifest.json` — Web App Manifest for Android Chrome WebAPK installation ("Install App" / "Add to Home Screen")
- `sw.js` — Offline-capable Service Worker required by Android Chrome to install and launch SetTimer as a standalone App
- `favicon.ico`, `favicon.png`, `apple-touch-icon.png`, `icon-192.png`, `icon-512.png` — App icon suite for PC bookmarks, iOS, and Android Home Screen / App Drawer

Fixing "Could not open app" on Android Chrome (GitHub Pages Subpath Fix)

Why It Still Happened After the Previous Update

1. **Manifest `"id": "./"` Subpath Collision on GitHub Pages**:
    - According to the W3C Web App Manifest specification and Chrome's Manifest Parser, while `start_url` and `scope` resolve relative to the manifest's directory (`https://<username>.github.io/SetTimer/`), the `id` property resolves relative to the **root domain origin** (`https://<username>.github.io/`).
    - Having `"id": "./"` caused Android Chrome's WebAPK builder to assign the app's identity to the root domain `https://<username>.github.io/` (outside

the `/SetTimer/` subfolder scope), causing the installed Android WebAPK launcher intent to fail with **"Could not open app"**.
    - **Fix**: Removed `"id": "./"` so Chrome automatically binds the app identity to `"start_url": "./index.html"` inside your `/SetTimer/` repository path, simplified `"name"` to pure ASCII `"SetTimer"`, and ensured every icon entry in `manifest.json` has a unique URL.
2. **Service Worker (`sw.js`) Fallback & Cache Refresh**:
    - Updated `sw.js` (`v3`) to only intercept same-origin requests (allowing external CDNs to load natively), fixed the offline navigation Promise chain so `event.respondWith()` always returns a valid `Response`, and configured `app.js` to automatically trigger `registration.update()` on load.

Steps to Cleanly Re-Install on Your Android Phone

Because Android caches failed WebAPK registrations from previous attempts, perform these quick cleanup steps once after uploading the new files to GitHub:

1. **Remove any stuck SetTimer app entry on Android**:
    - Open your phone's **Settings** → **Apps** → **See all apps** and search for **SetTimer**. If it appears in the app list, tap **Uninstall**. Also remove any old SetTimer shortcut from your home screen.
2. **Clear cached site data in Android Chrome**:
    - Open your live `https://<username>.github.io/SetTimer/` page in Android Chrome.
    - Tap the **tune / lock icon** on the left of the address bar → **Cookies and site data** (or **Site settings**) → **Delete data / Clear & reset**, then reload the page.
3. **Install the App**:
    - Tap the 📲 **Install App** button in the top bar (or open Chrome's ⋮ menu → **Add to Home screen** → **Install**).