EDA

October 25, 2026

1 Exploratory Data Analysis: NYC restaurant inspections

This notebook explores the processed NYC restaurant inspection dataset and examines patterns related to the main target variable, `fail`.

[2]:
```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

[3]:
```
df = pd.read_csv("../data/processed/inspections_model.csv")
df.shape
```

[3]: (44890, 24)

[4]:
```
df.head()
```

[4]:

	camis	dba	inspection_date	boro	zipcode	cuisine_description	latitude	longitude	is_chain	inspection_year	…	prev_initial_score	prev_initial_failed	mean_prior_initial_score	max_prior_initial_score	\
0	41219793	THE MONKEY ROOM	2023-01-03	Manhattan	10033.0	American	40.854623	-73.937051	0	2023	…	NaN	NaN			
1	41462617	MIKE'S UNICORN DINER	2023-01-03	Staten Island	10314.0	American	40.607389	-74.160675	0	2023	…	NaN	NaN			
2	41615012	VERONICA'S BAKERY	2023-01-03	Staten Island	10302.0	Mexican	40.631062	-74.130952	0	2023	…	NaN	NaN			
3	41630104	LUCKY CHINESE RESTAURANT	2023-01-03	Queens	11377.0	Chinese	40.736744	-73.895975	0	2023	…	31.0	1.0			
4	50003774	GOLDEN KRUST CARIBBEAN BAKERY & GRILL	2023-01-03	Brooklyn	11210.0	Caribbean	40.636919	-73.937311	1	2023	…	NaN	NaN			

```
0                       NaN                     NaN
1                       NaN                     NaN
2                       NaN                     NaN
3                      31.0                    31.0
4                       NaN                     NaN

   n_prior_critical_violations  n_prior_closures  days_since_prev_inspection  \
0                            0                 0                         NaN
1                            0                 0                         NaN
2                            0                 0                         NaN
3                            6                 0                       224.0
4                            0                 0                         NaN

   days_since_prev_initial  score  fail
0                      NaN    9.0     0
1                      NaN   19.0     1
2                      NaN   31.0     1
3                    250.0   41.0     1
4                      NaN   14.0     1

[5 rows x 24 columns]
```

[5]:
```
df.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 44890 entries, 0 to 44889
Data columns (total 24 columns):
 #   Column                        Non-Null Count  Dtype
---  ------                        --------------  -----
 0   camis                         44890 non-null  int64
 1   dba                           44890 non-null  str
 2   inspection_date               44890 non-null  str
 3   boro                          44848 non-null  str
 4   zipcode                       44295 non-null  float64
 5   cuisine_description           44890 non-null  str
 6   latitude                      44016 non-null  float64
 7   longitude                     44016 non-null  float64
 8   is_chain                      44890 non-null  int64
 9   inspection_year               44890 non-null  int64
 10  inspection_month              44890 non-null  int64
 11  inspection_dayofweek          44890 non-null  int64
 12  n_prior_inspections           44890 non-null  int64
 13  n_prior_initial_inspections   44890 non-null  int64
 14  prev_initial_score            24127 non-null  float64
 15  prev_initial_failed           24127 non-null  float64
 16  mean_prior_initial_score      24127 non-null  float64
 17  max_prior_initial_score       24127 non-null  float64
 18  n_prior_critical_violations   44890 non-null  int64
```

```
 19  n_prior_closures              44890 non-null  int64
 20  days_since_prev_inspection    32514 non-null  float64
 21  days_since_prev_initial       24127 non-null  float64
 22  score                         44890 non-null  float64
 23  fail                          44890 non-null  int64
dtypes: float64(10), int64(10), str(4)
memory usage: 8.2 MB
```

1.1 Target Distribution

[6]:
```
df["fail"].value_counts()
```

[6]:
```
fail
0    26906
1    17984
Name: count, dtype: int64
```

[7]:
```
df["fail"].value_counts(normalize=True)
```

[7]:
```
fail
0    0.599376
1    0.400624
Name: proportion, dtype: float64
```

[10]:
```
fail_rate = df["fail"].mean()
pass_rate = 1 - fail_rate

rates = [pass_rate, fail_rate]


plt.figure(figsize=(6, 5))

bars = plt.bar(
    ["Passed", "Failed"],
    rates,
    color=["lightgray", "coral"]
)

for i in range(len(bars)):
    plt.text(
        i,
        rates[i] + 0.01,
        f"{rates[i]:.1%}",
        ha="center"
    )

plt.ylabel("Proportion")
plt.title("About 40% of Initial Inspections Result in Failure")
```

```
plt.tight_layout()
plt.show()
```



Observation: About 40.1% of the initial inspections in the dataset are classified as failures, while 59.9% are passes. The target is therefore not extremely imbalanced.

1.2 Missing Values

[11]:
```
df.isna().sum()
```

[11]:
```
camis                      0
dba                        0
inspection_date            0
boro                      42
zipcode                  595
cuisine_description        0
latitude                 874
longitude                874
```

```
is_chain                          0
inspection_year                   0
inspection_month                  0
inspection_dayofweek              0
n_prior_inspections               0
n_prior_initial_inspections       0
prev_initial_score            20763
prev_initial_failed           20763
mean_prior_initial_score      20763
max_prior_initial_score       20763
n_prior_critical_violations       0
n_prior_closures                  0
days_since_prev_inspection    12376
days_since_prev_initial       20763
score                             0
fail                              0
dtype: int64
```

[12]:
```
df.isna().mean()
```

[12]:
```
camis                         0.000000
dba                           0.000000
inspection_date               0.000000
boro                          0.000936
zipcode                       0.013255
cuisine_description           0.000000
latitude                      0.019470
longitude                     0.019470
is_chain                      0.000000
inspection_year               0.000000
inspection_month              0.000000
inspection_dayofweek          0.000000
n_prior_inspections           0.000000
n_prior_initial_inspections   0.000000
prev_initial_score            0.462531
prev_initial_failed           0.462531
mean_prior_initial_score      0.462531
max_prior_initial_score       0.462531
n_prior_critical_violations   0.000000
n_prior_closures              0.000000
days_since_prev_inspection    0.275696
days_since_prev_initial       0.462531
score                         0.000000
fail                          0.000000
dtype: float64
```

[13]:
```
df.loc[
    df["prev_initial_score"].isna(),
    "n_prior_initial_inspections"
].value_counts()
```

[13]:
```
n_prior_initial_inspections
0    20763
Name: count, dtype: int64
```

Missing Value Interpretation: All 20,763 observations with a missing `prev_initial_score` have zero prior initial inspections. Therefore, these missing values are expected: if a restaurant has no prior initial inspection in the available data, there is no previous inspection score to record.

1.3 Feature Exploration

1.3.1 Borough

[14]:
```
boro_fail_rate = df.groupby("boro")["fail"].mean().sort_values()
boro_fail_rate
```

[14]:
```
boro
Manhattan        0.380622
Brooklyn         0.386890
Bronx            0.419518
Queens           0.433469
Staten Island    0.455112
Name: fail, dtype: float64
```

[16]:
```
colors = []

for boro in boro_fail_rate.index:
    if boro == "Staten Island":
        colors.append("coral")
    else:
        colors.append("lightgray")

plt.figure(figsize=(7, 5))


bars = plt.bar(
    boro_fail_rate.index,
    boro_fail_rate.values,
    color=colors
)

for i in range(len(bars)):
    plt.text(
        i,
        boro_fail_rate.values[i] + 0.005,
```

```
        f"{boro_fail_rate.values[i]:.1%}",
        ha="center"
    )

plt.xlabel("Borough")
plt.ylabel("Failure Rate")
plt.title("Staten Island Has the Highest Restaurant Inspection Failure Rate")

plt.xticks(rotation=45)
plt.tight_layout()
plt.show()
```



Observation: Staten Island has the highest inspection failure rate at 45.5%, while Manhattan has the lowest at 38.1%. However, the differences across boroughs are relatively modest.

1.3.2 Cuisine

[17]:
```
df["cuisine_description"].nunique()
```

[17]: 89

[18]:
```
df["cuisine_description"].value_counts().head(15)
```

[18]:
```
cuisine_description
American                          7861
Coffee/Tea                        4041
Chinese                           3464
Pizza                             2748
Bakery Products/Desserts          1927
Latin American                    1917
Mexican                           1711
Donuts                            1519
Italian                           1510
Caribbean                         1357
Japanese                          1353
Chicken                           1277
Hamburgers                        1121
Sandwiches                         963
Juice, Smoothies, Fruit Salads     892
Name: count, dtype: int64
```

[19]:
```
cuisine_summary = (
    df.groupby("cuisine_description")["fail"]
    .agg(["count", "mean"])
)

cuisine_summary = cuisine_summary[
    cuisine_summary["count"] >= 300
]
```

[21]:
```
cuisine_plot = pd.concat([
    cuisine_summary.nsmallest(5, "mean"),
    cuisine_summary.nlargest(5, "mean")
]).sort_values("mean")
```

[22]:
```
colors = []

for rate in cuisine_plot["mean"]:
    if rate >= 0.5:
        colors.append("coral")
    else:
        colors.append("lightgray")

plt.figure(figsize=(8, 6))


bars = plt.barh(
    cuisine_plot.index,
    cuisine_plot["mean"],
    color=colors
)
```

```
for i in range(len(cuisine_plot)):
    plt.text(
        cuisine_plot["mean"].iloc[i] + 0.01,
        i,
        f"{cuisine_plot['mean'].iloc[i]:.1%}",
        va="center"
    )

plt.xlabel("Failure Rate")
plt.ylabel("Cuisine")
plt.title("Failure Rates Vary Widely Across Common Cuisine Types")

plt.xlim(0, cuisine_plot["mean"].max() + 0.1)

plt.tight_layout()
plt.show()
```



Observation: Among cuisine categories with at least 300 inspections, failure rates vary substantially. The figure shows the five cuisines with the highest and lowest failure rates. Some of the highest-risk cuisines have failure rates above 50%, while the lowest are below 25%. This indicates

an association between cuisine category and inspection outcomes, but does not imply causation.

1.3.3 Inspection History

[23]:
```
df["prev_initial_score"].describe()
```

[23]:
```
count    24127.000000
mean        17.432006
std         13.913361
min          0.000000
25%          9.000000
50%         12.000000
75%         23.000000
max        142.000000
Name: prev_initial_score, dtype: float64
```

[24]:
```
prev_score_fail_rate = (
    df.groupby("prev_initial_score")["fail"]
    .agg(["count", "mean"])
)

prev_score_fail_rate
```

[24]:

prev_initial_score	count	mean
0.0	234	0.303419
2.0	893	0.208287
3.0	355	0.169014
4.0	492	0.182927
5.0	936	0.230769
…	…	…
121.0	1	1.000000
127.0	1	1.000000
128.0	1	1.000000
135.0	1	0.000000
142.0	1	0.000000

[113 rows x 2 columns]

[25]:
```
score_bins = [-1, 5, 13, 20, 30, np.inf]
score_labels = ["0-5", "6-13", "14-20", "21-30", "31+"]

df["prev_score_group"] = pd.cut(
    df["prev_initial_score"],
    bins=score_bins,
    labels=score_labels
)
```

[26]:
```
score_group_summary = (
    df.groupby("prev_score_group", observed=True)["fail"]
    .agg(["count", "mean"])
)

score_group_summary
```

[26]:

prev_score_group	count	mean
0-5	2910	0.214089
6-13	11853	0.312242
14-20	2083	0.447432
21-30	3840	0.515365
31+	3441	0.586167

[27]:
```
colors = []

for rate in score_group_summary["mean"]:
    if rate >= 0.5:
        colors.append("coral")
    else:
        colors.append("lightgray")


plt.figure(figsize=(7, 5))

bars = plt.bar(
    score_group_summary.index,
    score_group_summary["mean"],
    color=colors
)

for i in range(len(score_group_summary)):
    plt.text(
        i,
        score_group_summary["mean"].iloc[i] + 0.01,
        f"{score_group_summary['mean'].iloc[i]:.1%}",
        ha="center"
    )

plt.xlabel("Previous Initial Inspection Score")
plt.ylabel("Current Failure Rate")
plt.title("Current Failure Rate Increases with Previous Inspection Score")

plt.tight_layout()
plt.show()
```



Observation: Restaurants with higher previous initial inspection scores tend to have higher failure rates in their current inspection. The failure rate increases from 21.4% for restaurants with previous scores of 0–5 to 58.6% for those with previous scores of 31 or higher.

1.3.4 Chain Status

[28]:
```
df.groupby("is_chain")["fail"].agg(["count", "mean"])
```

[28]:
```
          count     mean
is_chain
0         35712  0.43624
1          9178  0.26204
```

[30]:
```
chain_fail_rate
```

[30]:
```
is_chain
0    0.43624
1    0.26204
Name: fail, dtype: float64
```

[31]:
```
chain_fail_rate = df.groupby("is_chain")["fail"].mean()


plt.figure(figsize=(6, 5))
```

```
bars = plt.bar(
    ["Non-chain", "Chain"],
    chain_fail_rate.values,
    color=["coral", "lightgray"]
)

for i in range(len(bars)):
    plt.text(
        i,
        chain_fail_rate.values[i] + 0.01,
        f"{chain_fail_rate.values[i]:.1%}",
        ha="center"
    )

plt.xlabel("Restaurant Type")
plt.ylabel("Failure Rate")
plt.title("Non-chain Restaurants Have Higher Inspection Failure Rates")

plt.tight_layout()
plt.show()
```



Observation: Non-chain restaurants have a substantially higher inspection failure rate than chain restaurants. The failure rate is 43.6% for non-chain restaurants, compared with 26.2% for chain restaurants. This suggests an association between chain status and inspection outcomes.