

Turbulence modulation via dilute surfactant additives in experimental Taylor–Green flow

Augusto H. P. Zanca, Yutaro Motoori, and Susumu Goto
Graduate School of Engineering Science, Osaka University
(Dated: August 25, 2026)

Abstract here.

I. INTRODUCTION

Since the discovery that trace amounts of dissolved polymer could lead to drag reduction in pipe flows [1], the use of additives for drag reduction in wall bounded flows has become established. Besides polymer solutions, it has since been discovered that self-assembling surfactant solutions share similar effects [2], owing to the fact that dilute surfactant solutions can form wormlike micelles whose relaxation dynamics mimic that of polymer chains while resisting mechanical degradation. Beyond the applications of drag reduction, it has shown that viscoelastic additives are known to modulate turbulence more broadly, reshaping the energy spectrum and producing an elastic range governed by additive elasticity rather than inertial at the small scales [3, 4], with surfactant-specific micellar structures shown to alter vortex shedding and turbulence statistics directly [5].

In spite of academic and commercial interest, comparatively few studies address the behavior of dilute surfactant solutions in the context of three-dimensional bulk turbulence, with most of the literature focused on wall-bounded or quasi-two-dimensional flows. This is in part related to the fact that the rheology of very dilute surfactant solutions remains difficult to pin down, with reported values of viscosity and relaxation time of CTAC/NaSal solutions (such as the considered in the present experiment) varying considerably between studies [6, 7]. In spite of the diverging measurements and reports that some of the dilute solutions behave as a Newtonian fluid under rheological measurement [6], such solutions are known to produce measurable drag reduction [8], which further reinforces the need to analyze such solutions more in depth.

Motivated by this gap, here we present an experimental analysis of the turbulence generated by a four-rotor, Taylor–Green-like experiment using dilute CTAC solutions, in an attempt to characterize the modulation of turbulence caused by the addition of the surfactant across a wide range of Reynolds numbers for flows driven by inertial forcing.

II. EXPERIMENTAL DEVICE

In the present study, we employ an experimental device designed to produce Taylor–Green-like forced turbulence on a laboratory setting. The apparatus, with schematic shown on figure 1, consists of a water tank




FIG. 1. CAD of the experimental device (left) and schematic showing normal orientation of camera and laser sheet, as well as direction of rotation of the rotors.




FIG. 2. Schematic of the altered orientation of camera and laser using mirror for imaging of the space between rotors. One of the rotors is omitted for clarity.

with four rotors which are driven by a gear system and rotate in opposing directions in order to produce turbulence in the region between them (hereinafter simply denominated bulk), which is the target of our studies. Spatially-resolved measurements are obtained via 2D particle tracking (briefly described in section II A) via a traditional laser-sheet and high-speed camera combination, which are positioned as also shown in figure 1 for the case of bulk imaging.

Aside from the imaging of the bulk region, it is also possible to change the relative orientations of the laser sheet and camera, and use a mirror to allow for top-down imaging of the region in the vicinity of the blades, as shown in the schematic of figure 2.

As shown in the schematics of figures 1 and 2, the rotors themselves are shaped as blades with rectangular cross-section. While the design of the experimental device allows for the geometry of the rotors to be changed between cylinders and the carved blades, the use of the latter allows us to isolate inertial forcing in the driving of the flow, and therefore ignore boundary-layer effects which would be present in the case of viscous driving which happens when cylindrical rotors are used. Addi-

tionally, the rotation direction is such that mean stretching of the flow happens in the out-of-plane component of the camera image (when imaging the bulk region in the vertical plane), and is accompanied by the formation of secondary vortices as shown in previous numerical studies [9]. For simplicity, the carved rotors will hereinafter simply be denominated blades.

While not shown in the schematics, the experimental device is also encased in thermal insulation and connected to an air-processor system. By controlling the temperature of the surrounding air, the water temperature was maintained at approximately 26 °C over the course of the experiments.

A. Data measurement and reduction

As previously mentioned, processing of the obtained images to calculate the velocity fields is conducted via a particle tracking velocimetry (PTV) code developed in-house. Although the details of the algorithm are out of the scope of the current document, the code is built as a collection of previously established methods. For the detection of tracer particles from the images, we employ a variation of the Iterative Particle Reconstruction (IPR) method, which is commonly employed for volumetric particle tracking as part of the Shake-the-Box method [10]. The tracking of detected particle positions between the video frames is carried out by a variation of the Polar Coordinate-System Similarity (PCSS) method [11].

Before the calculation of the final velocity vectors through finite differencing, the trajectories are filtered according to a Wiener Filter [12] which is calculated from the spectra of position of the obtained trajectories. The filtering is done in order to avoid the effect of the noise floor in the calculation of the velocities. (need to revisit this) (also need to mention the interpolation that is done before the spatial average) **also supplement this with the explanation of the uncertainty calculation and all.**

B. Surfactant solutions

The surfactant used in the current study was the cationic surfactant cetrimonium chloride (CTAC), with the addition of sodium salicylate on a molar ratio of approximately 4:1 to provide counterions. The solution is prepared by mixing the adequate amounts of surfactant and salt with tap water and then agitating in a magnetic stirrer over a period of at least 12 hours, after which the resulting solution is added to the experimental device. For simplicity, the surfactant and salt solution are here-

inafter denominated simply as the CTAC solution, with the solution concentration corresponding exclusively to the concentration of the surfactant counterpart.

For the analysis of the effect of solution concentration on the results, three CTAC solutions of concentrations of 33 ppm, 50 ppm, and 100 ppm were prepared. As previously mentioned, rheological measurements of such dilute solutions have historically yielded diverging results [6, 7], meaning that to the best of the author's knowledge, there is no precise measurement of the properties such as the relaxation time of micellar structures under these conditions.

Moreover, the molar ratio of 4:1 chosen for the current study differs from that of the aforementioned measurements, as well as that of drag reduction studies [8]. Although numerical studies have reported that such high molar ratios can lead to the formation of branched structures and loss of viscoelasticity [13], such claims have been made for solutions of much higher concentrations. In the experience of the authors, this effect is not as pronounced in the case of dilute solutions, and the use of a high molar ratio has been chosen to favor the formation of longer micellar structures.

In spite of these divergences, it can be expected from the aforementioned studies that this relaxation time should be in the order of 10^{-1} seconds. Since the relaxation time cannot be precisely known beforehand or independently controlled over a wide range, a sweep over the Weissenberg **you need to define what is the weissenberg number bro** number is instead achieved by changing the Reynolds number of the generated turbulence. For each of the prepared solutions, the rotation rate of the blades is changed 2^{-3} to 2^4 Hz in powers of two. Exclusively for the 100 ppm solution **say how the rotation rate was reduced further**. Although it is debatable whether the flow generated in the case of the lower rotation rates can be denominated turbulent, it remains chaotic and unsteady, so such cases are still useful in the determination of the effect of surfactant addition on such unsteady but low Reynolds number types of flows.

The next section describes briefly the characterization of the turbulence generated in the current experimental device for the case of Newtonian fluid.

III. TURBULENCE CHARACTERIZATION

IV. RESULTS

V. CONCLUSIONS

[1] B. A. Toms, Some observations on the flow of linear polymer solutions through straight tubes at large reynolds

numbers, Proceedings of the 1st International Congress on Rheology **2**, 135 (1948).

- [2] J. L. Lumley, Drag reduction by additives, Annual Review of Fluid Mechanics **1**, 367 (1969).
- [3] A. Groisman and V. Steinberg, Elastic turbulence in a polymer solution flow, Nature **405**, 53 (2000).
- [4] Y.-B. Zhang, E. Bodenschatz, H. Xu, and H.-D. Xi, Experimental observation of the elastic range scaling in turbulent flow with polymer additives, Science Advances **7**, eabd3525 (2021).
- [5] K. Fukushima, H. Kishi, H. Suzuki, and R. Hidema, Modification of turbulence caused by cationic surfactant wormlike micellar structures in two-dimensional turbulent flow, Journal of Fluid Mechanics **933**, A9 (2022).
- [6] Y. Kawaguchi, J. Wei, B. Yu, and Z. Feng, Rheological characterization of drag-reducing cationic surfactant solution: Shear and elongational viscosities of dilute solutions, in *Volume 1: Fora, Parts A, B, C, and D*, Fluids Engineering Division Summer Meeting (2003) pp. 721–728.
- [7] H.-x. Zhang, D.-z. Wang, W.-g. Gu, and H.-p. Chen, Effects of Temperature and Concentration on Rheological Characteristics of Surfactant Additive Solutions, Journal of Hydrodynamics, Ser. B **20**, 603 (2008).
- [8] F.-C. Li, Y. Kawaguchi, B. Yu, J.-J. Wei, and K. Hishida, Experimental study of drag-reduction mechanism for a dilute surfactant solution flow, International Journal of Heat and Mass Transfer **51**, 835 (2008).
- [9] S. Goto, Y. Saito, and G. Kawahara, Hierarchy of antiparallel vortex tubes in spatially periodic turbulence at high reynolds numbers, Physical Review Fluids **2**, 064603 (2017).
- [10] T. Jahn, D. Schanz, and A. Schröder, Advanced iterative particle reconstruction for lagrangian particle tracking, Experiments in Fluids **62**, 179 (2021).
- [11] L. Shindler, M. Moroni, and A. Cenedese, Spatial-temporal improvements of a two-frame particle-tracking algorithm, Measurement Science and Technology **21**, 115401 (2010).
- [12] N. Wiener, *Extrapolation, Interpolation, and Smoothing of Stationary Time Series* (MIT Press, Cambridge, MA, 1949).
- [13] P. Wang, S. Pei, M. Wang, Y. Yan, X. Sun, and J. Zhang, Study on the transformation from linear to branched wormlike micelles: An insight from molecular dynamics simulation, Journal of Colloid and Interface Science **494**, 47 (2017).