

Python Objects and Classes

Estimated time needed: 10 minutes

Objectives

In this reading, you will learn about:

- Fundamental concepts of Python objects and classes.
- Structure of classes and object code.
- Real-world examples related to objects and classes.

Introduction to classes and object

Python is an object-oriented programming (OOP) language that uses a paradigm centered around objects and classes.

Let's look at these fundamental concepts.

Classes

A class is a blueprint or template for creating objects. It defines the structure and behavior that its objects will have.

Think of a class as a cookie cutter and objects as the cookies cut from that template.

In Python, you can create classes using the `class` keyword.

Creating classes

When you create a class, you specify the `attributes` (data) and `methods` (functions) that objects of that class will have.

`Attributes` are defined as variables within the class, and `methods` are defined as functions.

For example,you can design a "Car" class with attributes such as "color" and "speed," along with methods like "accelerate."

Objects

An *object* is a fundamental unit in Python that represents a real-world entity or concept.

Objects can be tangible (like a car) or abstract (like a student's grade).

Every object has two main characteristics:

State

The *attributes* or *data* that describe the object. For your "Car" object, this might include attributes like "color", "speed", and "fuel level".

Behavior

The *actions* or *methods* that the object can perform. In Python, methods are functions that belong to objects and can change the object's state or perform specific operations.

Instantiating objects

- Once you've defined a class, you can create individual objects (instances) based on that class.
- Each object is independent and has its own set of attributes and methods.
- To create an object, you use the class name followed by parentheses, so: "my_car = Car()

Interacting with objects

You interact with objects by calling their methods or accessing their attributes using dot notation.

For example, if you have a Car object named **my_car**, you can set its color with **my_car.color = "blue"** and accelerate it with **my_car.accelerate()** if there's an accelerate method defined in the class.

Structure of classes and object code

Please don't directly copy and use this code because it is a template for explanation and not for specific results.

Class declaration (class ClassName)

- The `class` keyword is used to declare a class in Python.
- `ClassName` is the name of the class, typically following CamelCase naming conventions.

```
1 class ClassName:
```

Class attributes (class_attribute = value)

- Class attributes are variables shared among all class instances (objects).
- They are defined within the class but outside of any methods.

```
1 class ClassName:
2     # Class attributes (shared by all instances)
3     class_attribute = value
```

Constructor method (def init(self, attribute1, attribute2, ...):)

- The `__init__` method is a special method known as the constructor.
- It initializes the **instance attributes** (also called instance variables) when an object is created.
- The `self` parameter is the first parameter of the constructor, referring to the instance being created.
- attribute1, attribute2**, and so on are parameters passed to the constructor when creating an object.
- Inside the constructor, `self.attribute1` , `self.attribute2` , and so on are used to assign values to instance attributes.

```
1 class ClassName:
2     # Class attributes (shared by all instances)
3     class_attribute = value
4
5     # Constructor method (initialize instance attributes)
6     def __init__(self, attribute1, attribute2, ...):
7         pass
8     # ...
```

Instance attributes (self.attribute1 = attribute1)

- Instance attributes are variables that store data specific to each class instance.
- They are initialized within the `__init__` method using the self keyword followed by the attribute name.
- These attributes hold unique data for each object created from the class.

```
1 class ClassName:
2     # Class attributes (shared by all instances)
3     class_attribute = value
4
5     # Constructor method (initialize instance attributes)
6     def __init__(self, attribute1, attribute2, ...):
7         self.attribute1 = attribute1
8         self.attribute2 = attribute2
9     # ...
```

Instance methods (def method1(self, parameter1, parameter2, ...):)

- Instance methods are functions defined within the class.
- They operate on the instance's data (instance attributes) and can perform actions specific to instances.
- The `self` parameter is required in instance methods, allowing them to access instance attributes and call other methods within the class.

```
1 class ClassName:
2     # Class attributes (shared by all instances)
3     class_attribute = value
4
5     # Constructor method (initialize instance attributes)
6     def __init__(self, attribute1, attribute2, ...):
7         self.attribute1 = attribute1
8         self.attribute2 = attribute2
9     # ...
10
11     # Instance methods (functions)
12     def method1(self, parameter1, parameter2, ...):
13         # Method logic
14         pass
```

Using the same steps you can define multiple instance methods.

```
1 class ClassName:
2     # Class attributes (shared by all instances)
3     class_attribute = value
4
5     # Constructor method (initialize instance attributes)
6     def __init__(self, attribute1, attribute2, ...):
7         self.attribute1 = attribute1
8         self.attribute2 = attribute2
9     # ...
10
11     # Instance methods (functions)
12     def method1(self, parameter1, parameter2, ...):
13         # Method logic
14         pass
15
16     def method2(self, parameter1, parameter2, ...):
17         # Method logic
18         pass
```

Note: Now, you have successfully created a dummy class.

Creating objects (Instances)

- To create objects (instances) of the class, you call the class like a function and provide arguments the constructor requires.
- Each object is a distinct instance of the class, with its own instance attributes and the ability to call methods defined in the class.

```
1 # Create objects (instances) of the class
2 object1 = ClassName(arg1, arg2, ...)
3 object2 = ClassName(arg1, arg2, ...)
```

Calling methods on objects

- In this section, you will call methods on objects, specifically `object1` and `object2` .
- The methods **method1** and **method2** are defined in the `ClassName` **class**, and you're calling them on **object1** and **object2** respectively.
- You pass values **param1_value** and **param2_value** as arguments to these methods. These arguments are used within the method's logic.

Method 1: Using dot notation

- This is the most straightforward way to call an object's method. In this, use the dot notation (**object.method()**) to invoke the method on the object directly.
- For example, `result1 = object1.method1(param1_value, param2_value, ...)` calls method1 on object1.

```
1 # Calling methods on objects
2 # Method 1: Using dot notation
3 result1 = object1.method1(param1_value, param2_value, ...)
4 result2 = object2.method2(param1_value, param2_value, ...)
```

Method 2: Assigning object methods to variables

- Here's an alternative way to call an object's method by assigning the method reference to a variable.
- `method_reference = object1.method1` assigns the method **method1** of **object1** to the variable **method_reference**.
- Later, call the method using the variable like this: `result3 = method_reference(param1_value, param2_value, ...)`.

```
1 # Method 2: Assigning object methods to variables
2 method_reference = object1.method1 # Assign the method to a variable
3 result3 = method_reference(param1_value, param2_value, ...)
```

Accessing object attributes

- Here, you are accessing an object's attribute using dot notation.
- `attribute_value = object1.attribute1` retrieves the value of the attribute **attribute1** from **object1** and assigns it to the variable **attribute_value**.

```
1 # Accessing object attributes
2 attribute_value = object1.attribute1 # Access the attribute using dot notation
```

Modifying object attributes

- You will modify an object's attribute using dot notation.
- `object1.attribute2 = new_value` sets the attribute **attribute2** of **object1** to the new value **new_value**.

```
1 # Modifying object attributes
2 object1.attribute2 = new_value # Change the value of an attribute using dot notation
```

Accessing class attributes (shared by all instances)

- Finally, access a class attribute shared by all class instances.
- `class_attr_value = ClassName.class_attribute` accesses the class attribute `class_attribute` from the `ClassName` `class` and assigns its value to the variable `class_attr_value` .

```
1 # Accessing class attributes (shared by all instances)
2 class_attr_value = ClassName.class_attribute
```

Real-world example

Let's write a python program that simulates a simple car class, allowing you to create car instances, accelerate them, and display their current speeds.

1. Let's start by defining a `Car` class that includes the following attributes and methods:

- Class attribute `max_speed` , which is set to **120 km/h**.
- Constructor method `__init__` that takes parameters for the car's **make, model, color, and an optional speed (defaulting to 0)**. This method initializes instance attributes for make, model, color, and speed.
- Method `accelerate(self, acceleration)` that allows the car to accelerate. If the acceleration does not exceed the `max_speed` , update the car's **speed** attribute. Otherwise, set the speed to the **max_speed**.
- Method `get_speed(self)` that returns the current speed of the car.

```
1 class Car:
2     # Class attribute (shared by all instances)
3     max_speed = 120 # Maximum speed in km/h
4
5     # Constructor method (initialize instance attributes)
6     def __init__(self, make, model, color, speed=0):
7         self.make = make
8         self.model = model
9         self.color = color
10        self.speed = speed # Initial speed is set to 0
11
12    # Method for accelerating the car
13    def accelerate(self, acceleration):
14        if self.speed + acceleration <= Car.max_speed:
15            self.speed += acceleration
16        else:
17            self.speed = Car.max_speed
18
19    # Method to get the current speed of the car
20    def get_speed(self):
21        return self.speed
```

2. Now, you will instantiate two objects of the `Car` class, each with the following characteristics:

- car1: **Make = "Toyota", Model = "Camry", Color = "Blue"**
- car2: **Make = "Honda", Model = "Civic", Color = "Red"**

```
1 # Create objects (instances) of the Car class
2 car1 = Car("Toyota", "Camry", "Blue")
3 car2 = Car("Honda", "Civic", "Red")
```

3. Using the `accelerate` method, you will increase the speed of car1 by 30 km/h and car2 by 20 km/h.

```
1 # Accelerate the cars
2 car1.accelerate(30)
3 car2.accelerate(20)
```

4. Lastly, you will display the current speed of each car by utilizing the `get_speed` method.

```
1 # Print the current speeds of the cars
2 print(f"{car1.make} {car1.model} is currently at {car1.get_speed()} km/h.")
3 print(f"{car2.make} {car2.model} is currently at {car2.get_speed()} km/h.")
```

Next steps

In conclusion, this reading provides a fundamental understanding of objects and classes in Python, essential concepts in object-oriented programming. Classes serve as blueprints for creating objects, encapsulating data attributes and methods. Objects represent real-world entities and possess their unique state and behavior. The structured code example presented in the reading outlines the key elements of a class, including class attributes, the constructor method for initializing instance attributes, and instance methods for defining object-specific functionality.

In the upcoming laboratory session, you can apply the concepts of objects and classes to gain hands-on experience.

Author

Akansha Yadav