⊘ Correct

The letter 'e' appears 20 times in the quote.

Your latest: 100% • Your highest: 100% • To pass you need at least 70%. We keep your highest score.

	Which of the following expressions corresponds to a dictionary with no elements?	1/1 point
	✓ dict()	
	⊘ Correct	
	✓ {}	
	⊘ Correct	
	□ None	
	Given an existing dictionary favorites , what Python statement adds the key "fruit" to this dictionary with the corresponding value "blackberry" ?	1/1 point
	O favorites = {"fruit" : "blackberry"}	
	<pre>favorites["fruit"] = "blackberry"</pre>	
	<pre>favorites["fruit" = "blackberry"]</pre>	
	<pre>favorites["fruit" : "blackberry"]</pre>	
	<pre>favorites{"fruit" : "blackberry"}</pre>	
	⊘ Correct	
	Which of the expressions below returns True when the dictionary my_dictionary contains the key	1/1 point
	my_key and False otherwise?	
	wy_key in my_dictionary	
	⊘ Correct	
	my_dictionary.key(my_key)	
	my_dictionary.has_key(my_key)	
	my_dictionary[my_key]	
	Kove in a distinguity can have which of the following types?	1 / 1 noint
•	Keys in a dictionary can have which of the following types? ✓ tuple	1/1 point
	✓ Correct Tuples are immutable. Use them in place of lists as keys.	
	✓ string	
	⊘ Correct	
	Strings are immutable.	
	✓ int	
	⊘ Correct	
	Integers are immutable.	
	□ list	
•	Values in a dictionary can have which of the following types?	1/1 point
	✓ string	
	⊘ Correct	
	✓ tuple	
	⊘ Correct	
	✓ bool	
	⊘ Correct	
	✓ dict	
	⊘ Correct	
	Consider the following dictionary:	1/1 point
•	1 instructor_ratings = {"Joe" : "awesome", "Scott" : "hmmm"}	1/1 point
	What happens when Python evaluates the expression instructor_ratings["John"]?	
	Since "John" is not a key in the dictionary, Python raises a KeyError exception.	
	O Python returns the value None since "John" is not a key in the dictionary.	
	Since " John" is not a key in the dictionary. Bythen raises a syntax error	
	 Since "John" is not a key in the dictionary, Python raises a syntax error. Since "John" is not a value in the dictionary, Python raises a KeyError exception. 	
	 Since "John" is not a key in the dictionary, Python raises a syntax error. Since "John" is not a value in the dictionary, Python raises a KeyError exception. ✓ Correct 	
	Since "John" is not a value in the dictionary, Python raises a KeyError exception.	
	 Since "John" is not a value in the dictionary, Python raises a KeyError exception. ✓ Correct 	
•	Since "John" is not a value in the dictionary, Python raises a KeyError exception.	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ✓ Correct Write a function count_letters (word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in	1/1 point
•	 Since "John" is not a value in the dictionary, Python raises a KeyError exception. ✓ Correct Write a function count_letters (word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently 	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ⊘ correct Write a function count_letters (word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of	1/1 point
•	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ⊘ Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary	1/1 point
•	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ⊘ Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """	1/1 point
•	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ○ Correct Write a function count_letters (word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz"	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ✓ Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET:	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ⊘ correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 def count_letters(word_list): 1 def count_letters(word_list): 2 letter_count = {} }	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET: 8 letter_count[letter] = 0	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. Ocorrect Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. def count_letters(word_list):	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ⊘ Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1	1/1 point
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. Ocorrect Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmmopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET: 8 letter_count[letter] = 0 9 up the enter code here Complete your implementation of count_letters based on this snippet. As a test, count_letters(["hello", "world"]) should return the letter 'l' since 'l' appears 3 times total in the strings "hello" and "world". When you are confident in your code, compute the lower case letter return by	1/1 point
	O Since "John" is not a value in the dictionary, Python raises a KeyError exception. O Correct Write a function count_letters (word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 4	
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ② Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET: 8 letter_count[letter] = 0 9 # enter code here Complete your implementation of count_letters based on this snippet. As a test, count_letters(["hello", "world"]) should return the letter '1' since '1' appears 3 times total in the strings "hello" and "world". When you are confident in your code, compute the lower case letter return by count_letters(monty_words) where monty_words is defined as shown.	
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ② Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1	
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ② Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET: 8 letter_count[letter] = 0 9 # enter code here Complete your implementation of count_letters based on this snippet. As a test, count_letters(["hello", "world"]) should return the letter '1' since '1' appears 3 times total in the strings "hello" and "world". When you are confident in your code, compute the lower case letter return by count_letters(monty_words) where monty_words is defined as shown.	
	Since "John" is not a value in the dictionary, Python raises a KeyError exception. ② Correct Write a function count_letters(word_list) that takes as input a list of words that are composed entirely of lower case letters. This function should return the lower case letter that appears most frequently (total number of occurrences) in the words in word_list. (In the case of ties, return the earliest letter in alphabetical order.) The Python code snippet below represents a start at implementing count_letters using a dictionary letter_count whose keys are the lower case letters and whose values are the corresponding number of occurrences of each letter in the strings in word_list. 1 def count_letters(word_list): 2 """ See question description """ 3 ALPHABET = "abcdefghijklmnopqrstuvwxyz" 5 letter_count = {} 6 letter_count = {} 7 for letter in ALPHABET: 8 letter_count[letter] = 0 9 # enter code here Complete your implementation of count_letters based on this snippet. As a test, count_letters(["hello", "world"]) should return the letter '1' since '1' appears 3 times total in the strings "hello" and "world". When you are confident in your code, compute the lower case letter return by count_letters(monty_words) where monty_words is defined as shown.	