





■ Menu

Putting It Together

Putting it Together

First, pick a network architecture; choose the layout of your neural network, including how many hidden units in each layer and how many layers in total you want to have.

- Number of input units = dimension of features $\boldsymbol{x}^{(i)}$
- Number of output units = number of classes
- Number of hidden units per layer = usually more the better (must balance with cost of computation as it increases with more hidden units)
- Defaults: 1 hidden layer. If you have more than 1 hidden layer, then it is recommended that you have the same number of units in every hidden layer.


Training a Neural Network

- 1. Randomly initialize the weights
- 2. Implement forward propagation to get $h_{\Theta}(x^{(i)})$ for any $x^{(i)}$
- 3. Implement the cost function
- 4. Implement backpropagation to compute partial derivatives
- 5. Use gradient checking to confirm that your backpropagation works. Then disable gradient checking.
- 6. Use gradient descent or a built-in optimization function to minimize the cost function with the weights in theta.

When we perform forward and back propagation, we loop on every training example:

```
for i = 1:m,
Perform forward propagation and backpropagation using example (x(i),y(i))
(Get activations a(l) and delta terms d(l) for l = 2,...,L
```

The following image gives us an intuition of what is happening as we are implementing our neural network:



Ideally, you want $h_{\Theta}(x^{(i)}) \approx y^{(i)}$. This will minimize our cost function. However, keep in mind that $J(\Theta)$ is not convex and thus we can end up in a local minimum instead.

Go to next item

