Seamless API (1.0.0)

Download OpenAPI specification: Download

Terms of Service

Privacy Policy

In order to dramatically improve our offerings to customers, Seamless will be introducing a Public API which can be used to search Companies & Contacts, Enrich Lists, and offer integrations as an Endpoint for our
customers.

The API is build using RESTful principles and is secured using OAuth 2.0 with the implicit grant flow.

Authentication

API Key

1. Register Your Application

To use the Seamless API, you need to register your application to obtain an API key.
To create a new API key, go to Seamless.AI | Settings > API Key and click the *Create New Connection* button.
Note: The Public API Connections menu will only appear if your account has access to the Public API.

2. Use the Access Token

For all authenticated API requests, include the API key in the header:

```
Token: API_KEY
```

OAuth 2.0

1. Register Your Application

Before integrating, you have to setup your client credentials.

To create a new API client, go to Seamless.AI | Settings > OAuth Connections, and click the *Create New Connection* button.

Note: The Public API Connections menu will only appear if your account has access to the Public API.

- `client_id`
- `client_secret`
- `redirect_uri`

You'll use these to authenticate and obtain tokens.

---

2. Obtain Authorization Code

Redirect the user to Seamless.AI's OAuth authorization endpoint:

```
GET https://login.seamless.ai/oauth/authorize
```

Query Parameters:

Name	Description
`client_id`	Your client ID
`redirect_uri`	The URL users are redirected to
`state`	(Optional) CSRF protection string

Example URL:

```
GET https://login.seamless.ai/oauth/authorize?client_id=YOUR_CLIENT_ID&redirect_ur
```

Once the user authenticates, they will be redirected to your `redirect_uri` with a `code` parameter. If your `redirect_uri` contains any query parameters (such as `?foo=bar`), you must URL encode your

`redirect_uri` for this step.

---

3. Exchange Code for Access Token

```
POST https://api.seamless.ai/api/client/v1/oauth/accessToken
```

Request Body (JSON):

```
{
  "client_id": "YOUR_CLIENT_ID",
  "client_secret": "YOUR_CLIENT_SECRET",
  "redirect_uri": "https://yourapp.com/callback",
  "grant_type": "authorization_code",
  "code": "AUTHORIZATION_CODE_FROM_STEP_2"
}
```

Response:

```
{
  "access_token": "ACCESS_TOKEN",
  "refresh_token": "REFRESH_TOKEN",
  "expires_at": 1712000000
}
```

---

4. Use the Access Token

For all authenticated API requests, include the token in the header:

```
Authorization: Bearer ACCESS_TOKEN
```

---

5. Refreshing the Token

To refresh the access token:

```
POST https://api.seamless.ai/api/client/v1/oauth/accessToken
```

Request Body:

```
{
  "client_Id": "YOUR_CLIENT_ID",
  "client_secret": "YOUR_CLIENT_SECRET",
  "redirect_uri": "https://yourapp.com/callback",
  "grant_type": "refresh_token",
  "refresh_token": "YOUR_REFRESH_TOKEN"
}
```

Rate Limiting

The limit is currently around 100 requests per 60 seconds per Endpoint. You will receive a 429 HTTP response if you exceed the rate limit.

Rate limit and remaining credits information will be returned in the response header of each request. The parameters are:

Name	Example	Description
`X-RateLimit-Limit`	100	The maximum number of requests you're permitted to make in a given time period.
`X-RateLimit-Remaining`	55	The number of requests remaining in the current rate limit window.
`X-RateLimit-Reset`	1745587198	The time at which the current rate limit window resets in epoch seconds.
`X-PublicAPI-Credits`	1000	The number of credits remaining that can be used in requests.

OAuth

Get an access token

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json

client_id	string
client_secret	string
redirect_uri	string
grant_type required	string Enum: "authorization_code" "refresh_token"
code	string Required if grant_type is authorization_code
refresh_token	string Required if grant_type is refresh_token

Responses

- **200** The access token
- **401** Unauthorized
- **422** Insufficient credits or missing license
- **500** Unexpected error

POST /oauth/accessToken

Request samples

Payload

Content type

application/json

Copy

```
{
    "client_id": "string",
    "client_secret": "string",
    "redirect_uri": "string",
    "grant_type": "authorization_code",
    "code": "string",
    "refresh_token": "string"
}
```

Response samples

200 401 422 500

Content type
application/json

Copy

```
{
    "access_token": "string",
    "expires_at": 0,
    "refresh_token": "string"
}
```

Contact Search

Search contacts

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json
required

~~page~~
integer
Deprecated
Default: `1`
The page number to retrieve.

---

nextToken
string
Default: `null`
The next token for pagination.

---

limit
integer
Default: `50`
The number of contacts per page.

---

companyName
Array of strings <= 100 items
Contact company name search filter.

---

companyNameSearchType
string
Default: `"default"`
Enum: `"default"` `"related"` `"exact"`
The type of search to perform on the company name.

---

companyDomain
Array of strings <= 100 items
Contact company domain search filter.

---

contactState
Array of strings <= 10 items
Contact or Company state search filter.

---

contactCountry
Array of strings <= 10 items
Contact or Company country search filter.

---

contactZipCode
Array of strings <= 10 items
Contact or Company zipcode search filter.

---

locationType
string
Default: `"bothOR"`
Enum: `"bothOR"` `"bothAND"` `"company"` `"contact"`
You can search by contacts' location(contact), the companies' location(company), both Contact And company(bothAND), or both contact Or company(bothOR).

---

department
Array of strings <= 5 items
Items Enum: `"Sales"` `"Marketing"` `"Engineering"` `"Human Resources"` `"Finance"` `"IT"` `"Engineering"` `"Operations"` `"Support"` `"Legal"` `"Project Management"` `"Other"`
Contact department search filter.

`industry`
Array of strings <= 5 items
Contact industry search filter.

`fullname`
Array of strings <= 10 items
Contact fullname search filter.

`contactKeyword`
Array of strings <= 10 items
Contact keyword search filter.

`jobTitle`
Array of strings <= 10 items
Contact job title search filter.

`seniority`
Array of strings <= 5 items
Items Enum: `"C-Level"` `"VP"` `"Director"` `"Manager"` `"Senior"` `"Entry Level"` `"Mid-Level"` `"Other"`
Contact seniority search filter.

`companyFoundedOn`
Array of strings <= 4 items
Items Enum: `"Less than 1 Year"` `"Last 1-3 Years"` `"Last 4-10 Years"` `"10+ Years"`
Range of years since the company was founded.

`lastModifiedAfter`
string <date>
Filter on the lastModifiedAt(The last time the name, title, company, phone, or email changed).

`lastModifiedBefore`
string <date>
Filter on the lastModifiedAt(The last time the name, title, company, phone, or email changed).

Responses

- **200** Contact Search Results
- **401** Unauthorized
- **422** Insufficient credits or missing license
- **500** Unexpected error

POST /search/contacts

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all


```
{
    "page": 1,
    "nextToken": null,
    "limit": 50,
  - "companyName": [
        "Seamless.AI"
    ],
    "companyNameSearchType": "default",
    "companyDomain": [ ],
    "contactState": [ ],
    "contactCountry": [ ],
    "contactZipCode": [ ],
    "locationType": "bothOR",
    "department": [ ],
    "industry": [ ],
    "fullname": [ ],
    "contactKeyword": [ ],
    "jobTitle": [ ],
    "seniority": [ ],
  - "companyFoundedOn": [
        "Less than 1 Year",
        "Last 1-3 Years"
    ],
    "lastModifiedAfter": "2025-09-01T11:00:00Z",
    "lastModifiedBefore": "2025-09-07T11:00:00Z"
}
```


Response samples

200 401 422 500

Content type

application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
 - "supplementalData": {
       "isMore": true,
       "total": 0,
       "perPage": 0,
       "nextToken": "string"
   }
}
```

Company Search

Search companies

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json
required

~~page~~	integer Deprecated Default: `1` The page number to retrieve.
nextToken	string Default: `null` The next token for pagination.

`limit`
integer
Default: `50`
The number of contacts per page.

`companyName`
Array of strings `<= 100 items`
Company name search filter.

`companyNameSearchType`
string
Default: `"default"`
Enum: `"default"` `"related"` `"exact"`
The type of search to perform on the company name.

`companyDomain`
Array of strings `<= 100 items`
Company domain search filter.

`companyState`
Array of strings `<= 10 items`
Company state search filter.

`companyCountry`
Array of strings `<= 10 items`
Company country search filter.

`companyZipCode`
Array of strings `<= 10 items`
Company zipcode search filter.

`companyStreet`
Array of strings `<= 10 items`
Company street search filter.

`industry`
Array of strings `<= 5 items`
Company industry search filter.

`companyKeyword`
Array of strings `<= 10 items`
Company keyword search filter.

`companySize`
Array of strings `<= 10 items`
Items Enum: `"0 - 1 (Self-employed)"` `"2 - 10"` `"11 - 50"` `"51 - 200"` `"201 - 500"` `"501 - 1,000"` `"1,001 - 5,000"` `"5,001 - 10,000"` `"10,001+"`
Company size search filter.

`companyRevenue`
Array of strings `<= 10 items`
Items Enum: `"$0 - $100K"` `"$100K - $1M"` `"$1M - $5M"` `"$5M - $20M"` `"$20M - $50M"` `"$50M - $100M"` `"$100M - $500M"` `"$500M - $1B"` `"$1B+"`
Company revenue search filter.

`technologies`	Array of strings `<= 10 items` Company technologies search filter.
`foundedOn`	Array of strings `<= 4 items` Items Enum: `"Less than 1 Year"` `"Last 1-3 Years"` `"Last 4-10 Years"` `"10+ Years"` Range of years since the company was founded.

Responses

- **200** Company Search Results
- **401** Unauthorized
- **422** Insufficient credits or missing license
- **500** Unexpected error

POST `/search/companies`

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "page": 1,
    "nextToken": null,
    "limit": 50,
  - "companyName": [
        "Seamless AI"
    ],
    "companyNameSearchType": "default",
    "companyDomain": [ ],
```

```
    "companyState": [ ],
    "companyCountry": [ ],
    "companyZipCode": [ ],
    "companyStreet": [ ],
    "industry": [ ],
    "companyKeyword": [ ],
    "companySize": [ ],
    "companyRevenue": [ ],
    "technologies": [ ],
  - "foundedOn": [
        "Less than 1 Year",
        "Last 1-3 Years"
    ]
}
```

Response samples

200 401 422 500

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
  - "supplementalData": {
        "isMore": true,
        "total": 0,
        "perPage": 0,
        "nextToken": "string"
    }
}
```

Contact Research

Researched Contact Webhook Webhook

Pushes the results of a company research request.
To create a webhook, go to Seamless.AI | Settings > Webhooks and click the Create New Webhook button and select Contact Research as the type.

AUTHORIZATIONS: > *webhookSecret*

REQUEST BODY SCHEMA: application/json

`username`	string
`createdAt`	string
`updatedAt`	string
`firstName`	string
`middleName`	string
`lastName`	string
`fullName`	string
`name`	string
`nameOriginal`	string
`email`	string
`personalEmail`	string
`phone`	string
`contactPhone1`	string
`contactPhone1DataType`	string
`contactPhone1TotalAI`	string
`companyPhone1`	string
`companyPhone1DataType`	string

companyPhone1TotalAI	string
company	string
companyOriginal	string
companyIndustry	string
companyStaffCount	integer
companyStaffCountRange	string
companyAnnualRevenue	string
companyDomain	string
companyRevenueRange	string
companyLIProfileUrl	string
companyLinkedInId	string
title	string
lIProfileUrl	string
lISalesNavUrl	string
lIRecruiterUrl	string
contactLocation >	object
companyLocation >	object
website	string
email1	string
email1Selected	boolean
email1TotalAI	string
email1EmailAI	string
email2	string

email2TotalAI	string
email2EmailAI	string
email3	string
email3TotalAI	string
email3EmailAI	string
jobHistory >	Array of objects Contact's job history (requires Job Changes feature flag access)
apiResearchId	string The Id return from the /contacts/research endpoint

Responses

— **2XX** Return a 2XX status to indicate that the data was received successfully

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "username": "string",
    "createdAt": "string",
    "updatedAt": "string",
    "firstName": "string",
    "middleName": "string",
    "lastName": "string",
    "fullName": "string",
    "name": "string",
```

```
    "nameOriginal": "string",
    "email": "string",
    "personalEmail": "string",
    "phone": "string",
    "contactPhone1": "string",
    "contactPhone1DataType": "string",
    "contactPhone1TotalAI": "string",
    "companyPhone1": "string",
    "companyPhone1DataType": "string",
    "companyPhone1TotalAI": "string",
    "company": "string",
    "companyOriginal": "string",
    "companyIndustry": "string",
    "companyStaffCount": 0,
    "companyStaffCountRange": "string",
    "companyAnnualRevenue": "string",
    "companyDomain": "string",
    "companyRevenueRange": "string",
    "companyLIProfileUrl": "string",
    "companyLinkedInId": "string",
    "title": "string",
    "lIProfileUrl": "string",
    "lISalesNavUrl": "string",
    "lIRecruiterUrl": "string",
  - "contactLocation": {
        "city": "string",
        "state": "string",
        "postCode": "string",
        "county": "string",
        "country": "string",
        "stateAbbr": "string",
        "countryAbbr": "string",
        "countryAlpha2": "string",
        "countryAlpha3": "string",
        "countryNumeric": "string",
        "fullString": "string",
        "timezone": "string",
        "timezoneRawOffset": "string",
        "timezoneAbbr": "string"
    },
```

```
  - "companyLocation": {
        "street1": "string",
        "street2": "string",
        "street3": "string",
        "city": "string",
        "state": "string",
        "postCode": "string",
        "county": "string",
        "country": "string",
        "stateAbbr": "string",
        "countryAbbr": "string",
        "countryAlpha2": "string",
        "countryAlpha3": "string",
        "countryNumeric": "string",
        "fullString": "string"
    },
    "website": "string",
    "email1": "string",
    "email1Selected": true,
    "email1TotalAI": "string",
    "email1EmailAI": "string",
    "email2": "string",
    "email2TotalAI": "string",
    "email2EmailAI": "string",
    "email3": "string",
    "email3TotalAI": "string",
    "email3EmailAI": "string",
  - "jobHistory": [
     + { … }
    ],
    "apiResearchId": "string"
}
```

Research contacts

Research contacts by searchResultId from contact search results or Contact enrich

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json
required

`searchResultIds`	Array of strings <= 100 items The search result IDs to research
`isJobChange`	boolean
`contacts >`	Array of objects <= 100 items Contact enrich, must include one of the following properties: • contactName and companyName (optional title for Job Changes) • contactName and domain • email • liProfileUrl • liSalesNavUrl • liRecruiterUrl When isJobChange flag is set to true, searchResultIds should not be used.

Responses

> **202** The request IDs for research

> **401** Unauthorized

> **422** Insufficient credits or missing license

> **500** Unexpected error

POST `/contacts/research`

Request samples

Payload

Content type
application/json

Example

Example

Contact research via searchResultIds

Copy Expand all Collapse all

```
{
  - "searchResultIds": [
        "searchResultId1",
        "searchResultId2"
    ]
}
```

Response samples

202 401 422 500

Content type

application/json

Copy Expand all Collapse all

```
{
  - "requestIds": [
        "string"
    ]
}
```

Poll Contact Research

Get the results/status of a contact research request

AUTHORIZATIONS: > *OAuth2*

QUERY PARAMETERS

`requestIds` required	Array of strings [1 .. 100] items Example: `requestIds=1,2,3,4,5` The id of the research request.

Responses

> **200** Poll Results

> **401** Unauthorized

> **422** Insufficient credits or missing license

> **500** Unexpected error

GET /contacts/research/poll

Response samples

200 401 422 500

Content type
application/json

Copy Expand all Collapse all

```
{
    "success": true,
  - "data": [
      + { … }
    ]
}
```

Company Research

Researched Company Webhook Webhook

Pushes the results of a company research request.
To create a webhook, go to Seamless.AI | Settings > Webhooks and click the Create New Webhook button

and select Company Research as the type.

AUTHORIZATIONS: > *webhookSecret*

REQUEST BODY SCHEMA: application/json

`advertisingIntelligenceUrl`	string
`alexaScoreUrl`	string
`annualRevenue`	string
`apiResearchId`	string The API research identifier for companies created through API research
`phones`	string
`phonesAiScores`	string
`createdAt`	string
`description`	string
`domain`	string
`employeeReviewsUrl`	string
`foundedOn`	string
`googleFinanceUrl`	string
`googleResearchUrl`	string
`industries`	string
`intelUrl`	string
`jobPostingsUrl`	string
`linkedInProfileUrl`	string
`linkedInId`	string
`localSportsTeamsUrl`	string

localWeatherUrl	string
location >	object
name	string
newsUrl	string
paidSearchIntelligenceUrl	string
paidSearchKeywordsIntelligenceUrl	string
revenueRange	string
searchMarketingIntelligenceUrl	string
secFilingsUrl	string
seoResearchUrl	string
sicCode	string
similarWebsitesUrl	string
socialMediaMentionsUrl	string
socialMediaPostsUrl	string
socialPostsUrl	string
staffCount	string
staffCountRange	string
topTechnologies	string
updatedAt	string
webTechnologiesUrl	string
websiteAuditUrl	string
websiteAudit2Url	string
websiteGraderUrl	string

`whoisUrl`	string
`wikipediaUrl`	string
`yahooFinanceUrl`	string

Responses

— **2XX** Return a 2XX status to indicate that the data was received successfully

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "advertisingIntelligenceUrl": "string",
    "alexaScoreUrl": "string",
    "annualRevenue": "string",
    "apiResearchId": "research-123",
    "phones": "string",
    "phonesAiScores": "string",
    "createdAt": "2024-04-21T14:30:00.000Z",
    "description": "string",
    "domain": "string",
    "employeeReviewsUrl": "string",
    "foundedOn": "string",
    "googleFinanceUrl": "string",
    "googleResearchUrl": "string",
    "industries": "string",
    "intelUrl": "string",
    "jobPostingsUrl": "string",
    "linkedInProfileUrl": "string",
```

```
        "linkedInId": "string",
        "localSportsTeamsUrl": "string",
        "localWeatherUrl": "string",
      - "location": {
            "street1": "string",
            "city": "string",
            "state": "string",
            "postCode": "string",
            "country": "string",
            "countryAbbr": "string",
            "countryAlpha2": "string",
            "countryAlpha3": "string",
            "fullString": "string"
        },
        "name": "string",
        "newsUrl": "string",
        "paidSearchIntelligenceUrl": "string",
        "paidSearchKeywordsIntelligenceUrl": "string",
        "revenueRange": "string",
        "searchMarketingIntelligenceUrl": "string",
        "secFilingsUrl": "string",
        "seoResearchUrl": "string",
        "sicCode": "string",
        "similarWebsitesUrl": "string",
        "socialMediaMentionsUrl": "string",
        "socialMediaPostsUrl": "string",
        "socialPostsUrl": "string",
        "staffCount": "string",
        "staffCountRange": "string",
        "topTechnologies": "string",
        "updatedAt": "2024-04-21T14:30:00.000Z",
        "webTechnologiesUrl": "string",
        "websiteAuditUrl": "string",
        "websiteAudit2Url": "string",
        "websiteGraderUrl": "string",
        "whoisUrl": "string",
        "wikipediaUrl": "string",
        "yahooFinanceUrl": "string"
    }
```

Research companies

Research companies by searchResultId from company search results

AUTHORIZATIONS: > *OAuth2*

REQUEST BODY SCHEMA: application/json
required

`searchResultIds`	Array of strings <= 100 items
`companies` >	Array of objects <= 100 items Must include one of the following properties: • domain • companyName

Responses

> **202** The request IDs for research

> **401** Unauthorized

> **422** Insufficient credits or missing license

> **500** Unexpected error

POST `/companies/research`

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "searchResultIds": [
        "string"
    ],
  - "companies": [
      + { … }
    ]
}
```

Response samples

202 401 422 500

Content type
application/json

Copy Expand all Collapse all

```
{
  - "requestIds": [
        "string"
    ]
}
```

Poll Company Research

Get the results/status of a company research

AUTHORIZATIONS: > *OAuth2*

QUERY PARAMETERS

`requestIds` required	Array of strings [1 .. 100] items Example: `requestIds=1,2,3,4,5` The id of the research request.

Responses

> **200** Poll Results

> **401** Unauthorized

> **422** Insufficient credits or missing license

> **500** Unexpected error

GET /companies/research/poll

Response samples

200 401 422 500

Content type
application/json

Copy Expand all Collapse all

```
{
 - "data": {
      "requestId": "string",
      "status": "string",
    + "results": [ … ]
   }
}
```

Org Contacts

Get Org Contacts

Get a list of contacts from your orgs

AUTHORIZATIONS: > *OAuth2*

QUERY PARAMETERS

`page`	integer Default: `1` Example: `page=1` The page number to retrieve.
`limit`	integer `<= 500` Default: `500` Example: `limit=100` The number of results per page.
`startDate` required	string <date> Example: `startDate=2020-01-01T10:00:00Z` An ISO8601 date time string that defines the start date of the lookback period to return results from.
`endDate` required	string <date> Example: `endDate=2020-01-01T11:00:00Z` An ISO8601 date time string that defines the end date of the lookback period to return results from.

Responses

> **200** Contact Results

> **401** Unauthorized

> **422** Insufficient credits or missing license

> **500** Unexpected error

GET /contacts

Response samples

200 401 422 500

Content type

application/json

Copy Expand all Collapse all

```
{
 - "data": [
     + { … }
   ]
}
```

Org Companies

Get Org Companies

Get a list of companies from your orgs

AUTHORIZATIONS: > *OAuth2*

QUERY PARAMETERS

`page`	integer Default: `1` Example: `page=1` The page number to retrieve.
`limit`	integer <= 500 Default: `500` Example: `limit=100` The number of results per page.
`startDate` required	string <date> Example: `startDate=2020-01-01T10:00:00Z` An ISO8601 date time string that defines the start date of the lookback period to return results from.

endDate required	string <date> Example: `endDate=2020-01-01T11:00:00Z` An ISO8601 date time string that defines the end date of the lookback period to return results from.

Responses

- **200** Company Results
- **401** Unauthorized
- **422** Insufficient credits or missing license
- **500** Unexpected error

GET /companies

Response samples

200 401 422 500

Content type

application/json

Copy Expand all Collapse all

```
{
 - "data": [
     + { … }
   ]
}
```