

Sublime build(linux):

```
{
    "shell": true,
    "cmd": "g++ -std=c++17 '${file}' -o
    '${file_path}/${file_base_name}' &&
    '${file_path}/${file_base_name}' < input.txt >
    output.txt",
    "working_dir": "${file_path}",
    "selector": "source.cpp"
}
```

Windows:

```
{
    "cmd": ["g++.exe",
    "-std=c++17", "${file}",
    "-o",
    "${file_base_name}.exe",
    "&&",
    "${file_base_name}.exe<input.txt>output.txt"],
    "shell": true,
    "working_dir": "${file_path}",
    "selector": "source.cpp"
}
```

Nothing

```
#pragma GCC optimize("Ofast")
ios_base::sync_with_stdio(false), cin.tie(NULL),
cout.tie(NULL);
#ifdef ONLINE_JUDGE
freopen("input.txt", "r",
stdin), freopen("output.txt", "w", stdout);
#endif
auto rd = []() { ll x; cin >> x; return x; };
#define dbg(x) cerr << "[" #x "]" = " << (x) << "\n"
"

mt19937_64 rnd((unsigned
int) chrono::steady_clock::now().time_since_epoch
().count());
int64_t Random(int64_t l, int64_t r) { return (l +
(rnd() % (r - l + 1))); }
```

$\sum \text{coprime of } (x) = (x \cdot \phi(x)) / 2.$

PBDS

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template <class T>
using OS = tree<T, null_type, less<T>,
rb_tree_tag,
tree_order_statistics_node_update>;
// to erase in multiset-> less_equal<T> and
// s.erase(s.find_by_order(s.order_of_key(x)))
// ll idx = s.order_of_key(x)
// if(idx == s.size()) -> no lower_bound
// else lb = *s.find_by_order(idx) // as
// 0-indexing
// idx-1 will give highest value which is strictly
// less than x
// for upper_bound->do the same with (x+1)
```

Custom cmp pbds:

```
struct cmp {bool operator() (const int &a, const
int
&b) {return a <= b;}};
typedef
tree<int, null_type, cmp, rb_tree_tag, tree_order_s
tatistics_node_update> ordered_set;
```

GP Hash Table

```
struct chash {
    static uint64_t splitmix64(uint64_t x)
    {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    int operator()(int x) const
    {
        static const uint64_t FIXED_RANDOM =
        chrono::steady_clock::now().time_since_epoch()
        .count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
gp_hash_table<ll, ll, chash> mp;
```

DSU

```
struct DSU{
    vector<int> p, rank, setSize;
    int numSets;
    DSU(int N)
    {
        p.assign(N, 0);
        iota(p.begin(), p.end(), 0);
        rank.assign(N, 0), setSize.assign(N, 1);
        numSets = N;
    }
    int findSet(int i) { return (p[i] == i) ? i : (p
    [i] =
    findSet(p[i])); }
    bool isSameSet(int i, int j) { return findSet(i)
    ==
    findSet(j); }
    int numDisjointSets() { return numSets; }
    int sizeOfSet(int i) { return setSize[findSet(i)
    ]; }
    void unionSet(int i, int j)
    {
        if (isSameSet(i, j))
            return;
        int x = findSet(i), y = findSet(j);
        if (rank[x] > rank[y])
            swap(x, y);
        p[x] = y;
        if (rank[x] == rank[y])
            ++rank[y];
        setSize[y] += setSize[x];
        --numSets;
    }
};
```

Fenwick Tree Point update and range query.

```
template<typename T>
struct BIT {
    int n;
    vector<T> bit;
    BIT(int n = 0) { init(n); }
    void init(int n_) { n = n_; bit.assign(n + 1, 0)
    ; }
    void add(int i, T v) { for (; i <= n; i += i & -
    i)
        bit[i] += v; }
    T sum(int i) { T r = 0; for (; i > 0; i -= i & -
    i) r
        += bit[i]; return r; }
    T sum(int l, int r) { return sum(r) - sum(l - 1)
    }
```

Persistent Segment Tree

```

struct PST {
    struct Node { int l, r, val; };
    vector<Node> t;
    int T = 0;
    PST(int max_nodes) { // estimate 20 * n for
        // max_nodes
        t.resize(max_nodes);
    }
    int build(int b, int e) {
        int cur = T++;
        if (b == e) return cur;
        int m = (b + e) / 2;
        t[cur].l = build(b, m);
        t[cur].r = build(m + 1, e);
        return cur;
    }
    int update(int pre, int b, int e, int i, int v)
    {
        int cur = T++;
        t[cur] = t[pre];
        if (b == e) {
            t[cur].val += v;
            return cur;
        }
        int m = (b + e) / 2;
        if (i <= m) t[cur].l = update(t[pre].l, b, m,
            i, v);
        else t[cur].r = update(t[pre].r, m + 1, e, i,
            v);
        t[cur].val = t[t[cur].l].val + t[t[cur].r].val;
        return cur;
    }
    int query(int pre, int cur, int b, int e, int k)
    {
        if (b == e) return b;
        int cnt = t[t[cur].l].val - t[t[pre].l].val;
        int m = (b + e) / 2;
        if (cnt >= k) return query(t[pre].l, t[cur].l,
            b, m, k);
        return query(t[pre].r, t[cur].r, m + 1, e, k -
            cnt);
    }
};

int main() {
    ios::sync_with_stdio(0); cin.tie(0);
    int n, q;
    cin >> n >> q;
    vector<int> a(n + 1), root(n + 1), V;
    map<int, int> comp;
    for (int i = 1; i <= n; i++) cin >> a[i],
        comp[a[i]];
    int id = 0;
    V.resize(comp.size() + 1);
    for (auto& [x, _] : comp) comp[x] = ++id, V[id]
        = x;
    PST pst(20 * (n + 1)); // Allocate enough space
    root[0] = pst.build(1, id);
    for (int i = 1; i <= n; i++)
        root[i] = pst.update(root[i - 1], 1, id,
            comp[a[i]], 1);
    while (q--) {
        int l, r, k;
        cin >> l >> r >> k;
        cout << V[pst.query(root[l - 1], root[r], 1,
            id,

```

```

        ; }
    };
};

```

Usage: BIT<ll> fenw(5);

//Fenwick 2D

```

struct BIT2D {
    int n, m;
    vector<vector<ll>> bit;
    BIT2D(int n, int m): n(n), m(m) {
        bit.assign(n + 1, vector<ll>(m + 1, 0));
    }
    void add(int x, int y, ll val) {
        for (int i = x; i <= n; i += i & -i)
            for (int j = y; j <= m; j += j & -j)
                bit[i][j] += val;
    }
    ll sum(int x, int y) {
        ll res = 0;
        for (int i = x; i > 0; i -= i & -i)
            for (int j = y; j > 0; j -= j & -j)
                res += bit[i][j];
        return res;
    }
    ll query(int x1, int y1, int x2, int y2) {
        return sum(x2, y2) - sum(x1 - 1, y2) - sum(x2,
            y1 - 1) + sum(x1 - 1, y1 - 1);
    }
};

BIT2D fenw2(4, 4);
fenw2.add(1, 1, 5);
fenw2.add(3, 2, 7);
cout << fenw2.query(1, 1, 3, 3) << "\n"; // sum
// inside rectangle [(1,1)-(3,3)]

```

Range update and range query.

```

using ll = long long;
ll bit1[200005], bit2[200005], n, m;
void update(ll bit[], ll i, ll val) {
    for (; i <= n; i += (i & -i)) {
        bit[i] += val;
    }
}

void range_update(ll l, ll r, ll val) {
    update(bit1, l, val);
    update(bit1, r + 1, -val);
    update(bit2, l, val * (l - 1));
    update(bit2, r + 1, -(r * val));
}

ll sum(ll bit[], ll i) {
    ll re = 0;
    for (; i > 0; i -= (i & -i)) {
        re += bit[i];
    }
    return re;
}

ll prefix_sum(ll i) {
    return sum(bit1, i) * i - sum(bit2, i);
}

ll range_sum(ll l, ll r) {
    return prefix_sum(r) - prefix_sum(l - 1);
}

```

range_update(l, r, val);

range_sum(l, r);

Merge Sort Tree

```

struct MergeSortTree {
    vector<vector<int>> tree;

```

```

    k)] << '\n';
}
return 0;
}

int V[N], root[N], a[N];
int32_t main() {
    map<int, int> mp;
    int n, q;
    cin >> n >> q;
    for(int i = 1; i <= n; i++) cin >> a[i], mp[a[i]]];
    int c = 0;
    for(auto x : mp) mp[x.first] = ++c, V[c] = x.first;
    root[0] = t.build(1, n);
    for(int i = 1; i <= n; i++) {
        root[i] = t.upd(root[i - 1], 1, n, mp[a[i]], 1);
    }
    while(q--) {
        int l, r, k;
        cin >> l >> r >> k;
        cout << V[t.query(root[l - 1], root[r], 1, n, k)]
            << '\n';
    }
    return 0;
}

```

Sparse Table Max/Min/GCD Query

```

struct SparseTable {
    SparseTable(vector<int>& data)
    {
        int n = data.size();
        int maxLog = log2(n) + 1;
        table.assign(n, vector<int>(maxLog));
        for (int i = 0; i < n; ++i) {
            table[i][0] = data[i];
        }
        for (int j = 1; (1 << j) <= n; ++j) {
            for (int i = 0; (i + (1 << j) - 1) < n; ++i) {
                table[i][j] = max(table[i][j - 1], table[i + (1 << (j - 1))][j - 1]);
            }
        }
    }
    int query(int L, int R)
    {
        int j = log2(R - L + 1);
        return max(table[L][j], table[R - (1 << j) + 1][j]);
    }
    vector<vector<int>> table;
};

int main()
{
    vector<int> data = { 1, 3, 2, 7, 9, 11, 3, 5, 6, 8 };
    SparseTable st(data);
    cout << "Max in range [1, 4]: " << st.query(1, 4)
        << endl;
}

```

Sparse Table 2D (up to 500 x 500 is safe)

```

struct SparseTable2D {

```

```

    vector<int> arr;
    int n;
    MergeSortTree(vector<int>& a)
    {
        arr = a, n = a.size();
        tree.resize(4 * n);
        build(1, 0, n - 1);
    }
    void build(int node, int l, int r)
    {
        if (l == r) {
            tree[node].push_back(arr[l]);
            return;
        }
        int mid = (l + r) / 2;
        build(node * 2, l, mid), build(node * 2 + 1, mid + 1, r);
        merge(tree[node * 2].begin(), tree[node * 2].end(), tree[node * 2 + 1].begin(), tree[node * 2 + 1].end(), back_inserter(tree[node]));
    }
    int query(int node, int l, int r, int ql, int qr, int k)
    {
        if (l > qr || r < ql)
            return 0;
        if (l >= ql && r <= qr) {
            int hi = tree[node].size() - 1, lo = 0, ind = -1;
            // while (hi >= lo) { } // Modify your // function here
            return ind;
        }
        int mid = (l + r) / 2;
        return query(node * 2, l, mid, ql, qr, k) + query(node * 2 + 1, mid + 1, r, ql, qr, k);
    }
};

```

Find the number of distinct elements in a range.

```

void merge(vector<int> tree[], int treeNode)
{
    int len1 = tree[2 * treeNode].size();
    int len2 = tree[2 * treeNode + 1].size();
    int index1 = 0, index2 = 0;
    while (index1 < len1 && index2 < len2) {
        if (tree[2 * treeNode][index1] > tree[2 * treeNode + 1][index2]) {
            tree[treeNode].push_back(tree[2 * treeNode + 1][index2]);
            index2++;
        }
        else {
            tree[treeNode].push_back(tree[2 * treeNode][index1]);
            index1++;
        }
    }
    while (index1 < len1) {
        tree[treeNode].push_back(tree[2 * treeNode][index1]);
        index1++;
    }
    while (index2 < len2) {
        tree[treeNode].push_back(tree[2 * treeNode + 1][index2]);

```

```

static const int LG = 10;
int n, m;
vector<vector<int>> a;
vector<int> lg2;
vector<vector<vector<vector<int>>>> st;
SparseTable2D(int n, int m) : n(n), m(m) {
    a.assign(n, vector<int>(m, 0));
    lg2.resize(max(n, m) + 1, 0);
    for (int i = 2; i <= max(n, m); i++) lg2[i] =
        lg2[i >> 1] + 1;
    st.assign(n, vector<vector<vector<int>>>(m,
        vector<vector<int>>(LG, vector<int>(LG,
            0))));
}
void set_val(int i, int j, int val) { a[i][j] =
    val; }
void build() {
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            st[i][j][0][0] = a[i][j];
    for (int a = 0; a < LG; a++) {
        for (int b = 0; b < LG; b++) {
            if (a + b == 0) continue;
            for (int i = 0; i + (1 << a) <= n; i++) {
                for (int j = 0; j + (1 << b) <= m; j++)
                {
                    if (!a)
                        st[i][j][a][b] = max(st[i][j][a][b -
-1],
                        st[i][j + (1 << (b - 1))][a][b - 1])
                    ;
                    else
                        st[i][j][a][b] = max(st[i][j][a - 1][b
-1],
                        st[i + (1 << (a - 1))][j][a - 1][b])
                    ;
                }
            }
        }
    }
}
int query(int x1, int y1, int x2, int y2) {
    int a = lg2[x2 - x1 + 1], b = lg2[y2 - y1 +
    1];
    int m1 = max(st[x1][y1][a][b], st[x2 - (1 << a
-1)][y1][a][b]);
    int m2 = max(st[x1][y2 - (1 << b) + 1][a][b],
    st[x2 - (1 << a) + 1][y2 - (1 << b) + 1][a][b
-1]);
    return max(m1, m2);
}
};
// st.set_val(i, j, grid[i][j]);
// st.build(); // st.query(0, 0, 1, 2); // max in
// submatrix [(0,0) to (1,2)]
int query(vector<int> tree[], int treeNode, int
start,
int end, int left, int right)
{
    if (start > right || end < left) {
        return 0;
    }
    if (start >= left && end <= right) {
        return tree[treeNode].end()
        - upper_bound(tree[treeNode].begin(),
        tree[treeNode].end(), right);
    }
    int mid = (start + end) / 2;

```

```

        index2++;
    }
    return;
}
void build(vector<int> tree[], int* arr, int start
,
int end,
int treeNode)
{
    if (start == end) {
        tree[treeNode].push_back(arr[start]);
        return;
    }
    int mid = (start + end) / 2;
    build(tree, arr, start, mid, 2 * treeNode);
    build(tree, arr, mid + 1, end, 2 * treeNode + 1)
    ;
    merge(tree, treeNode);
    return;
}
int query(int ci, int st, int end,
int l, int r, int k)
{
    if (st == end)
        return seg[ci][0];
    int p = upper_bound(seg[2 * ci + 1].begin(),
    seg[2 * ci + 1].end(), r)
    - lower_bound(seg[2 * ci + 1].begin(),
    seg[2 * ci + 1].end(), l);
    int mid = (st + end) / 2;
    if (p >= k)
        return query(2 * ci + 1, st, mid, l, r, k);
    else
        return query(2 * ci + 2, mid + 1, end, l, r, k
        - p);
}
int main()
{
    int arr[] = { 3, 1, 5, 2, 4, 7, 8, 6 };
    int n = sizeof(arr) / sizeof(arr[0]);
    pair<int, int> B[n];
    for (int i = 0; i < n; i++) {
        B[i] = { arr[i], i };
    }
    sort(B, B + n);
    build(0, 0, n - 1, B);
    cout << "3rd smallest element in range 3 to 7 is
    :
    "
    << arr[query(0, 0, n - 1, 2, 6, 3)] << "\n";
}

```

Treap

```

mt19937
rnd(chrono::steady_clock::now().time_since_epoch
().count());
struct Node {
    int64_t prior, data, sum, toProp;
    int size; bool rev; Node *l, *r;
    Node(int64_t val) {
        prior = rnd(), data = sum = val;
        size = 1; rev = toProp = 0;
        l = r = nullptr;
    }
};
struct Treap {
    Node *root;
    Treap() : root(nullptr) {}
}

```

```

int op1 = query(tree, 2 * treeNode, start, mid,
left,
right);
int op2 = query(tree, 2 * treeNode + 1, mid + 1,
end,
left, right);
return op1 + op2;
}
int main()
{
    int n; cin >> n;
    int arr[n];
    for(int i=0;i<n;i++) cin >> arr[i];
    int next_right[n];
    vector<int> tree[4 * n];
    unordered_map<int, int> ump;
    for (int i = n - 1; i >= 0; i--) {
        if (ump[arr[i]] == 0) {
            next_right[i] = n;
            ump[arr[i]] = i;
        }
        else {
            next_right[i] = ump[arr[i]];
            ump[arr[i]] = i;
        }
    }
    build(tree, next_right, 0, n - 1, 1);
    int q; cin >> q;
    while(q--){
        int l, r; cin >> l >> r;
        l-- , r--;
        cout << query(tree,l,0,n-1,l,r) << "\n";
    }
    return 0;
}

```

Kth smallest value in a range (SegTree)

```

#define N (int)1e5
vector<int> seg[N];
void build(int ci, int st, int end,
pair<int, int>* B)
{
    if (st == end) {
        seg[ci].push_back(B[st].second);
        return;
    }
    int mid = (st + end) / 2;
    build(2 * ci + 1, st, mid, B);
    build(2 * ci + 2, mid + 1, end, B);
    merge(seg[2 * ci + 1].begin(), seg[2 * ci + 1].end(),
seg[2 * ci + 2].begin(), seg[2 * ci + 2].end(),
back_inserter(seg[ci]));
}

void split(Node *t, Node *&l, Node *&r, int key,
int add = 0) {
    if (!t) l = r = nullptr;
    else {
        push(t);
        if (key <= add + size(t -> l)) split(t -> l,
l,
t -> l,
key, add), r = t;
        else split(t -> r, t -> r, r, key,
add + 1 + size(t ->
l)), l = t;
        update(t);
    }
}

```

```

int size(Node *&t) { return t ? t -> size : 0; }
int64_t sum(Node *&t) { return t ? t -> sum : 0; }
}

void update(Node *&t) {
    if (!t) return;
    t -> size = size(t -> l) + size(t -> r) + 1;
    t -> sum = t -> data + t -> size * t -> toProp;
    if (t -> l) t -> sum += t -> l -> sum + t -> l ->
    size * t -> l -> toProp;
    if (t -> r) t -> sum += t -> r -> sum + t -> r ->
    size * t -> r -> toProp;
}

void push(Node *&t) {
    if (!t) return;
    if (t -> rev) {
        t -> rev = false; swap(t -> l, t -> r);
        if (t -> l) t -> l -> rev ^= true;
        if (t -> r) t -> r -> rev ^= true;
    }
    if (t -> toProp) {
        t -> data += t -> toProp;
        if (t -> l) t -> l -> toProp += t -> toProp;
        if (t -> r) t -> r -> toProp += t -> toProp;
        t -> toProp = 0;
    }
}

```

Graph Condense // Implements Kosaraju's algorithm to find all // Strongly Connected Components (SCCs).

```

vector<bool> visited;
void dfs(int v, vector<vector<int>> const& g,
vector<int>& output) {
    visited[v] = true;
    for (auto u : g[v])
        if (!visited[u])
            dfs(u, g, output);
    output.push_back(v);
}

void strongly_connected_components(
vector<vector<int>> const& g,
vector<vector<int>>& components,
vector<vector<int>>& g_cond,
vector<int>& roots)
){
    int n = sz(g);
    components.clear(); g_cond.clear();
    vector<int> order;
    visited.assign(n, false);
    for (int i = 0; i < n; ++i)
        if (!visited[i])
            dfs(i, g, order);
    vector<vector<int>> g_rev(n);
    for (int v = 0; v < n; ++v)
        for (int u : g[v])
            g_rev[u].push_back(v);
    visited.assign(n, false);
    reverse(order.begin(), order.end());
    roots.assign(n, -1);
    int component_id = 0;
    for (int v : order) {
        if (!visited[v]) {
            vector<int> component;
            dfs(v, g_rev, component);
            for (int u : component)
                roots[u] = component_id;
            components.push_back(component);
        }
    }
}

```

```

void merge(Node *t, Node *l, Node *r) {
    push(l), push(r);
    if (!l || !r) t = l ? l : r;
    else if (l -> prior > r -> prior) merge(l -> r, l -> r, l -> r);
    else merge(r -> l, l, r -> l), t = r;
    update(t);
}

void insert(Node *t, int key, int64_t val) {
    Node *left, *right; split(t, left, right, key);
    merge(left, left, new Node(val)), merge(t, left, right);
}

void reverse(Node *t, int l, int r) {
    Node *left, *mid, *right;
    split(t, left, right, l), split(right, mid, right, r - l + 1);
    assert(mid); mid -> rev ^= true;
    merge(t, left, mid), merge(t, t, right);
}

int erase(Node *t, int key) {
    assert(size(t) > key); Node *left, *mid, *right;
    split(t, left, right, key), split(right, mid, right, 1);
    merge(t, left, right); int ret = mid -> data;
    delete mid; return ret;
}

int64_t query_sum(Node *t, int l, int r) {
    Node *left, *mid, *right;
    split(t, left, right, l), split(right, mid, right, r - l + 1);
    int64_t ret = mid -> sum; merge(t, left, mid), merge(t, t, right);
    return ret;
}

void rangeAdd(Node *t, int l, int r, int64_t val) {
    Node *left, *mid, *right;
    split(t, left, right, l), split(right, mid, right, r - l + 1);
    mid -> toProp += val; merge(t, left, mid), merge(t, t, right);
}

void set(Node *t, int p, int64_t val) {
    Node *left, *mid, *right;
    split(t, left, right, p), split(right, mid, right, 1);
    merge(t, left, new Node(val)), merge(t, t, right);
}
};

```

HopcroftKarp

```

struct HopcroftKarp { // Bipartite Matching
    int n, m;
    vector<vector<int>>> g;
    vector<int> dist, pairU, pairV;
    static const int INF = 1e9;
    HopcroftKarp(int n_ = 0, int m_ = 0) {
        n = n_; m = m_;
        g.assign(n, {});
        pairU.assign(n, -1);
        pairV.assign(m, -1);
    }
};

```

```

        component_id++;
    }
}

g_cond.assign(component_id, {});
for (int v = 0; v < n; ++v) {
    for (int u : g[v]) {
        if (roots[v] != roots[u]) {
            g_cond[roots[v]].push_back(roots[u]);
        }
    }
}
}

```

Articulation Points and Bridges in Graph

```

vector<int> dfs_num, dfs_low, dfs_parent;
vector<bool> articulation_vertex;
int dfsNumberCounter, dfsRoot, rootChildren;
vector<pair<int, int>> bridges;
const int UNVISITED = -1;
void articulationPointAndBridge(int u)
{
    dfs_num[u] = dfsNumberCounter++;
    dfs_low[u] = dfs_num[u];
    for (auto &[v, w] : g[u])
    {
        if (dfs_num[v] == UNVISITED)
        {
            dfs_parent[v] = u;
            if (u == dfsRoot)
                ++rootChildren;
            articulationPointAndBridge(v);
            if (dfs_low[v] >= dfs_num[u])
                articulation_vertex[u] = true;
            if (dfs_low[v] > dfs_num[u])
                bridges.push_back({u, v});
            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
        }
        else if (v != dfs_parent[u])
            dfs_low[u] = min(dfs_low[u], dfs_num[v]);
    }
}

// inside int main()
bridges.clear();
dfs_num.assign(n, UNVISITED);
dfs_low.assign(n, 0);
dfs_parent.assign(n, -1);
articulation_vertex.assign(n, false);
dfsNumberCounter = 0;
for (int u = 0; u < n; ++u) {
    if (dfs_num[u] == UNVISITED)
    {
        dfsRoot = u;
        rootChildren = 0;
        articulationPointAndBridge(u);
        articulation_vertex[dfsRoot] = (rootChildren > 1);
    }
}
}

```

Dinic's Algorithm(Max Flow)

```

const int64_t inf = 1LL << 61;
struct Dinic {
    struct edge {
        int to, rev;
        int64_t flow, w;
    };
    int n, s, t;
    vector<int> d;
};

```

```

    dist.assign(n, 0);
}
void add_edge(int u, int v) {
    g[u].push_back(v);
}
bool bfs() {
    queue<int> q;
    for (int u = 0; u < n; ++u) {
        if (pairU[u] == -1) {
            dist[u] = 0;
            q.push(u);
        } else {
            dist[u] = INF;
        }
    }
    bool foundAug = false;
    while (!q.empty()) {
        int u = q.front(); q.pop();
        for (int v : g[u]) {
            int u2 = pairV[v];
            if (u2 == -1) {
                foundAug = true;
            } else if (dist[u2] == INF) {
                dist[u2] = dist[u] + 1;
                q.push(u2);
            }
        }
    }
    return foundAug;
}
bool dfs(int u) {
    for (int v : g[u]) {
        int u2 = pairV[v];
        if (u2 == -1 || (dist[u2] == dist[u] + 1 &&
            dfs(u2))) {
            pairU[u] = v;
            pairV[v] = u;
            return true;
        }
    }
    dist[u] = INF;
    return false;
}
int max_matching() {
    int matching = 0;
    while (bfs()) {
        for (int u = 0; u < n; ++u)
            if (pairU[u] == -1 && dfs(u))
                ++matching;
    }
    return matching;
}
vector<pair<int,int>> matching_edges() const
{
    vector<pair<int,int>> res;
    for (int v = 0; v < m; ++v)
        if (pairV[v] != -1)
            res.emplace_back(pairV[v], v);
    return res;
}
};

```

Binary Lifting

```

int up[200001][20];
vector<vector<int>> tree(200001);
void binary_lifting(int src, int par) {
    up[src][0] = par;
    for (int i = 1; i <= 19; i++) {
        if (up[src][i - 1] != -1)

```

```

vector<int> done;
vector<vector<edge>> g;
Dinic() {};
Dinic(int _n) {
    n = _n + 10, g.resize(n);
}
void add_edge(int u, int v, int64_t w) {
    edge a = {v, (int)g[v].size(), 0, w};
    edge b = {u, (int)g[u].size(), 0, 0};
    g[u].push_back(a), g[v].push_back(b);
}
bool bfs() {
    d.assign(n, -1), d[s] = 0;
    queue<int> Q;
    Q.push(s);
    while (Q.size()) {
        int u = Q.front(); Q.pop();
        for (auto &e : g[u]) {
            int v = e.to;
            if (!~d[v] && e.flow < e.w) d[v] = d[u] +
1,
                Q.push(v);
        }
    }
    return d[t] != -1;
}
int64_t dfs(int u, int64_t flow) {
    if (u == t) return flow;
    for (int &i = done[u]; i < (int)g[u].size(); i
++) {
        edge &e = g[u][i];
        if (e.w <= e.flow) continue;
        int v = e.to;
        if (d[v] == d[u] + 1) {
            int64_t nw = dfs(v, min(flow, e.w - e.flow
));
            if (nw > 0) {
                e.flow += nw;
                g[v][e.rev].flow -= nw;
                return nw;
            }
        }
    }
    return 0;
}
int64_t max_flow(int _s, int _t) {
    s = _s, t = _t;
    int64_t flow = 0;
    while (bfs()) {
        done.assign(n, 0);
        while (int64_t nw = dfs(s, inf)) flow += nw;
    }
    return flow;
}
};

int query(int u, int v) { // Range Sum Query
    int res = 0;
    while (head[u] != head[v]) {
        if (depth[head[u]] < depth[head[v]])
            swap(u, v);
        res += segtree.sum(pos[head[u]], pos[u]);
        u = parent[head[u]];
    }
    if (depth[u] > depth[v])
        swap(u, v);
    res += segtree.sum(pos[u], pos[v]);
    return res;
}
void addVal(int idx, int delta) {

```

```

        up[src][i] = up[up[src][i-1]][i-1];
    else
        up[src][i] = -1;
    }
    for (int i = 0; i < tree[src].size(); i++)
        if (tree[src][i] != par)
            binary_lifting(tree[src][i], src);
}

int lift_node(int node, int k) {
    if (node == -1 || k == 0)
        return node;
    for (int i = 19; i >= 0; i--)
        if (k >= (1 << i))
            return lift_node(up[node][i], k-(1<<i));
}

```

Tree Flattening (Euler Tour)

```

void eulerDFS(ll node, ll par, ll arr[], vector<ll>
    >&
    flatTree, vector<ll> tree[], pair<ll, ll>
    subTreeRange[], ll& timer)
{
    subTreeRange[node].first = ++timer;
    flatTree.push_back(arr[node]);
    for (auto& child : tree[node])
        if (child != par)
            eulerDFS(child, node, arr, flatTree, tree,
                subTreeRange, timer);
    subTreeRange[node].second = timer;
}

void solve() {
    vector<ll> flatTree;
    pair<ll, ll> subTreeRange[n + 1];
    ll timer = -1;
    eulerDFS(1, 0, arr, flatTree, tree,
        subTreeRange, timer);
}

```

Heavy Light Decomposition (HLD on Tree) // u to v range query

```

struct HLD {
    int n, cur_pos = 0;
    vector<int> arr, parent, size, depth, heavy,
    head, pos;
    vector<vector<int>> adj;
    FenwickTree segtree;
    HLD(int n) : n(n), arr(n + 1), parent(n + 1),
    size(n + 1), depth(n + 1), heavy(n + 1, 0), head
    (n +
    1), pos(n + 1), adj(n + 1),
    segtree(FenwickTree(n + 1)) {}
    void add_edge(int u, int v) {
        adj[u].push_back(v), adj[v].push_back(u);
    }
    void dfs(int u, int p) {
        parent[u] = p;
        size[u] = 1;
        int max_sz = 0;
        for (int v : adj[u]) {
            if (v == p)
                continue;
            depth[v] = depth[u] + 1;
            dfs(v, u);
            size[u] += size[v];
            if (size[v] > max_sz) {
                max_sz = size[v], heavy[u] = v;
            }
        }
    }
}

```

```

    segtree.add(pos[idx], delta);
    arr[idx] += delta;
}

void editVal(int idx, int value) {
    segtree.add(pos[idx], value - arr[idx]);
    arr[idx] = value;
}
};

```

Centroid Decomposition

```

vector<vector<int>> adj;
vector<bool> is_removed;
vector<int> subtree_size;
int get_subtree_size(int node, int parent = -1) {
    subtree_size[node] = 1;
    for (int child : adj[node]) {
        if (child == parent || is_removed[child])
            continue;
        subtree_size[node] +=
            get_subtree_size(child, node);
    }
    return subtree_size[node];
}

int get_centroid(int node, int tree_size, int
    parent
    = -1) {
    for (int child : adj[node]) {
        if (child == parent || is_removed[child])
            continue;
        if (subtree_size[child] * 2 > tree_size)
            return get_centroid(child, tree_size, node);
    }
    return node;
}

void build_centroid_decomp(int node = 0) {
    int centroid = get_centroid(node,
        get_subtree_size(node));
    // do something
    is_removed[centroid] = true;
    for (int child : adj[centroid]) {
        if (is_removed[child]) continue;
        build_centroid_decomp(child);
    }
}

```

// Ahsan's

```

int tot = 0;
vector<int> sz(n, 1), removed(n, 0), cenpar(n, -1)
;
auto dfs_sz = [&](auto &&self, int node, int pr)
->
void {
    tot += 1;
    sz[node] = 1;
    for (auto &son : g[node]) {
        if (son == pr || removed[son]) continue;
        self(self, son, node);
        sz[node] += sz[son];
    }
};

auto find_cen = [&](auto &&self, int node, int pr)
-> int {
    for (auto &son : g[node]) {
        if (son == pr || removed[son]) continue;
        if (sz[son] > tot / 2) return self(self, son,
            node);
    }
    return node;
}

```

```

void decompose(int u, int h) {
    head[u] = h;
    pos[u] = cur_pos++;
    segtree.add(pos[u], arr[u]); // Update
    // Fenwick tree with the +value of arr[u]
    if (heavy[u])
        decompose(heavy[u], h);
    for (int v : adj[u])
        if (v != parent[u] && v != heavy[u])
            decompose(v, v);
}

```

Tree

```

vector<vector<int>>>t,parents;
vector<int>level;
int mx;
void dfs(int node, int parent, int cLevel){
    level[node] = cLevel;
    parents[0][node] = parent;
    for(auto &x: t[node]){
        if(x!=parent) dfs(x,node, cLevel+1);
    }
}
int kthParent(int a, int k){
    for(int i = 0; i<mx; i++){
        if(a==--1) return a;
        if(k&(1<<i)) a = parents[i][a];
    }
    return a;
}
int lca(int a, int b){
    if(level[a]>level[b]){
        a = kthParent(a, level[a] - level[b]);
    }else{
        b = kthParent(b, level[b] - level[a]);
    }
    if(a==b) return a;
    for(int i = mx-1; i>=0; i--){
        if(parents[i][a]!=parents[i][b]){
            a = parents[i][a];
            b = parents[i][b];
        }
    }
    return parents[0][a];
}
int distance(int a,int b){
    return level[a]+level[b] - 2*level[lca(a,b)];
}
int main(){
    int n;
    cin>>n;
    mx = log2(n)+1;
    //resize and input
    dfs(1,-1,0);
    for(int i = 1; i<mx; i++){
        for(int j = 1; j<=n; j++){
            int prevParent = parents[i-1][j];
            if(prevParent!=-1) parents[i][j] =
                parents[i-1][prevParent];
        }
    }
}

```

String Double Hashing

```

ll mod1 = 127657753, mod2 = 987654319, p1 = 31,
p2 = 37;
ll invp1 = ModPow(p1, mod1 - 2, mod1), invp2 =
ModPow(p2, mod2 - 2, mod2);
vector<pair<ll, ll>> pPow(1, {1, 1}), iPow(1, {1,

```

```

});
auto decompose = [&](auto &&self, int node, int
pr) -> void {
    tot = 0;
    dfs_sz(dfs_sz, node, pr);
    int cen = find_cen(find_cen, node, pr);
    removed[cen] = 1;
    cenpar[cen] = pr;
    for (auto &son : g[cen]) {
        if (son == pr || removed[son]) continue;
        self(self, son, cen);
    }
};
decompose(decompose, 0, -1);

```

KMP

```

vector<int> getLps(const string &t) {
    int n = t.size();
    vector<int> pi(n, 0);
    int lps = 0;
    for (int q = 1; q < n; q++) {
        while (lps > 0 && t[lps] != t[q]) {
            lps = pi[lps - 1];
        }
        if (t[lps] == t[q]) {
            lps += 1;
        }
        pi[q] = lps;
    }
    return pi;
}

```

Z-Algorithm

```

vector<int> z_function(string& s)
{
    int n = s.size();
    vector<int> z(n);
    z[0] = 0;
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (i <= r)
            z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    return z;
}

```

Manacher's Algorithm

```

struct Manacher {
    vector<int> p[2];
    // p[1][i] = (max odd length palindrome
    // centered at i) / 2 [floor division]
    // p[0][i] = same for even, it considers the
    // right
    // center
    // e.g. for s = "abbabba", p[1][3] = 3,
    // p[0][2] = 2
    Manacher(string s) {
        int n = s.size();
        p[0].resize(n + 1);
        p[1].resize(n);
        for (int z = 0; z < 2; z++) {
            for (int i = 0, l = 0, r = 0; i < n; i++) {
                int t = r - i + !z;
                if (i < r) p[z][i] = min(t, p[z][l + t]);
                int L = i - p[z][i], R = i + p[z][i] - !z;
                while (L >= 1 && R + 1 < n && s[L - 1] ==

```

```

1});
void genP(ll n) {
    while ((ll)pPow.size() <= n) {
        pPow.push_back({pPow.back().xx * p1 %
            mod1, pPow.back().yy * p2 % mod2});
        iPow.push_back({iPow.back().xx * invp1 %
            mod1, iPow.back().yy * invp2 % mod2});
    }
}
struct Hash {
    int n = 0;
    vector<pair<ll, ll>> sHash;
    void genHash(string& s) {
        sHash.resize(n + 1, {0, 0}); // 0-indexed
        for (int i = 0; i < n; i++) {
            sHash[i + 1].xx = (sHash[i].xx + (s[i] - 'a'
                + 1) * pPow[i].xx) % mod1;
            sHash[i + 1].yy = (sHash[i].yy + (s[i] - 'a'
                + 1) * pPow[i].yy) % mod2;
        }
    }
    pair<ll, ll> getHash(int l, int r) {
        ll h1 = (sHash[r + 1].xx - sHash[l].xx + mod1)
            % mod1 * iPow[l].xx % mod1;
        ll h2 = (sHash[r + 1].yy - sHash[l].yy + mod2)
            % mod2 * iPow[l].yy % mod2;
        return {h1, h2}; // 0-indexed
    }
    pair<ll, ll> getHash() {
        return sHash[n]; // Get the hash of the whole
        // string
    }
    Hash(string& s) {
        n = s.size();
        genP(n), genHash(s);
    }
};

```

Suffix Array

```

struct SuffixArray {
    vector<int> sa, rank, lcp;
    SuffixArray(const string &s, int lim = 256) {
        int n = s.size();
        sa.resize(n);
        rank.resize(n);
        vector<int> tmp(n, cnt(max(n, lim)));
        for (int i = 0; i < n; i++)
            cnt[rank[i] = s[i]]++;
        for (int i = 1; i < lim; i++)
            cnt[i] += cnt[i - 1];
        for (int i = n - 1; i >= 0; i--)
            sa[--cnt[s[i]]] = i;
        for (int k = 1, r = 0; r < n - 1; k <= 1,
            lim = r + 1) {
            int p = 0;
            for (int i = n - k; i < n; i++)
                tmp[p++] = i;
            for (int i = 0; i < n; i++)
                if (sa[i] >= k)
                    tmp[p++] = sa[i] - k;
            fill(cnt.begin(), cnt.begin() + lim, 0);
            for (int i = 0; i < n; i++)
                cnt[rank[tmp[i]]]++;
            for (int i = 1; i < lim; i++)
                cnt[i] += cnt[i - 1];
            for (int i = n - 1; i >= 0; i--)
                sa[--cnt[rank[tmp[i]]]] = tmp[i];
        }
    }
};

```

```

s[R
    + 1]) p[z][i]++, L--, R++;
    if (R > r) l = L, r = R;
}
}
}
bool is_pal(int l, int r) {
    int mid = (l + r + 1) / 2, len = r - l + 1;
    return 2 * p[len % 2][mid] + len % 2 >= len;
}
};

```

Aho-Corasick //The Aho-Corasick algorithm allows us to quickly //search for multiple patterns in a text.

```

const int K = 26;
struct Vertex {
    vector<int> next_char, go;
    bool output = false;
    int link = -1;
    Vertex() {
        next_char.assign(K, -1);
        go.assign(K, -1);
    }
};
vector<Vertex> Trie(1);
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (Trie[v].next_char[c] == -1) {
            Trie[v].next_char[c] = Trie.size();
            Trie.emplace_back();
        }
        v = Trie[v].next_char[c];
    }
    Trie[v].output = true;
}
void add_links() {
    queue<int> q;
    Trie[0].link = 0;
    for (int c = 0; c < K; c++) {
        int u = Trie[0].next_char[c];
        if (u != -1) {
            Trie[u].link = 0;
            q.push(u);
            Trie[0].go[c] = u;
        } else {
            Trie[0].go[c] = 0;
        }
    }
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        for (int c = 0; c < K; c++) {
            int v = Trie[u].next_char[c], suffix_link =
                Trie[u].link;
            if (v != -1) {
                while (suffix_link != 0 &&
                    Trie[suffix_link].next_char[c] == -1) {
                    suffix_link = Trie[suffix_link].link;
                }
                if (Trie[suffix_link].next_char[c] != -1)
                    Trie[v].link =
                        Trie[suffix_link].next_char[c];
                else
                    Trie[v].link = 0;
                q.push(v);
            }
            Trie[u].go[c] = (v != -1) ? v :

```

```

    tmp[sa[0]] = r = 0;
    for (int i = 1; i < n; i++) {
        if (rank[sa[i]] != rank[sa[i - 1]] ||
            (sa[i] + k < n ? rank[sa[i] + k] : -1) !=
            (sa[i - 1] + k < n ? rank[sa[i - 1] + k] :
            -1))
            r++;
        tmp[sa[i]] = r;
    }
    rank = tmp;
}
lcp.assign(n, 0);
vector<int> inv(n);
for (int i = 0; i < n; i++) inv[sa[i]] = i;
for (int i = 0, k = 0; i < n; i++) {
    if (inv[i] == 0) continue;
    int j = sa[inv[i] - 1];
    while (i + k < n && j + k < n && s[i + k] ==
    s[j + k]) k++;
    lcp[inv[i]] = k;
    if (k) k--;
}
}
};

int main() {
    string s = "banana";
    SuffixArray sa(s);
    for (int i : sa.sa) cout << i << ' ';
    cout << "\n";
    // LCP = Longest Common Prefix between sa[i]
    // and sa[i+1]
    for (int i = 1; i < s.size(); i++)
        cout << sa.lcp[i] << ' ';
}

```

Trie

```

// Initialize: Trie T;
// Insert Value: T.add(val, 1);
// Delete Value: T.add(val, -1);
// Count values < K: T.count_xor_less(0, K);
// Rank of val: T.count_xor_less(0, val) + 1;
// Get Median: T.get_kth((T.root->cnt + 1) / 2);
// Min XOR with x: int v = T.get_xor_kth(x, 1);
// (Result is v^x)
// Max XOR with x: int v = T.get_xor_kth(x,
// T.root->cnt);
// Special: T.count_special(X);
struct Trie {
    static const int B = 31;
    struct Node {
        Node *c[2];
        int cnt;
        Node() { c[0] = c[1] = nullptr, cnt = 0; }
    } *root;
    Trie() { root = new Node(); }
    // v = 1 to Insert, v = -1 to Erase
    void add(int x, int v) {
        Node *u = root;
        u->cnt += v;
        for (int i = B - 1; ~i; --i) {
            int d = (x >> i) & 1;
            if (!u->c[d]) u->c[d] = new Node();
            u = u->c[d], u->cnt += v;
        }
    }
    // Count values where (val ^ x) < k
    int count_xor_less(int x, int k) {
        Node *u = root;
        int ans = 0;

```

```

        Trie[suffix_link].go[c];
    }
}

int main() {
    vector<string> patterns = {"a", "ab", "bab", "bc",
    "bca", "c", "caa"};
    for (const string& s : patterns) {
        add_string(s);
    }
    add_links();
    // Search for patterns in a text
    string text = "abccab";
    cout << "Text: " << text << endl;
    cout << "Found:" << endl;
    int currentState = 0;
    for (int i = 0; i < text.length(); ++i) {
        int c = text[i] - 'a';
        // Use the 'go' transition to move to next
        state
        currentState = Trie[currentState].go[c];
        // Check current state and all suffix/failure
        links
        // for matches
        int checkState = currentState;
        while (checkState != 0) {
            if (Trie[checkState].output) {
                // Found a pattern ending at this index
                cout << " - Pattern ended at index " << i
                << endl;
            }
            checkState = Trie[checkState].link; //
            Follow
            // the failure link
        }
    }

    // Check if x exists in the Trie
    int count(int x) {
        Node *u = root;
        for (int i = B - 1; ~i; --i) {
            int d = (x >> i) & 1;
            if (!u->c[d] || u->c[d]->cnt == 0) return 0;
            u = u->c[d];
        }
        return u->cnt;
    }
    // Returns value 'v' where (v ^ x) is the K-th
    // smallest XOR sum
    // k=1 -> Min XOR | k=Total -> Max XOR
    int get_xor_kth(int x, int k) {
        Node *u = root;
        if (u->cnt < k) return -1;
        int ans = 0;
        for (int i = B - 1; ~i; --i) {
            int d = (x >> i) & 1;
            int count_desired = u->c[d] ? u->c[d]->cnt :
            0;
            if (k <= count_desired) u = u->c[d], ans |=
            (d
            << i);
            else k -= count_desired, u = u->c[!d], ans
            |=
            ((!d) << i);
        }
        return ans;
    }
}

```

```

for (int i = B - 1; ~i; --i) {
    if (!u) break;
    int d = (x >> i) & 1;
    if ((k >> i) & 1) ans += (u->c[d] ?
        u->c[d]->cnt : 0), u = u->c[!d];
    else u = u->c[d];
}
return ans;
}
int count_xor_greater(int x, int k) {
    return root->cnt - count_xor_less(x, k + 1);
}
// Returns the K-th smallest number in the Trie
// (1-based)
int get_kth(int k) {
    Node *u = root;
    if (u->cnt < k) return -1;
    int ans = 0;
    for (int i = B - 1; ~i; --i) {
        int left = u->c[0] ? u->c[0]->cnt : 0;
        if (k <= left) u = u->c[0];
        else k -= left, u = u->c[1],
            ans |= (1 << i);
    }
    return ans;
}

```

GCD Properties: In particular, recalling that gcd is a positive integer valued function we obtain that $\text{gcd}(a, b \cdot c) = 1$ if and only if $\text{gcd}(a, b) = 1$ and $\text{gcd}(a, c) = 1$.

15. If none of $a_1, a_2, \dots, a_r$ is zero, then $\text{gcd}(a_1, a_2, \dots, a_r) = \text{gcd}(\text{gcd}(a_1, a_2, \dots, a_{r-1}), a_r)$

16. $\text{gcd}(a, b) \cdot \text{lcm}(a, b) = |a \cdot b|$, so for any two numbers LCM is always multiple of GCD.

17. In a Cartesian coordinate system, $\text{gcd}(a, b)$ can be interpreted as the number of segments between points with integral coordinates on the straight line segment joining the points $(0, 0)$ and (a, b) .

18. Two numbers are called relatively prime, or coprime, if their greatest common divisor equals 1. For example, 9 and 28 are relatively prime.

19. Any two consecutive integers will be Co-Prime. Ex: 25, 26 is co-prime. 5, 6 is co-prime and so on. This will work because, let x divides 25 so remainder is something. If we divided 26 by x then remainder will be 1. This is the logic.

20. Two or more odd consecutive positive integer GCD is also 1.

```

int gcdFast(int a, int b)
{
    int result;
    __asm__ __volatile__(
        "movl %1, %%eax;"
        "movl %2, %%ebx;"
        "CONTD: cmpl $0, %%ebx;"
        "je DONE;"
        "xorl %%edx, %%edx;"
        "idivl %%ebx;"
        "movl %%ebx, %%eax;"
        "movl %%edx, %%ebx;"
        "jmp CONTD;"
        "DONE: movl %%eax, %0;"
        : "=g"(result)

```

```

// special: Count values satisfying:
// val <= (val ^ x) <= x
int64_t go(Node *u, int b, int x, int t1, int t2)
{
    if (!u || !t1 || t2 == 2) return 0;
    if ((t1 == 2 && !t2) || b < 0) return u->cnt;
    int d = (x >> b) & 1;
    int64_t res = 0;
    if (d) {
        res += go(u->c[1], b - 1, x,
            t1 == 1 ? 0 : t1, t2 == 1 ? 0 : t2);
        res += go(u->c[0], b - 1, x,
            t1 == 1 ? 2 : t1, t2);
    } else {
        res += go(u->c[1], b - 1, x, t1,
            t2 == 1 ? 2 : t2);
        res += go(u->c[0], b - 1, x, t1, t2);
    }
    return res;
}
int64_t count_special(int x) {
    return go(root, B - 1, x, 1, 1);
}
};

```

Minimum Lexicographic Rotation(Booth's Algorithm)

```

int minLex(string &s) {
    int len = s.size();
    int n = 2 * len, i = 0, j = 1, k = 0;
    int a, b;
    while (i + k < n && j + k < n) {
        a = (i + k >= len) ? s[i + k - len] : s[i + k];
        b = (j + k >= len) ? s[j + k - len] : s[j + k];
        if (a == b) ++k;
        else if (a > b) {
            i = i + k + 1;
            if (i <= j) i = j + 1;
            k = 0;
        } else {
            j = j + k + 1;
            if (j <= i) j = i + 1;
            k = 0;
        }
    }
    return min(i, j);
}

```

SegSieve

```

vector<char> segmentedSieve(long long L, long long R) {
    // generate all primes up to sqrt(R)
    long long lim = sqrt(R);
    vector<char> mark(lim + 1, false);
    vector<long long> primes;
    for (long long i = 2; i <= lim; ++i) {
        if (!mark[i]) {
            primes.emplace_back(i);
            for (long long j = i * i; j <= lim; j += i)
                mark[j] = true;
        }
    }
    vector<char> isPrime(R - L + 1, true);
    for (long long i : primes) {
        ll sm = (L / i) * i;
        if (sm < L) sm += i;
        for (long long j = max(i * i, sm); j <= R; j += i)

```

```

    : "g"(a), "g"(b));
    return result;
}

```

Extended Euclid and CRT

```

using T = __int128_t;
T egcd(T a, T b, T &x, T &y) {
    T xx = y = 0, yy = x = 1;
    while (b) {
        T q = a / b;
        T t = b; b = a % b; a = t;
        t = xx; xx = x - q * xx; x = t;
        t = yy; yy = y - q * yy; y = t;
    }
    return a;
}
// finds x such that x % m1 = a1, x % m2 = a2.
// m1 and m2 may not be coprime
// here, x is unique modulo m = lcm(m1, m2).
// returns (x, m). on failure, m = -1.
pair<T, T> crt(T a1, T m1, T a2, T m2) {
    T p, q;
    T g = egcd(m1, m2, p, q);
    if (a1 % g != a2 % g) return {0, -1};
    T m = m1 / g * m2;
    p = (p % m + m) % m;
    q = (q % m + m) % m;
    T x = p * a2 % m * (m1 / g) % m + q * a1 % m *
        (m2 / g) % m;
    return {x % m, m};
}

```

SPE, Mobius, Primes in O(N)

```

const int N = 1e6 + 2;
vector<int> spf(N), mob(N), primes;
void build() {
    mob[1] = 1;
    for (int i = 2; i < N; i++) {
        if (spf[i] == 0) {
            spf[i] = i, mob[i] = -1,
            primes.push_back(i);
        }
        for (int j = 0; i * primes[j] < N; j++) {
            spf[i * primes[j]] = primes[j];
            if (i % primes[j])
                mob[i * primes[j]] = mob[i] *
                mob[primes[j]];
            else mob[i * primes[j]] = 0;
            if (primes[j] == spf[i]) break;
        }
    }
}

```

Basis Vector

```

template<typename T = int, int LG = 31>
struct Basis {
    T basis[LG]; int sz;
    vector<int> who;
    Basis() {
        fill(basis, basis + LG, 0), sz = 0;
        who.clear();
    }
    void reset() {
        fill(basis, basis + LG, 0), sz = 0;
        who.clear();
    }
    bool insert(T mask, int idx = -1) {
        for (int i = LG - 1; i >= 0; --i) {
            if (mask >> i & 1) {

```

```

                isPrime[j - L] = false;
            }
            if (L == 1) isPrime[0] = false;
            return isPrime;
        }
    }
}

```

Phi

```

int phi(int n) {
    int result = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            result -= result / i;
        }
    }
    if (n > 1)
        result -= result / n;
    return result;
}
void phi_1_to_n(){
    phi[1] = 1;
    for(int i = 2; i < N; i++) {
        if(phi[i] == 0){
            primes.push_back(i);
            phi[i] = i - 1;
        }
        for(int p : primes){
            if(i * p >= N) break;
            if(i % p == 0){
                phi[i * p] = phi[i] * p;
                break;
            }else {
                phi[i * p] = phi[i] * (p - 1);
            }
        }
    }
}

```

Large number prime check (M.R.)

```

ull pow(ull a, ull t, ull mod) {
    ull r = 1;
    for (; t; t >>= 1, a = (ull)a * a % mod)
        if (t & 1) r = (ull)r * a % mod;
    return r;
}
bool isprime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull A[] = {2, 325, 9375, 28178, 450775,
        9780504, 1795265022},
    s = __builtin_ctzll(n - 1), d = n >> s;
    for (ull a : A) {
        ull p = pow(a % n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = (ull)p * p % n;
        if (p != n - 1 && i != s) return 0;
    }
    return 1;
}

```

Matrix Exponentiation

```

vector<vector<int>>
multiply(vector<vector<int>>& a,
    vector<vector<int>>& b) {
    int n = sz(a), m = sz(b[0]), p = sz(b[0][0]);
    vector<vector<int>> result(n, vector<int>(p,
        0));
    for (int i = 0; i < n; i++) {

```

```

        if (basis[i]) mask ^= basis[i];
    else {
        basis[i] = mask, ++sz;
        who.push_back(idx);
        return true;
    }
}
}
return false;
}
T maxXor() {
    T ans = 0;
    for (int i = LG - 1; i >= 0; --i) {
        ans = max(ans, ans ^ basis[i]);
    }
    return ans;
}
bool can(T x) {
    for (int i = LG - 1; i >= 0; --i) {
        if (x >> i & 1) {
            if (!basis[i]) return false;
            x ^= basis[i];
        }
    }
    return true;
}
T kth(T k) {
    if (k < 1 || k > ((T)1 << sz)) return -1;
    T mask = 0;
    int64_t tot = 1LL << sz;
    for (int i = LG - 1; i >= 0; --i) {
        if (basis[i]) {
            int64_t low = tot / 2;
            if ((low < k && (~mask >> i & 1)) ||
                (low >= k && (mask >> i & 1))) {
                mask ^= basis[i];
            }
            if (low < k) k -= low;
            tot /= 2;
        }
    }
    return mask;
}
// number of subsets having xor < x
T count_less(T x) {
    if (x < 0) {
        return 0;
    }
    T ret = 0;
    T cnt = ((T)1 << sz);
    T mask = 0;
    for (int i = LG - 1; i >= 0; i--) {
        if (basis[i]) {
            if (x >> i & 1) {
                ret += (cnt >> 1);
                if (~mask >> i & 1) {
                    mask ^= basis[i];
                }
            } else {
                if (mask >> i & 1) {
                    mask ^= basis[i];
                }
            }
            cnt >>= 1;
        } else {
            if ((x ^ mask) >> i & 1) {
                if (x >> i & 1) {
                    return ret + cnt;
                } else {

```

```

                for (int k = 0; k < m; k++) {
                    if (a[i][k] == 0) continue;
                    for (int j = 0; j < p; j++) {
                        result[i][j] = ((result[i][j] + a[i][k] *
                            b[k][j]) % mod + mod) % mod;
                    }
                }
            }
        }
        return result;
    }
}
vector<vector<int>> expo(vector<vector<int>> t,
int p) {
    int n = t.size();
    vector<vector<int>> result(n, vector<int>(n,
0));
    for (int i = 0; i < n; i++) {
        result[i][i] = 1;
    }
    while (p > 0) {
        if (p & 1) result = multiply(result, t);
        t = multiply(t, t);
        p >>= 1;
    }
    return result;
}

```

SOS DP

```

void zeta_subset(vector<int64_t> &dp, int bits) {
    for (int b = 0; b < bits; b++) {
        for (int mask = 0; mask < (1 << bits); mask++) {
            if (mask >> b & 1) {
                dp[mask] += dp[mask ^ (1 << b)];
            }
        }
    }
}
void zeta_superset(vector<int64_t> &dp, int bits) {
    for (int b = 0; b < bits; b++) {
        for (int mask = 0; mask < (1 << bits); mask++) {
            if (!(mask >> b & 1)) {
                dp[mask] += dp[mask | (1 << b)];
            }
        }
    }
}
void Solve() {
    ll n;
    cin >> n;
    vector<ll> arr(n);
    for (auto& x : arr)
        cin >> x;
    ll N = 1 + __lg(*max_element(arr.begin(),
arr.end()));
    vector<ll> sos2(1 << N, 0), sos(1 << N, 0);
    for (auto it : arr) {
        sos[it]++;
        sos2[((1 << N) - 1) ^ it]++;
    }
    for (int i = 0; i < N; ++i)
        for (int mask = 0; mask < (1 << N); ++mask)
            if (mask & (1 << i))
                sos[mask] += sos[mask ^ (1 << i)],
                sos2[mask] += sos2[mask ^ (1 << i)];
    // the number of elements y such that x|y = x
    // the number of elements y such that x&y = x
}

```

```

        return ret;
    }
}
}
return ret;
}
T count_leq(T x) {
    return count_less(x + 1);
}
T jumpK(T val, T k) {
    T p = count_leq(val);
    return kth(p + k);
}
};

```

Sum Of Digits upto N

```

uint64_t sumDigitsUpTo(uint64_t n){
    if(n <= 0) return 0;
    uint64_t sum = 0;
    for(uint64_t f = 1; f <= n; f *= 10){
        uint64_t hi = n / (f * 10);
        uint64_t cur = (n / f) % 10;
        uint64_t lo = n % f;
        sum += hi * 45LL * f;
        sum += cur * (lo + 1);
        sum += f * (cur * (cur - 1) / 2);
    }
    return sum;
}

```

Number of digits upto N

```

int64_t get(int64_t n) {
    int64_t base = 1, digits = 1, now = 0;
    while (base * 10 <= n) {
        base *= 10;
        now += (base - (base / 10 == 0 ? 1 : base / 10))
        * digits;
        digits += 1;
    }
    n -= (base - 1);
    now += n * digits;
    return now;
}

```

Linear Combination Checking Given $arr[] = \{a, b, c, d, \dots\}$ and an integer N , the task is to check if N can be represented as a linear combination of the array elements.

For example, $N = a \cdot x + b \cdot y + c \cdot z + \dots$ where $x, y, z, \dots$ are integers.

Ans: if $N \bmod \text{GCD}(\text{all array elements})$ is zero.

All possible submask in $O(n^3)$

```

for (int mask = 0; mask < 1 << n; mask++) {
    for (int sub = mask; sub > 0;
        sub = (sub - 1) & mask) {
    }
}

```

Max Rectangular Sum in Matrix

```

int main() {
    int n;
    while (scanf("%d", &n) != EOF) {
        int mx = -1280, arr[n + 1][n + 1], linear[n],
            gsum, csum, qsum[n][n];
        for (int i = 0; i < n; i++) {

```

```

// the number of elements y such that x&y != 0
for (auto& it : arr) {
    cout << sos[it] << ' ';
    cout << sos2[((1 << N) - 1) ^ it] << ' ';
    cout << n - sos[((1 << N) - 1) ^ it] << ' ';
}
}

```

LIS

```

int lis(vector<int> const& a) {
    int n = a.size();
    const int INF = 1e9;
    vector<int> d(n+1, INF);
    d[0] = -INF;
    for (int i = 0; i < n; i++) {
        int l = upper_bound(d.begin(), d.end(),
            a[i]) - d.begin();
        if (d[l-1] < a[i] && a[i] < d[l])
            d[l] = a[i];
    }
    int ans = 0;
    for (int l = 0; l <= n; l++) {
        if (d[l] < INF)
            ans = l;
    }
    return ans;
}

```

LIS up to every index

```

vector<int>
longestObstacleCourseAtEachPosition(vector<int>
    &a) {
    vector<int> lis, ans;
    for(auto &it:a){
        int indx =
            upper_bound(lis.begin(), lis.end(), it) - lis.
            begin();
        if(indx==(int)lis.size()) lis.push_back(it);
        else lis[indx] = it;
        ans.push_back(indx+1);
    }
    return ans;
}

```

Subset sum bitset optimization // Only works when the sum of values is not // greater than N ; // TC : $O(N / 32 * \sqrt{N})$;

```

const int N = 1e6 + 6;
bitset<N> dp;
dp.set(0);
for (auto &[w, c] : comp) { // w is the value and
    c
    // is the count of it's
    for (int i = 0; 1 << i <= c; ++i) {
        dp |= dp << (w * (1 << i));
        c -= 1 << i;
    }
    dp |= dp << (w * c);
}
dp.test(k) // if it's possible to make sum equal
    to k

```

Burnside's Lemma/Polya Enumeration

```

using Permutation = vector<int>;
void operator*=(Permutation& p, Permutation
    const& q) {
    Permutation copy = p;
    for (int i = 0; i < p.size(); i++)
        p[i] = copy[q[i]];
}

```

```

for (int j = 0; j < n; j++) {
    scanf("%d", &arr[i][j]);
    if (j == 0)
        qsum[i][j] = arr[i][j];
    else
        qsum[i][j] = arr[i][j] + qsum[i][j - 1];
}
}
gsum = arr[0][0];
for (int j = 0; j < n; j++) {
    for (int k = j; k < n; k++) {
        for (int i = 0; i < n; i++) {
            int temp = qsum[i][k] - qsum[i][j] +
                arr[i][j];
            if (i == 0) {
                csum = temp;
                continue;
            }
            csum = max(temp, csum + temp);
            gsum = max(csum, gsum);
        }
    }
}
printf("%d\n", gsum);
}
return 0;
}

```

Dearrangement:

```

if (n > 0) D[1] = 0;
if (n > 1) D[2] = 1;
for (int i = 3; i <= n; i++) {
    D[i] = (i - 1) * (D[i - 1] + D[i - 2]);
}

```

Stars and bars: $C(n+k-1, k)$;**Catalan:**

n = number of pairs: $C(2n, n) - C(2n, n-1)$;

n = number of brackets: $\frac{1}{n+1} \cdot C(2n, n)$

```

long long lucas(long long n, long long r) {
    if (r == 0) return 1;
    return lucas(n / MOD, r / MOD) * nCr(n %
        MOD, r % MOD) % MOD;
}

```

Binomial Coefficient Properties

$$\binom{n}{k} = \binom{n}{n-k}$$

$$\sum_{k=0}^m \binom{n-1}{k-1} = \binom{n+m-1}{m}$$

$$\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k}$$

$$\sum_{k=0}^n \binom{n}{k} = 2^n$$

$$\binom{n}{0} + \binom{n}{1} + \dots + \binom{n}{n} = 2^n$$

$$\binom{n}{0} + \binom{n}{2} + \binom{n}{4} + \dots = 2^{n-1}$$

$$1 \binom{n}{1} + 2 \binom{n}{2} + \dots + n \binom{n}{n} = n \cdot 2^{n-1}$$

```

int count_cycles(Permutation p) {
    int cnt = 0;
    for (int i = 0; i < p.size(); i++) {
        if (p[i] != -1) {
            cnt++;
            for (int j = i; p[j] != -1; j = p[j]) {
                int next = p[j];
                p[j] = -1;
                j = next;
            }
        }
    }
    return cnt;
}

int solve(int n, int m) {
    Permutation p(n*m), p1(n*m), p2(n*m),
    p3(n*m);
    for (int i = 0; i < n*m; i++) {
        p[i] = i;
        p1[i] = (i % n + 1) % n + i / n * n;
        p2[i] = (i / n + 1) % m * n + i % n;
        p3[i] = (m - 1 - i / n) * n + (n - 1 - i % n);
    }
    set<Permutation> s;
    for (int i1 = 0; i1 < n; i1++) {
        for (int i2 = 0; i2 < m; i2++) {
            for (int i3 = 0; i3 < 2; i3++) {
                s.insert(p);
                p *= p3;
            }
            p *= p2;
        }
        p *= p1;
    }
    int sum = 0;
    for (Permutation const& p : s) {
        sum += 1 << count_cycles(p);
    }
    return sum / s.size();
}

```

Exclusion DP There is only difference to calculate $f[i]$ for different problems,

for ordered pair means (a, b) and (b, a) are not same then $f[i] = d[i] \cdot d[i]$;

for unordered pair means (a, b) and (b, a) are same then

-for repetitive $\rightarrow f[i] = (d[i] + 1)C2 \rightarrow d[i] \cdot (d[i] + 1)/2$;

-for non-repetitive $\rightarrow f[i] = d[i]C2 \rightarrow d[i] \cdot (d[i] - 1)/2$;

for k -tuples:

-for ordered tuples : $f[i] = (d[i])^k$;

-for unordered tuples :

-for non-repetitive $\rightarrow f[i] = d[i]Ck$

-for repetitive $\rightarrow f[i] = (d[i] + k - 1)Ck$

here $d[i]$ = number of elements divisible by i .

and C denotes combination

Bishop Placement /* Number of ways to place K bishops on an $N \times N$ chessboard so that no two bishops attack each other. */

```

int bishop_placements(int N, int K)
{

```

Connection With Fibonacci numbers:

$$\binom{n}{0} + \binom{n-1}{1} + \dots + \binom{n-k}{k} + \dots + \binom{0}{n} = F_{n+1}$$

Geometry Formulas

Triangle:

Side length a, b, c

Area: $\frac{1}{2} \times \text{base} \times \text{height}$

$$s = \frac{a+b+c}{2}, \text{Area} = \sqrt{s(s-a)(s-b)(s-c)}$$

Inradius: $r = \frac{\text{Area}}{s}$

Circumradius: $R = \frac{abc}{4 \times \text{Area}}$

Circles:

Arc Length: $L = \theta r$

Sector Area: $\text{Area} = \frac{1}{2} r^2 \theta$

Segment Area (Area of the part cut off by a chord): $\text{Area} = \frac{1}{2} r^2 (\theta - \sin \theta)$

- **Rhombus:**

- Area: $\frac{1}{2} \times d_1 \times d_2$ (where d_1 and d_2 are diagonals).

- **Trapezium:**

- Area: $\frac{1}{2} \times (\text{Base}_1 + \text{Base}_2) \times \text{Height}$.

3. Regular Polygon (n sides):

- Perimeter: $n \times a$

- Area: $\frac{1}{4} n a^2 \cot\left(\frac{\pi}{n}\right)$ (where a is the side length).

Curved Shapes

1. Circle

- Circumference: $2\pi r$

- Area: πr^2

2. Ellipse

- Area: πab (where a is the semi-major axis and b is the semi-minor axis).

✓ Polygon

- Interior angle sum: $(n-2) \times 180^\circ$

- Each internal angle (regular): $\frac{(n-2) \times 180^\circ}{n}$

4. Tetrahedron

- Volume: $\frac{1}{6} \times \text{Base Area} \times \text{Height}$.

```
if (K > 2 * N - 1)
    return 0;
vector<vector<int>> D(N * 2, vector<int>(K + 1));
for (int i = 0; i < N * 2; ++i)
    D[i][0] = 1;
D[1][1] = 1;
for (int i = 2; i < N * 2; ++i)
    for (int j = 1; j <= K; ++j)
        D[i][j] = D[i-2][j] + D[i-2][j-1] *
            (squares(i) - j + 1);
int ans = 0;
for (int i = 0; i <= K; ++i)
    ans += D[N*2-1][i] * D[N*2-2][K-i];
return ans;
}
```

Handling Precision (EPS)

```
const double EPS = 1e-9;
bool equal(double a, double b) { return abs(a - b) < EPS; }
bool lessThan(double a, double b) { return a < b - EPS; }
bool greaterThan(double a, double b) { return a > b + EPS; }
```

Point and Vector

```
const double EPS = 1e-9;
struct Point {
    double x, y;
    Point operator+(const Point& other) const {
        return {x + other.x, y + other.y}; }
    Point operator-(const Point& other) const {
        return {x - other.x, y - other.y}; }
    Point operator*(double s) const { return {x * s, y * s}; }
    Point operator/(double s) const { return {x / s, y / s}; }
    bool operator<(const Point& other) const {
        if (abs(x - other.x) > EPS) return x < other.x;
        return y < other.y - EPS;
    }
    bool operator==(const Point& other) const {
        return abs(x - other.x) < EPS && abs(y - other.y) < EPS;
    }
};
typedef Point Vector;
double dot(Vector a, Vector b) { return a.x * b.x + a.y * b.y; }
double norm_sq(Vector a) { return dot(a, a); }
double length(Vector a) { return sqrt(norm_sq(a)); }
double cross(Vector a, Vector b) { return a.x * b.y - a.y * b.x; }
// Returns: > 0 for Left Turn, < 0 for Right Turn, // 0 for Collinear
double orientation(Point p, Point a, Point b) {
    return cross(a - p, b - p);
}
double distToLine(Point p, Point a, Point b) {
    return abs(cross(p - a, b - a)) / length(b - a);
}
double distToSegment(Point p, Point a, Point b) {
    if (dot(p - a, b - a) < 0) return length(p - a);
    if (dot(p - b, a - b) < 0) return length(p - b);
}
```

Curved 3D Shapes

1. Sphere

- Surface Area: $4\pi r^2$
- Volume: $\frac{4}{3}\pi r^3$

2. Cylinder

- Surface Area: $2\pi r(r+h)$
- Volume: $\pi r^2 h$



3. Cone

- Surface Area: $\pi r(r+l)$, where $l = \sqrt{r^2 + h^2}$ is the slant height.
- Volume: $\frac{1}{3}\pi r^2 h$.

Other Shapes

1. Torus

- Surface Area: $4\pi^2 Rr$
- Volume: $2\pi^2 Rr^2$, where R is the distance from the center of the tube to the center of the torus, and r is the radius of the tube.



```

return distToLine(p, a, b);
}
double polygonArea(const vector<Point>& p) {
    double area = 0;
    for (int i = 0; i < (int)p.size(); i++) {
        area += cross(p[i], p[(i + 1) % p.size()]);
    }
    return abs(area) / 2.0;
}

void convex_hull(vector<pt>& a, bool
include_collinear = false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt
a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y,
b.x);
    });
    sort(a.begin(), a.end(), [&p0](const pt& a,
const
pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x-a.x)*(p0.x-a.x) +
(p0.y-a.y)*(p0.y-a.y)
< (p0.x-b.x)*(p0.x-b.x) +
(p0.y-b.y)*(p0.y-b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size()-1;
        while (i >= 0 && collinear(p0, a[i], a.back()))
            i--;
        reverse(a.begin()+i+1, a.end());
    }
    vector<pt> st;
    for (int i = 0; i < (int)a.size(); i++) {
        while (st.size() > 1 && !cw(st[st.size()-2],
st.back(), a[i], include_collinear))
            st.pop_back();
        st.push_back(a[i]);
    }
    if (include_collinear == false && st.size() == 2
&& st[0] == st[1])
        st.pop_back();
    a = st;
}

```

Closest pair of points:

```

struct Res {
    int64_t d;
    P a, b;
};

int64_t sq(int64_t x) { return x * x; }
int64_t dist(P &a, P &b) {
    return sq(a.x - b.x) + sq(a.y - b.y);
}

// p = py = tmp, all are same sorted by x co-ordi
.

Res closest_pair(vector<P>& p, vector<P>& py,
vector<P>& tmp, int l, int r) {
    int n = r - l + 1;
    if (n <= 1) return {LLONG_MAX, {}, {}};
    if (n == 2) {
        if (py[l].y > py[l + 1].y)
            swap(py[l], py[l + 1]);
        return {dist(p[l], p[l + 1]), p[l], p[l + 1]};
    }
    int m = (l + r) >> 1;
    int midx = p[m].x;

```

```

Res res_l = closest_pair(p, py, tmp, l, m);
Res res_r = closest_pair(p, py, tmp, m + 1, r);
Res res = (res_l.d < res_r.d ? res_l : res_r);
for (int i = l, j = m + 1, k = l; k <= r; k++) {
    if (j > r || (i <= m && py[i].y < py[j].y))
        tmp[k] = py[i++];
    else tmp[k] = py[j++];
}
for (int i = l; i <= r; i++) py[i] = tmp[i];
vector<P> stripe;
for (int i = l; i <= r; i++) {
    if (sq(py[i].x - midx) < res.d)
        stripe.push_back(py[i]);
}
for (int i = 0; i < (int)stripe.size(); i++) {
    for (int j = i + 1; j < (int)stripe.size(); j++) {
        if (sq(stripe[i].y - stripe[j].y) >= res.d)
            break;
        int64_t d = dist(stripe[i], stripe[j]);
        if (d < res.d) res = {d, stripe[i], stripe[j]};
    }
}
return res;
}

long double L, W;
if(!(cin >> L >> W)) return 0;
// hypotenuse of each right triangle
long double h = sqrtl(L*L + W*W);
// perimeter for incenter-weights: P = L + W + h
long double P = L + W + h;
// incenter of triangle with vertices
// (0,0), (L,0), (L,W)
long double x1 = L*(L + h)/P;
long double y1 = L*W/P;
// incenter of triangle with vertices
// (0,0), (0,W), (L,W)
long double x2 = L*W/P;
long double y2 = W*(W + h)/P;
long double dx = x1 - x2;
long double dy = y1 - y2;
long double D = sqrtl(dx*dx + dy*dy);
cout << fixed << setprecision(6) << (double)D
<< "\n";

long double r1, r2, r3;
cin >> r1 >> r2 >> r3;
// side-lengths of triangle ABC
long double a = r2 + r3;
long double b = r3 + r1;
long double c = r1 + r2;
long double s = (a + b + c) / 2.0L;
long double T = sqrtl(s*(s - a) * (s - b) * (s - c));
// helper to compute angle opposite side a
auto angle = [&](long double opp, long double x, long double y){
    long double cosv = (x*x + y*y - opp*opp) /
        (2.0L * x * y);
    // guard numerical drift
    cosv = min((long double)1.0, max((long double)-1.0, cosv));
    return acosl(cosv);
};
long double A = angle(a, b, c);
long double B = angle(b, c, a);
long double C = angle(c, a, b);
// subtract the sectors
long double sectorSum = 0.5L*(r1*r1*A +

```

```

r2*r2*B + r3*r3*C);
long double blackArea = T - sectorSum;
cout << fixed << setprecision(6) <<
(double)blackArea << "\n";
return 0;
}

```

Intersecting Point of Two Lines Given as Pair of 2 Points

```

// Intersecting point of two lines (a1-a2, b1-b2)
using P = pair<ll,ll>;
auto cross = [&](P a, P b){ return
(__int128)a.first*b.second -
(__int128)a.second*b.first; };
auto intersect = [&](P a1, P a2, P b1, P b2) ->
optional<pair<long double,long double>> {
    P da = {a2.first - a1.first,
a2.second - a1.second};
    P db = {b2.first - b1.first,
b2.second - b1.second};
    P dc = {b1.first - a1.first,
b1.second - a1.second};
    __int128 D = cross(da, db);
    if (!D) return {}; // parallel or coincident
    long double t = (long double)cross(dc, db) /
(long double)D;
    return {{a1.first + da.first * t,
a1.second + da.second * t}};
};
// Example: // if (auto p = intersect(a1,a2,b1,b2)
)
// cout << llround(p->first) << " " <<
// llround(p->second) << "\n";
// else
// cout << "No intersection\n";
// For segments add this before returning
long double u = (long double)cross(dc, da) / (long
double)D;
if (t < 0 || t > 1 || u < 0 || u > 1) return {};
// no segment intersection

```

Polygon:

```

const ld EPS = 1e-9;
const ld PI = acos(-1.0);
int sgn(ld x) { return (x > EPS) - (x < -EPS); }
struct P {
    using T = int64_t;
    T x, y;
    void read() { cin >> x >> y; }
    P operator - (const P &b) const {
        return P{x - b.x, y - b.y}; }
    P operator + (const P &b) const {
        return P{x + b.x, y + b.y}; }
    void operator -= (const P &b) {
        x -= b.x; y -= b.y; }
    void operator += (const P &b) {
        x += b.x; y += b.y; }
    bool operator < (const P &b) const {
        return x == b.x ? y < b.y : x < b.x; }
    bool operator == (const P &b) const {
        return x == b.x && y == b.y; }
    T operator * (const P &b) const {
        return x * b.y - y * b.x; }
    T operator ^ (const P &b) const {
        return x * b.x + y * b.y; }
    T dot (P &a, P &b) const {
        return (a - *this) ^ (b - *this); }
    T cross (P &a, P &b) {
        return (a - *this) * (b - *this); }
    long double slope() {

```

```

        return (long double)y / x; }
    ld sq() const { return x * x + y * y; }
    ld abs() const { return sqrtl(sq()); }
    P rot() const { return P(-y, x); } // Rotate 90
    deg CCW
    P rot(ld a) const {
        return P(x*cos(a) - y*sin(a),
            x*sin(a) + y*cos(a)); }
};

bool collinear(P &a, P &b, P &c) {
    return (b - a) * (c - a) == 0;
}

inline bool on_segment(P &p, P &q, P &r) {
    if (!collinear(p, q, r)) return false;
    return r.x <= max(p.x, q.x) && r.x >= min(p.x,
        q.x) && r.y <= max(p.y, q.y) &&
        r.y >= min(p.y, q.y);
}

ld dist(P a, P b) { return (a - b).abs(); }
// --- Lines & Segments ---
// Project C onto line AB
P project(P a, P b, P c) {
    return a + (b - a) * (((c - a) ^ (b - a)) /
        (b - a).sq());
}

// Reflect C across line AB
P reflect(P a, P b, P c) {
    return project(a, b, c) * 2 - c;
}

// Dist from C to infinite line AB
ld dist_pt_line(P a, P b, P c) {
    return fabsl((b - a) * (c - a)) / (b - a).abs();
}

// Dist from C to segment AB
ld dist_pt_seg(P a, P b, P c) {
    if (((c - a) ^ (b - a)) <= 0) return (c - a).abs
        ();
    if (((c - b) ^ (a - b)) <= 0) return (c - b).abs
        ();
    return dist_pt_line(a, b, c);
}

// Check if P is on segment AB
bool on_seg(P a, P b, P p) {
    return !sgn((b - a) * (p - a)) &&
        ((p - a) ^ (p - b)) <= EPS;
}

// Line-Line Intersection (returns false if
// parallel)
bool line_int(P a, P b, P c, P d, P &res) {
    ld cp = (b - a) * (d - c);
    if (!sgn(cp)) return false;
    res = a + (b - a) * (((d - c) * (c - a)) / cp);
    return true;
}

// Segment-Segment Intersection
bool seg_int(P a, P b, P c, P d) {
    auto cp = [&](P x, P y, P z) {
        return sgn((y - x) * (z - x)); };
    if (on_seg(a, b, c) || on_seg(a, b, d) ||
        on_seg(c, d, a) || on_seg(c, d, b)) return true;
    return cp(a, b, c) != cp(a, b, d) &&
        cp(c, d, a) != cp(c, d, b);
}

long double polygon_area(vector<P> &p) {
    int64_t area = 0, n = p.size();
    for (int i = 0; i < n; ++i)
        area += p[i] * p[(i + 1) % n];
    return abs(area) / 2;
}

```

```

vector<P> convexHull(vector<P> p) {
    int n = p.size(), k = 0;
    if (n <= 2) return p;
    vector<P> h(2 * n);
    sort(p.begin(), p.end());
    for (int i = 0; i < n; h[k++] = p[i++])
        while (k >= 2 && h[k - 2].cross(h[k - 1],
            p[i]) <= 0) k--;
    for (int i = n - 2, t = k + 1; i >= 0;
        h[k++] = p[i--])
        while (k >= t && h[k - 2].cross(h[k - 1],
            p[i]) <= 0) k--;
    h.resize(k - 1);
    return h;
}

int is_point_in_polygon(const vector<P>& p, P
q) {
    int c = 0;
    for (int i = 0, n = p.size(); i < n; ++i) {
        P a = p[i], b = p[(i + 1) % n];
        if ((b - a) * (q - a) == 0 && min(a.x, b.x) <=
            q.x
            && q.x <= max(a.x, b.x) && min(a.y, b.y) <= q.
                y
            && q.y <= max(a.y, b.y)) return 2;
        if ((a.y > q.y) != (b.y > q.y) &&
            ((b - a) * (q - a) > 0) == (a.y < b.y))
            c = !c;
    }
    return c;
}

double angle_at_vertex(P &a, P &b, P &c) {
    double ang_rad = atan2l(fabs(b.cross(a, c)),
        b.dot(a, c));
    return ang_rad * 180.0L / acosl(-1.0L);
}

ld dist_point_line(P a, P b, P c) {
    ld area2 = fabsl((b - a) * (c - a));
    ld base = hypotl(b.x - a.x, b.y - a.y);
    return area2 / base;
}

```

MO:

```

sort(cu.begin(), cu.end(), [&](auto &x, auto &y){
    if (x.l / B != y.l / B) return x.l / B < y.l / B
    ;
    return (x.l / B) % 2 ? x.r > y.r : x.r < y.r;
});
int R = -1, L = 0;
while (R < r) add(++R);
while (L > l) add(--L);
while (R > r) rem(R--);
while (L < l) rem(L++);

```

Fast Factorization (Maybe not prime)

```

#define ull uint64_t
struct Montgomery {
    ull n, nr;
    Montgomery(ull n) {
        this->n = n, nr = 1;
        for (int i = 0; i < 6; i++)
            nr *= 2 - n * nr;
    }
    ull reduce(__uint128_t x) const {
        ull q = ull(x) * nr,
            m = ((__uint128_t)q * n) >> 64;
        return (x >> 64) + n - m;
    }
    ull multiply(ull x, ull y) {

```

```

        return reduce((__uint128_t)x * y); }
};
ull f(ull x, Montgomery& m, ull a) {
    return m.multiply(x, x) + a; }
ull diff(ull a, ull b) {
    return a > b ? a - b : b - a; }
const int M = 1024;
const ull SEED = 42;
ull find_factor(ull n, ull x0 = 2, ull a = 1)
{
    Montgomery m(n);
    ull x = SEED;
    for (int l = M; l < (1 << 20); l *= 2) {
        ull y = x, p = 1;
        for (int i = 0; i < l; i += M) {
            for (int j = 0; j < M; j++)
                x = f(x, m, a), p = m.multiply(p,
                    diff(x, y));
            if (ull g = gcd(p, n); g != 1)
                return g;
        }
    }
    return n;
}
int32_t main() {
    ll n;
    cin >> n;
    ll factor = find_factor(n);
    if (factor != 1) {
        cout << "Factor found: " << factor << endl;
    } else {
        cout << "No factor found" << endl;
    }
    return 0;
}

```

OR convolution = SOS DP