NETWORK RECONNAISSANCE AND OPEN-SOURCE INTELLIGENCE (OSINT) ASSESSMENT

W2-PM- FINAL | Cybersecurity Internship Technical Report | NETWORKWALKS

Prepared by: Ahwen Israel Lutor | LinkedIn | GitHub
Programme Batch: B084E-Networkwalks
Assessment Period: 8 November 2026 – 15 November 2026
Target Domain: `networkwalks.com`

TABLE OF CONTENTS

1. Executive Summary & Liability Disclaimer
2. Introduction
3. Assessment Objectives
4. Scope and Methodology
5. Tools and Technologies Used
6. External Domain Reconnaissance
    - 6.1 WHOIS Enumeration
    - 6.2 Web Technology Fingerprinting
    - 6.3 DNS Lookup
    - 6.4 DNS Enumeration
    - 6.5 Web Application Firewall Detection
    - 6.6 HTTP Header Analysis
7. Internal Network Discovery
8. Open-Source Intelligence Using Maltego
9. Consolidated Findings and Security Analysis
10. Security Recommendations
11. Assessment Limitations
12. Conclusion
13. Appendices

---

1. EXECUTIVE SUMMARY & LIABILITY DISCLAIMER

This report documents the execution and analysis of a cybersecurity assessment involving external domain reconnaissance, internal network discovery, and open-source intelligence (OSINT).

The assessment was conducted individually using a structured internship guide, with `networkwalks.com` serving as the assigned target domain for the external reconnaissance and OSINT activities. A separate internal network discovery exercise was conducted within a self-configured VirtualBox laboratory environment.

Several cybersecurity tools were employed, including WHOIS, WhatWeb, nslookup, DNSrecon, WAFW00F, cURL, Nmap/Zenmap, and Maltego. These tools were used to gather publicly accessible information, identify network infrastructure details, fingerprint web technologies, examine DNS records, detect an externally identifiable web application firewall, and discover publicly associated email information.

The activities produced several useful observations, including the domain's registration details, hosting and DNS information, publicly identifiable technologies, security-related HTTP headers, DNS configuration, and the presence of ModSecurity. The internal network exercise successfully identified four active hosts within the local virtual network. The Maltego investigation also identified one publicly discoverable email address associated with the target domain.

Beyond the technical findings, the assessment provided practical experience in reconnaissance, network enumeration, information gathering, tool selection, result interpretation, and documentation. The ability to execute these activities individually, interpret their outputs, and correlate observations across multiple tools demonstrates a developing foundation in cybersecurity operations and an ability to undertake structured entry-level technical assignments.

No exploitation or intrusive testing was performed. The assessment was limited to reconnaissance, discovery, and analysis.

I have performed these activities only on the systems & devices where I had secured written permission or the devices/systems that I own myself. All these materials are for education and research purpose only. Do not use anything from here to break the law. The instructor, the authors and Networkwalks are not responsible for what you do with this knowledge. Every action you take is your own responsibility. Misuse can lead to criminal charges, heavy fines, loss of your job and a permanent record. In most countries unauthorised access is a crime even when nothing is damaged.

2. INTRODUCTION

Reconnaissance and information gathering are important stages of cybersecurity assessment. Before security professionals can meaningfully evaluate an organisation's exposure, they must understand the systems, technologies, infrastructure, and publicly accessible information associated with the environment under review.

This assessment was designed to provide practical exposure to these activities through the use of industry-relevant tools in Kali Linux, Windows, and a virtualised laboratory environment.

The work focused on three areas:

- External reconnaissance of an assigned internet-facing domain.
- Discovery of active devices within a controlled internal virtual network.
- OSINT investigation to identify publicly discoverable email information associated with the assigned domain.

The assessment provided an opportunity to apply theoretical knowledge in a practical environment, develop familiarity with common cybersecurity tools, and strengthen the ability to interpret technical findings.

3. ASSESSMENT OBJECTIVES

The primary objectives of the assessment were to:

1. Gather publicly available registration and infrastructure information about the assigned domain.
2. Identify the technologies and services exposed by the target website.
3. Examine DNS records and identify relevant domain configuration details.
4. Detect the presence of an externally identifiable web application firewall.
5. Analyse HTTP response headers and identify security-related observations.
6. Discover active hosts within a controlled virtual network.
7. Use Maltego to identify publicly discoverable email addresses associated with the target domain.
8. Interpret and document findings while identifying potential security implications.
9. Demonstrate practical familiarity with reconnaissance and information-gathering tools.

4. SCOPE AND METHODOLOGY

The assessment was divided into three practical activities.

4.1 External Domain Reconnaissance

The assigned domain, `networkwalks.com`, was examined using six reconnaissance tools. The investigation focused on domain registration information, DNS records, web technologies, HTTP response behaviour, and externally identifiable security controls.

4.2 Internal Network Discovery

A separate network discovery exercise was conducted within a self-configured VirtualBox NAT Network. Zenmap was used from a Windows virtual machine to identify active devices within the laboratory subnet.

This activity was restricted to the user's own virtual laboratory environment and did not involve scanning the target organisation's internal infrastructure.

4.3 Open-Source Intelligence

Maltego was installed, activated, and used to investigate the assigned domain. A domain entity was created, and an appropriate transformation was executed to identify publicly discoverable email information.

4.4 Assessment Approach

The activities were performed individually, following a structured internship guide. The guide provided direction for the assigned tasks, while the installation, configuration, execution of tools, examination of outputs, and documentation of results were carried out by the participant.

This distinction is important: the assessment demonstrates the ability to follow a defined technical process, operate relevant tools, and interpret their outputs independently within an assigned scope.

5. TOOLS AND TECHNOLOGIES USED

Tool	Purpose
Kali Linux	Operating system used for external reconnaissance and OSINT-related activities.
WHOIS	Retrieval of domain registration and registrar information.
WhatWeb	Identification of web technologies and server-side components.
nslookup	DNS resolution and retrieval of domain IP information.
DNSrecon	DNS enumeration and collection of DNS records.
WAFW00F	Detection of externally identifiable web application firewalls.
cURL	Retrieval and examination of HTTP response headers.
VirtualBox	Creation and management of the virtual laboratory environment.
Windows VM	Host environment used to execute Zenmap for internal network discovery.
Nmap/Zenmap	Discovery of active hosts within the local network.
Maltego	Graph-based OSINT investigation and email discovery.

6. EXTERNAL DOMAIN RECONNAISSANCE

The external reconnaissance phase involved gathering information about the assigned domain through several complementary tools. Each tool provided a different perspective on the target's publicly observable infrastructure and configuration.

6.1 WHOIS Enumeration

Objective: Retrieve domain registration information and identify relevant administrative and infrastructure details.

Tool: WHOIS

The WHOIS lookup was performed against `networkwalks.com` to obtain publicly available registration information.

Key observations:

- **Domain:** `networkwalks.com`
- **Registrar:** GoDaddy.com, LLC
- **Creation date:** 6 November 2019
- **Last updated:** 12 November 2025
- **Expiration date:** 6 November 2027
- **Registrant information:** Registration Private, Domains By Proxy, LLC
- **DNSSEC:** Unsigned
- **Registrar WHOIS server:** `whois.godaddy.com`

The domain was also found to have the following listed nameservers:

- `NS6135.HOSTGATOR.COM`
- `NS6136.HOSTGATOR.COM`
- `NS29.DOMAINCONTROL.COM`

- `NS30.DOMAINCONTROL.COM`

Several registrar status codes were returned, including `clientTransferProhibited`, `clientUpdateProhibited`, `clientRenewProhibited`, and `clientDeleteProhibited`.

Analysis:


The results established the domain's registrar, registration timeline, privacy status, and listed nameservers. The use of registration privacy limits the amount of registrant information publicly available, while the client status restrictions indicate protective registrar locks.

The unsigned DNSSEC status is a configuration observation worth reviewing because DNSSEC provides an additional mechanism for validating DNS responses.

The WHOIS results also provided a useful reference point for comparison with the DNS enumeration results obtained later in the assessment.

Competency demonstrated: Ability to retrieve and interpret domain registration information, recognise common registrar status codes, and identify DNS-related configuration observations.

Evidence:



6.2 Web Technology Fingerprinting

Objective: Identify technologies and components associated with the target website.

Tool: WhatWeb

The following command was executed:

```
whatweb networkwalks.com
```

Key observations:

- HTTP response: `200 OK` over HTTPS.
- Web server: Apache.
- Operating system/server environment: Not conclusively identified.
- Content management system: WordPress.
- WordPress Download Manager detected.

- JavaScript library: jQuery 3.7.1.
- Google Tag Manager detected.
- HTML5 and Open Graph metadata detected.
- Website title: Networkwalks Academy.
- Publicly identifiable email address: `info@networkwalks.com`.
- Resolved IP address: `192.232.216.135`.

WhatWeb also reported a Bootstrap version, although automated fingerprinting can produce inaccurate version identification. This observation should therefore be independently verified before being treated as definitive.

The initial HTTP request was also observed to redirect to HTTPS with a `301 Moved Permanently` response.

Analysis:


The results provided insight into the website's externally identifiable technology stack. Identifying the content management system, server software, and supporting components is useful during reconnaissance because it helps security professionals understand the technologies that may require further review.

However, technology identification does not establish that a component is vulnerable. The reported versions would need to be verified and compared against reliable vulnerability information before any security conclusion could be reached.

The country information returned by WhatWeb is based on IP geolocation and should not be interpreted as confirmation of the organisation's physical location.

Competency demonstrated: Ability to perform web technology fingerprinting, interpret automated tool output, distinguish confirmed observations from unverified identification, and recognise the relevance of technology exposure during reconnaissance.

Evidence:



6.3 DNS Lookup

Objective: Determine the IP address associated with the target domain.

Tool: nslookup

The following command was executed:

```
nslookup networkwalks.com
```

Key observations:


- DNS resolver: `8.8.8.8` (Google Public DNS).
- Domain: `networkwalks.com`.
- Resolved IPv4 address: `192.232.216.135`.
- Response type: Non-authoritative answer.

Analysis:

The lookup successfully resolved the domain to its publicly returned IPv4 address. This information provides a starting point for understanding the domain's external network presence and supports further infrastructure enumeration.

Competency demonstrated: Ability to use command-line DNS utilities, interpret DNS resolution results, and identify the relationship between a domain name and its resolved IP address.

Evidence:



6.4 DNS Enumeration

Objective: Identify publicly available DNS records and gather additional information about the domain's DNS infrastructure.

Tool: DNSrecon

The following command was executed:

```
dnsrecon -d networkwalks.com
```

Key observations:

The enumeration returned the following information:

Record type	Result
SOA	`ns6135.hostgator.com`
NS	`ns6135.hostgator.com` and `ns6136.hostgator.com`
A	`192.232.216.135`
MX	`mail.networkwalks.com` resolving to `192.232.216.135`
TXT	SPF record and Google site verification record
SRV	cPanel email autodiscovery records
DNSSEC	No answer returned for DNSSEC query

The SPF record returned was:

```
v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
```

DNSrecon also identified the following BIND version information for the nameservers:

```
9.16.23-RH
```

Eight SRV records associated with cPanel email autodiscovery were identified, pointing to `cpanelemaildiscovery.cpanel.net` over port 443.

Analysis:

The enumeration provided additional information about the domain's DNS configuration, including its authoritative nameserver records, mail exchange configuration, TXT records, and service discovery records.


The SPF record uses the soft-fail qualifier (`~all`). This is not automatically a security weakness, but it is worth reviewing alongside the domain's DKIM and DMARC configuration to assess the overall email authentication posture.

The BIND version information represents publicly identifiable infrastructure information. Version disclosure alone does not establish that the DNS servers are vulnerable; their actual patch status and configuration would require further verification.

A difference was also observed between the nameservers returned by WHOIS and those identified by DNSrecon. WHOIS listed both HostGator and DomainControl nameservers, whereas DNSrecon returned the HostGator pair. This discrepancy should be validated against the authoritative DNS delegation before being treated as a configuration issue.

Competency demonstrated: Ability to perform DNS enumeration, identify different DNS record types, interpret mail-related records, recognise infrastructure version disclosures, and compare results obtained from separate reconnaissance tools.

Evidence:



6.5 Web Application Firewall Detection

Objective: Identify whether an externally detectable web application firewall is protecting the target website.

Tool: WAFW00F

The following command was executed:

```
wafw00f https://networkwalks.com
```

Key observation:

WAFW00F identified:

```
ModSecurity (SpiderLabs)
```

The detection was completed using two HTTP requests.

Analysis:

The result indicates that ModSecurity was externally identifiable as a web application firewall associated with the target website.


A WAF provides an additional layer of protection by inspecting web traffic and applying rules intended to detect or block malicious requests.

The presence of a WAF is a positive defensive observation. However, detection alone does not establish the effectiveness of its rules, the completeness of its coverage, or its ability to prevent specific attacks.

No bypass testing or attack simulation was performed.

Competency demonstrated: Ability to use WAF detection tools, interpret security-control identification results, and distinguish the presence of a defensive mechanism from proof of its effectiveness.

Evidence:



6.6 HTTP Header Analysis

Objective: Examine the target website's HTTP response headers and identify relevant security-related configuration details.

Tool: cURL

The following command was executed:

```
curl -I https://networkwalks.com
```

Key observations:

- HTTP response: `200 OK`.
- Server: Apache.
- Content type: `text/html; charset=UTF-8`.
- WordPress REST API endpoint advertised.
- Cookie: `__wpdm_client`.
- Cookie attributes included `Secure` and `HttpOnly`.
- Referrer Policy: `no-referrer-when-downgrade`.
- Permissions Policy header present.

The response also advertised the following endpoint:

```
https://networkwalks.com/wp-json/
```

The following security-related headers were not observed in the captured response:

- `Strict-Transport-Security`
- `Content-Security-Policy`
- `X-Content-Type-Options`
- `X-Frame-Options`

Analysis:

The successful HTTPS response confirmed that the website was accessible over an encrypted connection at the time of testing. The HTTP-to-HTTPS redirect observed during the WhatWeb activity also indicates that the site directs ordinary HTTP requests to its HTTPS version.

The `Secure` and `HttpOnly` attributes on the observed cookie are positive security characteristics. The former restricts cookie transmission to secure connections, while the latter limits access through client-side scripts.


The response included a Permissions Policy header and a Referrer Policy header. The observed Referrer Policy, `no-referrer-when-downgrade`, is valid but less restrictive than some alternatives and may warrant review depending on the site's requirements.

The absence of the four headers listed above in this particular response does not prove that they are absent from every response or endpoint. Further verification would be necessary.

The advertised WordPress REST API endpoint is normal WordPress functionality and is not inherently a vulnerability. Its exposed information and access permissions would need to be reviewed separately.

Competency demonstrated: Ability to retrieve HTTP response headers, interpret cookie security attributes, identify security-related headers, and distinguish configuration observations from confirmed vulnerabilities.

Evidence:



7. INTERNAL NETWORK DISCOVERY

7.1 Objective

To identify active devices within a controlled virtual network and gain practical experience with host discovery, subnet enumeration, and network mapping.

7.2 Environment and Tools

The internal network discovery exercise was performed within a VirtualBox NAT Network configured for the user's laboratory environment.

Zenmap, the graphical interface for Nmap, was installed and executed from a Windows virtual machine.

The target subnet was:

`10.0.0.0/24`

The following command was used:

```
nmap -sn 10.0.0.0/24
```

The `-sn` option performs host discovery without conducting a port scan.

7.3 Results

The scan identified four active hosts:

IP address	Identified device	Role
`10.0.0.1`	VirtualBox NAT Gateway	Default gateway
`10.0.0.2`	Kali Linux VM	Linux virtual machine
`10.0.0.10`	Windows VM	Scanning machine

`10.0.0.254` DHCP Server Dynamic IP address allocation

The device identities were determined using the known configuration of the VirtualBox laboratory network.

The Windows command below was also used to retrieve local network configuration details and inspect the Windows virtual machine's MAC address:

```
ipconfig /all
```

7.4 Analysis

The scan successfully identified the active devices within the configured subnet. This demonstrated the ability to apply subnet notation during network discovery and interpret the results in relation to a known network topology.


The exercise also provided practical exposure to the relationship between virtual machines, network gateways, and DHCP services within a NAT Network.


The use of `-sn` was appropriate for the objective because the task required identifying active hosts rather than enumerating open ports or services.

Competency demonstrated:

- Network discovery and host enumeration.
- Understanding of IPv4 subnet notation.
- Practical use of Nmap and Zenmap.
- Familiarity with virtual network infrastructure.
- Interpretation of scan results in relation to known network configurations.
- Use of Windows command-line utilities for network diagnostics.

Evidence:





8. OPEN-SOURCE INTELLIGENCE USING MALTEGO

8.1 Objective

To identify publicly discoverable email addresses associated with the assigned domain using a graph-based OSINT tool.

8.2 Tool and Procedure

Tool: Maltego

Maltego was downloaded, installed, and activated using a Maltego ID.

The investigation was performed as follows:

1. Maltego was launched after installation and activation.
2. A new graph was created.
3. The domain `networkwalks.com` was added as a Domain entity.
4. The Transform menu was accessed.
5. The email-related transformation named **Utilities to email@domain** was selected and executed.
6. The resulting graph was examined for email entities associated with the domain.

8.3 Results

The investigation returned one publicly discoverable email address:

`info@networkwalks.com`

The same email address was also identified during the WhatWeb reconnaissance activity.

8.4 Analysis

The Maltego exercise demonstrated how entity-based transformations can be used to investigate relationships between publicly available information.

The successful identification of an email address provided an example of how OSINT techniques can support information gathering and help establish an organisation's publicly visible digital footprint.

The appearance of the same email address in both the WhatWeb and Maltego results provided an opportunity to correlate observations obtained through different tools.


The result does not establish that the mailbox is active, identify its owner, or confirm that all email addresses associated with the domain have been discovered.

Competency demonstrated:

- Installation and activation of an OSINT tool.
- Creation and use of graph-based entities.
- Selection and execution of relevant transformations.
- Interpretation of OSINT results.

- Correlation of information obtained through different reconnaissance tools.

Evidence:



9. CONSOLIDATED FINDINGS AND SECURITY ANALYSIS

The following table summarises the major observations from the assessment, their potential security implications, and a preliminary risk assessment.

No.	Finding	Observation	Security implication	Risk assessment
1	DNSSEC configuration	DNSSEC was reported as unsigned by WHOIS, with DNSrecon returning no answer to its DNSSEC query.	DNS responses do not benefit from DNSSEC-based validation of authenticity and integrity.	**Medium** – Worth reviewing as part of DNS security hardening.
2	SPF configuration	The domain's SPF record uses the soft-fail qualifier (`~all`).	Receiving mail systems may treat unauthorised senders less strictly than they would under a hard-fail policy.	**Medium** – Review SPF alongside DKIM and DMARC before making policy changes.
3	Technology disclosure	WhatWeb identified WordPress, Apache, jQuery, and other website technologies.	Technology information can help an attacker identify components for further research and targeted attacks.	**Low–Medium** – Verify versions and maintain a consistent patching process.
4	HTTP security headers	HSTS, CSP, X-Content-Type-Options, and X-Frame-Options were not observed in the captured response.	If confirmed to be absent where appropriate, browser-side security protections may be reduced.	**Medium** – Verify across relevant responses and implement suitable headers.
5	DNS server version disclosure	DNSrecon identified BIND version `9.16.23-RH`.	Public version information may assist infrastructure fingerprinting.	**Low–Medium** – Verify patch status; version disclosure alone does not establish a vulnerability.

6	Nameserver discrepancy	WHOIS and DNSrecon returned different sets of nameservers.	The difference may reflect stale registration information or differences between data sources.	**Medium – Investigate** – Verify authoritative delegation before concluding that a misconfiguration exists.
7	WordPress REST API	The `/wp-json/` endpoint and a page API endpoint were advertised in the HTTP response.	Public API endpoints may reveal application information useful for enumeration.	**Informational** – Normal WordPress functionality; review exposed data and access permissions.
8	Web application firewall	WAFW00F identified ModSecurity.	Indicates the presence of an externally identifiable defensive layer for web traffic.	**Positive control** – A favourable observation, but effectiveness was not tested.
9	Cookie security attributes	The observed `__wpdm_client` cookie included `Secure` and `HttpOnly`.	These attributes help protect cookie transmission and reduce exposure to client-side script access.	**Positive control** – Confirmed favourable attributes in the captured response; other cookie settings were not established.
10	Internal network discovery	Four active devices were identified within the laboratory subnet.	Demonstrates visibility of devices within the tested network segment.	**Informational** – No security weakness was established by this host-discovery exercise.
11	Public email discovery	Maltego identified `info@networkwalks.com`, also observed through WhatWeb.	Publicly available email addresses may be collected for legitimate communication or targeted social engineering.	**Informational** – Public exposure is not inherently a vulnerability; consider appropriate email security controls.

9.1 Overall Security Assessment

The assessment identified several configuration areas that may benefit from further review, particularly DNSSEC, email authentication, HTTP security headers, and the validation of DNS delegation information.

It also identified positive security observations, including the presence of an externally detectable ModSecurity WAF and the use of `Secure` and `HttpOnly` cookie attributes in the captured response.

The internal network discovery exercise confirmed that four known devices were active within the tested virtual subnet. The OSINT investigation also demonstrated that an email address associated with the target domain was publicly discoverable through more than one tool.

It is important to distinguish between information disclosure, configuration observations, and confirmed vulnerabilities. The activities conducted were reconnaissance and discovery exercises; they did not establish exploitability, demonstrate successful compromise, or measure the effectiveness of the identified security controls.

The risk ratings in this report are preliminary assessments based on the available observations, not the results of a full vulnerability assessment.

10. SECURITY RECOMMENDATIONS

Based on the observations made during the assessment, the following recommendations are proposed for further review.

No.	Area	Recommendation	Expected security benefit
1	DNSSEC	Review the feasibility of implementing DNSSEC and ensure DNS records are correctly signed and maintained.	Improves DNS response authenticity and integrity validation.
2	Email authentication	Review the SPF policy and assess the implementation of DKIM and DMARC.	Strengthens email authentication and helps reduce domain spoofing risks.
3	Software maintenance	Verify the versions of WordPress, plugins, themes, and supporting technologies. Apply security updates promptly.	Reduces exposure to known software vulnerabilities.
4	HTTP security headers	Review the use of HSTS, CSP, X-Content-Type-Options, and suitable framing protections.	Strengthens browser-side security controls.
5	DNS infrastructure	Verify authoritative nameserver delegation and investigate the WHOIS/DNSrecon discrepancy.	Helps ensure DNS registration and delegation information is accurate and consistent.
6	DNS server maintenance	Confirm the BIND version and patch status of the DNS infrastructure.	Helps ensure the DNS service is maintained against known vulnerabilities.
7	Web application security	Review ModSecurity configuration, rule coverage, logging, and update practices.	Helps ensure the WAF provides an effective layer of protection.
8	WordPress API	Review publicly accessible REST API information and ensure sensitive data is not exposed.	Reduces unnecessary information exposure.
9	Email security awareness	Maintain appropriate email security controls and user awareness practices.	Helps reduce the risk of phishing and social engineering attacks.

These recommendations are intended as areas for further investigation and security improvement. Their implementation should be based on the organisation's requirements, infrastructure, and validation of the relevant findings.

11. ASSESSMENT LIMITATIONS

The following limitations should be considered when interpreting the results:

1. **Limited assessment scope:** The activities focused on reconnaissance, host discovery, and OSINT. No exploitation or intrusive penetration testing was performed.
2. **External visibility:** Findings were based on information accessible from the assessment environment at the time of testing. Internal systems and configurations were not examined.
3. **Automated tool limitations:** Results from automated fingerprinting and detection tools may contain inaccuracies and require independent verification.
4. **No vulnerability validation:** Identified technologies and configuration observations were not subjected to exploitability testing.

5. **Limited network discovery:** The internal scan used Nmap's host-discovery option and did not enumerate open ports or running services.
6. **OSINT limitations:** The email discovery activity identified one publicly discoverable address but did not establish that it was active or that all associated addresses had been identified.
7. **Time-specific results:** Domain records, website technologies, and network configurations may change after the assessment.

These limitations do not invalidate the observations made; rather, they define the extent to which the results can reasonably be interpreted.

12. CONCLUSION

The assessment successfully covered three important areas of foundational cybersecurity practice: external domain reconnaissance, internal network discovery, and open-source intelligence.

Through the use of WHOIS, WhatWeb, nslookup, DNSrecon, WAFW00F, cURL, Nmap/Zenmap, and Maltego, relevant information was gathered, examined, and documented.

The external reconnaissance phase provided insight into the target domain's registration information, DNS infrastructure, web technologies, HTTP response characteristics, and identifiable security controls. The internal network discovery exercise successfully identified four active devices within the controlled VirtualBox environment. The Maltego investigation also identified a publicly discoverable email address associated with the assigned domain.

The assessment was completed individually using a structured guide. This provided an opportunity to demonstrate the ability to follow a technical procedure, operate relevant tools, interpret results, identify observations requiring further investigation, and produce a formal technical report.

Overall, the exercise strengthened practical familiarity with cybersecurity reconnaissance and information-gathering processes. It also provided evidence of analytical thinking, technical documentation, responsible testing practices, and the foundational competencies expected of an aspiring entry-level cybersecurity professional.

The experience represents a useful step toward developing the practical skills required to contribute to cybersecurity teams and undertake more advanced security assessment activities under appropriate supervision.

13. APPENDICES

Appendix A: Tools and Commands

Tool	Command or activity
WHOIS	`whois networkwalks.com`
WhatWeb	`whatweb networkwalks.com`
nslookup	`nslookup networkwalks.com`
DNSrecon	`dnsrecon -d networkwalks.com`
WAFW00F	`wafw00f https://networkwalks.com`
cURL	`curl -I https://networkwalks.com`
Nmap	`nmap -sn 10.0.0.0/24`
Windows IP configuration	`ipconfig /all`

Maltego	Domain entity with the **Utilities to email@domain** transformation

Appendix B: Scope and Responsible Testing Statement

All activities were conducted within the assigned assessment scope. External reconnaissance was limited to publicly accessible information associated with the assigned domain. Internal network discovery was restricted to the participant's own VirtualBox laboratory network.

No unauthorised access, exploitation, credential attacks, service disruption, or intrusive testing was performed.

The findings and recommendations in this report are based on the observations obtained during the assessment and should be independently validated before being used to make operational security decisions.

END OF REPORT