EXP_F098933F · PRE-REGISTERED DESIGN BRIEF · ENGINEER

· SEALED 2026-06-06T23:55:05.994909+00:00 · DURATION

exp_f098933f

AT A GLANCE

Primary metric is ; decision is binary against the pre-registered rules below.

SAMPLE REQUIRED (PER ARM)

0

to detect a relative effect at a = 0.05, power = 0.80

BASELINE

0.0%

TOTAL SAMPLE

0

DURATION

FEASIBILITY

VIABLE

MECHANISM

Why we think this works

METRICS


is the verdict-driving metric.

Primary is ; secondaries inform interpretation but do not influence the verdict. Guardrails block ship if their CI crosses the pre-registered non-inferiority margin in the adverse direction.

PRIMARY	Proportion · baseline 0.0% · MDE · direction higher is better

POWER

Detecting smaller effects requires much more sample.



Smaller effects require disproportionately more sample. Our design point is feasible inside the available user_id surface.

ASSIGNMENT + COHORTS

First-exposure attribution at the user_id level.

UNIT	**user_id** One row per (user_id, experiment_id) in the assignments table; first_exposure_at gates which events are attributed.
ARMS	

DECISION RULES

Pre-registered. The analyze verb walks the same tree against the same metrics.

SHIP	Primary 95% CI excludes zero on benefit side · no guardrail breach · novelty late-ratio ≥ 0.7
LIFT WITH CAVEAT	Real lift but below MDE/2 — surface the caveat in the readout but still consider rolling out
NO-SHIP · GUARDRAIL	Any guardrail's 90% CI lies past its harm threshold
NO-LIFT	Well-powered, primary CI straddles zero with half-width > 2 × MDE
INCONCLUSIVE	Underpowered (n < required) AND primary CI straddles zero
INVALID	SRM χ^2 $p < 0.0005$ and no override resolved — investigate assignment

INTEGRITY LOCK · THREE-PART SEAL

brief.sealed.yaml binds intent + metric definitions + expected shape.

Tampering with any of the three components after seal will fail `agentxp.schemas.brief_seal.verify_or_raise`; `agentxp analyze` refuses to open a brief whose seal does not verify (R11). This is the architectural wall, not a guideline.

DESIGN_CHAIN_HASH	e278d675a95553b5b6731d1fee7b9c37e24dd52ad885652fba6d9aa788410087
METRIC_SNAPSHOT	1 metric hashed
CONVERSION_RATE	f775e246e2992c91fa7a04f5d22bb93d2cb9ed5078144479b7792e6cdf9a5fe1
EXPECTED_SHAPE	user_id ·
SEALED_AT	2026-06-06T23:55:05.994909+00:00
SEALED_BY	

BRIEF.SEALED.YAML SEAL E278D675A955… · 2026-06-06T23:55:05.994909+00:00 · R1 R11