

AVYOL 4T SUPER SJ 20W-40 MA2

Advanced 4-Stroke Motorcycle Engine Oil

Description

AVYOL 4T SUPER SJ 20W-40 MA2 is a premium-quality motorcycle engine oil developed to meet the lubrication requirements of modern 4-stroke two-wheelers. It is formulated using high-quality hydro-processed base oils and advanced additive technology to deliver reliable engine protection, enhanced cleanliness, and smooth clutch performance. The balanced viscometric characteristics help maintain a strong oil film, reducing wear and ensuring dependable performance even under high-temperature and stop-go riding conditions.

Application

Recommended for new-generation 4-stroke motorcycles where SAE 20W-40 viscosity grade oil is specified. Suitable for air-cooled 4-stroke engines of two-wheelers operating under city traffic, daily commuting, and high-temperature conditions.

Performance / Benefits

- Quick Engine Start: Ensures rapid oil circulation for smooth starts and improved engine response.
- Oxidation & Thermal Stability: Provides excellent resistance to oil degradation at high operating temperatures, reducing deposit formation and oil thickening.
- Excellent Engine Protection: Advanced additive technology offers strong protection against wear of engine and clutch components, extending engine life.
- Enhanced Control: Optimised friction characteristics enable smoother clutch engagement and improved gear shifting.
- Gear Protection: Provides superior protection to gears during frequent stop-go riding conditions.
- Deposit Control: Controls sludge and varnish formation, maintaining cleaner engine internals.
- Rust Protection: Offers high resistance to rust, helping reduce maintenance requirements.

Credentials

- Meets & exceeds API SJ
- JASO MA2 (T903:2016)
- JASO MA (T903:2016)

Typical Characteristics

Particulars	Units	Method	Value
SAE Grade	-	-	20W-40 SJ
Appearance	-	Visual	Clear & Bright
Color	-	ASTM D-1500	Golden
Density @ 29.5°C	gm/cc	ASTM D-4052	0.86 - 0.89
Viscosity @ 40°C	cSt	ASTM D-445	105.8 - 118.5
Viscosity @ 100°C	cSt	ASTM D-445	14 - 15
Viscosity Index	-	ASTM D-2270	>100
Flash Point (Min.)	°C	ASTM D-92	210
Pour Point (Max.)	°C	ASTM D-97	-10
TBN	mg KOH/g	ASTM D-2896	4 - 6

Storage & Handling

Store indoors in sealed containers to prevent contamination. Avoid freezing and ensure storage under protected conditions.

Health & Safety

The product is unlikely to be hazardous when used as recommended. Contamination from other oils, greases, chemicals, or water should be avoided. Periodic monitoring of the oil in service is recommended.