

Oct 31, 14 15:10 genic Page 1/3

```

from __future__ import division, print_function
import sys, random, re
sys.dont_write_bytecode = True

5 def cached(f=None, cache={}):
    """To know the active options, cache their
    most recent setting."""
    if f:
        def wrapper(**d):
            tmp = cache[f.__name__] = f(**d)
            return tmp
        return wrapper
    else:
        for x in cache: print(x, cache[x])

15 #####
@cached
def genic0(**d):
    def tiny(u, w):
        return u < w.opt.era/w.opt.k/2
    return o(
        k=10,
        era=1000,
        tiny= tiny,
        num='$',
        klass='=',
        seed=1).update(**d)

@cached
30 def rows0(**d): return o(
    skip="?",
    sep = ',',
    bad = r'(["\'\\t\r\n]|#.*')
    ).update(**d)

35 #####
rand= random.random
seed= random.seed

40 def say(c):
    sys.stdout.write(str(c))

def fun(x):
    return x.__class__.__name__ == 'function'

45 def g(lst, n=3):
    for col, val in enumerate(lst):
        if isinstance(val, float):
            val = round(val, n)
    50     lst[col] = val
    return lst

def printm(matrix):
    s = [[str(e) for e in row] for row in matrix]
    55     lens = [max(map(len, col)) for col in zip(*s)]
    fmt = '%t'.join('{{{}}}'.format(x) for x in lens)
    for row in s:
        print(row)

60 class o:
    "Define a bag of names slots with no methods."
    def __init__(i, **d): i.update(**d)
    def update(i, **d):
        i.__dict__.update(**d); return i
    65     def __repr__(i):
        def name(x):
            return x.__name__ if fun(x) else x
        d = i.__dict__
        show = ['%s=%s' % (k, name(d[k]))
            70             for k in sorted(d.keys())
            if k[0] is not '_']
        return '{'+'.join(show)+'}'

```

Oct 31, 14 15:10 genic Page 2/3

```

75 #####
def rows(file, w=None):
    """Leaps over any columns marked 'skip'.
    Turn strings to numbers or strings.
    Kill comments. Join lines that end in 'sep'."""
    80     w = w or rows0()
    def atom(x):
        try: return int(x)
        except ValueError:
            try: return float(x)
            85             except ValueError: return x
    def lines():
        n, kept = 0, ""
        for line in open(file):
            now = re.sub(w.bad, "", line)
            kept += now
            90             if kept:
                if not now[-1] == w.sep:
                    yield n, map(atom, kept.split(w.sep))
                    n += 1
                    kept = ""
            95             todo = None
        for n, line in lines():
            todo = todo or [col for col, name
                in enumerate(line)
                100                 if not w.skip in name]
            yield n, [ line[col] for col in todo ]

def header(w, row):
    def numOrSym(val):
        105         return w.num if w.opt.num in val else w.sym
    def indepOrDep(val):
        return w.dep if w.opt.klass in val else w.indep
    for col, val in enumerate(row):
        numOrSym(val).append(col)
        indepOrDep(val).append(col)
        110         w.name[col] = val
        w.index[val] = col

def data(w, row):
    115     for col in w.num:
        val = row[col]
        w.min[col] = min(val, w.min.get(col, val))
        w.max[col] = max(val, w.max.get(col, val))

120 def indep(w, cols):
    for col in cols:
        if col in w.indep: yield col

#####
125 def nearest(w, row):
    def norm(val, col):
        lo, hi = w.min[col], w.max[col]
        130         return (val - lo) / (hi - lo + 0.00001)
    def dist(centroid):
        n, d = 0, 0
        for col in indep(w, w.num):
            x1, x2 = row[col], centroid[col]
            n1, n2 = norm(x1, col), norm(x2, col)
            d += (n1 - n2)**2
            135             n += 1
        for col in indep(w, w.sym):
            x1, x2 = row[col], centroid[col]
            d += (0 if x1 == x2 else 1)
            140             n += 1
        return d**0.5 / n**0.5
    lo, out = 10**32, None
    for n, (_, __, centroid) in enumerate(w.centroids):
        d = dist(centroid)
        145         if d < lo:
            lo, out = d, n
    return out

```

Oct 31, 14 15:10 genic Page 3/3

```

def move(w, new, n):
    150     u0, u, age, old = w.centroids[n]
    u1 = 1
    out = [None]*len(old)
    for col in w.sym:
        x0, x1 = old[col], new[col]
        155         out[col] = x1 if rand() < 1/(u0+u1) else x0
    for col in w.num:
        x0, x1 = old[col], new[col]
        out[col] = (u0*x0 + u1*x1)/(u0+u1)
        w.centroids[n] = (u0 + u1, u+u1, age+1, out)
    160
def less(w, n):
    b4 = len(w.centroids)
    w.centroids = [(1, u, dob, row)
        165         for u0, u, dob, row in
            w.centroids
            if not w.opt.tiny(u0, w)]
    print("n=%s deaths=%s%%" % (
        n, int(100*(b4 - len(w.centroids))/b4)))

170 def genic(src='data/diabetes.csv', opt=None):
    w = o(num=[], sym=[], dep=[], indep=[],
        centroids=[],
        min={}, max={}, name={}, index={},
        opt=opt or genic0())
    175     for n, row in rows(src):
        if n == 0:
            header(w, row)
        else:
            data(w, row)
            180             if len(w.centroids) < w.opt.k:
                w.centroids += [(1, 1, n, row)]
            else:
                move(w, row, nearest(w, row))
                if 0 == (n % w.opt.era):
                    185                     less(w, n)
    return w, sorted(w.centroids, reverse=True)

def report(w, clusters):
    cols = w.index.keys()
    header = sorted(w.name.keys())
    header = [w.name[i] for i in header]
    matrix = [['gen', 'caughtLast', 'caughtAll', 'dob'] + head
    190         er]
    caught=0
    for m, (u0, u, age, centroid) in enumerate(clusters):
        if not w.opt.tiny(u0, w):
            caught += u0
            matrix += [[m+1, u0, u, age] + g(centroid, 2)]
            195             print("\ncaught in last gen=%s%%\n" %
                int(100*caught/w.opt.era))
    200     printm(matrix)

if __name__ == '__main__':
    src='data/diabetes.csv'
    if len(sys.argv) == 2:
        src = sys.argv[1]
    205     print("")
    opt=genic0(era=100, k=8)
    seed(opt.seed)
    report(*genic(src, opt))
    210     cached()

```