

192面向对象程序设计

Test

复查测验提交: 10th_Chapter07_Exercise

复查测验提交: 10th_Chapter07_Exercise

用户	计算机1801 莫明达
课程	192面向对象程序设计
测试	10th_Chapter07_Exercise
已开始	19-11-20 上午9:58
已提交	19-11-20 上午9:58
状态	已完成
尝试分数	得 0 分, 满分 810 分
已用时间	0 分钟
显示的结果	已提交的答案, 正确答案

问题 1

得 0 分, 满分 10 分


What is the correct term for numbers[99]?

所选答案:  [未给定]正确答案:  D.indexed variable

问题 2

得 0 分, 满分 10 分


Which code fragment would correctly identify the number of arguments passed via the command line to a Java application, excluding the name of the class that is being invoked?

所选答案:  [未给定]正确答案:  B.int count = args.length;

问题 3

得 0 分, 满分 10 分

If a key is not in the list, the binarySearch method returns _____.

所选答案:  [未给定]正确答案:  D.-(insertion point + 1)

问题 4

得 0 分, 满分 10 分

In the following code, what is the printout for list2?

```
class Test {
    public static void main(String[] args) {
        int[] list1 = {3, 2, 1};
        int[] list2 = {1, 2, 3};
        list2 = list1;
        list1[0] = 0; list1[1] = 1; list2[2] = 2;

        for (int i = list2.length - 1; i >= 0; i--)
            System.out.print(list2[i] + " ");
    }
}
```

所选答案:  [未给定]

正确答案:  C.2 1 0

问题 5

得 0 分, 满分 10 分

The name length is a method in an array.

所选答案:  [未给定]

正确答案:  A.false

问题 6


得 0 分, 满分 10 分

Consider the following code fragment:

```
int[] list = new int[10];
for (int i = 0; i <= list.length; i++) {
    list[i] = (int)(Math.random() * 10);
}
```

Which of the following statements is true?

所选答案:  [未给定]


正确答案:  C.The code has a runtime error indicating that the array is out of bound.

问题 7

得 0 分, 满分 10 分

Suppose array a is int[] a = {1, 2, 3}, what is a[0] - a[2]?

所选答案:  [未给定]

正确答案:  A.-2

问题 8

得 0 分, 满分 10 分

In the following code, what is the printout for list1?

```
public class Test {
    public static void main(String[] args) {
        int[] list1 = {1, 2, 3};
        int[] list2 = {1, 2, 3};
        list2 = list1;
        list1[0] = 0; list1[1] = 1; list2[2] = 2;

        for (int i = 0; i < list1.length; i++)
            System.out.print(list1[i] + " ");
    }
}
```

所选答案:  [未给定]

正确答案:  D.0 1 2

问题 9

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {
    public static void main(String[] args) {
        int[] oldList = {1, 2, 3, 4, 5};
        reverse(oldList);
        for (int i = 0; i < oldList.length; i++)
            System.out.print(oldList[i] + " ");
    }

    public static void reverse(int[] list) {
        int[] newList = new int[list.length];

        for (int i = 0; i < list.length; i++)
            newList[i] = list[list.length - 1 - i];

        list = newList;
    }
}
```

所选答案:  [未给定]

正确答案:  B.The program displays 1 2 3 4 5.

问题 10


得 0 分, 满分 10 分

Analyze the following code.

```
public class Test {
    public static void main(String[] args) {
```

```
int[] x = new int[3];
System.out.println("x[0] is " + x[0]);
}
}
```

所选答案:  [未给定]

正确答案:  B.The program runs fine and displays x[0] is 0.


问题 11

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {
    public static void main(String[] args) {
        int[] a = new int[4];
        a[1] = 1;
        a = new int[2];
        System.out.println("a[1] is " + a[1]);
    }
}
```

所选答案:  [未给定]

正确答案:  D.The program displays a[1] is 0.

问题 12

得 0 分, 满分 10 分

For the `binarySearch` method in Section 7.10.2, what is low and high after the first iteration of the while loop when invoking `binarySearch(new int[]{1, 4, 6, 8, 10, 15, 20}, 11)`?

所选答案:  [未给定]

正确答案:  E.low is 5 and high is 4

问题 13

得 0 分, 满分 10 分

What is output of the following code:

```
public class Test {
    public static void main(String[] args) {
        int list[] = {1, 2, 3, 4, 5, 6};

        for (int i = 1; i < list.length; i++)
            list[i] = list[i - 1];

        for (int i = 0; i < list.length; i++)
            System.out.print(list[i] + " ");
    }
}
```

所选答案:  [未给定]

正确答案:  D.1 1 1 1 1 1


问题 14

得 0 分, 满分 10 分

The reverse method is defined in the textbook. What is list1 after executing the following statements?

```
int[] list1 = {1, 2, 3, 4, 5, 6};  
list1 = reverse(list1);
```

所选答案:  [未给定]

正确答案:  B.list1 is 6 5 4 3 2 1

问题 15

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = new int[5];  
        int i;  
        for (i = 0; i < x.length; i++)  
            x[i] = i;  
        System.out.println(x[i]);  
    }  
}
```

所选  [未给定]

答
案:

正确 


答 D.The program has a runtime error because the last statement in the
案: main method causes ArrayIndexOutOfBoundsException.

问题 16

得 0 分, 满分 10 分

Use the selectionSort method presented in this section to answer this question. Assume list is {3.1, 3.1, 2.5, 6.4, 2.1}, what is the content of list after the first iteration of the outer loop in the method?

所选答案:  [未给定]


正确答案:  D.2.1, 3.1, 2.5, 6.4, 3.1

问题 17

得 0 分, 满分 10 分

Suppose int[] numbers = new int[10], what is numbers[0]?

所选答案:  [未给定]





正确答案:  C.0

问题 18

得 0 分, 满分 10 分

Which of the following is the correct header of the main method?

所选答案:  [未给定]

正确答案:  A. public static void main(String[] x)
 B. public static void main(String x[])
 D. public static void main(String[] args)
 E. public static void main(String args[])

问题 19

得 0 分, 满分 10 分

The element in the array must be of a primitive data type.

所选答案:  [未给定]

正确答案:  A. false

问题 20

得 0 分, 满分 10 分

What is the output of the following code?

```
int[] myList = {1, 2, 3, 4, 5, 6};

for (int i = myList.length - 2; i >= 0; i--) {
    myList[i + 1] = myList[i];
}

for (int e: myList)
    System.out.print(e + " ");
```

所选答案:  [未给定]

正确答案:  B. 1 1 2 3 4 5

问题 21

得 0 分, 满分 10 分

Given the following program:

```
public class Test {
    public static void main(String[] args) {
        for (int i = 0; i < args.length; i++) {
            System.out.print(args[i] + " ");
        }
    }
}
```

What is the output, if you run the program using

```
java Test 1 2 3
```

所选答案:  [未给定]正确答案:  B.1 2 3**问题 22**


得 0 分, 满分 10 分

Assume `int[] scores = {1, 20, 30, 40, 50}`, what is the output of `System.out.println(java.util.Arrays.toString(scores))`?

所选答案:  [未给定]正确答案:  D.[1, 20, 30, 40, 50]**问题 23**

得 0 分, 满分 10 分

_____ declares an array of char.

所选答案:  [未给定]正确答案:  B.char[] chars D.char chars[]**问题 24**

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        double[] x = {2.5, 3, 4};  
        for (double value: x)  
            System.out.print(value + " ");  
    }  
}
```

所选答案:  [未给定]正确答案:  A.The program displays 2.5 3.0 4.0**问题 25**

得 0 分, 满分 10 分

In the following code, what is the printout for list2?

```
public class Test {  
    public static void main(String[] args) {  
        int[] list1 = {1, 2, 3};  
        int[] list2 = {1, 2, 3};  
        list2 = list1;  
        list1[0] = 0; list1[1] = 1; list2[2] = 2;
```

```
        for (int i = 0; i < list2.length; i++)  
            System.out.print(list2[i] + " ");  
    }  
}
```

所选答案:  [未给定]正确答案:  C.0 1 2**问题 26**

得 0 分, 满分 10 分

The arraycopy method does not allocate memory space for the target array. The target array must already be created with memory space allocated.

所选答案:  [未给定]正确答案:  A.true**问题 27**

得 0 分, 满分 10 分


How can you initialize an array of two characters to 'a' and 'b'?

所选答案:  [未给定]正确答案:  B.char[] charArray = new char[]{'a', 'b'}; D.char[] charArray = {'a', 'b'};**问题 28**

得 0 分, 满分 10 分

What is the output of the following code?

```
double[] myList = {1, 5, 5, 5, 5, 1};  
double max = myList[0];  
int indexOfMax = 0;  
for (int i = 1; i < myList.length; i++) {  
    if (myList[i] >= max) {  
        max = myList[i];  
        indexOfMax = i;  
    }  
}  
System.out.println(indexOfMax);
```

所选答案:  [未给定]正确答案:  D.4**问题 29**

得 0 分, 满分 10 分

The reverse method is defined in this section. What is list1 after executing the following statements?


```
int[] list1 = {1, 2, 3, 4, 5, 6};  
int[] list2 = reverse(list1);
```

所选答案:  [未给定]

正确答案:  B.list1 is 1 2 3 4 5 6


问题 30

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = new int[5];  
        for (int i = 0; i < x.length; i++)  
            x[i] = i;  
        System.out.println(x[i]);  
    }  
}
```

所选答案:  [未给定]
案:


正确答案: 
案: B.The program has a syntax error because i is not defined in the last statement in the main method.

问题 31

得 0 分, 满分 10 分

When you pass an array to a method, the method receives _____.

所选答案:  [未给定]

正确答案:  C.the reference of the array

问题 32

得 0 分, 满分 10 分

The array index is not limited to int type.

所选答案:  [未给定]


正确答案:  B.false

问题 33

得 0 分, 满分 10 分

Assume int[] t = {1, 2, 3, 4}. What is t.length?

所选答案:  [未给定]

正确答案:  D.4

问题 34

得 0 分, 满分 10 分

The _____ method sorts the array scores of the double[] type.

所选答案:  [未给定]

正确答案:  B.java.util.Arrays.sort(scores)

问题 35

得 0 分, 满分 10 分

x.length does not exist if x is null.

所选答案:  [未给定]


正确答案:  B.true

问题 36

得 0 分, 满分 10 分

Given the following statement
`int[] list = new int[10];`

所选答案:  [未给定]
案:


正确答案: 
案: B.The array variable list contains a memory address that refers to an array of 10 int values.

问题 37

得 0 分, 满分 10 分

Assume `int[] scores = {1, 20, 30, 40, 50}`, what value does `java.util.Arrays.binarySearch(scores, 3)` return?

所选答案:  [未给定]

正确答案:  E.-2

问题 38

得 0 分, 满分 10 分

You can use the operator `==` to check whether two variables refer to the same array.

所选答案:  [未给定]

正确答案:  B.true

问题 39

得 0 分, 满分 10 分

Binary search can be applied on an unsorted list.

所选答案:  [未给定]


正确答案:  B.false

问题 40

得 0 分, 满分 10 分

Assume `double[] scores = {1, 2, 3, 4, 5}`, what value does `java.util.Arrays.binarySearch(scores, 3.5)` return?

所选答案:  [未给定]

正确答案:  D.-4


问题 41

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        final int[] x = {1, 2, 3, 4};  
        int[] y = x;  
  
        x = new int[2];  
  
        for (int i = 0; i < y.length; i++)  
            System.out.print(y[i] + " ");  
    }  
}
```

所选答案:  [未给定]

正确答案: 
C.The program has a compile error on the statement `x = new int[2]`, because `x` is final and cannot be changed.


问题 42

得 0 分, 满分 10 分

Analyze the following code.

```
int[] list = new int[5];  
list = new int[6];
```

所选答案:  [未给定]

正确答案: 
C.The code can compile and run fine. The second line assigns a new array to `list`.

问题 43

得 0 分, 满分 10 分

The JVM stores the array in an area of memory, called _____, which is used for dynamic memory allocation where blocks of memory are allocated and freed in an arbitrary order.

所选答案:  [未给定]


正确答案:  A.heap

问题 44

得 0 分, 满分 10 分

When you return an array from a method, the method returns _____.

所选答案:  [未给定]


正确答案:  B.the reference of the array

问题 45

得 0 分, 满分 10 分

Assume `int[] scores = {1, 20, 30, 40, 50}`, what value does `java.util.Arrays.binarySearch(scores, 30)` return?

所选答案:  [未给定]

正确答案:  D.2

问题 46

得 0 分, 满分 10 分

Which of the following is correct to create an array?

所选答案:  [未给定]


正确答案:  D.`int[] m = {1, 2, 3};`

问题 47

得 0 分, 满分 10 分

If you declare an array `double[] list = {3.4, 2.0, 3.5, 5.5}`, the highest index in array list is _____.

所选答案:  [未给定]

正确答案:  A.3

问题 48


得 0 分, 满分 10 分

Identify the problems in the following code.

```
public class Test {
    public static void main(String argv[]) {
        System.out.println("argv.length is " +
            argv.length);
    }
}
```

所选答  [未给定]

案:

正确答 

案: B.If you run this program without passing any arguments, the program would display argv.length is 0.

问题 49


得 0 分, 满分 10 分

Analyze the following code:

```
public class Test1 {  
    public static void main(String[] args) {  
        xMethod(new double[] {3, 3});  
        xMethod(new double[5]);  
        xMethod(new double[3] {1, 2, 3});  
    }  
  
    public static void xMethod(double[] a) {  
        System.out.println(a.length);  
    }  
}
```

所选答  [未给定]

案:

正确答 

案: C.The program has a compile error because xMethod(new double[3]{1, 2, 3}) is incorrect.

问题 50

得 0 分, 满分 10 分

Which of the following declarations are correct?

所选答案:  [未给定]

正确答案:  C.int[] list = {1, 2, 3, 4};

 D.int[] list = new int[]{1, 2, 3, 4};

问题 51

得 0 分, 满分 10 分

Assume the signature of the method xMethod is as follows.

```
public static void xMethod(double[] a)
```

Which of the following could be used to invoke xMethod?

所选答案:  [未给定]


正确答案:  D.xMethod(new double[2]);


问题 52

得 0 分, 满分 10 分

Which of the following statements is valid?

所选答案:  [未给定]

正确答案:  B.double d[] = new double[30];

 C.int[] i = {3, 4, 3, 2};

问题 53


得 0 分, 满分 10 分

Suppose a method p has the following heading:

```
public static int[] p()
```

What return statement may be used in p()?

所选答案:  [未给定]


正确答案:  B.return new int[]{1, 2, 3};

问题 54

得 0 分, 满分 10 分

Which of the following is correct?

所选答案:  [未给定]

正确答案:  A.String[] list = {"red", "yellow", "green"};

 B.String[] list = new String[]{"red", "yellow", "green"};

问题 55

得 0 分, 满分 10 分

What is output of the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = {120, 200, 016};  
        for (int i = 0; i < x.length; i++)  
            System.out.print(x[i] + " ");  
    }  
}
```

所选答案:  [未给定]

正确答案:  D.120 200 14


问题 56

得 0 分, 满分 10 分

The _____ method copies the sourceArray to the targetArray.

所选答案:  [未给定]

案:

正确答案:  C.System.arraycopy(sourceArray, 0, targetArray, 0, sourceArray.length);

问题 57

得 0 分, 满分 10 分

Show the output of the following code:

```
public class Test {
    public static void main(String[] args) {
        int[] x = {1, 2, 3, 4, 5};
        increase(x);


        int[] y = {1, 2, 3, 4, 5};
        increase(y[0]);

        System.out.println(x[0] + " " + y[0]);
    }

    public static void increase(int[] x) {
        for (int i = 0; i < x.length; i++)
            x[i]++;
    }

    public static void increase(int y) {
        y++;
    }
}
```

所选答案:  [未给定]


正确答案:  D.2 1

问题 58

得 0 分, 满分 10 分

If you declare an array `double[] list = {3.4, 2.0, 3.5, 5.5}`, `list[1]` is _____.

所选答案:  [未给定]

正确答案:  B.2.0

问题 59

得 0 分, 满分 10 分

What is the output of the following code?

```
int[] myList = {1, 2, 3, 4, 5, 6};
for (int i = 1; i < myList.length; i++) {
    myList[i - 1] = myList[i];
}

for (int e: myList)
    System.out.print(e + " ");
```

所选答案:  [未给定]


正确答案:  C.2 3 4 5 6 6

问题 60

得 0 分, 满分 10 分

What is the representation of the third element in an array called a?

所选答案:  [未给定]

正确答案:  D.a[2]

问题 61

得 0 分, 满分 10 分

How can you get the word "abc" in the main method from the following call?

```
java Test "+" 3 "abc" 2
```

所选答案:  [未给定]

正确答案:  B.args[2]


问题 62

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = {0, 1, 2, 3, 4, 5};  
        xMethod(x, 5);  
    }  
  
    public static void xMethod(int[] x, int length) {  
        for (int i = 0; i < length; i++)  
            System.out.print(" " + x[i]);  
    }  
}
```

所选答案:  [未给定]


正确答案:  D.The program displays 0 1 2 3 4.

问题 63

得 0 分, 满分 10 分

Given the following statement
`int[] list = new int[10];`
list.length has the value _____.

所选答案:  [未给定]

正确答案:  A.10

问题 64

得 0 分, 满分 10 分

Which of the following declarations are correct?

所选答案:  [未给定]

正确答案:  A. public static void print(double... numbers)

 B. public static void print(int n, double... numbers)


问题 65


得 0 分, 满分 10 分

Which of the following is incorrect?

所选答案:  [未给定]

正确答案:  B. int a() = new int[2];

 C. int[] a = new int(2);

 D. int a = new int[2];


问题 66

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = {1, 2, 3, 4};  
        int[] y = x;  
  
        x = new int[2];  
  
        for (int i = 0; i < y.length; i++)  
            System.out.print(y[i] + " ");  
    }  
}
```

所选答案:  [未给定]

正确答案:  B. The program displays 1 2 3 4

问题 67

得 0 分, 满分 10 分

The array size is specified when the array is declared.

所选答案:  [未给定]

正确答案:  B. false

问题 68

得 0 分, 满分 10 分

Use the `selectionSort` method presented in this section to answer this question. What is `list1` after executing the following statements?

```
double[] list1 = {3.1, 3.1, 2.5, 6.4};
selectionSort(list1);
```

所选答案:  [未给定]

正确答案:  B.list1 is 2.5 3.1, 3.1, 6.4

问题 69

得 0 分, 满分 10 分

The arguments passed to the main method is an array of strings. If no argument is passed, `args.length` is 0.

所选答案:  [未给定]


正确答案:  A.true

问题 70

得 0 分, 满分 10 分

An array can be used in which of the following ways?

所选答案:  [未给定]

正确答案:  D.All of the above


问题 71

得 0 分, 满分 10 分

Which of the following statements are correct to invoke the `printMax` method in Listing 7.5 in the textbook?

所选答案:  [未给定]

正确答案:  B.`printMax(1.0, 2.0, 2.0, 1.0, 4.0);`

 C.`printMax(1, 2, 2, 1, 4);`

 D.`printMax(new double[]{1, 2, 3});`

问题 72

得 0 分, 满分 10 分

What would be the result of attempting to compile and run the following code?

```
public class Test {
    public static void main(String[] args) {
        double[] x = new double[]{1, 2, 3};
        System.out.println("Value is " + x[1]);
    }
}
```

所选答案:  [未给定]

案:

正确答案: 

案: B.The program compiles and runs fine and the output "Value is 2.0" is printed.

问题 73

得 0 分, 满分 10 分

Suppose `int i = 5`, which of the following can be used as an index for array `double[] t = new double[100]`?

所选答案:  [未给定]

正确答案:  C.i + 10

 D.i

 E.(int)(Math.random() * 100))

问题 74

得 0 分, 满分 10 分

The array index of the first element in an array is 0.

所选答案:  [未给定]

正确答案:  A.true

问题 75

得 0 分, 满分 10 分

Which correctly creates an array of five empty Strings?

所选答案:  [未给定]

正确答案:  C.String[] a = {"", "", "", "", ""};


问题 76

得 0 分, 满分 10 分

Analyze the following code:

```
public class Test {  
    public static void main(String[] args) {  
        int[] x = {1, 2, 3, 4};  
        int[] y = x;  
  
        x = new int[2];  
  
        for (int i = 0; i < x.length; i++)  
            System.out.print(x[i] + " ");  
    }  
}
```

所选答案:  [未给定]

正确答案:  C.The program displays 0 0

问题 77

得 0 分, 满分 10 分

Do the following two programs produce the same result?

Program I:

```
public class Test {
    public static void main(String[] args) {
        int[] list = {1, 2, 3, 4, 5};
        reverse(list);
        for (int i = 0; i < list.length; i++)
            System.out.print(list[i] + " ");
    }

    public static void reverse(int[] list) {
        int[] newList = new int[list.length];

        for (int i = 0; i < list.length; i++)
            newList[i] = list[list.length - 1 - i];

        list = newList;
    }
}
```

Program II:


```
public class Test {
    public static void main(String[] args) {
        int[] oldList = {1, 2, 3, 4, 5};
        reverse(oldList);
        for (int i = 0; i < oldList.length; i++)
            System.out.print(oldList[i] + " ");
    }

    public static void reverse(int[] list) {
        int[] newList = new int[list.length];

        for (int i = 0; i < list.length; i++)
            newList[i] = list[list.length - 1 - i];

        list = newList;
    }
}
```

所选答案:  [未给定]


正确答案:  B.Yes

问题 78

得 0 分, 满分 10 分

Which of the following are valid array declarations?

所选答案:  [未给定]

正确答案:  A.char[] charArray = new char[26];

问题 79

得 0 分, 满分 10 分

An array variable can be declared and redeclared in the same block.

所选答案:  [未给定]


正确答案:  B.false

问题 80

得 0 分, 满分 10 分

How many elements are in array `double[] list = new double[5]`?

所选答案:  [未给定]

正确答案:  C.5


问题 81

得 0 分, 满分 10 分

What is the output of the following code?

```
double[] myList = {1, 5, 5, 5, 5, 1};
double max = myList[0];
int indexOfMax = 0;
for (int i = 1; i < myList.length; i++) {
    if (myList[i] > max) {
        max = myList[i];
        indexOfMax = i;
    }
}
System.out.println(indexOfMax);
```

所选答案:  [未给定]

正确答案:  A.1

2019年11月20日 星期三 上午09时58分23秒 CST

← 确定