

得0分,满分10分

192面向对象程序设计

Test

复查测验提交: 10th_Chapter04_Exercise

复查测验提交: 10th_Chapter04_Exercise

用户 计算机1801 莫明达 192面向对象程序设计 测试 10th_Chapter04_Exerci 已开始 19-11-20 上午9:56 已提交 19-11-20 上午9:57 状态 已完成 尝试分数 得 0 分,满分 740 分	
测试10th_Chapter04_Exerci已开始19-11-20 上午9:56已提交19-11-20 上午9:57状态已完成尝试分数得 0 分,满分 740 分	
已开始 19-11-20 上午9:56 已提交 19-11-20 上午9:57 状态 已完成 尝试分数 得 0 分,满分 740 分	
已提交 19-11-20 上午9:57 状态 已完成 尝试分数 得 0 分,满分 740 分	ise
状态 已完成 尝试分数 得 0 分,满分 740 分	
尝试分数 得 0 分,满分 740 分	
已用时间 0分钟	
显示的结果 已提交的答案, 正确答案	2

问题 1 得0分,满分10分

"ab".compareTo("aB") is _____.

所选答案: 🗯 [未给定]

正确答案: OB.greater than 0

Math.ceil(5.5) evaluates to _____.

所选答案: 🗯 [未给定]

问题 2

正确答案: 🕜 D.6.0

问题 3 得0分,满分10分

Which of the following method results in 8.0?

所选答案: 🔞 [未给定]

正确答案: O.Math.floor(8.5)

D.Math.rint(8.5)

问题 4 得0分,满分10分

Math.cos(Math.PI) returns _____

所选答案: 🙆 [未给定]

正确答案: 🚫 C.-1.0

问题 5

得0分,满分10分

Suppose s1 and s2 are two strings. What is the result of the following code?

s1.equals(s2) == s2.equals(s1)

所选答案: 🗯 [未给定]

正确答案: 💍 B.true

问题 6

得0分,满分10分

"abcdefgh".subString(1, 3) returns _____.

所选答案: ② [未给定]

正确答案: 💍 B.bc

问题 7

得0分,满分10分

Which of the following is a possible output for (int)(51 * Math.random())?

所选答案: 🙆 [未给定]

正确答案: 🕜 A.50

C.0

问题 8

得0分,满分10分

An int variable can hold ______.

所选答案: 🗯 [未给定]

正确答案: 👩 B.'x'

C.120

问题 9

得0分,满分10分

Which of the following statements are incorrect?

所选答案: 🗯 [未给定]

正确答案: 🕜 A.float f = 4.5;

B.int k = null;

C.char c = "r";

D.String s = 'r';

问题 10 得0分,满分10分 The expression 'c' - 'e' is _____ 所选答案: ② [未给定] 正确答案: 🕜 B.-2 问题 11 得0分,满分10分 The statement System.out.printf("%3.1f", 1234.56) outputs _____ 所选答案: 🗯 [未给定] 正确答案: 💍 B.1234.6 问题 12 得0分,满分10分 What is Math.round(3.6)? 所选答案: ② [未给定] 正确答案: 🚫 D.4 问题 13 得0分,满分10分 Which of the following is the correct statement to return JAVA? 所选答案: ② [未给定] 正确答案: 🕜 A."Java".toUpperCase() 问题 14 得 0 分, 满分 10 分 A Java character is stored in ______. 所选答案: 🗯 [未给定] 正确答案: 🚫 A.two bytes 问题 15 得0分,满分10分 You can assign the value in _____ to an int variable. 所选答案: 🔞 [未给定] 正确答案: 🚫 A.93 O.'x'

问题 16

得0分,满分10分

You can cast a character value to an int, or an int to char.

所选答案: 🗯 [未给定]

正确答案: 👩 A.true

问题 17

得 0 分,满分 10 分

Which of the following is the correct expression of character a?

所选答案: ② [未给定]

正确答案: 👩 D.'a'

问题 18

得0分,满分10分

Will System.out.println((char)4) display 4?

所选答案: ② [未给定]

正确答案: 🚫 A.No

问题 19

得0分,满分10分

The _____ method parses a string s to an int value.

所选答案: 🗯 [未给定]

正确答案: 👩 B.Integer.parseInt(s);

问题 20

得0分,满分10分

What is "Welcome" + 1 + 1*2?

所选答案: 🗯 [未给定]

正确答案: 🕜 C.Welcome12

问题 21

得0分,满分10分

parseDouble is a method in the _____ class.

所选答案: 🗯 [未给定]

正确答案: 👩 B.Double

问题 22

得0分,满分10分

returns true.

所选答案: 👸 [未给定]

正确答案: OB."peter".equalsIgnoreCase("peter")

C."peter".equals("peter")

E."peter".equalsIgnoreCase("Peter")

问题 23

得 0 分, 满分 10 分

What is the return value of "SELECT".substring(4, 4)?

所选答案: ② [未给定]

正确答案: 🔗 A.an empty string

问题 24

得 0 分, 满分 10 分

The statement System.out.printf("%3.1e", 1234.56) outputs ______.

所选答案: 🗯 [未给定]

正确答案: 💍 E.1.2e+03

问题 25

得 0 分, 满分 10 分

Analyze the following code:

int i = 3434; double d = 3434; System.out.printf("%5.1f %5.1f", i, d);

所选答 🗯 [未给定]

案:

正确答 😋

案:

A.i is an integer, but the format specifier %5.1f specifies a format for

double value. The code has an error.

问题 26

得 0 分, 满分 10 分

What is Math.rint(3.6)?

所选答案: 🔞 [未给定]

正确答案: 🕜 C.4.0

问题 27

得0分,满分10分

Note that the Unicode for character A is 65. The expression "A" + 1 evaluates to

所选答案: 🔼 [未给定]

正确答案: 👩 A.A1

得 0 分, 满分 10 分

Assume that the ASCII code for character c is 99 and for a is 97. What is the printout of the following code?

System.out.println("AB" + 'a' + 'c');

所选答案: 🗯 [未给定]

正确答案: 🕜 A.ABac

问题 29

得0分,满分10分

Which of the following statements are correct to concatenate string s1 into s2.

所选答案: 🗯 [未给定]

正确答案: 🕜 B.s2 += s1;

C.s2.concate(s1);

问题 30

得0分,满分10分

Math.asin(0.5) returns _____.

所选答案: ② [未给定]

正确答案: OB.Math.toRadians(30)

问题 31

得0分,满分10分

The expression "Java " + 1 + 2 + 3 evaluates to _____.

所选答案: 🗯 [未给定]

正确答案: 🕜 C.Java 123

问题 32

得0分,满分10分

To concatenate s1, s2, s3, and s4, you write ____

所选答案: 🗯 [未给定]

正确答案: 🕜 A.s1.concate(s2).concate(s3).concate(s4);

B.s1.concate(s2) + s3.concate(s4);

C.((s1.concate(s2)).concate(s3)).concate(s4);

问题 33

得0分,满分10分

Assume that the ASCII code for character c is 99 and for a is 97. What is the printout of the following

code?

System.out.println('a' + 'c');

所选答案: ② [未给定]

正确答案: 🕜 C.196

问题 34

得0分,满分10分

Math.sin(Math.PI) returns _____.

所选答案: 🗯 [未给定]

正确答案: 🕜 C.0.0

问题 35

得 0 分, 满分 10 分

Which of the following are valid specifiers for the printf statement?

所选答案: 🗯 [未给定]

正确答案: 👩 A.%4c

B.%10.2e

O.%10b

E.%6d

问题 36

得0分,满分10分

"AbA".compareTolgnoreCase("abC") returns ______.

所选答案: 🗯 [未给定]

正确答案: 🕜 D.-2

问题 37

得0分,满分10分

The statement System.out.printf("%5d", 123456) outputs ______.

所选答案: 🗯 [未给定]

正确答案: 🕜 A.123456

问题 38

得0分,满分10分

'3' - '2' + 'm' / 'n' is _____.

所选答案: 🗯 [未给定]

正确答案: 🕜 B.1

得0分,满分10分

Suppose s is a string with the value "java". What will be assigned to x if you execute the following code?char x =Â s.charAt(4);

所选

(3) [未给定]

答

案:

正确

答 B.Nothing will be assigned to x, because the execution causes the

案: runtime error StringIndexOutofBoundsException.

问题 40

得 0 分, 满分 10 分

Which of the following method returns the sine of 90 degree?

所选答案:

😘 [未给定]

正确答案: C.Math.sin(Math.toRadian(90))

问题 41

得 0 分, 满分 10 分

The _____ method parses a string s to a double value.

所选答案: 🗯 [未给定]

正确答案: C.Double.parseDouble(s);

问题 42

得0分,满分10分

What is Math.ceil(3.6)?

所选答案: 🙆 [未给定]

正确答案: 💍 D.4.0

问题 43

得0分,满分10分

Which of the following statement prints smith\exam1\test.txt?

所选答案:

🔼 [未给定]

正确答案: 🕜 B.System.out.println("smith\\exam1\\test.txt");

问题 44

得0分,满分10分

To obtain the sine of 35 degrees, use ___

所选答案: 🔞 [未给定]

正确答案:

E.Math.sin(Math.toRadians(35))

得0分,满分10分

To check if a string s contains the prefix "Java", you may write

所选答

🚨 [未给定]

案:

正确答

案:

A.if (s.charAt(0) == 'I' && s.charAt(1) == 'I' && s.charAt(2) == 'I' &&

s.charAt(3) == 'a') ...

- B.if (s.indexOf("Java") == 0) ...
- C.if (s.startsWith("Java")) ...
- O.if (s.substring(0, 4).equals("Java")) ...

问题 46

得 0 分, 满分 10 分

Suppose s1 and s2 are two strings. Which of the following statements or expressions is incorrect?

所选答案: 🗯 [未给定]

- 正确答案: 🕜 A.char c = s1[0];
 - B.char c = s1.charAt(s1.length());
 - C.boolean b = s1.compareTo(s2);
 - D.String s3 = s1 s2;

问题 47

得 0 分, 满分 10 分

Is 'a' larger than 'A'?

所选答案: 🔞 [未给定]

正确答案: 💍 B.Yes

问题 48

得0分,满分10分

parseInt is a method in the _____ class.

所选答案: 🗯 [未给定]

正确答案: 🕜 C.Integer

问题 49

得 0 分, 满分 10 分

What is the printout of System.out.println('z' - 'a')?

所选答案: 🔞 [未给定]

正确答案: 🚫 B.25

得 0 分, 满分 10 分

To check if a string s contains the suffix "Java", you may write

所选 🙆 [未给定]

答

案:

正确 👩 A.if (s.substring(s.length() - 4).equals("Java")) ...

答

案:

B.if (s.endsWith("Java")) ...



D.if (s.charAt(s.length() - 4) == '|' && s.charAt(s.length() - 3) == 'a' && s.charAt(s.length() - 2) == 'v' && s.charAt(s.length() - 1) == 'a') ...

问题 51

得 0 分, 满分 10 分

Which of the following is not a correct method in the Character class?

所选答案: 🙆 [未给定]

正确答案: 🔗 B.toUpperCase()

O.isDigit()

问题 52

得 0 分, 满分 10 分

Assume that the ASCII code for character c is 99. What is the printout of the following code?

System.out.println("a" + 'c');

所选答案: 🗯 [未给定]

正确答案: 💍 D.ac

问题 53

得0分,满分10分

Which of the following is the correct expression of character 4?

所选答案: 🔞 [未给定]

正确答案: 👩 A.'4'

问题 54

得0分,满分10分

Note that the Unicode for character A is 65. The expression 'A' + 1 evaluates to

所选答案: 🗯 [未给定]

正确答案: A.66 问题 55 得 0 分, 满分 10 分

"smiles".substring(1, 5) returns "mile".

所选答案: 🗯 [未给定]

正确答案: B.true

问题 56 得0分,满分10分

What is the return value of "SELECT".substring(0, 5)?

所选答案: 🗯 [未给定]

正确答案: 🕜 B."SELEC"

问题 57 得0分,满分10分

Which of the following assignment statements is correct to assign character 5 to c?

所选答案: 🗯 [未给定]

正确答案: 🕜 C.char c = '5';

问题 58 得0分,满分10分

> Suppose i is an int type variable. Which of the following statements display the character whose Unicode is stored in variable i?

所选答案: 🗯 [未给定]

正确答案: O.System.out.println((char)i);

问题 59 得0分,满分10分

> Suppose x is a char variable with a value 'b'. What is the printout of the statement System.out.println(++x)?

所选答案: 🗯 [未给定]

正确答案: 🕜 C.c

问题 60 得 0 分, 满分 10 分

To obtain the arc sine of 0.5, use _____.

所选答案: 🗯 [未给定]

正确答案: OB.Math.asin(0.5)

20			复查测验提交: 10th_Chapter04_Exercise – 192面向对象程序设计		
	问题 61			得 0 分,满分 10 分	
		Math.sqrt(4			
		所选答案:			
		正确答案:	O D.2.0		
	问题 62			得 0 分,满分 10 分	
		To check wh	nether a char variable ch is an uppercase letter, yo	ou write	
		所选答案:	【未给定】		
		正确答案:	C.(ch >= 'A' && ch <= 'Z')		
	问题 63			得 0 分,满分 10 分	
		The statem	ent System.out.printf("%10s", 123456) outputs	(Note: *	
		represents	- · · · · · · · · · · · · · · · · · · ·	(14000.	
		所选答案:	😮 [未给定]		
		正确答案:	✓ C.****123456		
	问题 64			得 0 分,满分 10 分	
		"unhappy".:	substring(2) returns "happy".		
		所选答案:	❷ [未给定]		
		正确答案:	A.true		
	问题 65			得 0 分,满分 10 分	
		Math nav.	2) zetuma		
		·	3, 3) returns		
		所选答案:	② [未给定]		
		止佣合系:	⊘ D.27.0		
)7P= 46				
	问题 66			得 0 分,满分 10 分	

"abc".compareTo("aba") returns ______.

所选答案: 🗯 [未给定]

正确答案: 👩 A.2

问题 67 得0分,满分10分 Which of the following assignment statements is correct?

所选答案: 🗯 [未给定]

正确答案: 🔗 A.char c = 'd';

D.char c = 100;

问题 68 得 0 分, 满分 10 分

What is Math.rint(3.5)?

所选答案: 🗯 [未给定]

正确答案: 🕜 C.4.0

问题 69 得0分,满分10分

What is Math.floor(3.6)?

所选答案: 🗯 [未给定]

正确答案: 🕜 A.3.0

问题 70 得 0 分, 满分 10 分

Math.floor(5.5) evaluates to _____.

所选答案: 🗯 [未给定]

正确答案: 🕜 B.5.0

问题 71 得0分,满分10分

Suppose Character x = new Character('a'), _____ returns true.

所选答案: 🔞 [未给定]

正确答案: 🕢 A.x.equals(new Character('a'))

B.x.equals('a')

问题 72 得0分,满分10分

> Given two Strings s1 = "Welcome to Java" and s2 = "Programming is fun", which of the following is true?

所选答案: 🗯 [未给定]

正确答案: O.!s1.contains(s2)

问题 73 得0分,满分10分

You compare two strings s1 and s2 using ______.

所选答案: ② [未给定]

正确答案: OB.s1.compareTo(s2)

问题 74 得0分,满分10分

The Unicode of 'a' is 97. What is the Unicode for 'c'?

所选答案: 🗯 [未给定]

正确答案: 🚫 B.99

2019年11月20日 星期三 上午09时57分08秒 CST

← 确定