

BONDTITE ACRYLIC FIX is an innovative adhesive formulated with advanced technology. It's designed for bonding Acrylic sheet and alike substrates where regular white adhesives or rubber-based adhesives does not function.

BONDTITE ACRYLIC FIX is the best adhesive for pasting Acrylic Sheet to any wooden surfaces like Plywood | MDF | WPC | HDHMR etc.

FEATURES & BENEFITS

- High initial grab
- Fast setting
- Low odour
- Low VOC
- Waterproof and Heat resistance

AREAS OF APPLICATIONS

BONDTITE ACRYLIC FIX can be used in following applications

- Acrylic sheet to Plywood | MDF | WPC | HDHMR

HOW TO USE

- Ensure both the surfaces are clean and free from contaminants like oil, grease, dust etc.
- If HDHMR | MDF are getting used as a substrate then preferably sand it using emery paper no. 80-120 to make it rough enough to promote better adhesion for better bonding.
- Apply BONDTITE ACRYLIC FIX evenly using spreader on Plywood | sanded MDF, HDHMR etc. for full coverage over surface. Leave surface applied with adhesive as it is up to 8 -10 minutes for drying under surrounding climatic conditions.
- Gently wipe-out backside of ACRYLIC SHEET to be bonded over Plywood | MDF | HDHMR etc. with moist cloth (water droplet should not be dripping down while wiping so if excess water is there then wipe out surface with another dry cloth)
- For faster drying leave this up to 10-20 Minutes (During monsoon season | rainy day don't use any moist cloth since environment is already having high moisture)
- Bring both surfaces together, align & apply even pressure by rubbing with dry cloth or roller, press machine for getting a good bond.
- Keep bonded surface together under pressure with the help of clamps, nails, tape etc. up to 2-4 Hrs.
- Handling strength will be obtained within 2-4 Hrs.
- Full bond strength development will be reached in 24 hours for best performance post which cutting is advisable.
- Wipe out excess material oozing out at the edges of panels.
- Vertical application is not recommended.

TECHNICAL DETAILS

PROPERTIES	SPECIFICATION	UNIT
Physical State	Viscous Liquid	
Appearance	Opaque	
Colour	OFF White	
Density at 25° C in	1.48 – 1.52	Gm/cc
Drying time 120 µ at 25°C	20-25	Min.

SHELF LIFE

12 months in unopened packaging in dry and cool place, at temperatures between 5°C to 25°C

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please consult the corresponding product data sheet.

PACKING

In sausage pack 500g

STORAGE

Product should be stored below 40°C in a cool & dry place away from sunlight in properly tight container.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India. P: +91 79 6621 2000 | F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com Website: www.astraladhesives.com



Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com