

BONDTITE FOAMBOND-SR is a synthetic rubber-based(contact) adhesive which is specially designed for excellent bonding of different types of foams used in sofas, revolving chairs, rexine mattresses and upholstery etc.

FEATURES & BENEFITS

- Excellent bond strength and fast setting
- Soft on foam and comfortable
- Ease of application with good coverage
- Mild smell
- Benzene free

AREAS OF APPLICATIONS

Suitable for use in different industries for manufacturing and repair

Purpose in below applications.

- Foam to foam bonding
- Foam to Leather articles
- Mattress and upholstery

HOW TO USE

- Ensure that substrates to be bonded are clean, dry and free from oil, grease and foreign particles such as dust and rust.
- Stir adhesive well and make it homogeneous prior to use.
- Apply adhesive uniformly as thin layer on both the substrates to be bonded with brush, spatula or any suitable tool.
- Allow evaporation of solvents from adhesive layer to develop tack. The evaporation of solvent may take up to 10 minutes, which depends upon surrounding temperature and humidity.
- Bring both the surfaces together and align properly from end to end. Apply uniform pressure to eliminate possible air entrapment and achieve close contact without air pockets for long lasting bond.
- The optimum bond strength is achieved after 24 hours.

STORAGE

Product should be stored in a dry place in their original, properly closed containers at temperatures between 2°C to 40°C. Partially used containers should be closed immediately.

TECHNICAL DETAILS

PROPERTIES	TESTING STANDARD	RESULTS	UNIT
Color	-	Golden yellow viscous liquid	-
Specific gravity @ 25 °C	ASTM D 1475	0.82-0.86	-
Viscosity @ 25 °C	ASTM D2196-05	1000-1400	cPs
Drying time, 60μ film @ 25°C	STP_042	30-90	sec
Tack retention time*	STP_065	30-60	Min
Lap Shear strength, 24 hrs.	ASTM D 1002	8-15	kg/cm ²

* (Tack retention time (open time) is generally measured after evaporation of solvent once adhesive applied in thin film. It may vary depending upon ambient temperature and humid conditions.)

SHELF LIFE

18 months in unopened packaging in a dry and cool storage place, at temperatures between 5°C to 25°C.

HANDLING PRECAUTIONS

Product should be stored in cool and dry place away from moisture, heat and direct sunlight. It contains highly volatile solvents, which will be released during application, processing and use. These volatile solvents are highly flammable; hence adhesive must not come in contact with heat, spark and necked flame. Please refer to the Safety Data Sheet (SDS) for detailed instructions on storage and handling.

PACKING

200 mL, 500 mL, 1L, 5L, 25L

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India. P:

+91 79 6621 2000 | F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com Website: www.astraladhesives.com



Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com