

BONDITITE MULTIBOND SR is a general-purpose synthetic rubber-based (contact) adhesive suitable for bonding variety of substrates such as PVC flooring, HVAC duct insulation, rubber, leather, rexine, footwear, canvas, and upholstery foam etc.

FEATURES & BENEFITS

- Excellent bond strength
- Ease of application with good coverage
- Higher tack and tack retention time
- Mild smell
- Benzene free

AREAS OF APPLICATIONS

Suitable for different industries in manufacturing and repair purpose as below.

- Foam, Footwear industry.
- Electronics
- Automotive interiors
- PVC flooring

HOW TO USE

- Clean the surface to remove oil, grease and foreign particles such as dust and rust.
- Stir adhesive well and make it homogeneous prior to use.
- Apply adhesive uniformly as a thin layer on both the substrates to be bonded with brush/spreader.
- Allow evaporation of solvents from adhesive layer to develop tack. Evaporation of solvent may take up to 10 minutes depending on surrounding temperature and humidity.
- Bring both the surfaces together and align properly from end to end. Apply uniform pressure to eliminate possible air entrapment and achieve close contact without air pockets for long lasting bond.
- Optimum bond strength is achieved after 24 hours.

STORAGE

Product should be stored in a dry place in their original, properly closed container at temperatures between 2°C to 40°C. Partially used container should be close immediately.

TECHNICAL DETAILS

PROPERTIES	TESTING STANDARD	RESULTS	UNIT
Color	-	Golden yellow viscous liquid	-
Specific gravity @ 25°C	ASTM D 1475	0.82-0.86	-
Viscosity @ 25°C	ASTM D2196-05	1400-1800	cPs
Drying time, 60μ film @ 25°C	STP-042	25-40	sec
Tack retention time*	STP-065	25-50	Min
Lap Shear strength, 24 Hrs.	ASTM D 1002	8-15	kg/cm ²

* (Tack retention time (open time) is generally measured after evaporation of solvent once adhesive applied in thin film. It may vary depending upon ambient temperature and humid conditions.)

SHELF LIFE

18 months in unopened packaging stored in dry and cool place, at temperatures between 5°C to 25°C.

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please consult the corresponding product data sheet.

PACKING

200mL, 500mL, 1L, 5L, 25L

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India. P: +91 79 6621 2000 | F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com Website: www.astraladhesives.com



Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com