

BONDITITE QUIK SPRAY is a sprayable rubber-based adhesive for bonding various materials where immediate bond strength and heat resistance are required.

FEATURES & BENEFITS

- High initial strength
- Excellent tack
- Temperature resistant
- Low VOC

AREAS OF APPLICATIONS

Suitable for many application areas in manufacturing and repair purposes as below.

- Decorative Laminate to Plywood
- Suitable for application on difficult to reach areas like ceiling, inside of wardrobes
- Bonds multiple substrates like foam, metal, wood, etc. with each other

HOW TO USE

- Ensure surfaces are clean and free from contaminants.
- Shake the can well.
- Hold the can 10-12 cm away at 90° angle to the surface.
- Spray evenly on surface with a 50% overlap for full coverage.
- Leave surfaces as it is upto 1-2 minutes until dry to touch.
- Bring both the surfaces together and align properly from end to end. Apply uniform pressure to eliminate possible air entrapment and achieve close contact without air pockets for long lasting bond.

STORAGE

Product should be stored in a dry place in their original, properly closed cartridge at temperatures between 2°C to 40°C.

TECHNICAL DETAILS

PROPERTIES	TESTING STANDARD	RESULTS	UNIT
Appearance	-	White	-
Viscosity @ 25°C	ASTM D2196-05	180	cPs
Drying time	-	3-5	min
Share adhesion failure temp.	-	(Soft) 100gm >126°	-
Sheer	-	250	psi

* (Tack retention time (open time) is generally measured after evaporation of solvent once adhesive applied in thin film. It may vary depending upon ambient temperature and humid conditions.)

SHELF LIFE

12 months in unopened packaging in a dry and cool storage place, at temperatures between 5°C to 25°C.

HANDLING PRECAUTIONS

Product should be stored in cool and dry place away from moisture, heat and direct sunlight. It contains highly volatile solvents, which will release during application, processing and use. These volatile solvents are highly flammable, hence adhesive must not come in contact with heat, spark and necked flame. Please refer to the Safety Data Sheet (SDS) for detailed instructions on storage and handling.

PACKING

200 mL, 500 mL

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India. P: +91 79 6621 2000 | F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com Website: www.astraladhesives.com



MORE
CONVENIENCE



FASTER
FEEDBACK



ADDRESS TO
TECHNICAL QUERY

Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com