

BONDTITE CLEAR BOND is a rubber-based solvent-borne contact adhesive that provides higher tack for excellent bonding of wooden substrate. It also possesses quick grab property and strong bonding efficiency. It's free from chemicals like Benzene, Toluene and Xylene which are harmful to human health and environment.

FEATURES & BENEFITS

- Transparent bonding - In-visible glue line
- BTX Free
- Excellent bond strength and fast setting
- High tack retention time
- Ease of application with good coverage

AREAS OF APPLICATIONS

Suitable for manufacturing and repair purposes in many applications of different furniture industries as below.

- Plywood to Decorative Laminates bonding
- Suitable for Vertical lamination

HOW TO USE

- Ensure that substrates to be bonded are clean, dry and free from oil, grease and foreign particles such as dust and rust.
- Stir adhesive well and make it homogeneous prior to use.
- Apply adhesive uniformly in thin layer on both the substrates to be bonded with spreader, spatula or any suitable tool.
- Allow evaporation of solvents from adhesive layer to develop tack. The evaporation of solvent may take 5 minutes to 10 minutes, which depends upon ambient temperature and humidity.
- Assemble both the substrates with uniform pressure to achieve intimate contact without air pockets.
- The optimum bond strength is achieved after 24 hours.

STORAGE

Product should be stored in a dry place in their original, properly closed cartridge at temperatures between 2°C to 40°C. Partially used container should be closed immediately

TECHNICAL DETAILS

PROPERTIES	TESTING STANDARD	RESULTS	UNIT
Color	-	Transparent viscous liquid	-
Viscosity @ 25 °C	ASTM D2196-05	1400-2000	cPs
Drying time, 60μ film @ 25°C	STP_042	25-50	sec
Lap Shear strength, 24 hrs.	ASTM D 1002	13-23	kg/cm ²

SHELF LIFE

18 months in unopened packaging in a dry and cool storage place, at temperatures between 5°C to 25°C.

HANDLING PRECAUTIONS

Product should be stored in cool and dry place away from moisture, heat and direct sunlight. It contains highly volatile solvents, which will be released during application, processing and use. These volatile solvents are highly flammable; hence adhesives must not come in contact with heat, spark and necked flame. Please refer to the Safety Data Sheet (SDS) for detailed instructions on storage and handling.

PACKING

200mL, 500mL, 1L, 5L

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India. P: +91 79 6621 2000 | F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134
E-mail: customercare@astraladhesives.com Website: www.astraladhesives.com



Experience A Better Connect With The Company

**Exclusively for our
Channel Partners & Customers**

Visit us at:

wecare.astraladhesives.com