



BATHMATE

BATHROOM SEALING

ACRYLIC SEALANT

RESIBOND BATHMATE is a high-quality, permanently flexible, water-based acrylic sealant. Bathmate forms a watertight bond to surfaces and contains a powerful anti-fungal compound to prevent mould growth.


Interior | Contains antifungal additives



ASTM G21
certified



Strong
adhesion
to ceramic



High
flexibility

FEATURES AND BENEFITS



Eco-friendly



Anti-fungal
and resists mould growth



Water-tight seal


AREAS OF APPLICATION



Sealing in the
wash basin



Sealing electrical
switch board



Sealing in
wooden to the wall

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	White, Black, Brown	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	1.40-1.55	g/cc
Skin formation time	-	5-10	Min
Tack-free time	ASTM C 679-15	60	Min
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	>500	%
Hardness (Shore-A)	ASTM D 2240	35-45	-
Tensile strength	ASTM D 412	>3	kg/cm ²

HOW TO USE

Preparation:

The substrate areas that will be in contact with the sealant must be clean, dry and free of all loose material such as dust, dirt, rust, oil and other contaminants. Non-porous substrates should be cleaned with a solvent and a clean, lint-free cotton cloth. Remove residual solvent before it evaporates with a fresh, clean, and dry cloth.

Masking:

Masking will ensure a clean, neat appearance and reduce cleanup by protecting surrounding areas from excess sealant.

Applying:

Cut the nozzle at 45° and screw it onto the cartridge, and place it into the caulking gun. Air-operated or hand-operated caulking guns can be used. Apply sealant into the base of the joint so that it fills the joint, wetting both sides. Do not simply lay a bead on the surface, as the sealant will not penetrate the joint under its own weight.

Tooling:

Tool the surface of the joint immediately after sealant application to provide a smooth, even finish and to ensure the sealant wets the sides of the joint. A tool with a convex profile is recommended to keep the sealant within the joint. After a skin has formed, do not disturb the joint for 24 hrs.

RESTRICTIONS ON USE

Do not use in applications involving continuous water immersion. Do not apply if rain or frost is imminent.

SHELF LIFE

Usable life is 18 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

300 ml cartridge
75 g and 150 g tube

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



MORE
CONVENIENCE



FASTER
FEEDBACK



ADDRESS TO
TECHNICAL QUERY

— Experience A Better Connect With The Company —

EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS

Visit us at:

wecare.astraladhesives.com