



# DOORS & WINDOWS

## uPVC FRAME SEALING

### ACRYLIC SEALANT

RESIBOND DOORS & WINDOWS is a high-quality, multipurpose, flexible acrylic sealant. It is specially developed for door and window frame sealing. It contains an anti-fungal compound to prevent mould growth and provide good adhesion to metals, ceramic tiles, concrete, uPVC and PVC.

**Interior | Superior crack resistance**



All-weather  
flexibility



Paintable



Minimal  
shrinkage

## FEATURES AND BENEFITS



Superior  
crack resistance



Anti-fungal

## AREAS OF APPLICATION



uPVC  
window sealing



Sealing in the frame  
of the exhaust fan  
and cassette AC



Joints on window sills,  
between plinths and  
walls, and between  
masonry surfaces



uPVC doors  
and windows

## DOORS &amp; WINDOWS

## TECHNICAL DATA

| PROPERTIES                    | TESTING STANDARD | SPECIFICATION         | UNIT               |
|-------------------------------|------------------|-----------------------|--------------------|
| Colour                        | -                | White, Black and Grey | -                  |
| Uncured – 25°C, 50% R.H.      |                  |                       |                    |
| Paste density                 | ASTM D 1475      | 1.45-1.55             | g/cc               |
| Skin formation time           | -                | 5-10                  | Min                |
| Tack-free time                | ASTM C 679-15    | 120                   | Min                |
| Cured 7 days – 25°C, 50% R.H. |                  |                       |                    |
| Elongation                    | ASTM D 412       | >500                  | %                  |
| Hardness (Shore-A)            | ASTM D 2240      | 40-55                 | -                  |
| Tensile strength              | ASTM D 412       | >3                    | kg/cm <sup>2</sup> |

## HOW TO USE

**Preparation:**

The substrate areas that will be in contact with the sealant must be clean, dry and free of all loose material such as dust, dirt, rust, oil and other contaminants. Non-porous substrates should be cleaned with a solvent and a clean, lint-free cotton cloth. Remove residual solvent before it evaporates with a fresh, clean, and dry cloth.

**Masking:**

Masking will ensure a clean, neat appearance and reduce cleanup by protecting surrounding areas from excess sealant.

**Applying:**

Cut the nozzle at 45° and screw it onto the cartridge, and place it into the caulking gun. Air-operated or hand-operated caulking guns can be used. Apply sealant into the base of the joint so that it fills the joint, wetting both sides. Do not simply lay a bead on the surface, as the sealant will not penetrate the joint under its own weight.

**Tooling:**

Tool the surface of the joint immediately after sealant application to provide a smooth, even finish and to ensure the sealant wets the sides of the joint. A tool with a convex profile is recommended to keep the sealant within the joint. After a skin has formed, do not disturb the joint for 24 hrs.

## DOORS &amp; WINDOWS

## RESTRICTIONS ON USE

Do not use in applications involving continuous water immersion. Do not apply if rain or frost is imminent.

## SHELF LIFE

Usable life is 18 months in the original packaging. For more information, refer to the package.

## STORAGE

Store properly in a dry and well-ventilated place below 30°C.

## PACKING INFORMATION

300 ml cartridge

## HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



## ASTRAL LIMITED

Registered Office: 207/1, 'Astral House',  
B/h Rajpath Club, Off S.G. Highway,  
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000  
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: [customercare@astraladhesives.com](mailto:customercare@astraladhesives.com)  
Website: [www.astraladhesives.com](http://www.astraladhesives.com)  
Website: [www.resibond.com](http://www.resibond.com)



MORE  
CONVENIENCE



FASTER  
FEEDBACK



ADDRESS TO  
TECHNICAL QUERY

Experience A Better Connect With The Company

EXCLUSIVELY FOR OUR CHANNEL  
PARTNERS and CUSTOMERS

Visit us at:

[wecare.astraladhesives.com](http://wecare.astraladhesives.com)