



FIRESHIELD

RESISTANCE TO FIRE SEALING

ACRYLIC SEALANT

RESIBOND NXT FIRESHIELD Fire Retardant Sealant is a water-based acrylic fire-stop sealant that provides movement capability for fire-rated joint applications. It is almost odour-free and non-corrosive. After drying, it forms a tough elastic seal.

Specialised | BS 476-20 4-hour fire-rated*



Smoke, fume
& water resistant



No halogenated
materials



Low
VOC

FEATURES AND BENEFITS



Confirm to BS 476-20
4 hour fire-rated



Paintable

AREAS OF APPLICATION



Gap filling between
fire retardant pipes
and concrete



Sealing fire-rated
doors and windows



Sealing in between
electrical cable
and wall

FIRESHIELD

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	White	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	1.45-1.60	g/cc
Skin formation time	-	5-10	Min
Tack-free time	ASTM C 679-15	120	Min
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	>100	%
Hardness (Shore-A)	ASTM D 2240	14-18	-
Tensile strength	ASTM D 412	>3	kg/cm ²

HOW TO USE

Preparation:

The substrate areas that will be in contact with the sealant must be clean, dry and free of all loose material such as dust, dirt, rust, oil and other contaminants. Non-porous substrates should be cleaned with a solvent and a clean, lint-free cotton cloth. Remove residual solvent before it evaporates with a fresh, clean, and dry cloth.

Masking:

Masking will ensure a clean, neat appearance and reduce cleanup by protecting surrounding areas from excess sealant.

Applying:

Cut the nozzle at 45° and screw it onto the cartridge, and place it into the caulking gun. Air-operated or hand-operated caulking guns can be used. Apply sealant into the base of the joint so that it fills the joint, wetting both sides. Do not simply lay a bead on the surface, as the sealant will not penetrate the joint under its own weight.

Tooling:

Tool the surface of the joint immediately after sealant application to provide a smooth, even finish and to ensure the sealant wets the sides of the joint. A tool with a convex profile is recommended to keep the sealant within the joint. After a skin has formed, do not disturb the joint for 24 hrs.

Remarks:

- Do not use in applications with continuous water immersion.
- Do not apply when rain or frost is imminent.

FIRESHIELD**SHELF LIFE**

Usable life is 18 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

300 ml cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

**ASTRAL LIMITED**

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

Experience A Better Connect With The Company

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com