



MIRROR MOUNT

MIRROR BONDING

HYBRID SEALANT

RESIBOND NXT MIRROR MOUNT is a high-performance single-component sealant with rapid curing and strong adhesion. It is specially developed for mirror pasting.

Interior | Non-corrosive nanotechnology



Non
staining



Fast curing



Excellent
bonding

FEATURES AND BENEFITS



Non-corrosive, odourless,
ready-to-use gun-grade sealant



Excellent unprimed adhesion on most
of the glass, metals and mirror coating



Outstanding resistance to
heat and humidity



Excellent vertical hold

AREAS OF APPLICATION




Internal and External
fixation of mirrors



Coated glass or metal
panels onto
various substrates



Bonding of glass
and back painted
panels



Mirror pasting

MIRROR MOUNT

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	White	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	1.5-1.6	g/cc
Skin formation time	-	20-22	-
Tack-free time	ASTM C 679-15	8	Hrs
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	250-500	%
Hardness (Shore-A)	ASTM D 2240	35-50	-
Tensile strength	ASTM D 412	>15	kg/cm²

HOW TO USE

Preparation:

The substrate areas that will be in contact with the sealant must be clean, dry and free of all loose material such as dust, dirt, rust, oil and other contaminants. Non-porous substrates should be cleaned with a solvent and a clean, lint-free cotton cloth. Remove residual solvent before it evaporates with a fresh, clean, and dry cloth.

Application Method:

The sealant is ready to use. Apply 10 mm wide vertical strips of sealant on the back of the mirror at 100 mm intervals. Press the mirror firmly onto the surface, maintaining a consistent bead thickness of 2 mm to ensure optimum curing and mechanical grab. Support the mirror for a minimum of 24 hours using adhesive tapes to ensure proper contact and minimize displacement. Allow air to circulate freely around the edges of the mirror to enable proper sealant curing.

Cleanup:

Excess sealant can be cleaned from tools and non-porous surfaces while in an uncured state using a suitable cleaner. If sealant is accidentally applied on porous substrates, allow it to partially cure and then remove it by peeling, cutting, or other mechanical methods. Ensure that the removal process does not damage plastic or coated surfaces.

Limitations:

When used with safety mirrors (single pane mirrors laminated with a plastic film at the back to prevent shattering of the glass when broken), first check adherence of Resibond NXT Mirror Mount on the plastic film.

MIRROR MOUNT

RESTRICTIONS ON USE

Not recommended for structural glazing applications.

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

435 g cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

— Experience A Better Connect With The Company —

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com