



SANITARY SUPER WHITE

SANITARY SEALING

ACETOXY SEALANT

RESIBOND NXT SANITARY SUPER WHITE is a one-part, room-temperature-curing, acetoxy silicone sealant.

Interior | Advanced mould-resistant formula



Ideal for humid conditions



ASTM G21 certified



Mould - resistant

FEATURES AND BENEFITS



Fungus and mildew-resistant



Superior finish



Resistant to ozone, ultraviolet radiation and temperature extremes



Excellent water-resistance properties


AREAS OF APPLICATION




Sealing in washbasins



Sealing commode and urinal



Sealing in bathtub



Sealing in glass cubical shower

SANITARY SUPER WHITE

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	White	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	0.94-0.98	g/cc
Skin formation time	-	4-8	Min
Tack-free time	ASTM C 679-15	15-30	Min
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	>350	%
Hardness (Shore-A)	ASTM D 2240	18-24	-
Tensile strength	ASTM D 412	>12	kg/cm ²

HOW TO USE

Preparation:

Remove all residual dirt, contaminants, and old sealant thoroughly. Wipe off grease and dirt from the surface using a clean white cloth dampened with solvent, then immediately wipe with another clean cloth to remove any residual solvent and contaminants from the surface.

Masking:

Masking will ensure a clean, neat appearance and reduce cleanup by protecting surrounding areas from excess sealant.

Applying:

Cut the nozzle at 45° and screw it onto the cartridge, and place it into the caulking gun. Air-operated or hand-operated caulking guns can be used. Apply sealant into the base of the joint so that it fills the joint, wetting both sides. Do not simply lay a bead on the surface, as the sealant will not penetrate the joint under its own weight.

Tooling:

Tool the surface of the joint immediately after sealant application to provide a smooth, even finish and to ensure the sealant wets the sides of the joint. A tool with a convex profile is recommended to keep the sealant within the joint. After a skin has formed, do not disturb the joint for 24 hrs.

Remarks:

Do not apply when rain or frost is imminent.

SANITARY SUPER WHITE**RESTRICTIONS ON USE**

Not recommended for general glazing applications: zinc, brass, copper, and polished surfaces like mirrors.

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

280 ml cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

**ASTRAL LIMITED**

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

— Experience A Better Connect With The Company —

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com