



TURF GRASS

ARTIFICIAL GRASS BONDING

HYBRID SEALANT

RESIBOND NXT TURF GRASS is a high-tack, fast-setting, one-component modified-silane hybrid adhesive designed for installing high-performance synthetic sports turf.

Specialised | High-tack adhesive for artificial grass bonding



Fast
setting



High
initial tack



Suitable for trowel
application

FEATURES AND BENEFITS



Can be applied to
wet surfaces



Solvent-free
and odourless



Fast tack and
rapid cure time



Non-shrinking and
permanently elastic



Can be used in all weather conditions.
Ideal for maintenance and repair work



Internal and
external use

AREAS OF APPLICATION



Artificial grass bonds
sports and recreation
areas like football fields,
cricket grounds, etc.



Residential like
home lawns, garden,
rooftop, etc.

TURF GRASS

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	Beige	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	1.50-1.60	g/cc
Skin formation time	-	20-30	Min
Tack-free time	ASTM C 679-15	15	Hrs
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	150-200	%
Hardness (Shore-A)	ASTM D 2240	40-45	-
Lap share strength (Wood to Wood)	ASTM D 1002	15-19	kg/cm ²

HOW TO USE

Preparation:

Ensure all surfaces are clean and free from dust, grease, oil or any other contaminants that may hinder adhesion.

Applying:

- Carefully cut the tip of the cartridge, taking care not to damage the threaded area. Screw on the nozzle and place the cartridge in a standard sealant gun.
- Apply the adhesive directly from the cartridge onto the seaming tape.
- Use a serrated trowel to spread evenly.
- Weight the joint to ensure a flat, even joint.
- Join the artificial grass and allow it to dry for a few minutes.
- Full cure will take approximately 24 hours.
- Remove any excess material and clean tools with white spirit or multi-wipes prior to curing. Cured adhesive must be removed mechanically.

Coverage:

On a typical seam, one cartridge should cover approximately 4 linear metres of jointing tape.

TURF GRASS

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

600 ml sausage

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



ASTRAL LIMITED

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

Experience A Better Connect With The Company

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com