



SAVES NAILS

MULTI-SUBSTRATE BONDING

SBS SEALANT

RESIBOND SAVES NAILS is an instant-grab construction adhesive that has an excellent bond strength on most construction substrates like concrete, wood, aluminium, particle board, MDF, stone, ceramic, etc. It is easy to apply, non-slump, paintable and is suitable for interior and exterior use. It can replace mechanical fixings in a variety of DIY applications.

Interior & Exterior | Construction adhesive



Strong adhesion
to construction
materials



Suitable for
interior and
exterior use



Instant
grab

FEATURES AND BENEFITS



Single component -
no mixing is required



High mechanical
strength




Bonds a variety of
construction and
building materials

AREAS OF APPLICATION



Wall moulding
bonding on concrete



Installation of battens
or other fixings to brick,
masonry or concrete walls



Wood, metal substrates
fixing to concrete, plaster
or other rigid surfaces



Nameplate fixing
on wall or tile

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	Beige	-
Uncured – 25°C, 50% R.H.			
Paste density	ASTM D 1475	1.300 - 1.400	g/cc
Skin formation time	-	10-15	Sec
Cured 7 days – 25°C, 50% R.H.			
Hardness (Shore-A)	ASTM D 2240	70-80	
Lap shear strength (wood-wood)	ASTM D 1002-10	>15	kg/cm2

HOW TO USE

Resibond Saves Nails can be applied either as a two-way contact or a one-way stick adhesive. In both cases, the first requirement is that both surfaces to be bonded are clean and dry and free of grease, oil or dust. Any loose or flaking paint must be removed and lightly sanded before application. (Substrate surface temperatures should not exceed 30°C, and the product should not be used where continued exposure to elevated temperatures will occur). To one of the freshly prepared surfaces, apply a 4 – 6mm bead of adhesive with a cartridge or extrusion gun, or similar type profiles with a notched trowel. Beads should not be more than 45cm apart, and butt joints should be adhered to both panel edges. Bring both surfaces together immediately.

Two-Way Method:

Press firmly over the entire surface to transfer the adhesive, then pull both surfaces apart. Allow to tack off for 3–5 minutes (depending on ambient weather conditions), then reposition and press firmly together. Contact areas should then be tapped with a hammer via a padded block to ensure intimate contact. Depending on the weather conditions and the surfaces bonded, maximum bond strength will take from 12 to 24 hours to achieve. Some weighted panels may require temporary mechanical fastening that should be retained for at least this period.

One-Way Method:

This method is recommended for heavier panels or those that are formed to place a load or stress on the bond line. After applying adhesive and bringing the substrates together, they should be clamped, nailed or screwed in a way that maintains maximum surface contact at the bonded interfaces. Mechanical fasteners should be retained if the joint is highly stressed, but temporary fasteners can be removed after a minimum of 24 hours. For flooring applications, the adhesive should be applied according to the flooring manufacturer's specifications. To stop floors from squeaking, apply a bead of adhesive into the groove of each board after it is laid and immediately before mating the tongue of the next panel or board.

Precaution:

- Always test the product on a small area before bonding.
- Plasticiser migration may occur with some PVC materials.
- Veneer plywood may be affected if the solvent soaks through the ply, causing the veneer to bubble.

Cleanup:

Any wet or partially wet adhesive can be removed with scraping. Dried adhesive is best removed with a scraper or by sanding.

Fire:

Sealant and vapour are flammable when temperatures exceed the flash point. Keep away from flames or sources of ignition.

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

290 ml cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

**ASTRAL LIMITED**

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

Experience A Better Connect With The Company

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com