



THERMOSEAL

HIGH-TEMPERATURE SEALING

NEUTRAL SEALANT

RESIBOND THERMOSEAL is a specially developed neutral cure silicone sealant which cures to a tough rubbery solid when exposed to moisture in the air. It is used for high temperature & heavy-duty applications. It replaces almost any gasket used in automobile & engineering applications.

Specialised | Superior temperature resistance



High flexibility



Excellent dielectric properties



Excellent oil resistance

FEATURES AND BENEFITS



Neutral cure, non-corrosive



Non-slumping, suitable for overhead or on side walls



Can be used in applications with continuous exposure to 250°C and intermittent exposure to 310°C

AREAS OF APPLICATION



Making FIP gasket



Sealing heating elements in appliances

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	Red	-
Uncured – 25°C, 50% R.H			
Paste density	ASTM D 1475	1.0-1.1	g/cc
Skin formation time	-	15-20	Min
Tack-free time	ASTM C 679-15	180	Min
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	>600	%
Hardness (Shore-A)	ASTM D 2240	18-24	-
Tensile strength	ASTM D 412	>10	kg/cm ²

HOW TO USE

Preparation:

The substrate areas that will be in contact with the sealant must be clean, dry and free of all loose material such as dust, dirt, rust, oil and other contaminants. Non-porous substrates should be cleaned with a solvent and a clean, lint-free cotton cloth. Remove residual solvent before it evaporates with a fresh, clean, and dry cloth.

Applying:

Cut the nozzle at a 45° angle and attach it securely to the cartridge. Place the cartridge into the caulking gun and apply the sealant onto the prepared surface in a continuous, uniform bead.

Tooling:

Tool the joint surface immediately after sealant application to provide a smooth, even finish and to ensure the sealant wets the sides of the joint.

Limitations:

Do not use for applications where the product will be in constant contact with gasoline, synthetic fuels or solvents.

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

300 ml cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

**ASTRAL LIMITED**

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

— Experience A Better Connect With The Company —

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com