



ZERO NAIL

ALL-PURPOSE

HYBRID SEALANT

RESIBOND ZERO NAIL is a high-strength, instant-grab, and high-load-bearing adhesive that bonds multiple substrates. It offers good weather resistance and excellent durability. It is easy to apply, non-slump, paintable, and suitable for both interior and exterior applications. It can also be applied to wet surfaces.

Interior | Best-in-class hanging load capacity



Low
VOC



Instant
grab



Hanging load-bearing
capacity: $\geq 100 \text{ kg/6 cm}^2$

FEATURES AND BENEFITS



Zero staining



Eco-friendly,
solvent-free



UV resistance,
Suitable for exterior uses



Primer less adhesion,
non-corrosive




Works on
damp surfaces

AREAS OF APPLICATION



Instant fixing of ACP,
mirrors, back painted
glass, metal, steel
and tiles



Louvres bonding



Marbles, wood
and sanitaryware etc.



General purpose
bonding on various
porous and non-porous
surfaces

TECHNICAL DATA

PROPERTIES	TESTING STANDARD	SPECIFICATION	UNIT
Colour	-	White	-
Uncured – 25°C, 50% R.H			
Paste density	ASTM D 1475	1.40-1.55	g/cc
Skin formation time	-	20	Min
Cured 7 days – 25°C, 50% R.H.			
Elongation	ASTM D 412	<200	%
Hardness (Shore-A)	ASTM D 2240	50-60	-
Tensile strength	ASTM D 412	>20	kg/cm ²

HOW TO USE

1. Clean both the surfaces being bonded to ensure that they are clean, dry, and free from dust, dirt, oil, loose particles, or any other contaminants.
2. Cut the Cartridge, insert it into the cartridge gun and fix V-cut nozzle on top.
3. Apply the sealant beads in a zig-zag pattern on one of the substrates with approx.10 cm distance between each sealant bead.
4. It is recommended to keep a gap of 35 mm at all sides of large panels where sealant will be applied to avoid any excess material coming out from the edges and to control any visible gap between the 2 bonded surfaces.
5. Align the surfaces together (as per requirement) as quickly as possible and press firmly for 2-3 minutes. Parts can be re-adjusted up to 5 minutes, depending upon the temperature.
6. For putting heavier weights, such as glass or stone shelves, on wall-mounted 'C' clamps or brackets, allow the adhesive to cure overnight before putting the shelves in place.
7. Seal the nozzle with the help of a tape. If the bottle is to be reused, ensure it is done within 24-48 hours of opening. Cut the nozzle tip to remove cured sealant before re-use.

Remarks: A heavy-duty gun is recommended for dispensing the material.

RESTRICTIONS ON USE

For use on PE, PP, PTFE, polycarbonate, silicone rubber and bituminous substrates.
Not to be used for high-temperature applications such as gasketing.

SHELF LIFE

Usable life is 12 months in the original packaging. For more information, refer to the package.

STORAGE

Store properly in a dry and well-ventilated place below 30°C.

PACKING INFORMATION

435 g cartridge

HANDLING PRECAUTIONS

Test it before use. The user is responsible to conduct property test before using it to confirm that the sealant produces satisfactory results. Especially for the surface, which is difficult to adhere to and coated substrates, the cohesiveness should be tested.

IMPORTANT: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

**ASTRAL LIMITED**

Registered Office: 207/1, 'Astral House',
B/h Rajpath Club, Off S.G. Highway,
Ahmedabad-380059, Gujarat, India. +91 79 6621 2000
F: +91 79 6621 2121 | CIN: L25200GJ1996PLC029134

E-mail: customercare@astraladhesives.com
Website: www.astraladhesives.com
Website: www.resibond.com



**MORE
CONVENIENCE**



**FASTER
FEEDBACK**



**ADDRESS TO
TECHNICAL QUERY**

Experience A Better Connect With The Company

**EXCLUSIVELY FOR OUR CHANNEL
PARTNERS and CUSTOMERS**

Visit us at:

wecare.astraladhesives.com