

BORETITE

Epoxy Based System For Bore Packing

ASTRAL

TRUBUILD™

TECHNICAL DATA SHEET VER NO. N.1

PRODUCT DESCRIPTIONS

TRUBUILD BORETITE is an epoxy-based, one-pack system specially formulated to achieve leak-free bore packing . It consists of moisture insensitive resin, hardener, selected filler & backer rod, provides fool proof bonding between PVC /CPVC /Iron pipes and concrete. It can be used for grouting/sealing gaps of pipe vents in bathrooms, toilet, balconies, roofs, fountains and artificial lakes etc which when applied properly, it serves as an excellent waterproofing system for bore.

FEATURES & ADVANTAGES



EXCELLENT
BOND STRENGTH



EXCELLENT
VIBRATION
DAMPENING



HIGH
ENDURANCE



SELF-LEVELLING


- Excellent bond strength with various surfaces
- High compressive strength
- Higher endurance
- Excellent vibration Self-levelling dampening properties
- Self-levelling

AREAS OF APPLICATION



Bore Packing

PACKAGING



METHOD OF APPLICATION

Vertical Bore - Clean all types of dirt, oil, grease and loose material from the bore using brush, dry cloth and air blower. Fix the backer rod inside gap at min. depth of 35-40 mm from the top of the surface. Then pour Part A and Part B in a container and mix it thoroughly until it becomes a homogeneous mixture, then slowly add filler to it and then mix it again properly. Slowly pour the mix at a single point, until it gets completely poured and it encircles the circumference of bore. Then sprinkle the sand upon it to aid bonding to further applied waterproofing coating, then leave it for 24 hours for complete curing.

PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and used. For additional information please read Material Safety Data Sheets.

STORAGE

Product should be stored in a dry place in its original, closed container at temperatures between 2 - 40°C.

TECHNICAL PROPERTIES

S.NO.	PROPERTIES	STANDARD	RESULTS
1.	Physical state	-	Liquid
2.	Setting time (hour)	In-House	24 hours
3.	Bond strength (MPa)	-	Uo to 3 MPa
4.	Vibration dampening	-	Good

COVERAGE

Width-5 mm* depth-50 mm- single 200 gm bore packing/ standard packet

Width-10 mm* depth-25 mm- single 200 gm bore packing/ standard packet

NOTE- Coverage may vary as per width and depth.

SHELF LIFE

24 months from the date of manufacturing

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.