

CRACKFILL POWDER

Two-Part Acrylic Cementitious Waterproof Coating

ASTRAL

TRUBUILD™

TECHNICAL DATA SHEET VER NO. N.1

PRODUCT DESCRIPTIONS

TRUBUILD CRACKFILL POWDER (formerly known as CFP-525) is a cement-based, polymer modified powder material for filling cracks in plastered surfaces. It is composed of cement, selected aggregates, polymer & additives which requires on site addition of water only. Cracks filled with Trubuild Crackfill Powder enhance the subsequent paints' quality and life.

FEATURES & ADVANTAGES



STRONG ADHESION



EASY TO USE



REDUCES PAINT CONSUMPTION



ON-SITE ADDITION OF WATER

- Adhesion - Strong adhesion to common building substrates
- Easy to use - It is a do it yourself product & requires only on-site addition of water
- Requires only addition of water on - site at the time of usage
- As a surface leveller before painting, it reduces paint consumption and increases the life of the paint making it economical

AREAS OF APPLICATION



- To fill static cracks of 3 to 5 mm.
- To level undulation on unplastered or plastered ceilings and walls prior to painting.
- To provide smooth finish to brick, stone, and concrete

PACKAGING



METHOD OF APPLICATION

Ensure the joints edges are neat and sound. Make sure that the surface is clean & free from standing water. The surface should be free of loose debris.

Contaminations of oil, grease or bitumen should be completely cleaned.

Under normal conditions, Trubuild Crackfill Powder does not require a primer. However, in critical areas water based acrylic or SBR based primer can be used depending on the severity of surface and application.

Mixing ratio of Trubuild Crackfill Powder to water varies with respect to area of application.

For filling deep holes and cracks, reduce the water quantity to get a thicker pasty consistency.

The final mixed product would be a paste of dough consistency. In case further soft consistency is required, measured quantity of water can be used.

APPLICATION

For crack filling – Fill the mixed paste into the crack by spatula or putty knife blade. Fill excess material and tool it by putty knife blade pressing against crack so that air voids get filled. By wet finger tool the surface of material in to a concave nature by pressing against joint edges.

For surface levelling – The mixed smooth paste should be applied by painter blade on the dampened wall or ceiling. The material should be applied in the desired thickness in a bottom- to -up fashion to avoid blade marks. For multiple coat applications, the previous coat should be allowed to cure for minimum 6 hrs. The subsequent coat should be at the right angle to the previous coat.

PRECAUTIONS

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing, physical, ecological, toxicological and other safety related data.

TECHNICAL PROPERTIES

S.NO.	PROPERTIES	UNIT	RESULTS	METHOD
1.	Appearance	Visual	Off white powder	-
2.	Colour	Visual	Off white	-
3.	Setting time	Hrs: min	3:10	-
4.	Bulk density	g/cc	1.44	ASTM D 7481-18
5.	Pot life	Minutes	20	ISO 13007-3-2010
6.	Tack free time	Minutes	40	ASTM C 679-2015
7.	Dry shrinkage	%	0.002	ASTM C 157-2017
8.	Pull off adhesion	N/mm2	0.44	ASTM D 7234-2021
9.	Water absorption @ 15 min	ml	1.2	Karsten tube
10.	Water absorption @ 30 min	ml	3.6	
11.	Water absorption @ 60 min	ml	5.5	
12.	Water absorption @ 4 hrs.	ml	9.6	
13.	Mix density	g/cc	1.52	-

PRECAUTION & LIMITATION

Do not apply for cracks of more than 5 mm width.

Do not apply on wet surfaces. Meant for plaster cracks.

Not for application in cracks of structural members, expansion joints & separation gaps.

Not for cracks in POP or painter's putty.

For application below 10°C, drying time will be delayed.

Container to be tightly closed after application.

CLEANING

Application equipment should be thoroughly cleaned with water after application.

RESTRICTION IN USE

Trubuild Crackfill Powder is for static joint filling only. It is suitable for cracks less than 5mm width.

It does not accommodate any movements and thus it is not suitable for dynamic cracks.

For outside use, Trubuild Crackfill Powder must be coated over with exterior paint to prevent water penetration.

COVERAGE

37.5 running meter per kg (for a depth & width of 5 mm)

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing under unopened conditions. Store in a cool & dry place, away from sun heat.

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.