

IW+ 111

Integral Waterproofing Compound

ASTRAL

TRUBUILD™

TECHNICAL DATA SHEET VER NO. N.1

PRODUCT DESCRIPTIONS

Trubuild IW+ 111 is silicate-based, integral, water proofing compound which is specially designed to reduce porosity in cement concrete, mortar & plaster. It helps in reducing permeability of concrete and makes it more cohesive.

Meets the requirement of IS: 2645-2003.



FEATURES & ADVANTAGES



IMPROVES
FINISHING



BETTER
COHESION



REDUCES
PERMEABILITY



ENHANCES
WORKABILITY


- Reduces permeability in concrete, thereby improving the water tightness and reduces the corrosion in reinforced steel.
- Single component product, easy to use.
- It improves workability of freshly mixed concrete and increases durability of concrete without affecting the strength of concrete.

AREAS OF APPLICATION



Trubuild IW+ 111 is used for water proofing of cement-sand mortar which is used for making roofslabs.

PACKAGING



METHOD OF APPLICATION

Charge cement & aggregates to concrete mixer as per the mix design. Mix in dry state for 1-2 minutes. Start addition of 75-80% mixing water & mix for 2-3 minutes.

Cure the applied mortar or concrete as per good construction practices.

Trubuild IW+ 111 is added as per the recommended dosage into the remaining mixing /gauging water, then add to concrete mixer & mix for another 2 minutes. Maintain the water to cement ratio as low as possible.

TECHNICAL PROPERTIES

S.NO.	PROPERTIES	STANDARD	RESULTS
1.	Physical state	-	Low viscous Liquid
2.	Appearance	-	Transparent
3.	pH	-	>9
4.	Specific gravity	-	1.03-1.05
5.	Setting time	IS: 2645: 2003	30-600 min
6.	Water permeability	IS: 2645: 2003	Pass
7.	Compressive strength	IS: 2645: 2003	As per the standard

RESTRICTION OF USE

Trubuild IW+ 111 should be used in recommended dosage
Make sure that water-cement ratio should be as low as possible

DOSAGE

200 ml per 50 kg bag of cement.

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please refer MSDS.

STORAGE

Product should be stored in a dry place in its original, properly closed container at temperatures between 2-40°C. Partially emptied container should be closed immediately.

SHELF LIFE

24 months from the date of manufacturing

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.