

PRODUCT DESCRIPTIONS

TRUBUILD TRUBOND DS TAPE is a cold applied double-sided tape with pressure sensitive adhesive and release liner on both sides. Its adhesive provides perfect bonding with pre-applied HDPE Waterproofing membranes and concrete.

FEATURES & ADVANTAGES



EFFECTIVE PROTECTION
AGAINST GROUND WATER



APPLICABLE ON PLASTIC,
RUBBER & CONCRETE SURFACES



LOW TEMPERATURE
RESISTANCE

AREAS OF APPLICATION

- It is used for joining end laps of HDPE waterproofing membranes.
- It is used for overlapping HDPE membranes after cutting at site.

PACKAGING



Roll size: 10 cm wide x 30-meter length.

METHOD OF APPLICATION

Substrate must be completely clean. All grease, moisture, oil, dust, substrate coatings and other contaminants should be removed. Trubuild Trubond DS Tapes are used to join end laps of HDPE waterproofing membranes and in overlapping the membranes after cutting at site. Remove the sand and adhesive for a width of 100 mm from the HDPE membrane at end laps or cut edges using hot air gun and fix double side tape after removing silicon liner and roll it firmly. To ensure positioning, place the next HDPE membrane above the bare HDPE surface after the removal of sand & adhesive and align for dimensional correction. Don't try to press or stick. Remove the silicon liner from the double-sided tape, place the next HDPE membranes and align the same. Press the membranes using rollers sufficiently to get enough pressure thereby ensuring proper adhesion at the overlap area.

TECHNICAL PROPERTIES

S.NO.	PROPERTIES	STANDARDS	RESULTS
01.	Flexibility at low temperature, -25°C	ASTM D1970	No Cracking
02.	Peel Adhesion Strength with HDPE Membrane	ASTM D1876	1.25 N/mm
03.	Peel Adhesion Strength with Concrete	ASTM D 903	0.5 N/mm

HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and used. For additional information please read Material Safety Data Sheets.

STORAGE

Protect the material from moisture and direct sunlight. The material should also be free from acid, alkali, oil and organic solvent; stored at an ambient temperature between +8°C to +35°C.

SHELF LIFE

12 months from the date of manufacturing.

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.