

Node.js Exercises - Correction

1) HELLO WORLD

Create a file named hello-world.js

```
console.log("HELLO WORLD");
```

Run command:

```
node hello-world.js
```

2) CREATE A SERVER

Create a file named server.js

```
const http = require("http");

const server = http.createServer((req, res) => {
  res.write("<h1>Hello Node!!!!</h1>\n");
  res.end();
});

server.listen(3000, () => {
  console.log("Server is running on port 3000");
});
```

Run command:

```
node server.js
```

Open in browser:

```
http://localhost:3000
```

3) FILE SYSTEM

Create a file named file-system.js

```
const fs = require("fs");

// Create welcome.txt
fs.writeFileSync("welcome.txt", "Hello Node");

// Read from hello.txt
const data = fs.readFileSync("hello.txt", "utf8");

console.log(data);
```

Create a file named hello.txt before running the program.

Run command:

```
node file-system.js
```

4) PASSWORD GENERATOR

Create a folder named password-generator

```
npm init -y
npm install generate-password

const generator = require("generate-password");

const password = generator.generate({
  length: 10,
  numbers: true,
});

console.log(password);
```

5) EMAIL SENDER

Create a folder named email-sender

```
npm init -y
npm install nodemailer

const nodemailer = require("nodemailer");

const transporter = nodemailer.createTransport({
  service: "gmail",
  auth: {
    user: "your_email@gmail.com",
    pass: "your_app_password",
  },
});

const mailOptions = {
  from: "your_email@gmail.com",
  to: "your_email@gmail.com",
  subject: "Test Email",
  text: "Hello from Node.js",
};

transporter.sendMail(mailOptions, (error, info) => {
  if (error) {
    console.log(error);
  } else {
    console.log("Email sent: " + info.response);
  }
});
```