Institutionen för systemteknik Department of Electrical Engineering

Examensarbete

Replacement of the DVB-CSA Subtitle goes here!

Examensarbete utfört i Subject goes here vid Tekniska högskolan vid Linköpings universitet av

Gustaf Bengtz

LiTH-ISY-EX--YY/NNNN--SE Linköping 2014



Linköpings universitet TEKNISKA HÖGSKOLAN

Genomgång av nya och alternativa krypterings- och scramblingssystem för digital-teve samt implementering av ny scrambling-algoritm (AES128) på FPGA

Subtitle goes here!

Examensarbete utfört i Subject goes here vid Tekniska högskolan vid Linköpings universitet av

Gustaf Bengtz

LiTH-ISY-EX--YY/NNNN--SE

Handledare: Oscar Gustafsson

ISY, Linköpings universitet

Patrik Lantto WISI NORDEN

Examinator: Kent Palmkvist

ISY, Linköpings universitet

Linköping, 06 mars 2014



Avdelning, Institution Division, Department

ISY Embedded systems Department of Electrical Engineering SE-581 83 Linköping Datum Date

2014-03-006

Språk Language □ Svenska/Swedish ⊠ Engelska/English □ URL för elektronisk version	Rapporttyp Report category Licentiatavhandling Examensarbete C-uppsats D-uppsats Övrig rapport	ISBN ISRN LiTH-ISY-EXYY/NNNNSE Serietitel och serienummer Title of series, numbering		
Title implemente	ring av ny scrambling-algori t of the DVB-CSA	terings- och scramblingsystem för o tm (AES128) på FPGA	digital-teve samt	

Sammanfattning

Abstract

This report adresses why the currently used scrambling standard CSA needs a replacement. Proposed replacements to CSA are analyzed to some extent, and an alternative replacement (AES) is analyzed.

It has been impossible to find proper information on CISSA and CSA3 due to them being confidential, and licensing was not allowed.

The implementation of the Advanced Encryption Standard (AES) is analyzed, and the general implementation is displayed.

Nyckelord

Keywords problem, solving, DVB, scrambling, CISSA, cipher, CSA, CSA3

Abstract

Här skriver jag texten som ska in i engelska abstracten. För närvarande: Nothing to say mon.



vi Notation

Notation

ABBREVIATIONS

Abbrevation	Meaning
AES	Advanced Encryption Standard
CAM	Conditional Access Module
CAS	Conditional Access System
CBC mode	Cipher block chaining mode
CC	Content Control
Ciphertext	Encrypted plaintext
CISSA	Common IPTV Software-oriented Scrambling Algo-
	rithm
CPU	Central Processing Unig
CSA	Common Scrambling Algorithm
CTR mode	Counter mode
CW	Control Word, which is a key
DVB	Digital Video Broadcasting
ECM	Entitlement Control Message. CW encrypted by the
	CAS
EMM	Entitlement Management Messages
ES	Elementary stream
ETSI	European Telecommunications Standards Institute
IPTV	Internet Protocol Television
IV	Initialization vector
LFSR	Linear Feedback Shift-Register
LSB	Least Significant Bit
MSB	Most Significant Bit
Nibble	Half a byte (4 bits)
Nonce	A value that is only used once
P-Box	Permutation-Box
PES	Packetized Elementary Stream
Plaintext	Content, data
PS	Program Stream
S-Box	Substitution-Box
STB	Set-top Box
TS	Transport Stream. Contains data
XRC	eXtended emulation Resistant Cipher

Contents

No	otatio	n	V				
1 Digital Video Broadcasting							
	1.1	Set-up	1				
	1.2	Conditional Access System	2				
		1.2.1 Standards	2				
	1.3	DVB-SimulCrypt	3				
	1.4	Common Interface	3				
		1.4.1 CIPlus	3				
	1.5	Conditional Access Module	3				
2	Scra	mbling	5				
	2.1	Why do we need cryptography?	5				
	2.2	Scrambling or Encrypting	6				
	2.3	Data packets	6				
		2.3.1 TS packets	6				
		2.3.2 PES packets	7				
	2.4	Encryption and Decryption	8				
		2.4.1 Symmetric-key encryption	8				
		2.4.2 Public-key encryption	8				
		2.4.3 Combination	9				
	2.5	Ciphers	9				
		2.5.1 Block cipher	10				
		2.5.2 Stream cipher	10				
	2.6	Confusion and Diffusion	10				
		2.6.1 S-boxes	11				
		2.6.2 P-Boxes	11				
	2.7	Secrecy	11				
3	Con	nmon Scrambling Algorithm	13				
	3.1	Why do we need a new standard?	13				
	3.2	Layout of the CSA	14				
	3.3	Security	14				

viii Contents

		3.3.1	Brute force	15			
4	4.1 4.2 4.3	4.1.1 CSA3 4.2.1	CSA3 Software friendly Hardware friendly sion	17 17 18 18 18			
5	Adv : 5.1	Method 5.1.1 5.1.2 5.1.3 5.1.4 5.1.5	Encryption Standard d InitialRound SubBytes ShiftRows MixColumns AddRoundKey pansion Key-schedule core Rijndael's S-Box Rcon	21 21 22 22 22 23 23 23 23 23 23			
6	Resu 6.1 6.2 6.3 6.4 6.5	Proble Hardw Flow . Special Impler 6.5.1 6.5.2 6.5.3	rare	25 25 25 26 26 26 26 26 26 27			
A	Matı	rixes		31			
В	Illus	tration	s	35			
C	Test	vectors		39			
D		nples CBC-n		45 45			
Lis	List of Figures 47						
Bi	bliog	raphv		49			

1

Digital Video Broadcasting

There are many parts that are needed to provide DVB with a secure way of transmitting streams without facing the risk of content getting stolen. The following parts will be treated in this thesis:

- CAS explained in section 1.2
- Common Interface explained in section 1.4
- Scrambler explained in chapter 2
- Descrambler the inverse of a scrambler.

1.1 Set-up

Transport Streams (TS) which contains data received from distributors are scrambled using a key which is called a *control word* (CW). Although the CW is required to be changed every 120th second, it is common to change it as often as every 10th seconds. Finding out just one CW has very little effect, since it will only be usable for a few seconds before it is changed. The high frequency in which the CW is changed thereby provides the system with security. The control word is generated randomly to make sure that consecutive control words are not related to each other.

The control word is sent to a *Conditional Access System* (CAS) where it is encrypted as an *Entitlement Control Message* (ECM). The CAS also generates an *Entitlement Management Message* (EMM) which tells the smart-card what content the user is allowed access to. The ECM and EMM are then sent back to the scrambler where it is attached to the scrambled TS using a multiplexer. This pack-

age is sent to a receiver, where the ECM, EMM and TS are separated. The ECM and TS are sent through the Common Interface (CI) to the Conditional Access *Module* (CAM), where the ECM is decrypted using the smart card. The resulting CW is then used to descramble the TS. The TS is encrypted once more if the CI is a CIPlus, otherwise it is sent in the clear back to the receiver where the data is processed before it is dispatched to the user. The CI and CIPlus as well as the extra encryption are all discussed in section 1.4.

1.2 Conditional Access System

Conditional Access (CA) is used to make sure that a user fulfills an amount of criteria before being able to view content. A CA system (CAS) consists among other of an EMM-generator (EMMG) and an ECM-generator (ECMG). The ECM is generated using the CW, while the EMM is generated based on information related to the user. That information varies, but might relate to what channels the user is subscribing to as well as when the subscription ends. A TV will not You need to find broadcast any channels without receiving an EMM telling it to do so.

> A simple example is that a user needs to pay for TV-services to be able to access content. The content provider generates an EMM which tells the smart-card whether the user is allowed to access the requested material or not. The content provider also generates an ECM based on the CW, which the smart-card decrypts and passes to the descrambler if the EMM allows it.

Remove?: 1.2.1 Or keep?

Source:

iust Patrik

Standards

Some of the CA systems currently in use are Viaccess, Conax, Irdeto, NDS, Strong and NagraVision. There are different *Conditional Access Modules* (CAM) that are used, and which one is needed depends on the content provider. NDS is used by Viasat, Conax is used by Com Hem, Viaccess is used by Boxer and Strong is used by Canal Digital for instance.

Viaccess

Viaccess is one of the most common CA systems. In Sweden it is used by Boxer and SVT. Viaccess supports CI+.

Conax

Conax is the CA-module used by Com Hem. Conax has got its headquarter in Norway and is a part of the Telenor Group, which deals with mobile telecommunications [Conax, 2014]. Conax supports CI+.

Strong



Strong is the CA-module used by Canal Digital. This is currently the third most Plus used content provider in Sweden.. According to Wikipedia.. Strong supports CI+.

1.3 DVB-SimulCrypt

DVB-SimulCrypt is widespread in Europe, and works as an interface between the head-end and the CA system [ETSI TS, 2008]. SimulCrypt encourages the use of several CAS at once [ETSI TS, 2008, p. 17].

This is done by sending the same CW to many CA systems at the same time, and then allowing them to generate an ECM and EMM based on the CW. The multiplexer in the head-end then creates TS packets based on those, since the EMMs will determine whether the user is allowed access or not.

1.4 Common Interface

The Common Interface is the interface between the CAM and the host (Digital TV receiver-decoder). There are currently two versions of common interfaces in use, which are the CI and the CI+. The difference between them is that the output from the CI is unencrypted, while the output from the CI+ is encrypted [LLP, 2011]. This means that a clear TS is sent between the CI and the host, that can be copied. The data sent between the CI+ and host can not be copied due to it being encrypted, and therefore provides more security for content providers [European Standard, 1997].

1.4.1 **CIPlus**

The CIPlus realizes the possibility of yet another means of protecting content which is called *Content Control*. CC is a means of encrypting the content inside of the CAM connected to the CIPlus Module. The key used for the CC encryption is paired with the Digital TV Receiver, where the TS is decrypted before being made available to users. The general idea can be viewed in Figure 1.1.

1.5 Conditional Access Module

CA modules (CAMs) are responsible of decoding the scrambled TS received from the host. The CAM is often input to a PCMCIA slot (Personal Computer Memory International Association) either in the TV or the STB. The CAM consists of a slot for a smart-card and a descrambler. The smart card decodes the ECM and sends the CW to the descrambler. The TS is then descrambled and the clear TS is sent back to the host from the CAM.




Figure 1.1: CIPlus interface. Image remade from [LLP, 2011, p. 10]

2

Scrambling

Security is not only about cryptography. But there is a main reason why cryptography is attacked, and that is because there is a very low chance of being detected. There will be no traces of the attack, since the attacker's access will look just like an ordinary access.

This can be compared to a real-life break-in. The break-in will be noticed if the thief breaks in using a crowbar. On the other hand, you might never notice that the security had been breached, if the thief were to pick the lock instead. [Schneier and Fergusson, 2003]

One of the more noteworthy cryptography rule is that you always are to assume that someone is out to get you. Because of this, Schneier and Fergusson [2003, pp. 12–14] says that we always need to look for possible ways to break systems, to ensure that the security can not be breached, and thereby provides security.

2.1 Why do we need cryptography?

Cryptography is the science of rendering plaintexts into ciphertexts to protect contents from unauthorized viewing. It is used in electronic communication for protection of e-mail messages and credit card information among other things. If we send data without encrypting it, someone who is eavesdropping to the transmission channel will most likely access the data.

For most people this is not a problem, but in some instances sending secure messages can be extremely important. One example is communication during war, where a single piece of intelligence might turn the tide of the entire war. You might also not want people to be able to read your account information and card

6 Scrambling



Figure 2.1: General layout of a data packet

Source: Typ Schneier har jag för mig? Låna om

numbers when buying things online either.

Another reason for scrambling is to reduce the number of adjacent data-bits with the same value, like strings of zeroes or ones. It could also serve to balance the number of zeroes and ones in strings. This is done as to try to obtain DC balance. DC balance is desired since it avoids voltage imbalance during communication between connected systems.

Rewrite: And find a good source for this

Scrambling or Encrypting

The difference between scrambling and encryption is that scrambling is the way we generate the secret control word (key) which is used when we make the data unreadable to outsiders while encryption is the way we protect the control word Det här måste jag bli during transmission.

Todo: säkrare på

2.3 Data packets

The data processed by the DVB systems is sent in data packets. All of them are created from ES packets (Elementary Streams) which generally is the output from an audio or video encoder. The ES packets are then packeted into PS, TS or PES packets and then distributed. Among the three ways of packing data, only two are commonly used. PS packets are used for storing data, while TS and PES are used for transmitting data. The interresting types, when working with DVB, are therefore the TS packets as well as the PES packets.

TS packets 2.3.1

TS packets are the ones used by the DVB society, possibly due to their fixed lenghts. TS packets have got a length of 188 bytes with a 4 byte long header, meaning the payload consists of 184 bytes. The layout of a TS packet can be viewed in figure 2.1[ETSI TS, 2013].

The TS packet consists of 4 different kinds of building blocks where only the header is guaranteed to be present. Those blocks are:

- Header
- Adaptation field
- Encrypted payload

2.3 Data packets 7

· Clear payload

The byte-sizes of the building blocks are:

- header size = 4
- adaptation_field_size = the size of the adaptation field
- payload_size = 188 (header_size + adaptation_field_size)
- encrypted_payload_size = payload_size [payload_size mod block_size]
- clear_payload_size = [payload_size mod block_size] (or simply payload_size
 encrypted_payload_size)

Header

The header consists of information regarding the packet, and has a sync_byte (with a hex-value of 0x47, or bit-value of 01000111) to display the beginning of the packet. The header also contains information as to whether there is an adaptation field and payload in the packet, what PID the packet has, if it is to be prioritized, whether the data is scrambled - and in that case if it was scrambled with an odd or even key, among others [ETSI TS, 2009, pp. 25–26]. The header is never to be encrypted and is always found at the beginning of a packet. [ETSI TS, 2013, pp. 10–11]

Adaptation field

The adaptation field is a sort of padding that you input when the end of the data does not align with the end of the TS packet. This is done to make sure that the TS packet is filled with known data. We only find adaptation fields we are working with the last string of data, if the data does not align. Adaptation fields are not encrypted. [ETSI TS, 2013, pp. 10–11]

Encrypted and clear payload

When working with block ciphers, we tend to end up with clear bytes of data since block ciphers only encrypt data blocks of fixed sizes. The clear data is always located at the end of the TS packets and might be of sizes up to one byte smaller than the block size at the most. The encrypted payload is always located in front of the clear payload. [ETSI TS, 2013, pp. 10–11]

2.3.2 PES packets

The PES packets have varying lengths of up to 64 KBytes, and are often packed into TS packets when distributed, due to the strength of TS packets. The payload data in the TS packets, when carrying PES packets, consist of the entire PES packets, which is the header as well as the data. PES packets do not use adaptation fields, since they are of adaptable lengths, as long as the length of the packet does not exceed 64 KBytes.

Since DVB seldom uses itself of PES packets, an analyzation of the header will not be done. The derivation of PES packets from TS packets can be seen in Figure

8 2 Scrambling




Figure 2.2: PES packet derived from TS packets

2.2 [ETSI, 1996, p. 9].

2.4 Encryption and Decryption

There are two things that you need when you encrypt and decrypt messages. Those are the algorithm as well as the key. There are plenty of ways to encrypt messages, but there are two ways of sharing the encryption-key. The first method being the symmetric-key encryption, and the second method being the public-key encryption.

2.4.1 Symmetric-key encryption

The symmetric-key encryption uses the same key to encode and decode messages. Distrubution of the key, when using the symmetric-key encryption is trouble-some and the fact that both parties need access to the same secret key is a major drawback of the symmetric key encryption, as compared to the public-key encryption method. Sending the key in an email is a bad idea, since the persons who wants to read our messages most likely already will be listening, and they will therefore obtain the key as well as the means to decode the messages we send.

2.4.2 Public-key encryption

The public-key encryption uses a public key that anyone can look up, and a secret key that only one person knows [Simmons, 1992, pp. 25–32]. For instance say that the two persons, Bob and Alice, want to communicate. Bob produces a keypair P_{Bob} (Bob's public key) and S_{Bob} (Bob's secret key) and publishes P_{Bob} for anyone to see. When Alice wants to send Bob a message, she looks up Bob's public key P_{Bob} , which she then uses to encode her message. When she sends Bob the message, Bob decodes the message using his secret key S_{Bob} [Schneier and Fergusson, 2003].

2.5 Ciphers **9**



Figure 2.3: Different kinds of ciphers [Wikipedia, 2014b]

2.4.3 Combination

The big question now is why we would use anything other than the public-key encryption, since it seems secure and easy to manage. The reason is that the public-key encryption is not as effective as the symmetric-key encryption. It is common to use a combination of those two since an easy and effective way to encrypt messages is what we desire. To do this we use a symmetric-key algorithm to encode the plaintext into ciphertext, and then we use the public-key encryption to encode the symmetric-key we used when encoding the plaintext. This encoded key is then sent together with the ciphertext to the recipient, who uses the secret key to decode the symmetric key, which is then used to decipher ciphertext and obtain the plaintext.

Decryption is often performed by reversing the encryption. You need to know the algorithm, preferably through a mathematical representation, to calculate how to obtain the plaintext from the ciphertext. A description of how this is done for the CBC-mode (described in 2.5.1) is described in D.1 in appendix D. We assume that we know the decryption algorithm here for simplicity.

Source: feels like a give but still

2.5 Ciphers

A cipher is the same as an algorithm, that operates on either plaintexts or ciphertexts to perform encryption or decryption. Figure 2.3 describes how the different kinds of ciphers can be split into sub-groups.

There are mainly two kinds of ciphers that are used when designing modern cryp-

Decision
Relevance?

10 2 Scrambling

Source:
At least the CSA uses it. But you need a source if you want this to be here

tosystems. Those ciphers are called block ciphers and stream ciphers. Many systems use a combination of block ciphers and stream ciphers to provide security.

2.5.1 Block cipher

A block cipher operates on blocks where each block consists of a fixed number of bytes. This might cause a need for padding the blocks, in case the plaintext contains a number of bytes that is not even with the blocksize. Block cipher often use itself of a combination of S-boxes and P-boxes in a so-called SP-network (Figure 2.4).

There are many modes of block ciphers, but the two recommended by Schneier and Fergusson [2003] are the CBC-mode and the CTR-mode.

CBC stands for *cipher block chaining* and is performed by first encrypting the result of an XOR between an IV and the plaintext. This is the ciphertext that corresponds to the first plaintext. This is then put into an XOR with the next plaintext, and then encrypted [Stinson, 2006, pp. 109–111]. For reference, see image B.3 in appendix B.

CTR stands for *counter*, and refers to the way the IV is generated. The counter outputs a value, which is encoded with the key. The output is then run in an XOR together with the plaintext, producing the ciphertext. The counter is then incremented and the procedure is iterated [Stinson, 2006, p. 111].

2.5.2 Stream cipher

Stream ciphers work on a stream of data (as implied by the name). They usually consist of some kind of a keystream generator which performs a modulo 2 addition with the data [Simmons, 1992, pp. 67]. An effective implementation of the stream cipher is to use a linear feedback shift-register which uses the current internal state (key) to produce the next state by a simple XOR-addition between two or more of the bits in the state. This is mainly used because of how easy it is to construct in hardware [Vaudenay et al., 2008].

2.6 Confusion and Diffusion

Two properties that are needed to ensure that a cipher provides security are confusion and diffusion [Shannon, 1949]. Note that a cipher is not secure just because these two properties are obtained.

Confusion refers to making the relationship between ciphertext and key as complex as possible. Diffusion refers to replacing and shuffling the data, to make it impossible to analyze data statistically. This is usually done by performing substitutions and permutations in a simple pattern multiple times. This can easily be done by using an SP-network (S-box / P-box network) [Stinson, 2006, pp. 74–79]. The very first, as well as last step, of SP-Networks is usually an XOR between the subkey and the data. This is called whitening, and is according to Stinson

2.7 Secrecy 11



Figure 2.4: SP-Network

[2006, p. 75] regarded as a very effective way to prevent encryption/decryption without a known key. The goal of this is to make it hard to find the key, even though one has access to multiple plaintext/ciphertext pairs produced with the same key [Shannon, 1949].

2.6.1 S-boxes

The S-box is one of the basic components that is used when creating ciphers. An S-box takes a number of input bits and creates a number of output bits in a non-linear fashion [Stinson, 2006, pp. 74–75]. They can effectively be implemented as lookup tables. Each input has to correspond to a unique output, to make sure that the input can be recreated in the descrambler.



2.6.2 P-Boxes

The second basic component used in cryptography is the P-box. A P-box shuffles/rearranges the order of given bits. This can be viewed in the SP-network in figure 2.4, where the P-box is represented by the dotted rectangle in the middle.

2.7 Secrecy

Although encryption is important, as well as the strength of the encryption, keeping the algorithm secret is never a good idea. A simple mistake when designing an algorithm might turn an encryption that would have been strong, incredibly weak. It is therefore a bad idea to use small scale algorithms (designed for the use of just a few persons for instance). If you instead use an open algorithm, faults will most likely be discovered and fixed by experienced cryptographers [Schneier and Fergusson, 2003, pp. 23]. Keeping the key, which is used to encrypt the data, secret is what is important.

Common Scrambling Algorithm

The CSA is currently the most commonly used encryption algorithm in DVB for encryption of video-streams. There are two versions of the DVB-CSA, CSA1 and CSA2, where the key-length is the only difference between them [DVB Scene, 2013, p. 23].

The CSA uses a combination of a block cipher, taking an input of a 64-bit block, and a stream cipher. Both of the ciphers use the same key, so that the entire system uses the same key [Li, 2007, pp. 271–272]. This means that the complete algorithm would break if the key would be recovered. Using the same key does on the other hand allow us to easily change the key at regular intervals.

CSA has been the official scrambling method for DVB since may 1994. CSA was to be easily implemented in hardware and hard to implement in software to make reverse-engineering difficult [DVB Scene, 2013].

3.1 Why do we need a new standard?

The DVB-CSA standard offers short-term protection (it assumes content is viewed in real time and not stored). Due to the development of how content is viewed during recent years, we now primarily need to be able to distribute content across homes. This means that the focus needs to be moved from securing delivery to securing content. [Farncombe Consulting Group, 2009]

Another thing to bear in mind is the fact that more CPU-based units, such as smart-phones, tablets and computers are used to access contents now more than ever. In order to allow for descrambling on CPU-based units, a software-friendly scrambling algorithm might be needed.



Figure 3.1: Number of bits in key used

3.2 Layout of the CSA

The CSA consists a block cipher and a stream cipher connected in sequence [Li, 2007, p. 271]. The block cipher reads 64-bit blocks of data, which is then run in Cipher Block Chaining-mode. The block cipher processes these blocks of data in 56 rounds. The output of this is sent to the stream cipher where additional encoding is performed. The first block of data sent from the block cipher to the stream cipher is used as an IV for the stream cipher, and is not encoded in this phase. [Weinmann and Wirt, 2006]

3.3 Security

One of the problems associated with CW distribution is the fact that CW sharing has become rather common [Farncombe Consulting Group, 2009]. This is possibly due to the fact that the CW is sent in the clear between the smart card and the STB, meaning that a user might grab the clear CW during transmission and redistribute it over the internet. This has become a financial problem for content distributors, since people stop paying for the content which they are watching.

One way of dealing with CW sharing is to decode the encrypted CW on the CI system, and then encrypt it once again on the CI, before sending it to the STB. The latter key is setup between the CI system and the STB through a one time sychronization. This means that users are not able to grab the clear CW and redistribute it. [Schrijen, 2011, pp. 12–13]

Another security issue that you need to think of when designing the hardware, to prevent content theft, is to make sure that no contacts are ever accessible from the top layer of the circuit board. This is due to the fact that people would be

3.3 Security 15

able to connect hardware to the board and download the material that way, if they were.

n forced

Source:

Except from Patri

We also need to be aware of people trying to break the algorithm through forced ways as well as CW sharing and hardware methods of stealing content.

There are a few standard ways to try when you want to break a cipher. Those are the brute force approach, known-plaintext attacks, chosen plaintext attacks and birthday attacks [Schneier and Fergusson, 2003, pp. 31-34]. You choose what method to use depending on what the ciphers look like. I will not discuss all of them, but I will talk about the most relevant ones here.

3.3.1 Brute force

The CSA uses a key consisting of 64-bits, which gives us 18.5 Quintillion possible keys (Quintillion is 10^{18}). But byte 3 and 7 are often used as parity bytes in CA systems which leads to only 48 bits being used in the key [Tews et al., 2012]. This can be seen in figure 3.1. 48 bits on other hand leads to 2^{48} combinations, which corresponds to 281 trillion possible keys (Trillion is 10^{12}). Testing a million keys per second is about what is possible through on a modern x86 processor using software methods , which means it would take roughly 3258 days to force brake the keys. That is roughly 8.8 years.

Todo:
How did I get the number?

Moreover, systems need to change the key at least every 120 seconds [Simpson et al., 2009] and most systems issues new keys every 10-120 second [Wirt, 2004].

It is possible to use dedicated hardware and FPGA implementations to speed this up, using hardware accelerations and other methods. But even if we would be able to scan through 2.8 trillion keys per second, precisely allowing us to be certain to find the key in two minutes, we could just change the key more often. As such, the brute force method of obtaining the key is not a feasible option.

CISSA and CSA3

There are currently two scrambling algorithms being assessed as replacements to the currently used DVB-CSA. This is done to assure content security for yet another ten years.

CISSA is meant to be a hardware-friendly as well as software-friendly algorithm designed to allow descrambling to be made on CPU-based units such as computers, smart phones and tablets [ETSI TS, 2013, p. 9].

CSA3 is a hardware-friendly, software-unfriendly scrambling algorithm chosen by the ETSI to replace the currently used CSA [ETSI TS, 2013, pp. 6–7]. Software-unfriendly means that descrambling is designed so that it is highly impractical to perform in software, but easily done in hardware.

Both of the algorithms are to be implemented in hardware for scrambling of data. The difference is that CSA3 is to make it hard to descramble the material using software. Since both of the algorithms are confidential, it is sadly impossible to find out what makes the CSA3 algorithm software-unfriendly, while the CISSA algorithm is software-friendly.

Source: Om jag får be snä

4.1 CISSA

CISSA stands for *Common IPTV Software-oriented Scrambling Algorithm* and is designed to be software-friendly. Opposite to the CSA3, CISSA is made to be easily descrambled in software, so that CPU-based systems such as computers and smart-phones can also implement it. Although it is software-friendly, it is supposed to able to be implemented efficiently on hardware as well as in software [ETSI TS, 2013, p. 9].

18 4 CISSA and CSA3

CISSA is to use the AES-128 block cipher in CBC-mode with a 16 byte IV with the value 0x445642544d4350544145534349535341. Each TS packet is to be process independetly of other TS packets, but each block of data in the payload depends on the previous blocks of data in the same payload. Both the header and adaptation field are to be left unscrambled. [ETSI TS, 2013, p. 11]

4.1.1 Software friendly

An FPGA implementation of the CISSA algorithm seems likely to be implementable, due to the fact that the scrambling of the content is supposed to be made in hardware, regardless as to whether the descrambling is supposed to be made either in hardware or software.

While having a scrambling algorithm designed to enable viewing on CPU-based units opens up the market for more users, it might increase the risk for algorithm theft. Since reverse-engineering is possible for software implementations, one might find the algorithm for descrambling, as well as scrambling through inversion of the algorithm. Knowing the algorithm enables cryptoanalysists to search for weaknesses in the algorithm, with the purpose of breaking it.

Source:No no, n
Wikipedia

"A cryptosystem should be secure even if everything about the system, except the key, is public knowledge." according to Kerckhoffs's Principle. This means that the only result of having a descrambling method suited for hardware as well as software implementation should possibly only result in some free implementations showing up. But it being implemented in software should therefore not lead to any problem.

4.2 CSA3

The CSA3 scrambling algorithm is based on a combination of an AES (*Advanced Encryption Standard*) block cipher using a 128-bit key, which is simply called the AES-128, and a confidential block cipher called the XRC [ETSI TS, 2013, p. 8]. XRC stands for eXtended emulation Resistant Cipher and is a confidential cipher used in DVB [ETSI TS, 2013, p. 8].

4.2.1 Hardware friendly

The CSA3 is designed to be hardware-friendly, meaning that descrambling through software methods is supposed to be next to impossible. Using a software-hostile descrambling algorithm means that reverse-engineering and algorithm theft becomes hard, if even possible. Even though it would decrease the probability of content theft, it closes the door to expansion onto the CPU-based units market, which is becoming larger and larger.

4.3 Conclusion 19

4.3 Conclusion

From what I've seen, both CISSA and CSA3 implement the AES-128 for scrambling, combined with a secret cipher. The secret cipher for CSA3 is the XRC cipher, and the secret CISSA cipher is yet to be known. It is not even sure that CISSA is to use a secret Cipher, but might instead use itself of merely the CBC-mode of operation for the AES128 cipher, or something.

CISSA sounds like a great idea in my opinion, allowing CPU-based units to descramble data streams without a dedicated HW-Chip. While that is good and all, CSA3 is a finished standard, and will probably be more easily implemented on an FPGA, while CISSA does not yet seem to be ready for the market. Starting out with an AES-128 chiper would provide for a basis to continue development of the scrambling, either towards the CISSA or the CSA3 solution, on a later stage.

Advanced Encryption Standard

The AES is based on an SP-network and is fast both in hardware as well as software. Rijndael, which is used in AES, has key-sizes of at least 128 bits, block lengths of 128 bits, 8 to 8 bit S-boxes and a minimum of 10 rounds of repetition [Stinson, 2006, p. 79]. It is a symmetric-key algorithm with a fixed block size of 128 bits, where the key-size can vary between 128, 192 or 256 bits. The number of cycles needed to convert the plaintext into ciphertext depends on the size of the key. The 128-bit key requires 10 cycles of repetitions (rounds). The 192-bit key requires 12 rounds and the 256-bit key requires 14 rounds [Stinson, 2006, p. 103].

5.1 Method

The AES consists of a number of steps that are repeated for each block to be encoded. The steps to be performed are, according to Stinson [2006]:

Set-up steps

- 1. KeyExpansion Produce round keys.
- 2. InitialRound Combine each byte of the state with a byte of round key.

Steps performed in rounds

- 1. SubBytes Each byte is substituted using the Rijndael's S-box.
- 2. ShiftRows The rows of the state matrix are *permutated*.
- 3. MixColums The columns of the matrix are multiplicated with a matrix.
- 4. AddRoundKey The state matrix is once again combined with round-keys.

In the final round we do everything except the MixColumns step

- 1. SubBytes
- 2. ShiftRows
- AddRoundKey

The ciphertext is then defined as the state-matrix [Stinson, 2006, p. 103]. As mentioned in section 2.6 (Confusion and Diffusion), both confusion and diffusion are nescessary. They can be seen in the SubBytes and ShiftRows steps above. These steps also performs whitening, which strengthens the cipher. Whitening is, as mentioned in 2.6, performed through an XOR between the subkey and the data.

The KeySchedule is explained in section 5.2.

5.1.1 InitialRound

This is simply an initial AddRoundKey.

5.1.2 SubBytes

In the SubBytes step, each byte is sent to a Rijndael S-box (which is basically a lookup table) where they are substituted in a non-linear fashion. This gives us a substituted state matrix.

5.1.3 ShiftRows

The next step is called the ShiftRows step, which left-shift the rows n-1 steps where n is the index of the row. This means that the first row is left as it is, the second row is shifted one step, the third row is shifted two steps, and the fourth row is shifted three steps.

5.1.4 MixColumns

In the MixColumns step, the four bytes of each row are combined through a matrix multiplication. The MixColumns function takes four bytes as input and multiplies them with a fixed matrix (figure A.3 in appendix A). While this might seem simple, it really is not. The multiplication makes sure that each input byte affect all output bytes. [Internet, 2014]

The matrix is multiplicated from the left to the vector (4x4 * 4x1 = 4x1) which is a column from the state-matrix. Multiplication with 1 means that the value is left untouched. Multiplication by 2 means left shift, then XOR with 0x1B is the value is larger than 0xFF. Multiplication with 3 means left-shift (including XOR with 0x1B if the value exceeds 0xFF), then XOR with the initial value. Addition had a reference to is replaced with XOR, due to the calculations taking place in $GF(2^8)$.

5.1.5 AddRoundKey

Each of the 16 bytes of the state is combined with a byte of the round key using bitwise xor. They are then combined to a state matrix (figure A.2 in appendix A) containing 4x4 bytes.

5.2 KeyExpansion

To generate round keys from the cipher key, we use the Rijndael's key schedule. This is done since AES requires a separate 128-bit round key for each round, plus one extra key for the initialization which means that the AES-128 requires 176 bytes, since AES-128 consists of 10 rounds.

The schedule consists of a loop, and a key-schedule core. The schedule core is the part that branches out from the check if c modulo 16 is zero. The entire KeyExpansion can be viewed in Figure B.2 in appendix B. To change the key schedule to fit a key size of 192 bits, you simply change the value c is compared to in the first branch in the flowchart from 176 to 206.

5.2.1 Key-schedule core

The key-schedule core takes an input of 4 bytes (32 bits) which it then rotates 1 byte (8 bits) to the left. Let us say that our key is *AB CD EF 01*. This would give us the key *CD EF 01 AB* after the rotation. This operation is also called the RotWord-operation [Stinson, 2006, p. 107]. The next step is to apply Rijndael's S-box to each of these bytes, giving us 4 new bytes. The bytes AB CD EF 01 would give us 62 BD DF 7C when input in the Rijndael S-box (Figure A.1).

The left-most byte is then XORed with a value from the Rcon function depending on what round you are currently at. You can read more about the Rcon function in section 5.2.3.

5.2.2 Rijndael's S-Box

Rijndael's S-box takes an input byte which it transforms according to a matrix (figure A.1 in appendix A). Where the most significant nibble is placed on the Y axis, and the least significant nibble is set on the X axis. Let us say we have an input of 0x31, then 0xC7 would be output from the Rijndael's S-box.

5.2.3 Rcon

The value input into the Rcon function depends on what round you are currently at. Which means that you would choose Rcon(1) for the first round, Rcon(2) for the second round, and so on. The values in the Rcon array are calculated mathematically, but might as well be accessed through a simple vector or such (A.4 in appendix A).

I illustrated the steps to be performed in the Rcon function using a flowchart which can be viewed in figure B.1 in appendix B.

ODO: liable sources than

If the input value is 0 or 1, we just return that value, otherwise the following steps are performed [Wikipedia, 2014c]. This can also be replaced by an S-box where you input your byte, and get another back, since the input byte is just used . You need more re- as a counter that decides how many times you perform steps 2 through 6

- 1. Set a variable c to 0x01.
- 2. If the input-value does not equal 1, set variable b to c & 0x80. Otherwise, go to 7.
- 3. Left shift c one step.
- 4. If b is equal to 0x80 proceed to 5, otherwise go to 6.
- 5. Store the result of a bitwise XOR between c and 0x1B in c.
- 6. The input value is decreased by one, and we go back to 2.
- 7. We set the output to c.

6

Result

Här är väl tanken att jag ska skriva lite om hur jag implementerat och bearbetat allt relevant som har med implementationen att göra. Vad jag gjort som blivit bättre än andra lösningar. Vad jag fokuserat på (throughput kontra mängd använd hårdvara).

6.1 Problems

Encountered problems:

- Not possible to get the license for CSA3
- Small interrest for CSA3
- · Next to no documentation of the CISSA algorithm

6.2 Hardware

Såhär ser hårdvaran ut i en sjukt snygg bild jag ritat:

Inputs				Outputs
1				1
2				2
3		HW		3
4				4
5				5

26 6 Result

6.3 Flow

Berätta om flödet på implementationen.

6.4 Special solutions

Berätta om hur det fungerar.

6.5 Implementation

My design is very hierarchical. The top layer is an aes128 block in CBC-mode, which takes an input of one TS-stream, and from there takes the packets to be scrambled, depending on whether or not there is an adaptation field and such.

6.5.1 Cipher blocks

The aes-128 cipher entity consists of 4 components. The data2state entity, which transforms the array into a matrix of data. A keyexpansion entity, which takes an input of a key, and generates an extended key as an output. An entity, which I chose to call rounds, which deals with the encryption of the 16 byte blocks. And finally a state2data entity, which transforms the data-matrix into an array once again. The cipher entity itself keeps track of timing mainly between the keyexpansion and the round entity, and makes sure to provide the round entity with the correct roundkey at the right time.

6.5.2 Keyexpansion blocks

The keyexpansion entity is divided into 3 keyblock entities. The first keyblock entity decides what 4 bytes of the expanded key we want to expand. The second keyblock entity is the keycore, which is only performed on every 4th set of 4 bytes. The third keyblock entity performs an xor and an incrementation of the internal counter used as an index when accessing 4 byte blocks of data.

Keycore entitites

The keycore entity consists of four entities. Rotword, Sbox, Rcon and a counter. The counter is used to get the right data-byte from the Rcon, and the index is only used in the keycore, and is thus best suited to be placed inside the keycore entity. Rotword rotates the bytes of the input one step to the left. Sbox replaces the input bytes according to the Rijndael Sbox. The Rcon entity both collects the correct rcon value from a precalculated vector, as well as inputs it into an xor together with the input.

6.5.3 Round entities

The round block consists of four entities. Subbytes, shiftrows, mixcolumns and addroundkey. Addroundkey is a somewhat special XOR. Subbytes is an Rijndael

6.6 Tests 27

Na	ime	Value	 55,500 ns	56,000 ns	56,500 ns	57,000 ns	57,500 ns	58,000 ns	
		1							
	₩ reset	0							
٠	datapacket[127:0]	3243f6a8885a308d			3243f6a8885a3	08d313198a2e0370734			
٠	in_key[15:0]	[2b,7e,15,16,28,			[2b,7e,15,16,28,ae,d	2,a6,ab,f7,15,88,09,cf,4f	[3c]		
٠	■ output[127:0]	3925841d02dc09fb	36363636363636363636	363636363636		3925841d0	2dc09fbdc118597196a0b3	2	
	Un finished	1							

Figure 6.1: Test vector 1

Sbox, which takes an input 16-byte state, substitutes it, and outputs another 16-byte state. Shiftrows transposes the rows of the second, third and fourth row of the state. Last, but not least, is the mixcolumns entity. It consists of 16 mulblock entities. The input state of mixcolumns is split into columns, and each column is sent to a mulblock entity, which multiplies the inputs according to an amount of rules. The function of the mixcolumns block is a rather complex matrix multiplication.

Addroundkey entity

Addroundkey is an entity which takes different inputs depending on what round we are currently dealing with. On the first round, addroundkey takes the input to the round entity. On the last round, it takes the output from the subbytes entity. The input to addroundkey is the output from mixcolumns the rest of the time.

The mulblock entity

The mulblock entity consists of one mul3 entity and one mul2 entity, which performs a special kind of hardware multiplication of 3, and 2, on the input. It also takes two inputs which it leaves alone. The four results are then XOR:ed with eachother, and returned to the mixcolumns entity which puts the result in the correct index in the matrix.

6.6 Tests

Even though I only display a few simulations in this part, I simulated all of the subblocks one by one, to make sure that they had the correct functionality. The reason as to why not more simulations than this are included is both since I do not think anyone will find it interresting enough to look through, and since I do not want to double the volume of the thesis through simulation-results.

Figure 6.1 through 6.3 are tests performed on the complete aes-128 block, before CBC-mode. In the figures, in_key is the input key to be extended and used, and datapacket is one packet from a TS. Test vector 1 and 2 are taken from [NIST, 2001], while test vector 3 is generated using a webpage.

Test vector 1 (Figure 6.1)

Input key: 2b 7e 15 16 28 ae d2 a6 ab f7 15 88 09 cf 4f 3c Plaintext: 32 43 f6 a8 88 5a 30 8d 31 31 98 a2 e0 37 07 34 Ciphertext: 39 25 84 1d 02 dc 09 fb dc 11 85 97 19 6a 0b 32

omformu Är det här för ca sual? Du måste no omformulera varfö du inte lagt til fle simuleringsresultat 28 6 Result




Figure 6.2: Test vector 2




Figure 6.3: Test vector 3

Test vector 2 (Figure 6.2)

Input key: 00 01 02 03 04 05 06 07 08 09 0a 0b 0c 0d 0e 0f Plaintext: 00 11 22 33 44 55 66 77 88 99 aa bb cc dd ee ff Ciphertext: 69 c4 e0 d8 6a 7b 04 30 d8 cd b7 80 70 b4 c5 5a

Test vector 3 (Figure 6.3)

Input key: 10 20 30 40 50 60 70 80 90 a0 b0 c0 d0 e0 f0 bb Plaintext: 00 11 22 33 44 55 66 77 88 99 aa bb cc dd ee ff Ciphertext: bf 99 1f aa 8b 0f e6 48 36 46 a0 2d 33 9e de a5



A

Matrixes

32 A Matrixes

Nibble	00	01	02	03	04	05	06	07	08	09	0A	0B	0 <i>C</i>	0D	0E	0F
00	63	7 <i>C</i>	77	7 <i>B</i>	F2	6 <i>B</i>	6F	C5	30	01	67	2 <i>B</i>	FE	D7	AB	76
10	CA	82	<i>C</i> 9	7D	FA	59	47	F0	AD	D4	A2	AF	9 <i>C</i>	A4	72	C0
20	<i>B</i> 7	FD	93	26	36	3 <i>F</i>	F7	CC	34	A5	E5	F1	71	D8	31	15
30	04	<i>C</i> 7	23	<i>C</i> 3	18	96	05	9 <i>A</i>	07	12	80	E2	EB	27	<i>B</i> 2	75
40	09	83	2 <i>C</i>	1 <i>A</i>	1 <i>B</i>	6 <i>E</i>	5 <i>A</i>	A0	52	3B	D6	В3	29	E3	2 <i>F</i>	84
50	53	D1	00	ED	20	FC	B1	5 <i>B</i>	6 <i>A</i>	CB	BE	39	4A	4C	58	CF
60	D0	EF	AA	FB	43	4D	33	85	45	F9	02	7 <i>F</i>	50	3 <i>C</i>	9 <i>F</i>	A8
70	51	A3	40	8F	92	9D	38	F5	BC	<i>B</i> 6	DA	21	10	FF	F3	D2
80	CD	0 <i>C</i>	13	EC	5 <i>F</i>	97	44	17	C4	A7	7 <i>E</i>	3D	64	5D	19	73
90	60	81	4F	DC	22	2A	90	88	46	EE	B8	14	DE	5 <i>E</i>	0B	DB
A0	E0	32	3A	0A	49	06	24	5 <i>C</i>	C2	D3	AC	62	91	95	E4	79
B0	E7	C8	37	6 <i>D</i>	8D	D5	4E	<i>A</i> 9	6 <i>C</i>	56	F4	EA	65	7A	AE	08
C0	BA	78	25	2E	1 <i>C</i>	A6	B4	C6	E8	DD	74	1 <i>F</i>	4B	BD	8B	8A
D0	70	3 <i>E</i>	<i>B</i> 5	66	48	03	F6	0E	61	35	57	В9	86	C1	1D	9E
E0	E1	F8	98	11	69	D9	8E	94	9 <i>B</i>	1E	87	E9	CE	55	28	DF
F0	8 <i>C</i>	A1	89	0D	BF	E6	42	68	41	99	2D	0F	B0	54	BB	16
	•														(A.1)

Figure A.1: Rijndael S-box

$$\begin{bmatrix} a_{1,1} & a_{1,2} & a_{1,3} & a_{1,4} \\ a_{2,1} & a_{2,2} & a_{2,3} & a_{2,4} \\ a_{3,1} & a_{3,2} & a_{3,3} & a_{3,4} \\ a_{4,1} & a_{4,2} & a_{4,3} & a_{4,4} \end{bmatrix}$$
(A.2)

Figure A.2: State-Matrix

$$\begin{bmatrix} 2 & 3 & 1 & 1 \\ 1 & 2 & 3 & 1 \\ 1 & 1 & 2 & 3 \\ 3 & 1 & 1 & 2 \end{bmatrix} \begin{bmatrix} a_{1,i} \\ a_{2,i} \\ a_{3,i} \\ a_{4,i} \end{bmatrix}, i = \{1, 2, 3, 4\}$$
 (A.3)

Figure A.3: Rijndael MixColumns equation

```
Rcon[256] = \{8D\ 01
                      02
                          04
                              08
                                  10
                                       20
                                           40
                                               80
                                                    1B
                                                        36
                                                            6C
                                                                D8
                                                                     AB 4D
                                                                             9A
             2F
                 5E
                      BC
                          63
                               C6
                                  97
                                       35
                                           6A
                                               D4
                                                    В3
                                                        7D
                                                            FA
                                                                EF
                                                                     C5
                                                                         91
                                                                             39
             72
                     D3
                                   C2
                                                    94
                                                        33
                                                                 CC
                 E4
                          BD
                              61
                                       9F
                                           25
                                               4A
                                                            66
                                                                     83
                                                                         1D
                                                                             3A
             74
                 E8
                      CB
                                       04
                                                    20
                                                            80
                                                                 1B
                                                                     36
                          8D
                              01
                                  02
                                           08
                                               10
                                                        40
                                                                         6C
                                                                             D8
             AB
                 4D 9A
                          2F
                               5E
                                   BC
                                       63
                                           C6
                                               97
                                                    35
                                                            D4
                                                                В3
                                                                     7D FA
                                                                             EF
                                                        6A
             C5
                 91
                      39
                          72
                              E4
                                  D3
                                       BD
                                               C2
                                                    9F
                                                        25
                                                            4A
                                                                94
                                                                     33
                                                                             CC
                                           61
                                                                         66
             83
                  1D
                     3A
                          74
                              E8
                                   CB
                                       8D
                                           01
                                               02
                                                    04
                                                        08
                                                            10
                                                                 20
                                                                     40
                                                                         80
                                                                             1B
                 6C
                     D8
                              4D
                                  9A
                                       2F
             36
                          AB
                                           5E
                                               BC
                                                    63
                                                        C6
                                                            97
                                                                35
                                                                     6A
                                                                         D4
                                                                             В3
                 FA EF
                                   39
                                       72
                                                            C2
             7D
                          C5
                              91
                                           E4
                                               D3
                                                    BD
                                                        61
                                                                9F
                                                                     25
                                                                         4A
                                                                             94
             33
                          83
                              1D
                                  3A
                                       74
                                           E8
                                               CB
                                                    8D
                                                            02
                                                                04
                  66
                      CC
                                                        01
                                                                     08
                                                                         10
                                                                             20
             40
                 80
                      1B
                          36
                              6C
                                  D8
                                       AB
                                           4D
                                               9A
                                                    2F
                                                        5E
                                                            BC
                                                                63
                                                                     C6
                                                                         97
                                                                             35
             6A
                 D4 B3
                          7D
                              FA
                                  EF
                                       C5
                                           91
                                               39
                                                    72
                                                        E4
                                                            D3
                                                                BD
                                                                     61
                                                                         C2
                                                                             9F
             25
                  4A
                      94
                          33
                              66
                                   CC
                                       83
                                           1D
                                               3A
                                                    74
                                                        E8
                                                            CB
                                                                8D
                                                                     01
                                                                         02
                                                                             04
                                                    AB
                                                                     5E
             08
                  10
                      20
                          40
                              80
                                   1B
                                       36
                                           6C
                                               D8
                                                        4D
                                                            9A
                                                                2F
                                                                         BC
                                                                             63
                                                            39
                                                                72
             C6
                 97
                      35
                              D4 B3
                                       7D
                                           FA EF
                                                    C5
                                                        91
                                                                     E4
                                                                         D3
                          6A
                                                                             BD
                 C2
                     9F
                          25
                              4A
                                  94
                                       33
                                           66
                                               CC 83
                                                        1D 3A
                                                                74
                                                                     E8
                                                                         CB 8D
             61
```

Figure A.4: The Rcon function represented as a vector

В

Illustrations

36 B Illustrations




Figure B.1: Flowchart of the Rcon function




Figure B.2: Flowchart of the key schedule



Figure B.3: Cipher block chaining mode, [Wikipedia, 2014a]



Test vectors

Test vector taken from NIST [2001, pp. 35–36]. This vector is run on a single aes-128 cipher. AES-128 (Nk=4, Nr=10)

Plaintext: 00112233445566778899AABBCCDDEEFF Key: 000102030405060708090A0B0C0D0E0F

Cipher (Encrypt):

round[0].input 00112233445566778899AABBCCDDEEFF round[0].k sch 000102030405060708090A0B0C0D0E0F round[1].start 00102030405060708090A0B0C0D0E0F0 round[1].s box 63CAB7040953D051CD60E0E7BA70E18C round[1].s row 6353E08C0960E104CD70B751BACAD0E7 round[1].m_col 5F72641557F5BC92F7BE3B291DB9F91A round[1].k_sch D6AA74FDD2AF72FADAA678F1D6AB76FE round[2].start 89D810E8855ACE682D1843D8CB128FE4 round[2].s_box A761CA9B97BE8B45D8AD1A611FC97369 round[2].s row A7BE1A6997AD739BD8C9CA451F618B61 round[2].m col FF87968431D86A51645151FA773AD009 round[2].k_sch B692CF0B643DBDF1BE9BC5006830B3FE round[3].start 4915598F55E5D7A0DACA94FA1F0A63F7 round[3].s box 3B59CB73FCD90EE05774222DC067FB68 round[3].s row 3BD92268FC74FB735767CBE0C0590E2D round[3].m col 4C9C1E66F771F0762C3F868E534DF256 round[3].k sch B6FF744ED2C2C9BF6C590CBF0469BF41 round[4].start FA636A2825B339C940668A3157244D17

40 Test vectors

round[4].s_box	2DFB02343F6D12DD09337EC75B36E3F0
round[4].s_row	2D6D7EF03F33E334093602DD5BFB12C7
round[4].m_col	6385B79FFC538DF997BE478E7547D691
round[4].k_sch	47F7F7BC95353E03F96C32BCFD058DFD
round[5].start	247240236966B3FA6ED2753288425B6C
round[5].s_box	36400926F9336D2D9FB59D23C42C3950
round[5].s_row	36339D50F9B539269F2C092DC4406D23
round[5].m_col	F4BCD45432E554D075F1D6C51DD03B3C
round[5].k_sch	3CAAA3E8A99F9DEB50F3AF57ADF622AA
round[6].start	C81677BC9B7AC93B25027992B0261996
round[6].s_box	E847F56514DADDE23F77B64FE7F7D490
round[6].s_row	E8DAB6901477D4653FF7F5E2E747DD4F
round[6].m_col	9816EE7400F87F556B2C049C8E5AD036
round[6].k_sch	5E390F7DF7A69296A7553DC10AA31F6B
round[7].start	C62FE109F75EEDC3CC79395D84F9CF5D
round[7].s_box	B415F8016858552E4BB6124C5F998A4C
round[7].s_row	B458124C68B68A014B99F82E5F15554C
round[7].m_col	C57E1C159A9BD286F05F4BE098C63439
round[7].k_sch	14F9701AE35FE28C440ADF4D4EA9C026
round[8].start	D1876C0F79C4300AB45594ADD66FF41F
round[8].s_box	3E175076B61C04678DFC2295F6A8BFC0
round[8].s_row	3E1C22C0B6FCBF768DA85067F6170495
round[8].m_col	BAA03DE7A1F9B56ED5512CBA5F414D23
round[8].k_sch	47438735A41C65B9E016BAF4AEBF7AD2
round[9].start	FDE3BAD205E5D0D73547964EF1FE37F1
round[9].s_box	5411F4B56BD9700E96A0902FA1BB9AA1
round[9].s_row	54D990A16BA09AB596BBF40EA111702F
round[9].m_col	E9F74EEC023020F61BF2CCF2353C21C7
round[9].k_sch	549932D1F08557681093ED9CBE2C974E
round[10].start	BD6E7C3DF2B5779E0B61216E8B10B689
round[10].s_box	7A9F102789D5F50B2BEFFD9F3DCA4EA7
round[10].s_row	7AD5FDA789EF4E272BCA100B3D9FF59F
round[10].k_sch	13111D7FE3944A17F307A78B4D2B30C5
round[10].output	69C4E0D86A7B0430D8CDB78070B4C55A

Keyexpansion based on test vector taken from NIST [2001, pp. 35–36].

		After	After		After ⊕		w[i] = temp
i(dec)	temp	RotWord	SubWord	Rcon(i)	with Rcon	w[i-16]	$\oplus w[i-16]$
4	09cf4f3c	cf4f3c09	8a84eb01	01000000	8b84eb01	2b7e1516	a0fafe17
5	a0fafe17					28aed2a6	88542cb1
6	88542cb1					abf71588	23a33939
7	23a33939					09cf4f3c	2a6c7605
8	2a6c7605	6c76052a	50386be5	02000000	52386be5	a0fafe17	f2c295f2
9	f2c295f2					88542cb1	7a96b943
10	7a96b943					23a33939	5935807a

11 5935807a 2a6c7605 7359f67f 12 7359f67f 59f67f73 cb42d28f 0400000 cf42d28f f2c295f2 3d80477d 3d80477d 4716fe3e 5935807a 1e237e44 15 1e237e44 7359f67f 6d7a883b 16 6d7a883b 7a883b6d dac4e23c 0800000 d2c4e23c 3d80477d ef44a541 4716fe3e a8525b7f e1237e44 b671253b e1237e44 b671253b b671253b dd1d1c6f8 21 dd41c6f8 22 7c839d87 b671253b caf2b8bc 23 caf2b8bc 24 11f915bc f915bc11 99596582 20000000 b9596582 dd1c6f8 6d88a37a 25 6d88a37a 26 110b3efd 27 dbf98641 27 dbf98641 27 dbf98641 27 dbf98641 28 ca0093fd 63dc5474 4000000 23dc5474 6d88a37a de3df92 de3df98641 31 84a64fb2 32 4ea6dc4f a6dc4f4e 2486842f 8000000 a486842f de3df986d2 312bf560 35 312bf560 36 312bf560 36 312bf560 36 312bf560 375006e 5c006e57 4a639f5b 3600000 7c639f5b ac7766f3 d014f988 41 d014f988 42 c9ee2589 28d12941 19facc2 c9ee2589 28d12941 c9ee2589 28								
13 3d80477d 7a96b943 4716fe3e 14 4716fe3e 5935807a 1e237e44 15 1e237e44 7359f67f 6d7a883b 16 6d7a883b 7a883b6d dac4e23c 08000000 d2c4e23c 3d80477d ef44a541 17 ef44a541 4716fe3e a8525b7f 4716fe3e a8525b7f 18 a8525b7f 1e237e44 b671253b 6d7a883b db0bad00 20 db0bad00 0bad00db 2b9563b9 1000000 3b9563b9 ef44a541 d4d1c6f8 21 d4d1c6f8 a8525b7f 7c839d87 7c839d87 2c7839d87 2c7839d87 <td>11</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	11							
14		7359f67f	59f67f73	cb42d28f	04000000	cf42d28f	f2c295f2	
15	13	3d80477d					7a96b943	4716fe3e
16 6d7a883b 7a883b6d dac4e23c 08000000 d2c4e23c 3d80477d ef44a541 17 ef44a541 4716fe3e a8525b7f 4716fe3e a8525b7f 18 a8525b7f 1e237e44 b671253b b671253b db0bad00 20 db0bad00 0bad00db 2b9563b9 10000000 3b9563b9 ef44a541 d4d1c6f8 21 d4d1c6f8 a8525b7f 7c839d87 b671253b caf2b8bc 23 caf2b8bc db0bad00 11f915bc caf2b8bc dd0bad00 11f915bc 24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd caf2b8bc dbf98641 27 dbf98641 11f915bc ca0093fd dbf98641 11f915bc ca0093fd de5f86641 29 4e54f70e 110b3efd 5f5c9f3 dbf98641 84a64fb2 ac093fd dea6dc4f 32 4ea6dc4f a6dc4f4e	14						5935807a	1e237e44
17	15	1e237e44					7359f67f	6d7a883b
18 a8525b7f le237e44 b671253b 19 b671253b 6d7a883b db0bad00 20 db0bad00 0bad00db 2b9563b9 10000000 3b9563b9 ef44a541 d4d1c6f8 21 d4d1c6f8 a8525b7f 7c839d87 5c42bbc 7c839d87 7c839d87 3c42bbc	16	6d7a883b	7a883b6d	dac4e23c	08000000	d2c4e23c	3d80477d	ef44a541
19	17	ef44a541					4716fe3e	a8525b7f
20 db0bad00 0bad00db 2b9563b9 10000000 3b9563b9 ef44a541 d4d1c6f8 21 d4d1c6f8 a8525b7f 7c839d87 22 7c839d87 b671253b caf2b8bc 23 caf2b8bc db0bad00 11f915bc 24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd caf2b8bc dbf98641 2af2b8bc dbf98641 11f915bc ca0093fd ca0093fd ca0093fd ca0093fd ca0093fd ca0093fd ca0093fd d688a37a 4e54f70e a454f70e a110b3efd 5f5fc9f3 dbf98641 84a64fb2 3a 4e54f70e a454f70e a454f70e a454f70e a42 a466c4f a24e6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 a3 a466dc4f a466dc4f a466dc4f a6dc4f a6dc4f a6dc4f a58dbad2 a5f5fc9f3 b58dbad2 a6dc4f a6dc4f	18	a8525b7f					1e237e44	b671253b
21 d4d1c6f8 a8525b7f 7c839d87 22 7c839d87 b671253b caf2b8bc 23 caf2b8bc db0bad00 11f915bc 24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd caf2b8bc dbf98641 27 dbf98641 11f915bc ca0093fd ca0093fd 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 3dbf98641 84a64fb2 31 84a64fb2 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 58dbad2 34a64fb2 312bf560 4ea6dc4f 4e36dc4f 4e34fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 36 7f8d292f 36 312bf560 36 3	19	b671253b					6d7a883b	db0bad00
22 7c839d87 b671253b caf2b8bc 23 caf2b8bc db0bad00 11f915bc 24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd 110b3efd dbf98641 11f915bc ca0093fd dbf98641 2a0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 4e54f70e 4e54f70e 110b3efd 5f5fc9f3 4e54f70e 30 3f5fc9f3 dbf98641 84a64fb2 4ea6dc4f 32 4ea6dc4f 4ea6dc4f 4ea6dc4f 32 4ea6dc4f 4ea6dc4f 4e346842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 35 312bf560 35 312bf560 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 312bf560 28d12941 312bf560 28d12941 39 28d12941	20	db0bad00	0bad00db	2b9563b9	10000000	3b9563b9	ef44a541	d4d1c6f8
23 caf2b8bc db0bad00 11f915bc 24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd caf2b8bc dbf98641 26 110b3efd 11f915bc ca0093fd dbf98641 11f915bc ca0093fd 28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 4e64fb2 31 84a64fb2 31 84a64fb2 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 35 312bf560 35 312bf560 35 312bf560 36 7f8d292f 36 7f8d292f 36463 312bf560 28d12941 312bf560 28d12941 312bf560 28d12941 312bf560 28d12941 312bf560	21	d4d1c6f8					a8525b7f	7c839d87
24 11f915bc f915bc11 99596582 20000000 b9596582 d4d1c6f8 6d88a37a 25 6d88a37a 7c839d87 110b3efd 26 110b3efd caf2b8bc dbf98641 27 dbf98641 11f915bc ca0093fd 28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 312bf560 312bf560 28d12941 7f8d292f 575c006e 40 5	22	7c839d87					b671253b	caf2b8bc
25 6d88a37a 7c839d87 110b3efd 26 110b3efd caf2b8bc dbf98641 27 dbf98641 11f915bc ca0093fd 28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5c9f3 5f5fc9f3 3dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 2486842f 80000000 a486842f 4e54f70e ead27321 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 34 b58dbad2 84a64fb2 312bf560 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36766f3 37 ac7766f3 312bf560 28d12941 312bf560 28d12941 312bf560 28d12941 312bf560 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57	23	caf2b8bc						11f915bc
26 110b3efd caf2b8bc dbf98641 27 dbf98641 11f915bc ca0093fd 28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 4ea6dc4f 7f8d292f 34 b58dbad2 4ea6dc4f 7f8d292f 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 312bf560 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8	24	11f915bc	f915bc11	99596582	20000000	b9596582	d4d1c6f8	6d88a37a
27 dbf98641 11f915bc ca0093fd 28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 312bf560 312bf560 312bf560 4ea6dc4f 7f8d292f 7f8d292f 312bf560 3	25	6d88a37a					7c839d87	110b3efd
28 ca0093fd 0093fdca 63dc5474 40000000 23dc5474 6d88a37a 4e54f70e 29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 558dbad2 312bf560 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 28d12941 e13f0cc8	26	110b3efd					caf2b8bc	dbf98641
29 4e54f70e 110b3efd 5f5fc9f3 30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 575c006e 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8 28d12941 e13f0cc8	27	dbf98641					11f915bc	ca0093fd
30 5f5fc9f3 dbf98641 84a64fb2 31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 28d12941 e13f0cc8	28	ca0093fd	0093fdca	63dc5474	40000000	23dc5474	6d88a37a	4e54f70e
31 84a64fb2 ca0093fd 4ea6dc4f 32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 28d12941 e13f0cc8	29	4e54f70e					110b3efd	5f5fc9f3
32 4ea6dc4f a6dc4f4e 2486842f 80000000 a486842f 4e54f70e ead27321 33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 28d12941 e13f0cc8	30	5f5fc9f3					dbf98641	84a64fb2
33 ead27321 5f5fc9f3 b58dbad2 34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	31	84a64fb2					ca0093fd	4ea6dc4f
34 b58dbad2 84a64fb2 312bf560 35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8		4ea6dc4f	a6dc4f4e	2486842f	80000000	a486842f	4e54f70e	ead27321
35 312bf560 4ea6dc4f 7f8d292f 36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8							5f5fc9f3	b58dbad2
36 7f8d292f 8d292f7f 5da515d2 1b000000 46a515d2 ead27321 ac7766f3 37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	34	b58dbad2					84a64fb2	312bf560
37 ac7766f3 b58dbad2 19fadc21 38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	35	312bf560					4ea6dc4f	7f8d292f
38 19fadc21 312bf560 28d12941 39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	36	7f8d292f	8d292f7f	5da515d2	1b000000	46a515d2	ead27321	ac7766f3
39 28d12941 7f8d292f 575c006e 40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	37	ac7766f3					b58dbad2	
40 575c006e 5c006e57 4a639f5b 36000000 7c639f5b ac7766f3 d014f9a8 41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	38	19fadc21					312bf560	28d12941
41 d014f9a8 19fadc21 c9ee2589 42 c9ee2589 28d12941 e13f0cc8	39	28d12941					7f8d292f	575c006e
42 c9ee2589 28d12941 e13f0cc8	40	575c006e	5c006e57	4a639f5b	36000000	7c639f5b	ac7766f3	d014f9a8
	41	d014f9a8					19fadc21	c9ee2589
43 e13f0cc8 575c006e b6630ca6	42	c9ee2589					28d12941	e13f0cc8
	43	e13f0cc8					575c006e	b6630ca6

Test vector taken from NIST [2001, pp. 35–36]. This vector is run on a single aes-128 cipher.

Plaintext: 32 43 f6 a8 88 5a 30 8d 31 31 98 a2 e0 32 07 34 Key: 2B 7E 15 16 28 AE D2 A6 AB F7 15 88 09 CF 4F 3C

Round	Start of	After	After	After	Round Key
Number	Round	SubBytes	ShiftRows	MixColumns	Value
input	32 88 31 e0 43 5a 31 37 f 6 30 98 07 a8 8d a2 34				$\oplus \begin{array}{c} 2b 28 ab 09 \\ 7e ae f7 cf \\ 15 d2 15 4f \\ 16 a6 88 3c \end{array}$

42 C Test vectors

1	19 a0 9a e9 3d f 4 c6 f 8 e3 e2 8d 48 be 2b 2a 08	d4 e0 b8 1e 27 bf b4 41 11 98 5d 52 ae f 1 e5 30	d4 e0 b8 1e bf b4 41 27 5d 52 11 98 30 ae f1 e5	04 e0 48 28 66 cb f 8 06 81 19 d3 26 e5 9a 7a 4c	\oplus	a0 88 23 2a f a 54 a3 6c f e 2c 39 76 17 b1 39 05
2	a4 68 6b 02 9c 9f 5b 6a 7f 35 ea 50 f2 2b 43 49	49 45 7 f 77 de db 39 02 d2 96 87 53 89 f 1 1 a 3 b	49 45 7 f 77 db 39 02 de 87 53 d2 96 3b 89 f 1 1 a	58 1b db 1b 4d 4b e7 6b ca 5a ca b0 f 1 ac a8 e5	⊕	f 2 7a 59 73 c2 96 35 59 95 b9 80 f6 f 2 43 7a 7f
3	aa 61 82 68 8f dd d2 32 5f e3 4a 46 03 ef d2 9a	ac ef 13 45 73 c1 b5 23 cf 11 d6 5a 7b df b5 b8	ac ef 13 45 c1 b5 23 73 d6 5a cf 11 b8 7b df b5	75 20 53 bb ec 0b c0 25 09 63 cf d0 93 33 7c dc	Φ	3d 47 1e 6d 80 16 23 7a 47 fe 7e 88 7d 3e 44 3b
4	48 67 4 <i>d d</i> 6 6 <i>c</i> 1 <i>d e</i> 3 5 <i>f</i> 4 <i>e</i> 9 <i>d b</i> 1 58 6 <i>e</i> 0 <i>d</i> 38 67	52 85 e3 f6 50 a4 11 cf 2f 5e c8 6a 28 d7 07 94	52 85 e3 f6 a4 11 cf 50 c8 6a 2f 5e 94 28 d7 07	0 f 60 6 f 5 e d6 31 c0 b3 da 38 10 13 a9 b f 6 b 01	\oplus	ef a8 b6 db 44 52 71 0b a5 5b 25 ad 4a 7f 3b 00
5	e0 c8 d9 85 92 63 b1 b8 7f 63 35 be e8 c0 50 01	e1 e8 35 97 4f f b c8 6c d2 f b 96 ae 9b ba 53 7c	e1 e8 35 97 f b c8 6c 4f 96 ae d2 f b 7c 9b ba 53	25 bd b6 4c d1 11 3a 4c a9 d1 33 c0 ad 68 8e b0	\oplus	d4 7c ca 11 d1 8d f2 f9 c6 9d b8 15 f8 87 bc bc
6	f 1 c 1 7 c 5 d 00 92 c 8 b 5 6 f 4 c 8 b d 5 5 5 e f 3 2 0 c	a1 78 10 4c 63 4f e8 d5 a8 29 3d 03 fc df 23 fe	a1 78 10 4c 4f e8 d5 63 3d 03 a8 29 fe fc df 23	4b 2c 33 37 86 4a 9d d2 8d 89 f4 18 6d 80 e8 d8	\oplus	6d 11 db ca 88 0b f 9 00 a3 3e 86 93 7a f d 41 f d
7	26 3 <i>d</i> e8 <i>f d</i> 0e 41 64 <i>d</i> 2 2e <i>b</i> 7 72 8 <i>b</i> 17 7 <i>d a</i> 9 25	f7 27 9b 54 ab 83 43 b5 31 a9 40 3d f0 f d 3	f7 27 9b 54 83 43 b5 ab 40 3d 31 a9 3f f0 ff d3	14 46 27 34 15 16 46 2 <i>a</i> <i>b</i> 5 15 56 <i>d</i> 8 <i>bf ec d</i> 7 43	\oplus	4e 5f 84 4e 54 5f a6 a6 f7 c9 4f dc 0e f3 b2 4f
8	5a 19 a3 7a 41 49 e0 8c 42 dc 19 04 b1 1 f 65 0c	be d4 0a da 83 3b e1 64 2c 86 d4 f 2 c8 c0 4d f e	be d4 0a da 3b e1 64 83 d4 f2 2c 86 fe c8 c0 4d	00 b1 54 f a 51 c8 76 1b 2f 89 6d 99 d1 f f cd ea	\oplus	ea b5 31 7f d2 8d 2b 8d 73 ba f5 29 21 d2 60 2f
9	ea 04 65 85 83 45 5d 96 5c 33 98 b0 f 0 2d ad c5	87 f 2 4d 97 ec 6e 4c 90 4a c3 46 e7 8c d8 95 a6	87 f 2 4d 97 6e 4c 90 ec 46 e7 4a c3 a6 8c d8 95	47 40 a3 4c 37 d4 70 9 f 94 e4 3a 42 ed a5 a6 bc	\oplus	ac 19 28 57 77 f a d 1 5c 66 dc 29 00 f 3 21 41 6e

10	eb 59 8b 1b 40 2e a1 c3 f2 38 13 42 1e 84 e7 d2	e9 cb 3d af 09 31 32 e2 89 07 7d 2c 72 5f 94 b5	e9 cb 3d af 31 32 e2 09 7d 2c 89 07 b5 72 5f 94	\oplus	d0 c9 e1 b6 14 ee 3 f 63 f 9 25 0c 0c a8 89 c8 a6
output	39 02 dc 19 25 dc 11 6a 84 09 85 0b 1d f b 97 32				

Examples

D.1 CBC-mode calculations

The ciphertext is obtained through the following equation where C_0 is the IV, and the XOR-operation is noted with \oplus .

 C_i is the ciphertext P_i is the plaintext E_k is the encryption algorithm D_k is the decryption algorithm

$$C_i = E_k(P_i \oplus C_{i-1}) \tag{D.1}$$

The inverse of the encryption algorithm E_k is the decryption algorithm D_k .

The inverse of the XOR-operation the XOR-operation.

This gives us:

$$D_k(C_i) = P_i \oplus C_{i-1} \tag{D.2}$$

which gives us

$$P_i = D_k(C_i) \oplus C_{i-1} \tag{D.3}$$

46 D Examples

List of Figures

1.1	CIPlus interface. Image remade from [LLP, 2011, p. 10]	4
2.1	General layout of a data packet	6
2.2	PES packet derived from TS packets	8
2.3	Different kinds of ciphers [Wikipedia, 2014b]	9
2.4	SP-Network	11
3.1	Number of bits in key used	14
6.1	Test vector 1	27
6.2	Test vector 2	28
6.3	Test vector 3	28
A.1	Rijndael S-box	32
A.2	State-Matrix	32
A.3	Rijndael MixColumns equation	32
A.4	The Rcon function represented as a vector	33
B.1	Flowchart of the Rcon function	36
B.2	Flowchart of the key schedule	
B.3	Cipher block chaining mode, [Wikipedia, 2014a]	37

- Conax, 2014. URL http://www.conax.com/about-us/. Accessed: 13 Feb 2014. Cited on page 2.
- DVB Scene. Delivering the digital standard not so sure about the title. *DVB Scene*, September 2013. URL http://www.dvb.org/resources/public/scene/DVB-SCENE42.pdf. Accessed: 10 Feb 2014. Cited on page 13.
- ETSI. Digital video broadcasting (dvb); support for use of scrambling and conditional access (ca) withing digital video broadcasting systems. *ETR 289*, October 1996. URL http://www.etsi.org/deliver/etsi_etr/200_299/289/01_60/etr_289e01p.pdf. Accessed: 21 Feb 2014. Cited on page 8.
- ETSI TS. Digital video broadcasting (dvb); head-end implementation of dvb simulcrypt. *ETSI TS 103 197*, 10 2008. Accessed: 13 Feb 2014. Cited on page 3.
- ETSI TS. Digital video broadcasting (dvb); specification for the use of video and audio coding in broadcasting applications based on the mpeg-2 transport stream. ETSI TS 101 154, 9 2009. URL http://www.etsi.org/deliver/etsi_ts/101100_101199/101154/01.09.01_60/ts_101154v010901p.pdf. Accessed: 6 March 2014. Cited on page 7.
- ETSI TS. Digital video broadcasting (dvb). ETSI TS 103 127, 05 2013. URL http://www.etsi.org/deliver/etsi_ts/103100_103199/103127/01.01.01_60/ts_103127v010101p.pdf. Accessed: 10 Feb 2014. Cited on pages 6, 7, 17, and 18.
- European Standard. Common interface specification for conditional access and other digital video broadcasting decoder applications. *EN 50221*, February 1997. URL http://www.dvb.org/resources/public/standards/En50221.V1.pdf. Accessed: 4 March 2014. Cited on page 3.
- Farncombe Consulting Group. Towards a replacement for the dvb common scrambling algorithm. Farncombe White Paper, October 2009. URL http:

//farncombe.eu/whitepapers/FTLCAWhitePaperTwo.pdf. Accessed: 28 jan 2014. Cited on pages 13 and 14.

- Mr Internet. Mixcolumns step for aes. *Empty*, January 2014. URL http://www.angelfire.com/biz7/atleast/mix_columns.pdf. Accessed: 28 jan 2014. Cited on page 22.
- Wei Li. Security analysis of dvb common scrambling algorithm. In Data, Privacy, and E-Commerce, 2007. ISDPE 2007. The First International Symposium on, pages 271–273. IEEE, IEEE Xplore, 2007. URL http://ieeexplore.ieee.org.lt.ltag.bibl.liu.se/stamp/stamp.jsp?tp=&arnumber=4402690. Accessed: 12 Feb 2014. Cited on pages 13 and 14.
- CI Plus LLP. Ci plus overview. *Common Interface Plus*, November 2011. URL http://www.ci-plus.com/data/ci-plus_overview_v2011-11-11.pdf. Accessed: 4 March 2014. Cited on pages 3, 4, and 47.
- NIST. Specification for the advanced encryption standard (aes), November 2001. URL http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf. Accessed: 17 Feb 2014. Cited on pages 27, 39, 40, and 41.
- Bruce Schneier and Niels Fergusson. *Practical Cryptography*. Wiley Publishing, Inc., first edition, 2003. Cited on pages 5, 8, 10, 11, and 15.
- G.J. Schrijen. Use case: Control word protection, May 2011. URL http://www.hisinitiative.org/_lib/img/Intrinsic-ID_ CWProtection_May_25.pdf. Accessed: 18 Feb, 2014. Cited on page 14.
- C. E. Shannon. Communication theory of secrecy systems*. *Bell System Technical Journal*, 28(4), 1949. ISSN 1538-7305. doi: 10.1002/j.1538-7305.1949.tb00928.
 x. URL http://dx.doi.org/10.1002/j.1538-7305.1949.tb00928.x.
 Accessed: 28 Jan 2014. Cited on pages 10 and 11.
- Gustavus J. Simmons. *Contemporary Cryptology*. IEEE Press, 1992. Cited on pages 8 and 10.
- Leonie Simpson, Matt Henricksen, and Wun-She Yap. Improved cryptanalysis of the common scrambling algorithm stream cipher. In *Information Security and Privacy*, pages 108–121. Springer, 2009. URL http://eprints.qut.edu.au/27578/1/c27578.pdf. Accessed: 12 Feb 2014. Cited on page 15.
- Douglas R. Stinson. *Cryptography : Theory and practice.* Chapman & Hall / CRC, third edition, 2006. Cited on pages 10, 11, 21, 22, and 23.
- Erik Tews, Julian Wälde, and Michael Weiner. Breaking dvb-csa. In Research in Cryptology, pages 45–61. Springer, 2012. URL http://link.springer.com.lt.ltag.bibl.liu.se/chapter/10.1007% 2F978-3-642-34159-5_4#page-14. Accessed: 3 Feb 2014. Cited on page 15.

Serge Vaudenay, Willi Meier, Simon Fischer, et al. Analysis of lightweight stream ciphers. École Polytechnique Fédérale De Lausanne, 2008. URL http://biblion.epfl.ch/EPFL/theses/2008/4040/EPFL_TH4040.pdf. Accessed: 3 Feb 2014. Cited on page 10.

- Ralf-Philipp Weinmann and Kai Wirt. Analysis of the dvb common scrambling algorithm. In Communications and Multimedia Security, pages 195–207. Springer, October 2006. URL http//sec.cs.kent.ac.uk/cms2004/Program/CMS2004final/p5al.pdf. Accessed: 31 Jan 2014. Cited on page 14.
- Unknown Wikipedia. Cbc encryption, 2014a. URL http://upload.wikimedia.org/wikipedia/commons/thumb/8/80/CBC_encryption.svg/2000px-CBC_encryption.svg.png. Accessed: 7 Feb 2014. Cited on pages 37 and 47.
- Unknown Wikipedia. Cipher-taxanomy, 2014b. URL http://upload.wikimedia.org/wikipedia/en/thumb/8/85/Cipher-taxonomy.svg/500px-Cipher-taxonomy.svg.png. Accessed: 5 Feb 2014. Cited on pages 9 and 47.
- Wikipedia Jr Wikipedia. Rijndael's key schedule. *Empty*, January 2014c. URL http://en.wikipedia.org/wiki/Rijndael_key_schedule. Accessed: 28 jan 2014. Cited on page 24.
- Kai Wirt. Fault attack on the dvb common scrambling algorithm, 2004. URL https://eprint.iacr.org/2004/289.pdf. Accessed: 13 Feb 2014. Cited on page 15.



Upphovsrätt

Detta dokument hålls tillgängligt på Internet — eller dess framtida ersättare — under 25 år från publiceringsdatum under förutsättning att inga extraordinära omständigheter uppstår.

Tillgång till dokumentet innebär tillstånd för var och en att läsa, ladda ner, skriva ut enstaka kopior för enskilt bruk och att använda det oförändrat för icke-kommersiell forskning och för undervisning. Överföring av upphovsrätten vid en senare tidpunkt kan inte upphäva detta tillstånd. All annan användning av dokumentet kräver upphovsmannens medgivande. För att garantera äktheten, säkerheten och tillgängligheten finns det lösningar av teknisk och administrativ art.

Upphovsmannens ideella rätt innefattar rätt att bli nämnd som upphovsman i den omfattning som god sed kräver vid användning av dokumentet på ovan beskrivna sätt samt skydd mot att dokumentet ändras eller presenteras i sådan form eller i sådant sammanhang som är kränkande för upphovsmannens litterära eller konstnärliga anseende eller egenart.

För ytterligare information om Linköping University Electronic Press se förlagets hemsida http://www.ep.liu.se/

Copyright

The publishers will keep this document online on the Internet — or its possible replacement — for a period of 25 years from the date of publication barring exceptional circumstances.

The online availability of the document implies a permanent permission for anyone to read, to download, to print out single copies for his/her own use and to use it unchanged for any non-commercial research and educational purpose. Subsequent transfers of copyright cannot revoke this permission. All other uses of the document are conditional on the consent of the copyright owner. The publisher has taken technical and administrative measures to assure authenticity, security and accessibility.

According to intellectual property law the author has the right to be mentioned when his/her work is accessed as described above and to be protected against infringement.

For additional information about the Linköping University Electronic Press and its procedures for publication and for assurance of document integrity, please refer to its www home page: http://www.ep.liu.se/