

Suricata Rules

1. Nmap Scan

Simulation	Nmap Scan from Kali Linux (attacker) to Windows 10 (victim) <pre>(aidan@kali)-[~/test] └─\$ nmap -sS -p 1-1000 192.168.110.100 Starting Nmap 7.98 (https://nmap.org) at 2026-06-19 10:44 -0400 Nmap scan report for 192.168.110.100 Host is up (0.00045s latency). All 1000 scanned ports on 192.168.110.100 are in ignored states. Not shown: 1000 filtered tcp ports (no-response) MAC Address: 00:0C:29:F6:B7:7E (VMware) Nmap done: 1 IP address (1 host up) scanned in 21.76 seconds</pre>
Rules	alert http any any -> \$HOME_NET any (msg:"CUSTOM Oversized HTTP GET Request"; flow:to_server,established; http.method; content:"GET"; http.uri; byte_test:2,>,500,0,relative; classtype:attempted-recon; sid:20260603; rev:1;)
Verification	<pre>aidan@aidan-virtual-machine:~/lab\$ cat /var/log/suricata/fast.log grep "20260601" 06/19/2026-21:44:52.391586 [**] [1:20260601:2] CUSTOM Nmap SYN Scan Detected [**] [Classification: (null)] [Priority: 3] {TCP} 192.168.110.133:36982 -> 192.168.110.100:443</pre>

2. FTP Brute Force

Simulation	FTP connection attempts from Kali Linux (attacker) to Ubuntu
------------	--

	<pre>(aidan@kali)-[~] └─\$ for i in {1..15}; do timeout 1 bash -c "</dev/tcp/192.168.110.131/21" 2>/dev/null echo "Attempt \$i" done Attempt 1 Attempt 2 Attempt 3 Attempt 4 Attempt 5 Attempt 6 Attempt 7 Attempt 8 Attempt 9 Attempt 10 Attempt 11 Attempt 12 Attempt 13 Attempt 14 Attempt 15</pre>
Rules	<pre>alert tcp any any -> \$HOME_NET 21 (msg:"CUSTOM FTP Brute Force Attempt"; flags:S; threshold:type both, track by_src, count 10, seconds 30; classtype:attempted-admin; sid:20260704; rev:1;)</pre>
Verification	<pre>06/25/2026-11:55:40.244795 [**] [1:20260704:1] CUSTOM FTP Brute Force Attempt [**] [Classification: Attempted Administrator Privilege Gain] [Priority: 1] {TCP} 192.168.110.133:37024 -> 192.168.110.131:21</pre>

3. Telnet Connection Attempt

Simulation	Telnet connection attempts from Kali Linux (attacker) to Ubuntu <pre>(aidan@kali)-[~] └─\$ telnet 192.168.110.131 23 Trying 192.168.110.131... telnet: Unable to connect to remote host: Connection refused</pre>
Rules	<pre>alert tcp any any -> \$HOME_NET 23 (msg:"CUSTOM Telnet Connection Attempt"; flags:S; classtype:attempted-admin; sid:20260605; rev:1;)</pre>
Verification	<pre>06/25/2026-11:58:38.675030 [**] [1:20260605:1] CUSTOM Telnet Connection Attempt [**] [Classification: Attempted Administrator Privilege Gain] [Priority: 1] {TCP} 192.168.110.133:47528 -> 192.168.110.131:23</pre>

4. Oversized HTTP GET Request

[illegible]

5. HTTP with “admin” in URI

Simulation	HTTP /admin attempts from Kali Linux (attacker) to Ubuntu <pre>(aidan@kali)~\$ curl http://192.168.110.131/admin <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/TR/html4/strict.dtd"> <html> <head> <meta http-equiv="Content-Type" content="text/html; charset=utf-8"> <title>Error response</title> </head> <body> <h1>Error response</h1> <p>Error code: 404</p> <p>Message: File not found.</p> <p>Error code explanation: HTTPStatus.NOT_FOUND - Nothing matches the given URI.</p> </body> </html></pre>
Rules	alert http any any -> \$HOME_NET any (msg:"CUSTOM Admin Panel Scanning Detected"; flow:to_server,established; http.uri; content:"/admin"; nocase; classtype:web-application-attack; sid:20260606; rev:1;)
Verification	<pre>06/25/2026-12:22:13.220858 [**] [1:20260606:1] CUSTOM Admin Panel Scanning Detected [*] [Classification: Web Application Attack] [Priority: 1] {TCP} 192.168.110.133:52010 - -> 192.168.110.131:80</pre>

6. Uncommon HTTP Method

Simulation	HTTP PUT request attempts from Kali Linux (attacker) to Ubuntu <pre>(aidan@kali)~\$ curl -X PUT http://192.168.110.131/ <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/TR/html4/strict.dtd"> <html> <head> <meta http-equiv="Content-Type" content="text/html; charset=utf-8"> <title>Error response</title> </head> <body> <h1>Error response</h1> <p>Error code: 501</p> <p>Message: Unsupported method ('PUT').</p> <p>Error code explanation: HTTPStatus.NOT_IMPLEMENTED - Server does not support this operation.</p> </body> </html></pre>
Rules	alert http any any -> \$HOME_NET any (msg:"CUSTOM Uncommon HTTP Method Detected"; flow:to_server,established; http.method; content:"PUT"; nocase; classtype:attempted-recon; sid:20260608; rev:1;)
Verification	<pre>06/25/2026-12:30:04.637809 [**] [1:20260608:1] CUSTOM Uncommon HTTP Method Detected [*] [Classification: Attempted Information Leak] [Priority: 2] {TCP} 192.168.110.133:330 28 -> 192.168.110.131:80</pre>

7. Suspicious DNS Query

Simulation	DNS Lookup from Ubuntu to a known suspicious/malware domains (example: malware.test) <pre> aidan@aidan-virtual-machine:/tmp\$ dig malware.test @8.8.8.8 ; <<>> DiG 9.18.39-0ubuntu0.22.04.4-Ubuntu <<>> malware.test @8.8.8.8 ;; global options: +cmd ;; Got answer: ;; ->>HEADER<<- opcode: QUERY, status: NXDOMAIN, id: 23384 ;; flags: qr aa rd ra; QUERY: 1, ANSWER: 0, AUTHORITY: 1, ADDITIONAL: 1 ;; OPT PSEUDOSECTION: ; EDNS: version: 0, flags:: udp: 4096 ;; QUESTION SECTION: ;malware.test. IN A ;; AUTHORITY SECTION: test. 10800 IN SOA localhost. nobody.invalid. 1 3600 1200 604800 10800 ;; Query time: 14 msec ;; SERVER: 8.8.8.8#53(8.8.8.8) (UDP) ;; WHEN: Thu Jun 25 12:58:54 WIB 2026 ;; MSG SIZE rcvd: 100 </pre>
Rules	alert dns \$HOME_NET any -> any 53 (msg:"CUSTOM Suspicious DNS Query - Test Domain"; dns_query; content:"malware.test"; nocase; classtype:bad-unknown; sid:20260610; rev:1;)
Verification	<pre> 06/25/2026-12:58:54.671428 [**] [1:20260610:1] CUSTOM Suspicious DNS Query - Test Domain [**] [Classification: Potentially Bad Traffic] [Priority: 2] {UDP} 192.168.110.131:60461 -> 8.8.8.8:53 </pre>

8. Suspicious User-Agent

Simulation	HTTP PUT request attempts using curl from Kali Linux (attacker) to Ubuntu
------------	---

	<pre> (aidan@kali)-[~] \$ curl http://192.168.110.131/ <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/TR/html4/strict.dtd"> <html> <head> <meta http-equiv="Content-Type" content="text/html; charset=utf-8"> <title>Directory listing for /</title> </head> <body> <h1>Directory listing for /</h1> <hr> .font-unix/ .ICE-unix/ .s.PGSQL.5432 .s.PGSQL.5432.lock .Test-unix/ .X0-lock .X1-lock .X1024-lock .X1025-lock .X11-unix/ .XIM-unix/ mongodb-27017.sock pulse-PKdhtXMmr18n/ snap-private-tmp/ systemd-private-a6330edbb08c4392b347919710e25099-colord.service-PioQb7/ systemd-private-a6330edbb08c4392b347919710e25099-fwupd.service-tgqpMZ/ systemd-private-a6330edbb08c4392b347919710e25099-ModemManager.service-Anqebf/ systemd-private-a6330edbb08c4392b347919710e25099-power-profiles-daemon.service-Aw7A6M/ systemd-private-a6330edbb08c4392b347919710e25099-redis-server.service-9cNhDE/ systemd-private-a6330edbb08c4392b347919710e25099-switcheroo-control.service-H7PFTk/ systemd-private-a6330edbb08c4392b347919710e25099-systemd-logind.service-CniiXm/ systemd-private-a6330edbb08c4392b347919710e25099-systemd-oomd.service-cup2ZV/ systemd-private-a6330edbb08c4392b347919710e25099-systemd-resolved.service-LYUprh/ systemd-private-a6330edbb08c4392b347919710e25099-systemd-timesyncd.service-j3jqQz/ </pre>
Rules	alert http any any -> \$HOME_NET any (msg:"CUSTOM Suspicious User-Agent Detected"; flow:to_server,established; http.user_agent; content:"curl"; nocase; classtype:attempted-recon; sid:20260609; rev:1;)
Verification	<pre> 06/25/2026-13:02:28.208057 [**] [1:20260609:1] CUSTOM Suspicious User-Agent Detected [**] [Classification: Attempted Information Leak] [Priority: 2] {TCP} 192.168.110.133:50 424 -> 192.168.110.131:80 </pre>