Aidra Collins hw05	- Written
April 7 2015	
destien 1 header	
ha fts	set header of rest to the new node  then set new nets -> next  to the old header -> next
(b) before hooder	preido code  make a temprey variable to hild hooder the  make header to nett equal to  felete the temperary variable
hooder I 7 I 7 III	Citate 1)  Pseedo (ede  woko a temp variable for node  after one given  - set the given node Twent to  given node > noxt > not)  - dilite the temp variable

```
3. (a) 13 valid
```

- (b) is invaled
  -linked list's iterators only have for word capabilities
  and connet be subtracted
  - (1) is valid

4. encon TokenType & EOL, VALUE, OPAREN, (PAREN, EXP.
MUIT, DIV, MOD, PLUS, MINUS 3)

Street Precedence

{
int inputSymbol;
int top Of Stock;
}
PREC\_TABLE[] =

{
EO,-1), {0,0},

£0,-1), £0,03, £100,03, £0,093, £6,53, £3,43, £3,43, £3,43, £1,23, £1,23

3,

MULT DIV

5.

6. it wooldn't work. Uld node is deleated to force

Pronth 13 assigned to proment port

To Pronth-woold not exist at this line
coosing a segmentation facility.

7. (a)

8 9 9 9 9 3 3 37 -25

8 9 9 9 9 8 7 77

(b) 22 16 16 16 4

(c) 44 4 4 4 - 2 - 2 - 2 - 11 - 15 - 5

(d) 9 3 3 6 6 5

(e) 5 8 7 4 7 4 58.8 58.8 62.8

