

Computer Science  
and Mathematics  
COC255  
B827126

**TIMETABLE CREATION  
USING  
ARTIFICIAL INTELLIGENCE**

by

Aiden Nico Tempest

Supervisor: Dr. S. Fatima

Department of Computer Science  
Loughborough University

August 2023

## **Abstract**

lol placeholder text for abstract lorem ipsum etc test

# Contents

<b>1</b>	<b>Literature Review</b>	<b>3</b>
1.1	The Timetabling Problem . . . . .	3
1.2	Methods . . . . .	4
1.2.1	Genetic Algorithms . . . . .	4
1.2.2	Binary Integer Programming . . . . .	5
1.2.3	Tabu Search . . . . .	9
1.2.4	Answer Set Programming . . . . .	11
1.2.5	Bat Inspired Algorithm . . . . .	13
1.3	Comparison of Methods . . . . .	15
1.4	Chosen Method . . . . .	16
<b>2</b>	<b>Requirements</b>	<b>17</b>
2.1	Necessary Requirements . . . . .	17
2.2	Aspirational Requirements . . . . .	18
<b>3</b>	<b>Design</b>	<b>19</b>
3.1	Modelling the Input Data . . . . .	19
3.2	Constraints . . . . .	20
3.2.1	Every module has all its hours timetabled . . . . .	20
3.2.2	Each session is taught by the correct teacher for the module . . . . .	21
3.2.3	Each session has the correct student group attending it . . . . .	21
3.2.4	A room is being used for at most one learning session in a time slot . . . . .	21
3.2.5	A student has at most one learning session in a time slot . . . . .	21
3.2.6	A teacher has at most one learning session in a time slot . . . . .	22
3.2.7	A session is in the correct type of room . . . . .	22
3.2.8	The number of students in the room must not exceed the capacity of the room	23
3.2.9	The size of the room is optimal for the number of students . . . . .	23
3.2.10	Teachers can make preferences for when they are teaching . . . . .	23

3.3	Timetable Encoding . . . . .	23
3.4	Genetic Algorithm Pseudocode . . . . .	23
3.4.1	Initial Population . . . . .	24
3.4.2	Fitness Function . . . . .	25
3.4.3	Selection . . . . .	26
3.4.4	Crossover . . . . .	26
3.4.5	Mutation . . . . .	27
<b>4</b>	<b>Implementation</b>	<b>29</b>
<b>5</b>	<b>Testing</b>	<b>30</b>
<b>6</b>	<b>Evaluation</b>	<b>31</b>
<b>7</b>	<b>Conclusion</b>	<b>32</b>
	<b>References</b>	<b>33</b>
<b>A</b>	<b>Source Code</b>	<b>34</b>
A.1	main.py . . . . .	34
A.2	ga.py . . . . .	35
A.3	initial population.py . . . . .	39
A.4	fitness function.py . . . . .	43
A.5	selection.py . . . . .	45
A.6	crossover.py . . . . .	48
A.7	mutation.py . . . . .	49

# Chapter 1

## Literature Review

### 1.1 The Timetabling Problem

The timetabling problem is a constraint satisfying problem and it is known to be NP-Complete. The aim is to create a university timetable where several constraints are met. These constraints are either hard constraints or soft constraints. For a solution to be valid, all the hard constraints must be met. Not all (or in fact, any) of the soft constraints need to be met for the solution to be valid, however it is preferable for as many soft constraints to be met as possible. Examples of possible hard constraints include:

- At most only one session (i.e., a lecture or lab) is happening in a specific room in a specific period
- A student can only be attending at most one session in a specific period
- A teacher (e.g., a lecturer or lab helper) can only be attending at most one session in a specific period
- The size of a student group cannot exceed the capacity of the room
- The room must be appropriate for the type of session, e.g., a lecture must be in a lecture theatre, and a lab session must be in a computer lab
- Part time teachers can only be assigned certain time slots, e.g., they may not work on Tuesdays, so sessions they teach cannot be scheduled for time slots on Tuesday.

Possible soft constraints include:

- Students do not have more than two consecutive hours scheduled
- The capacity of a room is well suited to the size of the student group, to make an efficient use

of space e.g., a group of twenty students are not going to be in a room with a capacity of two hundred

- If a student or teacher has one session immediately after another, then the respective rooms are relatively close to each other

A solution is invalid if at least one the hard constraints are met. For example, if a student is scheduled to be in two different sessions at the same time — this is known as a clash.

## 1.2 Methods

### 1.2.1 Genetic Algorithms

Genetic algorithms (GAs) make up a group of search metaheuristics, inspired by Darwin’s theory of evolution [7]. Here, the fittest members of a population survive and produce offspring, which inherit the characteristics of the parents. It is also possible for the offspring to have small mutations within their genetic code, which may or may not be beneficial towards the population’s survival. This theory can be applied to search problems. In this case, the population represents the search space, which is a collection of candidate solutions to a problem, and the population of solutions evolves as the algorithm searches for a desired solution.

There does not exist a rigorous definition of GAs, but most methods use these five phases:

1. Initial population — populations of chromosomes
2. Fitness function
3. Selection — according to fitness
4. Crossover — to produce new offspring
5. Mutation — random mutation of new offspring

The initial **population** is a set of **individuals**, where each individual represents a candidate solution to the problem. These solutions will almost definitely not satisfy the problem, as they are randomly generated, but that is not an issue.

An individual (and hence that candidate solution), is defined by its **chromosome**. The chromosome is often encoded as a string of binary characters; however, any alphabet can be used. These characters are called **alleles**, and a single character or group of adjacent characters that encode a particular element of the candidate solution are known as a **gene**.

Using the example of the university timetabling problem, several alleles may be used to encode a room, but together they are one gene.

The **fitness** function measures how well a candidate solution solves the problem. For example, in the instance of the university timetabling problem, the fitness of the solution could be measured by the number of times in the solution that a hard constraint is not met. This means that a solution with a score of 0 is a valid solution, as there are instances of a hard constraint not being met.

Once the fitness function has been used to calculate the fitness of each individual, the fittest individuals are chosen for reproduction in the **selection** phase. There are several ways to select individuals to use for producing offspring. One way is to simply choose the two individuals with the best fitness. Another way is to use roulette-wheel sampling, where any individual could be chosen for producing offspring, but fitter individuals are more likely to be chosen. This second method introduces more variation into the offspring, to reduce the chance of convergence onto a local maximum.

The **crossover** phase, or reproduction phase, is where genetic material is exchanged between two parents. The crossover operator randomly chooses a locus (position) in a chromosome, in between alleles. The subsequent before and after parts of the chromosome are swapped between the two parents to produce two offspring. This is repeated multiple times to produce a population of the same size as the initial population. Whether this is by two parents reproducing multiple times using different loci or not, depends on the method used in the selection phase.

After reproduction, **mutations** can be introduced into the offspring. For example, if the chromosomes are encoded by binary strings, then some bits are randomly flipped. However, there is a very small chance of this occurring at each bit, a suggested probability is 0.1%. By introducing mutations into the offspring, the likelihood of reaching a local maximum is reduced.

Once there is a new population made up of the offspring, the process repeats until a solution is found. Each repetition is called a **generation**, and the entire set of generations is known as a **run**.

A version of a genetic algorithm was implemented by Perzina (2006) [8] and was applied to a timetabling problem with real world data. Timetables were generated for 1807 students, but for how courses are organised at this university, there are no groups of students with the same timetable, and it is unlikely that two students would even have the same timetable. Because of this, the author anticipated that it would be too difficult to generate timetables without any clashes at all, and instead aimed to minimise the number of clashes. The best solution found had 83 students with at least one clash on their timetable, or 4.59% of the students.

### 1.2.2 Binary Integer Programming

Binary integer programming is used to solve constraint satisfiability problems. Variables must either take a value of 1 or 0 (hence binary integer), as they are used to represent decisions, i.e., in the case of the university timetabling problem, a teaching session is happening in a specific room, at a

specific time, on a specific day, with a specific teacher, with a specific teacher, with a specific student group, about a specific module, or not [2]. Then constraints are applied and used with the objective function to find what value each variable takes.

First, a mathematical model of the problem must be constructed. Abdellahi and Eledum (2006) [2] modelled the features of the university timetabling problem as a group of sets:

- $I = \{1, \dots, n_i\}$ : set of days in the week where courses are offered
- $J = \{1, \dots, n_j\}$ : set of time slots in a day
- $K = \{1, \dots, n_k\}$ : set of courses
- $L = \{1, \dots, n_l\}$ : set of student groups
- $M = \{1, \dots, n_m\}$ : set of teachers
- $N = \{1, \dots, n_n\}$ : set of classrooms

Next, the decision variables are defined. The basic variables  $x_{i,j,k,l,m,n}$  are defined as  $\forall i \in I, \forall j \in J, \forall k \in K, \forall l \in L, \forall m \in M, \forall n \in N$

$$x_{i,j,k,l,m,n} = \begin{cases} 1, & \text{if a course } k \text{ taught by teacher } m \text{ for the group of} \\ & \text{students } l \text{ is assigned to the } j^{th} \text{ time slot of day } i \text{ in} \\ & \text{classroom } n \\ 0, & \text{otherwise} \end{cases}$$

In other words, the basic variables represent the decision of whether or not a course is being taught by a specific teacher for a specific group of students is happening in a specific time slot of a specific day in a specific classroom. Then the authors defined their auxiliary variables as

$$\forall i \in I, \forall j \in J, \forall l \in L$$

$$y_{i,j,k,l} = \begin{cases} 1, & \text{if a course } k + s \text{ for group of students overlap with} \\ & \text{its prerequisite } k \text{ for the same group } l \text{ in the } j^{th} \text{ time} \\ & \text{slot of day } i \\ 0, & \text{otherwise} \end{cases}$$

for  $s \in 1, \dots, n_k - 1$ , where  $k + s \leq n_k$

Finally, (people) defined two further sets of variables:

- $z_{im}$ , which represents the existence of lectures for teacher  $m$  on day  $i$
- $z_{il}$ , which represents the existence of lectures for student  $l$  on day  $i$



$\forall m \in M$

$$z_{im} = \begin{cases} 1, & \text{if } \sum_{j \in J} x_{i,j,k,l,m,n} \neq 0 \\ 0, & \text{otherwise} \end{cases}$$

$\forall l \in L$

$$z_{il} = \begin{cases} 1, & \text{if } \sum_{j \in J} x_{i,j,k,l,m,n} \neq 0 \\ 0, & \text{otherwise} \end{cases}$$

$z_{im}$  and  $z_{il}$  are for use with the object function, later. The next thing to be modelled is the restraints. For the university modelled by the authors, these were:

1. There is no overlapping for courses
2. Each teacher cannot be assigned to more than one course for any given period
3. Each classroom cannot hold more than one course for any given period
4. A student has some courses amount to 18 hours per week. Each course consists of 3 hours and taught in 2 periods (each period is 90 minutes long), which is expressed as the number of slots worked per day.
5. For a student, each course occupies only one slot per day
6. The lectures of each course must be distributed in such a way that there is one day off between them
7. All lectures of a given course in a week must be held in the same classroom
8. The overlap of course with prerequisites for the same group of undergrad students  $l$  is permitted (note: the authors refer to undergrad students as pre-graduated students)

As an example, the first restraint is modelled as:

$$\sum_{k \in K} \sum_{m \in M} \sum_{n \in N} x_{i,j,k,l,m,n} \leq 1 \quad \forall i \in I, \forall j \in J, \forall l \in L$$

The objective function needs to be either minimised or maximised (dependent on how it is modelled), by changing the values assigned to the variables, whilst ensuring that the constraints are met [5]. In this instance, the total dissatisfaction of teachers and students needs to be minimised, which is equivalent to maximising the number of lectures per day, which implies decreasing the waiting time between lectures.

$$\begin{aligned} (\text{Total dissatisfaction}) = & \text{Teacher}\{\text{number of lectures per} \\ & \text{day}\} + \text{Regular student}\{\text{number of lectures per day}\} + \\ & \text{Predicted graduate student}\{\text{number of lectures per day}\} \end{aligned}$$

The model produced may not be tractable, meaning that the problem may not be able to be solved in a reasonable period. To make the problem easier to be solved, the model needs to be reduced. Abdellahi and Eledum achieved this by removing the index representing classrooms ( $n \in N$ ) and by adding another constraint, that the number of courses cannot exceed the number of classrooms in a timeslot  $j$  in a given day  $i$  (constraint 9). To further simplify the model, the term corresponding to the overlapping of courses and their prerequisites has been removed from the objective function, with the related constraint 8.

The model is now:

$$\max\{1.5 \sum_{j \in J} \sum_{k \in K} \sum_{l \in L} \sum_{m \in M} x_{i,j,k,l,m} + \sum_{m \in M} z_{im} + \sum_{l \in L} z_{il}\} \quad (\text{objective function})$$

subject to

$$\sum_{k \in K} \sum_{m \in M} x_{i,j,k,l,m} \leq 1 \quad \forall i \in I, \forall j \in J, \forall l \in L \quad (\text{Constraint 1})$$

$$\sum_{l \in L} \sum_{k \in K} x_{i,j,k,l,m} \leq 1 \quad \forall i \in I, \forall j \in J, \forall m \in M \quad (\text{Constraint 2})$$

$$\sum_{j \in J} \sum_{k \in K} \sum_{m \in M} x_{i,j,k,l,m} \leq n_j \quad \forall i \in I, \forall l \in L \quad (\text{Constraint 3})$$

$$\sum_{j \in J} x_{i,j,k,l,m} \leq 1 \quad \forall i \in I, \forall k \in K, \forall l \in L, \forall m \in M \quad (\text{Constraint 4})$$

$$\sum_{j \in J} (x_{i,j,k,l,m} + x_{i+2,j,k,l,m} = 2), i + 2 \leq 5 \quad \forall i \in I, \forall k \in K, \forall l \in L, \forall m \in M \quad (\text{Constraint 5})$$

$$\sum_{k \in K} \sum_{l \in L} \sum_{m \in M} x_{i,j,k,l,m} \leq n_n \quad \forall i \in I, \forall j \in J \quad (\text{Constraint 9})$$

$$s \in \{1, \dots, n_k - 1\}, k + s \leq n_k$$

$$\sum_{m \in M} z_{im} \leq 1 \quad \forall i \in I$$

$$\sum_{l \in L} z_{il} \leq n_i \quad \forall i \in I$$

$$x_{i,j,k,l,m}, y_{i,j,k,l,m}, z_{im}, z_{il} \geq 0 \quad (\text{so all variables are non-negative})$$

The model can be reduced further into two models, one for students and one for teachers. The problem is solved with using an external penalty function method. Penalty functions convert constrained problems to those without constraints by introducing a penalty for violating the constraints ([9]). By using a penalty function, the authors found a real solution to the unrestrained problem, and then approximated it to a binary solution with an algorithm.

When demonstrating their model, the authors assigned very small numbers to their parameters: 5 workable days per week, 2 slots per day, 3 courses to be assigned, 2 student groups and 2 classrooms. A timetable was generated.

### 1.2.3 Tabu Search

Tabu search is a metaheuristic that guides a local search to explore the solution space outside of the local optimum, by using a **Tabu list**. A Tabu list is flexible memory structure that stores solutions that are not to be used. Tabu search is used to solve combinatorial optimisation problems, which have a finite solution set. The university timetabling problem has a finite solution set, as there are a finite number of teachers, student groups, time slots, rooms, courses, etc., so there is a finite number of different ways that the timetable can be created. Tabu search makes use of three main strategies:

- Forbidding strategy: this controls what enters the Tabu list
- Freeing strategy: this controls what exits the Tabu list
- Short-term strategy: this is for managing interplay between the forbidding strategy and the freeing strategy to select trial solutions

Tabu search examines neighbouring solutions, which are solutions that are one “step” away from the current solution. Using the travelling salesman problem as an example, suppose the current solution is B C D A F E, where each letter represents a city. An example neighbouring solution is E C D A F B, where only one swap has occurred, between the positions of B and E. However, the solution E C D F A B is not in the neighbourhood of the current solution, as two swaps have occurred. If a solution has been used, then it is put into the Tabu list, until it meets an **aspiration criterion**. Aspiration criteria provide reasons for a solution to be freed from the Tabu table (freeing strategy). For example, if a using a Tabu move results in a solution better than any other so far, then it can come out of the Tabu table. Much like with genetic algorithms, a fitness function is used to measure how optimal a solution is [1].

A basic algorithm is:

1. Choose an initial solution  $i$  in the solution space  $S$ . Set  $i' = i$  and  $k = 0$ , where  $k$  is the number of iterations.
2. Set  $k = k + 1$  and generate a set of possible solutions  $N(i, k)$ , where  $N(i, k)$  is the set of neighbouring solutions.
3. Choose a best  $j \in N(i, k)$ , where  $j$  is not Tabu (in the Tabu list). If  $j$  is Tabu, but meets an aspiration criterion, then choose  $j$ . Set  $i = j$ .
4. If  $f(i) > f(i')$  (where  $f$  is the fitness function), set  $i' = i$ . Note this is for the case when a higher fitness function is better. For the case when a lower fitness function is better, set  $i' = i$  when  $f(i) < f(i')$ .
5. Put  $i$  into the Tabu table. Update aspiration criteria.
6. If a stopping condition is met, stop. Else, go to step 2.

There are several possible stopping criteria, such as:

- There are no more feasible solutions in the neighbourhood of the current solution
- $k$  is larger than the maximum number of allowed iterations
- The number of iterations since the last improvement of  $i'$  is greater than a specified number — meaning that convergence has been reached, and that there are diminishing returns on finding a more optimal solution
- An optimal solution has been obtained. There would need to be a method to find what the vicinity of the optimal solution, so that upper lower bounds can be set.

Tabu search has been used to solve the university timetabling problem [3]. Awad et al. defined four different neighbourhoods:

- Nb1: Randomly choose a particular course and progress to a feasible timeslot, which can produce the smallest cost
- Nb2: Randomly select a room. Also, randomly select two courses for that room. Next, swap timeslots.
- Nb3: Randomly select two times. Next, swap timeslots.
- Nb4: Randomly select a particular time and swap it with another time, in the range between 0 and 44, which can produce the smallest penalty cost.

In order to produce an initial solution which met all the hard constraints, a least saturation degree algorithm is used, where events that are more different to schedule are scheduled first. If that did not

produce a feasible solution, then Nb1 is used for a specific number of repetitions, then Nb2 is used for a specific number of repetitions if Nb1 did not reach a feasible solution. Next an improvement algorithm was used with Nb3 and Nb4, specifically adaptive Tabu search. The penalty cost is checked every 1,000 iterations and if the penalty cost has not changed, then two solutions are removed from the Tabu List.

The authors compared their algorithm to the work of others, by running 11 different datasets through them, and totalling the number of violations of their hard and soft constraints. The authors' algorithm performed best against other implementations of Tabu search, and was also compared to other algorithms that did not use Tabu search at all. The authors' implementation performed better than all the other algorithms, except variable neighbourhood search on the largest dataset, and simulated annealing which performed better across all dataset sizes.

### 1.2.4 Answer Set Programming

Answer set programming (ASP) reduces problems to logic programs, and then answer set solvers are used to do the search [4]. The logic programs are sets of rules that take the form:

$$a_0 :- a_1, \dots, a_m \text{ not } a_{m+1}, \dots, \text{ not } a_n$$

where every  $a_i$  is a propositional atom and `not` is default negation. If  $n = 0$  then a rule is a fact. A rule is an integrity constraint if  $a_0$  is omitted. A logic program induces a collection of answer sets, which are recognized models of the program determined by answer set semantics.

To make ASP better for real-world use, some extensions were developed. Rules with first-order variables are viewed as shorthand for the set of their ground instances. Additionally, there are conditional literals that take the form:

$$a : b_1, \dots, b_m$$

where  $a$  and  $b_i$  are possibly default-negated variables. There are also cardinality constraints which take the form:

$$s \{c_1, \dots, c_n\} t$$

where each  $c_j$  is a conditional literal.  $s$  and  $t$  provide lower and upper bounds on the number of satisfied literals in the cardinality constraint. For example,  $2 \{a(X) : b(X)\} 4$  is true when 2, 3 or 4 instances of  $(X)$  (subject to  $b(X)$ ) are true. Also  $N = c_1, \dots, c_n$  binds  $N$  to the number of satisfied conditional literals  $c_j$ . And objective functions that minimise the sum of weights  $w_j$  of conditional literals  $c_j$  are expressed as `#minimize {  $w_1 : c_1, \dots, w_n : c_n$  }`.

The logic programs can be written in a language called AnsProlog (Answer Set Programming in Logic), which can be used with answer set solvers such as `smodels`.

Banbara et al. (2019)[4] used Answer Set Programming to solve the timetabling problem. They split their constraints into hard and soft constraints, where the soft constraints have either constant cost or calculated cost. If a constraint has constant cost, then there is one penalty point per violation, whereas constraints that have a calculated cost attached to them have their penalty points calculated dynamically with each violation. The authors defined their constraints as:

- $H_1$  **Lectures**: All lectures of each course must be scheduled, and they must be assigned to distinct timeslots.
- $H_2$  **Conflicts**: Lectures of courses in the same curriculum or taught by the same teacher must be all scheduled in different timeslots.
- $H_3$  **RoomOccupancy**: Two lectures cannot take place in in the same room in the same timeslot.
- $H_4$  **Availability**: If the teacher of the course is unavailable to teach that course at a given timeslot, then no lecture of the course can be scheduled at that timeslot.
- $S_1$  **RoomCapacity**: For each lecture, the number of students that attend the course must be less than or equal the number of seats of all the room that host its lectures. The penalty points, reflecting the number of students above the capacity, are imposed on each violation.
- $S_2$  **MinWorkingDays**: The lectures of each course must be spread into a given minimum number of days. The penalty points, reflecting the number of days below the minimum, are imposed on each violation.
- $S_3$  **IsolatedLectures**: Lectures belonging to a curriculum should be adjacent to each other in consecutive timeslots. For a given curriculum we account for a violation every time there is one lecture not adjacent to any other lecture within the same day. Each isolated lecture in a curriculum counts as one violation.
- $S_4$  **Windows**: Lectures belonging to a curriculum should not have time windows (periods without teaching) between them. For a given curriculum we account for a violation every time there is one window between two lectures within the same day. The penalty points, reflecting the length in periods of time window, are imposed on each violation.
- $S_5$  **RoomStability**: All lectures of a course should be given in the same room. The penalty points, reflecting the number of distinct rooms but the first, are imposed on each violation.
- $S_6$  **StudentMinMaxLoad**: For each curriculum, the number of daily lectures should be within a given range. The penalty points, reflecting the number of lectures below the minimum or above the maximum, are imposed on each violation.

- $S_7$  **TravelDistance**: Students should have the time to move from one building to another one between two lectures. For a given curriculum we account for a violation every time there is an instantaneous move: two lectures in rooms located in different buildings in two adjacent periods within the same day. Each instantaneous move in a curriculum counts as 1 violation.
- $S_8$  **RoomSuitability**: Some rooms may not be suitable for a given course because of the absence of necessary equipment. Each lecture of a course in an unsuitable room counts as 1 violation.
- $S_9$  **DoubleLectures**: Some courses require that lectures in the same day are grouped together (double lectures). For a course that requires grouped lectures, every time there is more than one lecture in one day, a lecture non-grouped to another is not allowed. Two lectures are grouped if they are adjacent and in the same room. Each non-grouped lecture counts as 1 violation.

A solution is feasible when all the hard constraints are satisfied, but the objective is to find a solution with the minimal penalty cost. The authors formulated the problem in different ways, where a formulation is defined as specific set of soft constraints together with weights associated with each of them. Different formulations allow for timetables to be generated for different scenarios — for instance, double lectures may not be required, so the constraint  $S_9$  would not be used. Formally, the timetabling problem is formulated as a combinatorial optimisation problem with the objective function to minimise the weighted sum of the penalty points.

Next, the authors encoded the constraints and facts into the correct format for the specific ASP system, which then returned an assignment representing a solution.

When testing, the authors used multiple sets of input data, some of which were very large, for instance, one of them consisted of 850 courses, 132 rooms, 850 curricula, 7,780 unavailability constraints, and 45,603 room constraints. The system was run on a cluster of machines with server-grade hardware, which was probably necessary given the size of the datasets. They also used different configurations for their ASP system, all of which managed to produce optimal solutions.

### 1.2.5 Bat Inspired Algorithm

The Bat Inspired Algorithm (BA) is a heuristic method originally proposed by Yang (2010) [10]. It is inspired by echolocation, which is a method used by bats and other animals to navigate, using sound. To simplify echolocation, Yang suggested these rules:

1. Bats use echolocation to determine distance, and they can differentiate between food and barriers.
2. Bats fly randomly with velocity  $v_i$  at position  $x_i$  having a fixed frequency  $f_{\min}$ , varying wave-

length  $\lambda$  and loudness  $A_i$  to search for prey. In this rule, it is assumed that bats can adjust automatically the frequency (or wavelength) of their emitted pulses as well the rate of pulse emission  $r \in [0, 1]$ . The automatic adjustment relies on the proximity of the target.

3. The loudness of the bats can vary in many ways, however, it is assumed that the loudness can vary from between positive values  $A_0$  and  $A_{\min}$ .

Pseudocode for the Bat Algorithm can be described as:

Define the objective function  $f(x)$

Generate initial population of the bat  $X = \{x_1, \dots, x_n\}$

For each bat  $x_i$  in  $X$

Initialise the pulse rate  $r_i$ , velocity  $v_i$  and loudness  $A_i$

Define the pulse frequency  $f_i$

End for

While termination criterion not reached

For each bat  $x_i$  in  $X$

Generate new solutions using equations (1.1), (1.2) and (1.3)

Generate a random number  $rand$

If  $rand > r_i$

Select one solution among the best one

Generate a local solution around one of the best

End if

If  $(rand < A_i)$  and  $(f(x_i) < f(x_*))$

Accept the new solution

Increase  $r_i$  and reduce  $f(x_i)$

End if

End for

End while

Ranks the bats and obtain the current best bat

[6]

In the first step, the bat population initialised with parameters position  $x_i$ , velocity  $v_i$  and frequency  $f_i$ . With each generation, every bat moves by changing velocity  $v_i^t$  and position  $x_i^t$  at time  $t$  with the equations:

$$f_i = f_{\min} + (f_{\max} - f_{\min})\beta \quad (1.1)$$

$$v_i^t = v_i^{t-1} + (x_i^{t-1} - x_*)f_i \quad (1.2)$$

$$x_i^t = x_i^{t-1} + v_i^t \quad (1.3)$$



where  $\beta$  is a random number from the interval  $[0, 1]$  and  $x_*$  represents the current best global solution among all the bats in the population.

In the local search part, a new solution for each bat is generated using a random walk:

$$x_{new} = x_{old} + \epsilon < A^t >$$

where  $\epsilon$  is a random number from the interval  $[0, 1]$  and  $< A^t >$  is the average loudness of the bats in the population at a specific time step  $t$ . Also the rate of sound pulse emission  $r_i$  and the loudness  $A_i$  of each bat needs to be updated with the equation,:

$$A_i^t = \alpha A_i^{t-1}$$

$$r_i^t = r_i^0 [1 - e^{-\gamma t}]$$

where  $\alpha$  and  $\gamma$  are constants.

The above BA was designed for continuous optimisation problems, but as the timetabling problem is a discrete combinatorial optimisation problem, Limota et al. (2021) [6] modified the algorithm. In the context of the timetabling problem,  $i$  represents a candidate solution and each position  $x_i$  is initialised by randomly choosing a lecture and then an algorithm tries to find timeslots without clashes and a large enough room. This is to start with a good initial timetable.

The parameter frequency  $f_i$  is fixed to 1 to reduce the complexity of the algorithm, meaning that velocity is now calculated as:

$$v_i^t = f(x_i) - f(x_*)$$

$v_i$  can be interpreted as the number of operations that bat  $i$  will perform in updating the current position. The new position  $x_i^t$  is calculated with Equation 1.3, which implies that the current position is dependent on velocity and the previous position. But now, this can be interpreted to mean that the current position is obtained by performing  $v_i^t$  moves.

To update the current solution of an instance of the timetabling problem, a lecture is moved from one timeslot to another randomly selected one.

When testing their algorithm, the authors used input data consisting of 124 courses, 273 lectures, 10 rooms and 5551 students. They ran their algorithm 4 times, and each time generated timetables where all the hard constraints were satisfied.

### 1.3 Comparison of Methods

The below table summarises how the different methods for solving the timetabling problem performed.

	Genetic Algorithm[8]	Binary Integer Prog.[2]	Tabu Search[3]	Answer Set Prog.[4]	Bat Inspired Algorithm[6]
Dataset size (number of courses)	340	3	400*	850	124
Solution generated?	Yes	Yes	Yes	Yes	Yes
Errors?	84 students had at least one clash	None	347* hard/soft constraint violations	None	None

Table 1.1: Summative table of the results of the different methods.

\*largest dataset

It is also worth recalling a few other details about the different methods used:

- At the university used for the genetic algorithm method [8], courses are arranged in such a way that essentially every student has a unique timetable, therefore making the problem more complex compared to if students were put into groups.
- Multiple different configurations were used for the answer set programming system [4], some of which were able to produce a greater number of optimal solutions than others.

## 1.4 Chosen Method

I will not be using binary integer programming as my chosen method, as it was only tested on such a small dataset it is unknown how performance will scale for larger datasets. Likewise, I will not be using answer set programming as the dataset was so large that the algorithm had to be run on server-grade hardware, which I do not have access to, and I do not know how the performance scales with a decrease in the dataset size. I am not going to use Tabu search, as there were a large number of constraint violations in relation to the size of the dataset. I have hence decided to use a genetic algorithm as I think it would be easier to implement than a bat inspired algorithm.

# Chapter 2

## Requirements

### 2.1 Necessary Requirements

These are requirements that are specified by the project briefing, and it is ideal that they are all achieved.

1. The required information for the timetable can be entered by the user.
2. A correct timetable is generated, where:
  - (a) Every module has all its hours timetabled.
  - (b) A room is being used for at most one learning session in a time slot.
  - (c) A student has at most one learning session in a time slot.
  - (d) A teacher has at most one learning session in a time slot.
  - (e) A session is in the correct type of room, for example, a lecture is in a lecture theatre, and a lab session is in a lab.
  - (f) The number of students in the room must not exceed the capacity of the room.
  - (g) The size of the room is optimal for the number of students, meaning that the size of the room as small as possible.
  - (h) Teachers can make preferences for when they are teaching.
3. The generated timetable is returned to the user in a way that they can understand.

## 2.2 Aspirational Requirements

These are requirements that could be achieved, but are not essential for completion.

- Use a graphical user interface.
- Allow the user to change the parameters of the genetic algorithm.
- Return the final timetable as multiple timetables individualised to each teacher, student group, room, etc. The timetables should be in a very legible format, such as in a traditional tabular timetable format.

# Chapter 3

## Design

### 3.1 Modelling the Input Data

Before the whole algorithm can be modelled mathematically, we must first model the input data as set of variables.

- Let  $T = \{t_1, \dots, t_n\}$  be the set of teachers where:
  - a teacher  $t_i = \{M_{t_i}, H_{t_i}\}$  where:
    - \*  $H_{t_i} = \{h_{t_{i_1}}, \dots, h_{t_{i_n}}\}$  is the set of the teacher's preferred timeslots, and
    - \*  $M_{t_i} = \{m_{t_{i_1}}, \dots, m_{t_{i_n}}\}$  is the set of modules that the teacher teaches.
- Let  $R = \{r_1, \dots, r_n\}$  be the set of rooms where:
  - a room  $r_i = \{y_{r_i}, c_{r_i}\}$  where:
    - \*  $y_{r_i}$  is the type of room, which takes the value 1 if the room is a lecture theatre, or 2 if the room is a lab, and
    - \*  $c_{r_i}$  is the maximum capacity of the room.
- Let  $S = \{s_1, \dots, s_n\}$  be the set of student groups where:
  - a student group  $s_i = \{M_{s_i}, z_{s_i}\}$  where:
    - \*  $M_{s_i} = \{m_{s_{i_1}}, \dots, m_{s_{i_n}}\}$  is the set of modules taken by the student group  $s_i$ , and
    - \*  $z_{s_i}$  is the number of students in  $s_i$ .
- Let  $M = \{m_1, \dots, m_n\}$  be the set of modules where:
  - a module  $m_i = \{p_{m_i}, q_{m_i}\}$  where:

\*  $p_{m_i}$  is the number of lecture hours of the module  $m_i$ , and

\*  $q_{m_i}$  is the number of lab hours of the module  $m_i$ .

- Let  $H = \{h_1, \dots, h_n\}$  be the set of time slots.

Further to this, we can also describe a set of teaching sessions  $X$  where each session  $x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon}$  is a session taught by teacher  $t_\alpha$ , in room  $r_\beta$ , with student group  $s_\gamma$ , about module  $m_\delta$ , during time slot  $h_\epsilon$ .

## 3.2 Constraints

We next need to represent the constraints. We take the requirements from §2.1, but add two more constraints (2 and 3).

1. Every module has all its hours timetabled.
2. Each session is taught by the correct teacher for the module.
3. Each session has the correct student group attending it.
4. A room is being used for at most one learning session in a time slot.
5. A student has at most one learning session in a time slot.
6. A teacher has at most one learning session in a time slot.
7. A session is in the correct type of room, for example, a lecture is in a lecture theatre, and a lab session is in a lab.
8. The number of students in the room must not exceed the capacity of the room.
9. The size of the room is optimal for the number of students, meaning that the size of the room is as small as possible.
10. Teachers can make preferences for when they are teaching.

We will now formulate these constraints below.

### 3.2.1 Every module has all its hours timetabled

We can say that the number of sessions scheduled is equal to the sum of the number of lecture sessions and the number of lab sessions for all the modules, or:

$$|X| = \sum_{i=1}^{|M|} (p_{m_i} + q_{m_i})$$

However, this is not sufficient to prove that the correct number of sessions per module has been scheduled, for instance one module might be missing a session and another module might have an extra session scheduled, and the above statement would still hold. To further prove this, we also have constraint 7.

### 3.2.2 Each session is taught by the correct teacher for the module

This can be reworded to: for every session, the module taught in that session is in the set of modules taught by the teacher, or:

$$\forall x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \in X, m_\delta \in M_{t_\alpha}$$

### 3.2.3 Each session has the correct student group attending it

Very similarly to the previous constraint, this constraint can be reworded to: for every session, the module taught in that session is in the set of modules taken by the student group, or:

$$\forall x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \in X, m_\delta \in M_{s_\gamma}$$

### 3.2.4 A room is being used for at most one learning session in a time slot

This can be rephrased as: for each room, there is at most one of each time slot scheduled for that room.

$$\forall r_i \in R, \exists X_{r_i} \subseteq X \text{ where } X_{r_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid r_\beta = r_i\}$$

This creates subsets  $X_{r_i}$  which are all the learning sessions scheduled to the room  $r_i$ . Then:

$$\forall h_j \in H \exists X_{r_i, h_j} \subseteq X_{r_i} \text{ where } X_{r_i, h_j} = \{x_{t_\alpha, r_i, s_\gamma, m_\delta, h_\epsilon} \mid h_\epsilon = h_j\}$$

This creates subsets  $X_{r_i, h_j}$  which are all the learning session scheduled in time slot  $h_j$  for the room  $r_i$ . We then require the condition

$$|X_{r_i, h_j}| = 1 \text{ or } |X_{r_i, h_j}| = 0$$

to hold  $\forall X_{r_i, h_j}$ .

### 3.2.5 A student has at most one learning session in a time slot

This very similar to constraint 4.

$$\forall s_i \in S, \exists X_{s_i} \subseteq X \text{ where } X_{s_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid s_\gamma = s_i\}$$

$$\forall h_j \in H \exists X_{s_i, h_j} \subseteq X_{s_i} \text{ where } X_{s_i, h_j} = \{x_{t_\alpha, r_\beta, s_i, m_\delta, h_\epsilon} \mid h_\epsilon = h_j\}$$

It is then required that

$$|X_{s_i, h_j}| = 1 \text{ or } |X_{s_i, h_j}| = 0, \forall X_{s_i, h_j}.$$

### 3.2.6 A teacher has at most one learning session in a time slot

This very similar to constraints 4 and 5.

$$\forall t_i \in T, \exists X_{t_i} \subseteq X \text{ where } X_{t_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid t_\alpha = t_i\}$$

$$\forall h_j \in H \exists X_{t_i, h_j} \subseteq X_{t_i} \text{ where } X_{t_i, h_j} = \{x_{t_i, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid h_\epsilon = h_j\}$$

It is then required that

$$|X_{t_i, h_j}| = 1 \text{ or } |X_{t_i, h_j}| = 0, \forall X_{t_i, h_j}.$$

### 3.2.7 A session is in the correct type of room

This can be thought of as: for each module, the number of sessions in a lecture room is equal to the number of lecture sessions for that module. The same applies for lab sessions.

To begin with (recall that  $y_{r_i} = 1$  if  $r_i$  is a lecture room):

$$\exists X_{lecture} \subseteq X \text{ where } X_{lecture} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid \forall r_\beta, y_{r_\beta} = 1\}$$

This gives us  $X_{lecture}$ , a set that contains all the sessions in a lecture room. Then:

$$\forall m_i \in M, \exists X_{lecture, m_i} \subseteq X_{lecture} \text{ where } X_{lecture, m_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid m_\delta = m_i\}$$

Finally, it is required that

$$\forall X_{lecture, m_i}, |X_{lecture, m_i}| = p_{m_i}.$$

Similarly, for labs:

$$\exists X_{lab} \subseteq X \text{ where } X_{lab} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid \forall r_\beta, y_{r_\beta} = 2\}$$

$$\forall m_i \in M, \exists X_{lab, m_i} \subseteq X_{lab} \text{ where } X_{lab, m_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid m_\delta = m_i\}$$

and it is required that

$$\forall X_{lab, m_i}, |X_{lab, m_i}| = p_{m_i}.$$

As teaching sessions are either labs or lectures, it can be implied that  $|X_{lecture}| + |X_{lab}| = |X|$ .

Because of the above, there are the correct number of lectures and labs for each module, and the conditions are now sufficient for constraint 1 to hold.



### 3.2.8 The number of students in the room must not exceed the capacity of the room

This can be reworded to: for every session, the size of the student group must be less than or equal to the capacity of the room, or:

$$\forall x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \in X, z_{s_\gamma} \leq c_{r_\beta}$$

### 3.2.9 The size of the room is optimal for the number of students

This means, for every session  $x_i \in X$  in room  $r_i$ , if there exists a room  $r_j \in R$  where  $c_{r_j} < c_{r_i}$ , change  $r_i$  to  $r_j$ , only if no other constraints are violated. Or,  $r_i = \min\{r_j \mid c_{r_j} \geq c_{r_i}\} \in R$ .

### 3.2.10 Teachers can make preferences for when they are teaching

We first define a set of sessions for each teacher:

$$\forall t_i \in T, \exists X_{t_i} \subseteq X \text{ where } X_{t_i} = \{x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \mid t_\alpha = t_i\}$$

We then define a set containing just the time slots for each  $X_{t_i}$ :

$$\forall X_{t_i}, \exists H_{X_{t_i}} \text{ where } H_{X_{t_i}} = \{h_j \mid h_j = h_\epsilon \forall x_{t_\alpha, r_\beta, s_\gamma, m_\delta, h_\epsilon} \in X_{t_i}\}$$

Then, for the constraint to be satisfied,  $H_{X_{t_i}} \subseteq H_{t_i}$  must hold  $\forall t_i \in T$ , or alternatively, the constraint is violated if  $\exists H_{X_{t_i}} \ni h_j \notin H_{t_i}$ .

## 3.3 Timetable Encoding

A solution will be encoded as a set of 5-tuples, where each tuple is {time slot, room, student group, module, teacher}, where a solution represents an entire timetable.

For the genetic algorithm, the population is a set of solutions.

## 3.4 Genetic Algorithm Pseudocode

```
1 function GeneticAlgorithm
2
3   GetSettingsData (return: populationSize, mutationChance)
4   GetConfigData (return: sessions, rooms, timeSlots, teacherTimes)
5   CreatePopulation (return: population)
```

```

6 CheckFitness of population (return: populationFitness,
7                             validSolution, validSolutionBool)
8 while not validSolutionBool:
9     SelectParents (return: parentA, parentB)
10    CreateOffspring (return: offspring)
11    MutateOffspring (return: mutatedOffspring)
12    append parents to mutatedOffspring
13    CheckFitness of mutatedOffspring (return: offspringFitness,
14                                     validSolution, validSolutionBool)
15    if not validSolutionBool:
16        population := offspring
17        repeat(2):
18            remove individual from population with worst fitness
19        end repeat
20    end if
21 end while
22 output timetable from validSolution

```

The settings data contains `populationSize` and `mutationChance`, which are parameters for the genetic algorithm the user may wish to change. `populationSize` is quite self-explanatory, simply the number of individuals in the population. `mutationChance` is the reciprocal of the actual chance of a mutation occurring, for example, if the chance of a mutation occurring is  $\frac{1}{1000}$ , then `mutationChance` needs to be 1000.

Note that the `CheckFitness` function is called both inside the while loop and before it. This is so that the initial population generated can be checked for a valid solution, removing the need to proceed with the rest of the algorithm. Hence, the population's fitness needs to be calculated again inside the while loop, after the mutation phase.

### 3.4.1 Initial Population

```

1 function CreatePopulation
2 input: sessions, rooms, timeSlots, populationSize
3
4 population := empty list
5 repeat(populationSize):
6     solution := empty list
7     for session in sessions:

```

```

8         timeSlot := random(timeSlots)
9         room := random(rooms)
10        studentGroup := session[1]
11        module := session[0]
12        teacher := session[2]
13        newSession := (timeSlot, room, studentGroup, module, teacher)
14        append newSession to solution
15    end for
16    append solution to population
17 end repeat
18 return population

```

### 3.4.2 Fitness Function

```

1 function CheckFitness
2 input: population, teacherTimes
3
4 populationFitness := empty list
5 validSolutionBool := False
6 validSolution := None
7 for each solution in population:
8     sort solution by timeSlot
9     violations := 0
10    for i in range(size(solution) - 1):
11        if solution[i][0] == solution[i + 1][0]:
12            if solution[i][1] == solution[i + 1][1]:
13                violations := violations + 1
14            end if
15            if solution[i][2] == solution[i + 1][2]:
16                violations := violations + 1
17            end if
18            if solution[i][4] == solution[i + 1][4]:
19                violations := violations + 1
20            end if
21        end if
22    end for
23    for in range(size(solution)):

```

```

24         timeSlot = solution[i][0]
25         teacherNumber = solution[i][4]
26         CONTINUE WHEN FINISHED CODE
27     end for
28     if violations == 0:
29         solutionFitness := 0
30     else:
31         solutionFitness := 1 / violations
32     end if
33     append solutionFitness to populationFitness
34     if solutionFitness == 0:
35         valid solution bool := True
36         valid solution := solution
37         break for loop
38     end if
39 end for
40 return populationFitness, validSolution, validSolutionBool

```

### 3.4.3 Selection

```

1 function SelectParents
2 input: populationFitness
3
4 NormaliseValues(return: normalisedLimits)
5 ChooseParent(return: parentA)
6 remove the fitness of parentA from populationFitness
7 NormaliseValues(return: normalisedLimits)
8 ChooseParent(return: parentB)
9 return parentA, parentB

```

explain what normalised limits and choose parents are

### 3.4.4 Crossover

```

1 function CreateOffspring
2 input: populationSize, numOfSessions, parentA, parentB
3
4 offspring := empty list

```

```

5  halfPop := ceiling(populationSize / 2)
6  for i in range(halfPop):
7      outerLocus := RandomInteger(0, numOfSessions - 1)
8      if outerLocus == 0:
9          innerLocus := RandomInteger(1, 2)
10     else:
11         innerLocus := RandomInteger(0, 2)
12     end if
13     leftA := parentA[:outerLocus]
14     centreA = parentA[outerLocus][:innerLocus]
15             + parentB[outerLocus][innerLocus:]
16     rightA := parentB[outerLocus + 1:]
17     append centreA to leftA
18     childA := leftA + rightA
19     append childA to offspring
20     leftB := parentB[:outerLocus]
21     centreB := parentB[outerLocus][innerLocus]
22             + parentA[outerLocus][innerLocus:]
23     rightB := parentA[outerLocus + 1:]
24     append centreB to leftB
25     childB := leftB + rightB
26 end for
27 if halfPop /= floor(populationSize / 2):
28     delete the last element in offspring
29 end if
30 return offspring

```

### 3.4.5 Mutation

```

1  function MutateOffspring
2  input: offspring, mutationChance, timeSlots, rooms, sessions
3
4  mutatedOffspring = offspring
5  for solution in mutatedOffspring:
6      for session in solution:
7          for i in range(3):
8              mutate = RandomInteger(1, mutationChance)

```

```

9         if mutate == 0:
10             match i:
11                 case 0:
12                     newTimeSlot = random(timeSlots)
13                     offspring[solution][session][0] := newTimeSlot
14                 end case
15                 case 1:
16                     newRoom = random(rooms)
17                     offspring[solution][session][1] := newRoom
18                 end case
19                 case _:
20                     newSession = random.choice(sessions)
21                     offspring[solution][session][2] := newSession[0]
22                     offspring[solution][session][3] := newSession[1]
23                     offspring[solution][session][4] := newSession[2]
24                 end case
25             end match
26         end if
27     end for
28 end for
29 end for
30 return mutatedOffspring

```

## Chapter 4

# Implementation

# Chapter 5

## Testing



# Chapter 6

## Evaluation

## Chapter 7

## Conclusion

# References

- [1] IIT Kharagpur July 2018. Lecture 37: Tabu search. <https://www.youtube.com/watch?v=A7cTp1Fhg9o>, Sept. 2018.
- [2] Moustapha Abdellahi and Hussein Eledum. The university timetabling problem: modeling and solution using binary integer programming with penalty functions. *International Journal of Applied Mathematics and Statistics*, 56(6):164–178, 2017.
- [3] Fouad H Awad, Ali Al-Kubaisi, and Maha Mahmood. Large-scale timetabling problems with adaptive tabu search. *Journal of Intelligent Systems*, 31(1):168–176, 2022.
- [4] Mutsunori Banbara, Katsumi Inoue, Benjamin Kaufmann, Tenda Okimoto, Torsten Schaub, Takehide Soh, Naoyuki Tamura, and Philipp Wanko. teaspoon: solving the curriculum-based course timetabling problems with answer set programming. *Annals of Operations Research*, 275:3–37, 2019.
- [5] Cuemath. Objective function. <https://www.cuemath.com/algebra/objective-function/>. Accessed: 2022-12-22.
- [6] Ushindi Limota, Egbert Mujuni, and Allen Mushi. Solving the university course timetabling problem using bat inspired algorithm. *Tanzania Journal of Science*, 47(2):674–685, 2021.
- [7] Melanie Mitchell. *An introduction to genetic algorithms*. MIT press, 1998.
- [8] Radomír Perzina. Solving the university timetabling problem with optimized enrollment of students by a self-adaptive genetic algorithm. In *International Conference on the Practice and Theory of Automated Timetabling*, pages 248–263. Springer, 2006.
- [9] Stanford University. Penalty functions. <https://web.stanford.edu/group/sisl/k12/optimization/MO-unit5-pdfs/5.6penaltyfunctions.pdf>. Accessed: 2022-12-22.
- [10] Xin-She Yang. A new metaheuristic bat-inspired algorithm. In *Nature inspired cooperative strategies for optimization (NICSO 2010)*, pages 65–74. Springer, 2010.

# Appendix A

## Source Code

### A.1 main.py

```
1 """Main menu for the timetable maker.
2
3 Functions:
4     menu()
5     clear()
6     get_user_input()
7 """
8 from os import system, name
9 import ga
10
11
12 def menu():
13     """Print a welcome message to the user, with instructions."""
14     clear()
15     print("Timetable Maker\nPlease ensure that config.json is filled in
16 \
17 correctly. \nType start to create a timetable with output to a text \
18 file, or type help for more commands")
19     get_user_input()
20
21 def clear():
```

```

22     """Clear the terminal display."""
23     if name == "nt": # Windows
24         _ = system("cls")
25     else: # *nix based systems (Linux, MacOS, etc)
26         _ = system("clear")
27
28
29 def get_user_input():
30     """Get text input from the user."""
31     user_input = input()
32     match user_input:
33         case "start":
34             ga.generate_timetable()
35         case "help":
36             print("Please read the documentation.")
37             get_user_input()
38         case _:
39             print("'" + user_input + "' is not a recognised command.
Type \
40             help for the help guide")
41             get_user_input()
42
43
44 if __name__ == "__main__":
45     menu()

```

## A.2 ga.py

```

1 """Genetic algorithm base.
2
3 Functions:
4     generate_timetable()
5     get_settings_data() -> [int, int]
6     generate_output_text(solution: list, person_type: str)
7 """
8 import initial_population as p1
9 import fitness_function as p2

```

```

10 import selection as p3
11 import crossover as p4
12 import mutation as p5
13 import json
14
15
16 def generate_timetable():
17     """Generate the timetable.
18
19     Basis of the timetable generation, goes through the whole of the
20     genetic algorithm.
21     """
22     population_size, mutation_chance = get_settings_data()
23     sessions, rooms, time_slots, teacher_times = p1.get_config_data()
24     print("Generation 1:")
25     generation_count = 1
26     population = p1.generate_initial_population(sessions, rooms,
27                                                time_slots,
28                                                population_size)
29     print(population)
30     population_fitness, valid_solution_bool, valid_solution = \
31         p2.check_population_fitness(population, teacher_times)
32     for i in range(3): # TODO temp
33         # while not valid_solution_bool: TODO add back
34         # print("No timetable solution found.") TODO: add back
35         parent_a, parent_b = p3.select_parents(population_fitness)
36         # Note that parent_a and parent_b are indices
37         print("pop size:") # TODO remove
38         print(population_size) # TODO remove
39         offspring = p4.crossover(population[parent_a], population[
40                                 parent_b],
41                                 len(population[0]), population_size)
42         mutated_offspring = p5.mutate(offspring, time_slots, rooms,
43                                       sessions,
44                                       mutation_chance)
45         mutated_offspring.append(population[parent_a])
46         mutated_offspring.append(population[parent_b])

```

```

44         # check if any of the offspring is a valid solution
45         population_fitness, valid_solution_bool, valid_solution \
46             = p2.check_population_fitness(mutated_offspring,
teacher_times)
47         if not valid_solution_bool:
48             population = mutated_offspring
49             for i in range(2):
50                 worst_fitness = max(population_fitness)
51                 worst_fitness_index = population_fitness.index(
worst_fitness)
52                 del population_fitness[worst_fitness_index]
53                 del population[worst_fitness_index]
54                 generation_count += 1
55                 print("Generation " + str(generation_count) + ":")
56                 print(population)
57                 print(population_fitness)
58             print("Timetable solution found. Writing output to text files...")
59             generate_output_text(valid_solution, "teachers")
60             generate_output_text(valid_solution, "student_groups")
61             print("Output written to files in ./teacher-timetables and \
62                 ./student-group-timetables.")
63
64
65 def get_settings_data() -> [int, int]:
66     """Get settings for timetable generation.
67
68     Returns:
69         int: Population size set by the user.
70         int: Chance of mutation set by the user.
71     """
72     file = open("settings.json", "r", encoding="utf-8")
73     settings = json.load(file)
74     file.close()
75     population_size = int(settings["population-size"])
76     mutation_chance = int(settings["mutation-chance"])
77     return population_size, mutation_chance
78

```

```

79
80 def generate_output_text(solution: list, person_type: str):
81     """Generate output of a correct timetable to text files.
82
83     Args:
84         solution (list): A correct timetable solution.
85         person_type (str): Who the timetable is for, student_groups or
teachers
86     """
87     dictionary = {}
88     file = open("data.json", "r", encoding="utf-8")
89     data = json.load(file)
90     file.close()
91
92     for person in data[person_type]:
93         dictionary.update({person["id"]: []})
94     for session in solution:
95         if person_type == "teachers":
96             session_person = session[4]
97         else: # session_person == "student_groups"
98             session_person = session[2]
99         session_person_list = dictionary.get(session_person)
100         session_person_list.append(session)
101         dictionary.update({session_person: session_person_list})
102
103     print("Creating directory for " + str(person_type) + " timetables
...")
104     try:
105         os.mkdir("./" + str(person_type) + "_timetables")
106         print("Directory '" + str(person_type) + "_timetables' created.
")
107     except FileExistsError:
108         print("Directory already exists.")
109     for session_person in dictionary:
110         file = open(str(session_person) + ".txt", "w", encoding="utf-8"
)
111         person_sessions = dictionary[session_person]

```



```

112         for session in person_sessions:
113             file.write(str(session))
114         file.close()
115     print("Timetable output files created.")
116     # TODO: formatting?

```

## A.3 initial population.py

```

1  """Phase 1 (initial population) of genetic algorithm.
2
3  Functions:
4      get_config_data() -> [list, list, list, list]
5      generate_initial_population(sessions: list, rooms: list, time_slots
6      : list,
7      population_size: int) -> list
8      create_session_solution(session: list, rooms: list, time_slots:
9      list)
10     -> list
11     create_complete_solution(sessions: list, rooms: list, time_slots:
12     list)
13     -> list
14
15 """
16 import json
17 import random
18
19 def get_config_data() -> [list, list, list, list]:
20     """Get the timetable data from data.json.
21
22     Returns:
23         list: Session consisting of module ID, student group and
24         teacher.
25         list: List of rooms.
26         list: List of time slots.
27         list: List of teachers' preferred time slots.
28
29 """
30     print("Reading data file")

```

```

26     file = open("data.json", "r", encoding="utf-8")
27     data = json.load(file)
28     file.close()
29
30     sessions, rooms_id, time_slots_id = [], [], []
31     for module in data["modules"]:
32         session = [module["id"], module["student_group"], module["
teachers"]]
33         for i in range(int(module["lecture_hours"])):
34             sessions.append(session)
35         for i in range(int(module["lab_hours"])):
36             sessions.append(session)
37
38     for room in data["rooms"]:
39         rooms_id.append(room["id"])
40
41     day_number = 1
42     for day in data["time_slots"]:
43         for start_time in range(len(day["start_times"])):
44             time_number = day["start_times"][start_time]
45             time_slots_id.append(str(day_number) + str(time_number))
46             day_number += 1
47
48     teacher_times = []
49     for teacher in data["teachers"]:
50         teacher_time = []
51         for day in teacher["available_times"]:
52             match day:
53                 case "Monday":
54                     day_number = 1
55                 case "Tuesday":
56                     day_number = 2
57                 case "Wednesday":
58                     day_number = 3
59                 case "Thursday":
60                     day_number = 4
61                 case "Friday":

```

```

62         day_number = 5
63     case "Saturday":
64         day_number = 6
65     case "Sunday":
66         day_number = 7
67     case _:
68         day_number = 0
69     for i in range(len(day["start_times"])):
70         time_number = day["start_times"][i]
71         teacher_time.append(str(day_number) + str(time_number))
72     teacher_times.append(teacher_time)
73
74     return sessions, rooms_id, time_slots_id, teacher_times
75
76
77 def generate_initial_population(sessions: list, rooms: list,
78                                time_slots: list, population_size: int)
79     \
80         -> list:
81     """Generate the first population randomly from the imported data.
82
83     Args:
84         sessions (list): List of sessions consisting of module ID,
85         student
86         group and teacher.
87         rooms (list): List of rooms.
88         time_slots (list): List of time slots.
89         population_size (int): Size of the population.
90
91     Returns:
92         list: The generated population.
93     """
94     print("Generating initial population...")
95     population = []
96     for i in range(population_size):
97         solution = create_complete_solution(sessions, rooms, time_slots
98 )

```

```

96         population.append(solution)
97     print("Initial population generated.")
98     return population
99
100
101 def create_session_solution(session: list, rooms: list, time_slots:
    list) \
102     -> list:
103     """Create a session, to become part of a solution.
104
105     Args:
106         session (list): A single session consisting of module ID,
student
107         group and teacher.
108         rooms (list): List of rooms.
109         time_slots (list): List of time slots.
110
111     Returns:
112         list: The complete session with time slot and room.
113     """
114     time_slot = random.choice(time_slots)
115     room = random.choice(rooms)
116     student_group = session[1]
117     module = session[0]
118     teacher = session[2]
119     solution = [time_slot, room, student_group, module, teacher]
120     return solution
121
122
123 def create_complete_solution(sessions: list, rooms: list, time_slots:
    list) \
124     -> list:
125     """Create a complete solution from a list of session solutions.
126
127     Args:
128         sessions (list): List of sessions consisting of module ID,
student

```

```

129         group and teacher.
130     rooms (list): List of rooms.
131     time_slots (list): List of time slots.
132
133     Returns:
134         list: A solution, which is a member of the population.
135     """
136     solution = []
137     for session in sessions:
138         session_solution = create_session_solution(session, rooms,
139             time_slots)
140         solution.append(session_solution)
141     return solution

```

## A.4 fitness function.py

```

1 """Phase 2 (fitness function) of genetic algorithm.
2
3 Functions:
4     check_population_fitness(population: list, teacher_times: list) ->
5     [list,
6         bool, list]
7     calculate_fitness(solution: list, teacher_times: list) -> float
8 """
9
10 def check_population_fitness(population: list, teacher_times: list) \
11     -> [list, bool, list]:
12     """Calculate the fitness of the whole population.
13
14     Args:
15         population (list): The population of solutions.
16         teacher_times (list): The time slot preferences of the teachers
17         .
18
19     Returns:
20         list: The fitness values of the population.

```

```

20         bool: Whether or not there is a correct solution.
21         list: The correct solution (if it exists).
22     """
23     # print("Calculating the fitness of individuals...") TODO: add back
24     population_fitness = []
25     valid_solution_bool = False
26     valid_solution = None
27
28     for solution in population:
29         sol_fitness = calculate_fitness(solution, teacher_times)
30         population_fitness.append(sol_fitness)
31         if sol_fitness == 0:
32             valid_solution_bool = True
33             valid_solution = solution
34             break
35
36     # print("Fitness of individuals calculated.") TODO: add back
37     return population_fitness, valid_solution_bool, valid_solution
38
39
40 def calculate_fitness(solution: list, teacher_times: list) -> float:
41     """Calculate fitness of a solution.
42
43     Args:
44         solution (list): A possible solution to the timetabling problem
45         .
46         teacher_times (list): The time slot preferences of the teachers
47         .
48
49     Returns:
50         float: Fitness of the solution.
51     """
52     # Sort by time slot
53     solution.sort(key=lambda x: x[0])
54     problem_count = 0
55
56     for i in range(len(solution) - 1):

```

```

55
56     # Check if sessions are happening at the same time
57     if solution[i][0] == solution[i + 1][0]:
58
59         # Room clash:
60         if solution[i][1] == solution[i + 1][1]:
61             problem_count += 1
62
63         # Student group clash:
64         if solution[i][2] == solution[i + 1][2]:
65             problem_count += 1
66
67         # Teacher clash:
68         if solution[i][4] == solution[i + 1][4]:
69             problem_count += 1
70
71     for i in range(len(solution)):
72
73         # check teacher preferences
74         time_slot = solution[i][0]
75         teacher_num = int(solution[i][4])
76         # TODO: why the FUCK is this not finished?????
77
78     if problem_count == 0:
79         fitness = 0
80     else:
81         fitness = 1 / problem_count
82     return fitness

```

## A.5 selection.py

```

1 """Phase 3 (selection) of genetic algorithm.
2
3 Functions:
4     select_parents(population_fitness: list) -> [int, int]
5     normalise_values(fitness_values: list) -> list
6     choose_parent(range_limits: list) -> int

```

```

7 """
8 import random
9
10
11 def select_parents(population_fitness: list) -> [int, int]:
12     """Select the parents for crossover.
13
14     Args:
15         population_fitness (list): The fitness values of the population
16     .
17
18     Returns:
19         int: Index of the first parent.
20         int: Index of the other parent.
21     """
22     # print("Selecting parents for crossover...") TODO: add back
23     fitness_values = population_fitness
24     range_limits_a = normalise_values(fitness_values)
25     parent_a = choose_parent(range_limits_a)
26     # print("First parent selected.") TODO: add back
27     fitness_values.remove(fitness_values[parent_a])
28
29     range_limits_b = normalise_values(fitness_values)
30     parent_b = choose_parent(range_limits_b)
31     # print("Second parent selected.") TODO: add back
32     return parent_a, parent_b
33
34 def normalise_values(fitness_values: list) -> list:
35     """Normalise the fitness values so that they add up to 1.
36
37     Args:
38         fitness_values (list): The fitness values of the population.
39
40     Returns:
41         list: Cumulative sums of the normalised fitness values.
42     """

```



```

43     fitness_total = 0
44     for value in fitness_values:
45         fitness_total += value
46     range_limits = []
47     for i in range(len(fitness_values)):
48         value_norm = fitness_values[i] / fitness_total
49         range_limits.append(value_norm)
50         if i != 0:
51             range_limits[i] += range_limits[i - 1]
52     range_limits[len(fitness_values) - 1] = 1
53     range_limits.insert(0, 0)
54     return range_limits # limits are upper limits?
55
56
57 def choose_parent(range_limits: list) -> int:
58     """Perform a binary search to get the index of the chosen parent.
59
60     Args:
61         range_limits (list): Cumulative sums of the normalised fitness
        values.
62
63     Returns:
64         int: The index of the chosen parent.
65     """
66     choice = random.random()
67     lower, upper = 0, len(range_limits) - 1
68     found_parent = False
69     parent_index = None
70     while not found_parent:
71         middle = (lower + upper) // 2
72         if lower == upper - 1:
73             found_parent = True
74             parent_index = middle
75         elif range_limits[middle] < choice:
76             lower = middle
77         else:
78             upper = middle

```

```
79     return parent_index
```

## A.6 crossover.py

```
1  """Phase 4 (crossover) of genetic algorithm.
2
3  Functions:
4      crossover(parent_a: list, parent_b: list, num_of_sessions: int,
5                  population_size: int) -> list
6  """
7  import random
8  import math
9
10
11 def crossover(parent_a: list, parent_b: list, num_of_sessions: int,
12               population_size: int) -> list:
13     """Crossover parents to produce offspring.
14
15     Args:
16         parent_a (list): The first selected parent.
17         parent_b (list): The other selected parent.
18         num_of_sessions (int): How many lesson sessions are needed to
19             make up
20             the timetable.
21         population_size (int): The size of the population.
22
23     Returns:
24         list: The offspring.
25     """
26     # print("Producing offspring...") TODO: add back
27     offspring = []
28     half_pop = math.ceil(population_size / 2)
29     for i in range(half_pop):
30         # locus_outer: session that contains the split
31         locus_outer = random.randint(0, num_of_sessions - 1)
32
33         # locus_inner: split after session[locus_inner]
```

```

33         if locus_outer == 0:
34             locus_inner = random.randint(1, 2) # TODO: hard coding fix
35             ?
36         else:
37             locus_inner = random.randint(0, 2) # TODO: hard coding fix
38             ?
39
40         # Crossover of child a
41         left_a = parent_a[:locus_outer]
42         centre_a = parent_a[locus_outer][:locus_inner] + \
43             parent_b[locus_outer][locus_inner:]
44         right_a = parent_b[locus_outer + 1:]
45         left_a.append(centre_a)
46         child_a = left_a + right_a
47         offspring.append(child_a)
48         print(child_a) # TODO remove
49
50         # Crossover of child b
51         left_b = parent_b[:locus_outer]
52         centre_b = parent_b[locus_outer][:locus_inner] + \
53             parent_a[locus_outer][locus_inner:]
54         right_b = parent_a[locus_outer + 1:]
55         left_b.append(centre_b)
56         child_b = left_b + right_b
57         offspring.append(child_b) # TODO remove
58
59         # Remove last child if the population size is an odd number
60         if half_pop != math.floor(population_size / 2):
61             del offspring[-1]
62
63         # print("Offspring produced.") TODO: add back
64         return offspring

```

## A.7 mutation.py

```

1 """Phase 5 (mutation) of genetic algorithm.
2

```

```

3 Functions:
4     mutate(offspring_in: list, time_slots: list, rooms: list, sessions:
      list,
5         mutation_chance: int) -> list
6 """
7 import random
8
9
10 def mutate(offspring_in: list, time_slots: list, rooms: list, sessions:
      list,
11         mutation_chance: int) -> list:
12     """Chance for offspring to mutate.
13
14     Args:
15         offspring_in (list): The pre-mutation offspring.
16         time_slots (list): The list of time slots.
17         rooms (list): The list of rooms.
18         sessions (list): The list of sessions.
19         mutation_chance (int): The chance of mutation.
20
21     Returns:
22         list: List of mutated offspring.
23     """
24     # print("Mutating offspring...") TODO: remove probably
25     mutation_count = 0
26     offspring = offspring_in
27     for solution in offspring:
28         for session in solution:
29             for i in range(3):
30                 mutate = random.randint(1, mutation_chance)
31
32                 # Mutation does occur
33                 if mutate == 0:
34                     mutation_count += 1
35                     match i:
36
37                         # Mutation of time slot

```

```

38         case 0:
39             new_time_slot = random.choice(time_slots)
40             offspring[solution][session][0] =
new_time_slot
41
42         # Mutation of room
43         case 1:
44             new_room = random.choice(rooms)
45             offspring[solution][session][1] = new_room
46
47         # Mutation of session
48         case _:
49             new_session = random.choice(sessions)
50             offspring[solution][session][2] =
new_session[0]
51             offspring[solution][session][3] =
new_session[1]
52             offspring[solution][session][4] =
new_session[2]
53         # print("Offspring mutated. " + str(mutation_count) +
54         #       " mutation(s) occurred.") TODO remove probably
55         return offspring

```