

## 24V Sleeve bearing cooling fan 60x60x15mm

**Specifications** 

Size: 60 x 60x 15mm

Motor: Brushless DC, auto restart Impedance & polarity protected

Impellers & frame: Glassfibre reinforced thermoplastic

PBT UL94V-0

Insulation resistance: Min. 10M at DC 500V Dielectric strength: 500VAC/1 sec. max. leakage

500 micro amp

Permissible temperature range: Ball bearing -20°C to +75°C

Sleeve bearing -10°C to +50°C


Safety: UL>CUL>CE


Life expectancy at 40°C: Ball bearing 50000 hr.


Sleeve bearing 30000 hr.



Order code: 37-0661







| Order<br>code | Rated<br>voltage<br>(VDC) | Startup<br>voltage<br>VDC | Current<br>amp<br>(A) | Speed<br>(rpm) | Airflow<br>(CFM) | Static<br>pressure<br>(inch-H <sub>2</sub> O) | Noise<br>level<br>(dB-A) | Weight<br>(g) |
|---------------|---------------------------|---------------------------|-----------------------|----------------|------------------|---|--------------------------|---------------|
| 37-0661       | 24.00                     | 10.00                     | 0.10                  | 4500           | 16.60            | 0.15  | 31                       | 42.00         |