Hospital Directory API
Version 1.2 -- Proposed Additions

Three requests to extend the OpenAPI v1.1 contract currently in production. Each has been built and verified against our reference mock; none has been tested against the real server yet.

Document	Technical requirements, v1.2
Source repository	https://github.com/aidepartmentrah-pixel/RESTful-API-Integration
Spec file	Hospital_Directory_API_OpenAPI_v1.2.yaml (attached separately)
Generated	4 November 2026
Status	Internal proposal -- not yet submitted to / accepted by the vendor

Contents

Conventions that apply to every requirement
1. Proposed addendum to OpenAPI v1.1 — father-name candidate lookup
2. Proposed addendum to OpenAPI v1.1 — worker section/administration names
3. Proposed new endpoint — live ER visit roster (for HCopilot)

Conventions

Apply to every requirement below

- Auth: `X-API-Key` header. Missing or invalid key returns `401 UNAUTHORIZED`.
- Error body: `{"error": "<CODE>", "message": "<text>"}`. Codes used: `UNAUTHORIZED` (401), `VALIDATION_ERROR` (422), `SERVER_ERROR` (500).
- A search with no matches returns `200` with an empty list, never `404`.
- All IDs are strings, even when stored as numbers.
- Display names use the English value when stored, otherwise the Arabic value.
- `Content-Type: application/json; charset=utf-8`. Arabic text must arrive as valid UTF-8; we have seen Arabic arrive garbled from the current API, so please verify this on each new endpoint.
- Read-only. No write endpoints are requested.
- Everything not listed in this document is unchanged from v1.1.

Requirement 1

Father-name candidate lookup — `GET /patients/father-names`

> **Why:** To find a patient, HCAT currently tries up to 32 common father names one by one against `GET /patients`. This endpoint replaces the guessing with a single lookup.

Returns the distinct father names on file for a first + last name pair. It does not return patient records: once the user picks a father name, the caller uses the existing `GET /patients` with all three names.

Parameters

Name	Required	Rule
`first_name`	Yes	Non-blank (whitespace-only is rejected). Case-insensitive substring match on the Arabic or English column, same as `/patients`.
`last_name`	Yes	Same rule as `first_name`.
`limit`	No	Integer 1..200, default 50.

Response — `200 OK`

```
{
  "success": true,
  "first_name": "عباس",
  "last_name": "زهرالدين",
  "candidates": [
    {"father_name": "محمد", "patient_count": 20},
    {"father_name": "حسن", "patient_count": 20},
    {"father_name": "أحمد", "patient_count": 1}
  ],
  "total_candidates": 3
}
```

Rules

- One entry per distinct, non-blank father name. `patient_count` = number of records with that exact first + father + last combination.
- Order: `patient_count` descending, then `father_name` alphabetically, so the list is identical between calls.

- `total_candidates` = number of distinct candidates **before** `limit` is applied (lets the UI show "showing 50 of 120").
- No `patient_id` or other patient fields in the response.

Errors

`401` bad key | `422` missing/blank `first_name` or `last_name`, or `limit` out of range | `500` server error

Requirement 2

Worker section and administration names — `Worker` in `GET /workers` and `GET /workers/{employee_id}`

> **Why:** `section_id` and `administration_id` are always `null` today, and an ID alone means nothing outside your system. HCAT users cannot tell which section or administration a worker belongs to.

Two parts, both on the existing `Worker` object:

- **Populate** the existing `section_id` and `administration_id` fields from the HR application.
- **Add** the resolved display names, the same way `department_name` is already resolved from `department_id`.

Field	Type	Value
`section_name`	string, nullable	Name resolved from `section_id`. `null` if the ID is null or cannot be resolved.
`administration_name`	string, nullable	Name resolved from `administration_id`. `null` if the ID is null or cannot be resolved.

No change to parameters, pagination or errors.

Requirement 3

Live ER visit roster (for HCopilot) — `GET /er/current-visits`

> **Why:** HCopilot nurses currently search for each ER patient by hand before starting a handover. A live roster lets them pick from a list. Today the roster only exists on the ER web page (`meraj:8080`), which has no JSON API.

Returns every patient currently in the ER. Please expose it with the same host, auth and conventions as the Directory API; the exact path is your choice.

Request

No parameters. `X-API-Key` auth. **No pagination:** every call returns the complete list. HCopilot detects departures by comparing `er_visit_id` sets between polls, so a partial page would make patients look departed. ER headcount is dozens, not thousands.

Response — `200 OK`


```
{
  "success": true,
  "items": [
    {
      "er_visit_id": "48213",
      "first_name": "عباس",
      "father_name": "محمد",
      "last_name": "زهرالدين",
      "arrival_time": "2026-09-18T14:32:00+03:00",
      "gender": null,
      "age": null,
      "chief_complaint": null
    }
  ],
  "total": 1
}
```


Fields

Field	Format	Notes
`er_visit_id`	string, required	Stable for the whole visit. Used as the comparison key.
`first_name`, `father_name`, `last_name`	string	Plain values. No Arabic/English split needed.
`arrival_time`	ISO-8601 with offset	**One** combined field (the ER page currently splits it into date and time).
`gender`	string or null	Open item: which values?
`age`	integer or null	Open item: `birth_date` preferred (age goes stale).
`chief_complaint`	string or null	Open item: a coded value is preferred over free text.

Rules

- Order: `arrival_time` ascending (earliest first), stable between polls.
- `total` = number of items.
- Not requested: `doctor_name` (always empty in practice); bed, triage time and departure time (HCopilot manages these itself).

Please confirm

- Is “creation time” the arrival time, and which timezone is it written in (we assume UTC+3)?
- Which values `gender` will contain.
- Whether `birth_date` can be returned instead of `age`.
- Whether `chief_complaint` is coded or free text.
- That the ordering can be guaranteed, and that UTF-8 is correct on this endpoint.