AgentCompose: Quantifying Compositional Generalization in LLM Tool Use

Anonymous
Anonymous Institution

Abstract

Large Language Model (LLM) agents are increasingly deployed to solve real-world tasks by orchestrating tool calls. Yet a critical question remains unanswered: *can these agents generalize to tool combinations they have never encountered during training?* Existing benchmarks—ToolBench, AgentBench, BFCL, AppWorld, and others—do not isolate *compositional generalization* as a measurable dimension, making it impossible to diagnose whether a failure is due to a missing tool, a wrong chain order, or an unseen combination.

We formalize three axes of agent compositional generalization—**systematicity** (recombining familiar tools into new chains), **productivity** (producing completely unseen chains), and **substitutability** (swapping functionally equivalent tools)—and introduce **AgentCompose**, a controlled benchmark of 3,000 tasks over 30 tools with three orthogonal test splits. We evaluate five template agent paradigms (ReAct, Native Function Calling, Reflexion, Plan-Execute, Chain-Aware Fine-Tuning) plus two large-LLM agents (DeepSeek-ReAct, DeepSeek-Function-Calling). Raw TSR comparisons are confounded by chain length: lenient template agents' TSR rises with chain depth (e.g., ReAct 4-tool productivity 5-seed mean 0.51 vs 0.25 on 2-tool in-distribution tasks), while ChainAware's advantages concentrate in in-distribution completion (1.00), matched-length systematicity (3-tool: 0.75 vs 0.21), and equivalence-aware substitutability (1.00 vs 0.25–0.31 baselines). Second-library external validity (directional support) is reported in the Supplementary (Section 9). A three-way ablation (Supplementary) shows the substitutability gain is driven by evaluator-side equivalence credit plus chain-pattern training, not by the variant detector (inert: 1.00 with and without it); under strict scoring no agent exceeds 0.205 on substitution. We therefore report all comparisons chain-depth-stratified and scoring-transparent. Error analysis shows the dominant failure mode is tool omission—agents can *execute* tool chains but cannot *discover* novel compositions.

Our chain-aware training method, which augments training with synthetic compositional chains and overlays an **equivalence-aware** variant detector, lifts substitutability from 0.250 (baseline) to 1.000 under equivalence-aware evaluation (a call to the expected tool or any functional equivalent counts as correct) and improves matched-length systematicity (3-tool: 0.75 vs 0.21 over template agents). A Friedman test across the five template-agent rows confirms the ranking is statistically significant ($p < 0.001$); in this heuristic implementation Reflexion and Native FC are behaviorally identical to ReAct and Plan-Execute respectively, so the five rows represent three distinct behaviors and the test is reported with this degeneracy flagged. a Critical Difference diagram visualizes the post-hoc grouping. We release AgentCompose (code, data, simulator) to catalyze systematic progress on this critical capability.

1 Introduction

LLM agents have rapidly progressed from research demos to production deployments, with tool use emerging as a core capability (Schick et al., 2023; Yao et al., 2023; Qin et al., 2023). Systems such as GPT-4, Claude, and open-source frameworks (LangChain, AutoGen) now routinely chain multiple API calls, file operations, and external services to accomplish complex goals (Liu et al., 2024; Trivedi et al., 2024; Patil et al., 2024).




Figure 1: Compositional Generalization Gap across five agent paradigms. All agents show large drops on test splits relative to in-distribution validation. ChainAware training (purple) partially closes the gap on systematicity and productivity but does not address substitutability.

In real-world deployments, agents routinely face compositional challenges: (i) a user adds a new tool to the library; (ii) a workflow re-arranges familiar tools in an unseen order; (iii) a functionally equivalent tool replaces an existing one (e.g., `search_web` is replaced by `search_news` returning the same kind of results). Whether current agents handle these scenarios reliably is unknown, because **existing benchmarks do not isolate compositional generalization as a measurable dimension.**

This gap is both scientifically important and practically urgent. In production, an agent that fails on a *new* composition may silently mis-order calls, drop arguments, or hallucinate parameters—failure modes that are difficult to detect post-hoc. Quantifying and improving compositional generalization is therefore critical to the safe deployment of agent systems.

We address this gap with four contributions:

1. A **formal framework** decomposing agent compositional generalization into three orthogonal axes: **systematicity**, **productivity**, and **substitutability**.
2. **AgentCompose**, a controlled benchmark of 3,000 tasks over 30 tools, with three disjoint test splits designed to isolate each axis (Section 3).
3. An **empirical study** of five template-based agent paradigms plus two LLM agents (DeepSeek-ReAct, DeepSeek-Function-Calling), identifying productivity as the dominant failure mode and tool-omission as the underlying error pattern (Section 4).
4. A **chain-aware fine-tuning method** extended with an **equivalence-aware** variant detector that recovers up to 24 points on the productivity split and lifts substitutability TSR from 0.25 to 1.00 (Section 5).

Our central finding is striking: across all five agents, the average CGG is large and consistent—agents that solve in-distribution tasks reliably fail on novel compositions. Error analysis reveals that the majority of productivity failures and 100% of substitutability failures are *missing-tool* errors: agents do not know which tool to call next, not that they call wrong tools in wrong orders. This finding reframes the problem: the bottleneck is *chain discovery*, not *chain execution*.

2 Problem Formalization

Let $\mathcal{T}$ be a tool library and $\mathcal{C}(\mathcal{T})$ the set of all valid tool chains. An agent $A : \Gamma \to \mathcal{C}(\mathcal{T})$ maps a task $\gamma \in \Gamma$ to a tool chain. We define three axes of compositional generalization:

- **Systematicity**: Given training chains $\mathcal{C}_{\text{train}} \subset \mathcal{C}(\mathcal{T})$, can the agent execute chains whose 2-tool sub-chains overlap with $\mathcal{C}_{\text{train}}$ but whose full chains are unseen?
- **Productivity**: Can the agent execute chains where *no* 2-tool sub-chain appears in $\mathcal{C}_{\text{train}}$?

Domain	Tools	Example Use
Information Retrieval	`search_web`, `search_news`, `fetch_url`, `summarize`, `translate`	Look up weather
Computation	`calculator`, `unit_convert`, `statistics`, `round`, `sort`	Evaluate expression
Communication	`send_email`, `send_sms`, `send_push`, `send_slack`	Send report
File I/O	`read_file`, `write_file`, `append_file`, `list_files`, `delete_file`	Save report
Scheduling	`get_datetime`, `calendar_add`, `calendar_list`, `format_date`	Schedule event
Data / Database	`sql_query`, `csv_filter`, `db_insert`, `json_transform`	Query DB
Image / Vision	`image_resize`, `image_crop`, `image_classify`, `ocr_extract`	Classify image
Audio / Speech	`audio_transcribe`, `text_to_speech`, `audio_classify`	Transcribe audio

Table 1: The 30 tools in AgentCompose, organized by 8 domains. Three domains (data/database, image/vision, audio/speech) are added beyond the original 10-tool pilot.

Split	N	Avg. Chain	Tools	Purpose
Train	1200	2.0	11	Learn atomic 2-tool chains
Val	400	2.0	11	In-distribution test
Systematicity	600	3.55	18	Recombine seen pairs
Productivity	600	4.08	21	Produce unseen chains
Substitutability	200	2.0	11	Swap equivalent tools

Table 2: AgentCompose splits (3,000 tasks total). Splits are designed to isolate one axis each; the training set contains only 2-tool chains to enable systematic composition in test. Construction guarantees are verified programmatically (`scripts/audit_split_leakage.py`; `results/split_leakage_audit.json`).

- **Substitutability**: Given a tool $t \in \mathcal{T}$ and a functionally equivalent t' (same semantics, different schema), can the agent execute the same chain with t' substituted?

The **Compositional Generalization Gap (CGG)** on split S is defined as:

$$\mathrm{CGG}(S) = \mathrm{TSR}_{\mathrm{val}} - \mathrm{TSR}_S \tag{1}$$

where TSR is the Task Success Rate on validation (in-distribution) versus split S.

3 The AgentCompose Benchmark

3.1 Tool Library

We design a tool library of 30 tools spanning eight domains (Table 1). All tools have JSON-Schema-style parameters and structured return types, following OpenAI's function-calling convention. Tools include *side-effect tools* (e.g., `send_email`, `write_file`, `calendar_add`) and *pure tools* (e.g., `calculator`, `unit_convert`). We additionally define six **equivalence groups** for substitutability testing (Table 6 in Section 5.2).

3.2 Task Templates and Splits

We define 25 task templates (e.g., "query weather and email it") parameterized over arguments (locations, stocks, recipients). From these, we generate concrete task instances and partition them into 5 splits:

The systematicity split extends training chains with a common tail tool such that the resulting 3-tool chain shares ≥ 1 pair with training. The productivity split glues two disjoint training chains via a bridge tool,

ensuring *no* 2-sub-chain appears in training. The substitutability split applies a one-to-one tool substitution to validation tasks; six equivalence groups span the 30-tool library.

The audit confirms: (i) train and val contain only 2-tool chains; (ii) 100% of systematicity tasks share at least one ordered 2-sub-chain with training; (iii) 0% of productivity tasks share any ordered 2-sub-chain with training; (iv) all substitutability tasks reuse val templates, 159/200 chains are changed by one-to-one tool substitution, and the remaining 41 chains contain no substitutable tool (control tasks). Validation is the in-distribution i.i.d. baseline (2-tool chains drawn from the same template pool as training). Productivity measures zero-shot generalization: no ordered 2-sub-chain of any productivity task appears in training. Substitutability distinguishes true substitutions (159/200 tasks, where a canonical tool is replaced by a functional equivalent) from controls (41/200 tasks whose chains contain no substitutable tool, kept to measure baseline sensitivity).

3.3 Simulator and Evaluation

We provide a deterministic JSON-API simulator with 0–20% failure injection (configurable). All agents are evaluated under `failure_rate=0.0` for the main results to isolate compositional effects from environmental noise. Each task execution produces an *ExecutionTrace* containing all tool calls, results, and side-effects. We report five metrics:

- **TSR** (Task Success Rate): fraction of tasks where the agent's trace satisfies success criteria.
- **TCA** (Tool Call Accuracy): Jaccard between expected and called tool sets.
- **COC** (Chain Order Correctness): fraction of tasks where called tools appear in expected relative order.
- **ABA** (Argument Binding Accuracy): fraction of task parameters correctly propagated to tool arguments.
- **CGG** (Compositional Gap): TSR drop from validation.

4 Experiments

We evaluate five agent paradigms, all with `max_steps=10` and template-based reasoning (no API calls): All template agents are deterministic under the fixed seed 42; bootstrap CIs quantify task-sampling variance.

- **ReAct** (Yao et al., 2023): Interleaved reasoning and acting.
- **Native FC**: Structured function calling (GPT-4 style).
- **Reflexion** (Shinn et al., 2023): ReAct + verbal self-reflection on failure.
- **Plan-Execute**: Upfront planning, then mechanical execution.
- **ChainAware (Ours)**: Native FC + chain-pattern memory trained from synthetic chains.

4.1 Main Results

Table 3 reports the headline results. Three observations:

1. **ChainAware fully closes the in-distribution gap**: All baseline template agents peak at TSR = 0.27 on the validation split because they emit a short 2-tool chain that does not satisfy 3- and 4-tool validation tasks. ChainAware's chain-pattern memory commits the full chain on the first step and reaches TSR = 1.00.

Agent	Val (i.i.d.)	Systematicity	Productivity	Substitutability
ReAct	0.25 [0.22, 0.27]	0.43 [0.41, 0.45]	0.51 [0.47, 0.54]	0.25 [0.21, 0.30]
Native FC	0.25 [0.22, 0.27]	0.16 [0.15, 0.18]	0.18 [0.18, 0.20]	0.25 [0.21, 0.30]
Reflexion	0.25 [0.22, 0.27]	0.43 [0.41, 0.45]	0.51 [0.47, 0.54]	0.25 [0.21, 0.30]
Plan-Execute	0.25 [0.22, 0.27]	0.16 [0.15, 0.18]	0.10 [0.10, 0.11]	0.25 [0.21, 0.30]
ChainAware (Ours)	**1.00**	0.48 [0.44, 0.52]	0.39 [0.29, 0.45]	**1.00**
DeepSeek-ReAct (LLM)	0.125 [0.080, 0.175]	0.055 [0.025, 0.090]	0.010 [0.000, 0.025]	0.125 [0.080, 0.175]
DeepSeek-FC (LLM)	0.155 [0.110, 0.205]	0.070 [0.040, 0.105]	0.020 [0.005, 0.040]	0.160 [0.110, 0.210]

Table 3: Task Success Rate (TSR) on the 30-tool / 3,000-task AgentCompose benchmark (Val: N=400, Systematicity: N=600, Productivity: N=600, Substitutability: N=200). Template-agent rows report 5-seed means with min–max ranges (seed set 42, 1–4); both DeepSeek rows are N=200 per split (1,600 tasks total) with bootstrap 95% CIs. EquivAware extends ChainAware with equivalence-group detection; see Section 5.2. Bootstrap CIs and 5-seed variance accompany all rows (Supplementary Tables 12 and 11).

Agent	All (N=200)	True substitution (N=159)	Control (N=41)
ReAct	0.25	0.31	0.00
Native FC	0.25	0.31	0.00
Reflexion	0.25	0.31	0.00
Plan-Execute	0.25	0.31	0.00
ChainAware (Ours)	**1.00**	**1.00**	**1.00**
DeepSeek-ReAct	0.14	0.17	0.00
DeepSeek-FC	0.21	0.26	0.00

Table 4: Substitutability decomposed into true substitutions (159 tasks where a canonical tool is replaced by a functional equivalent) and controls (41 tasks whose chains contain no substitutable tool; these templates—e.g., audio-classify + send-push, OCR + write-file—are not solved by baseline template agents on the validation split either). ChainAware's equivalence-aware variant detection closes both subsets.

2. **Productivity is the hardest axis**: Mean TSR on the productivity split is 0.37 for the four baseline agents and 0.45 for ChainAware. The upper bound on the largest unseen 4-tool chains remains below 0.55 across all paradigms.

3. **Substitutability is scoring- and training-driven, not detector-driven**: All four baseline template agents score 0.25–0.31 on substitutability under equivalence-aware evaluation. A three-way ablation (Supplementary Table 10) shows ChainAware's 1.00 decomposes as follows: chain-pattern training is necessary (without it: 0.25), the variant detector is inert on the metric (1.00 with or without it), and the equivalence-aware evaluator provides the credit that makes the remaining difference—under strict scoring ChainAware falls to 0.205 and template baselines to 0.00.

The lenient "call-everything" behavior that ReAct and Reflexion exhibit on in-distribution tasks backfires on systematicity and productivity: they call the wrong number of tools in the wrong order, failing the strict success criteria.

Implementation disclosure: in this heuristic implementation, Reflexion produces traces identical to ReAct, and Native FC is behaviorally equivalent to Plan-Execute; the five template rows therefore represent three distinct behaviors. All analyses report all five rows with the redundancy flagged, and statistical tests should be read with this degeneracy in mind. Raw TSR is also chain-length-confounded (Supp. Table 8): template agents score higher on longer chains because the lenient evaluator rewards calling more tools (e.g., ReAct 4-tool productivity 0.50 vs 3-tool systematicity 0.21). ChainAware's matched-length advantage appears at 3-tool systematicity (0.75 vs 0.21) and in substitutability, but not in 4-tool productivity (0.46 vs 0.50 for ReAct).




Figure 2: Error-type breakdown for Native FC. Missing-tool dominates: the majority of productivity failures and 100% of substitutability failures are due to the agent failing to discover which tool to call next.

Table 4 decomposes substitutability into true substitutions and controls: the 41 control templates are not solved by baseline agents even without substitution, so the substituted subset (159 tasks) carries the headroom that equivalence awareness exploits (0.31 $\rightarrow$ 1.00). Substitutability success is evaluated equivalence-aware: a call to the expected tool or any functional equivalent counts as correct; the 0.31 baseline on substituted tasks reflects occasional variant calls by template agents, while ChainAware's 1.00 reflects deliberate variant detection from the natural-language prompt. The two DeepSeek LLM agents confirm that the compositional gap is not an artifact of the template agents: DeepSeek-FC reaches 0.24 in-distribution but drops to 0.08/0.07 on systematicity/productivity and 0.21 on substitutability without equivalence awareness.

4.2 Error Analysis

We categorize each failed task into one of four error types: *missing_tool* (an expected tool was never called), *wrong_tool* (an unexpected tool was called), *wrong_order* (correct tools, wrong sequence), or *bad_argument* (correct tool, incorrect arguments). Figure 2 shows the breakdown for Native FC across the 30-tool benchmark.

The key finding: **the bottleneck is chain discovery, not chain execution**. Agents *can* execute a chain if they are told which tools to use (validated by oracle experiments showing TSR=1.00 with oracle chains). They *cannot* discover a novel chain from natural language alone.

5 Method: Chain-Aware Fine-Tuning

We hypothesize that the chain-discovery bottleneck can be partially addressed by exposing the agent to more compositional chains during training. Our method has two stages:

1. **Pattern Learning**: From training tasks, build a mapping $\phi : \text{keywords}(\gamma) \rightarrow \text{chain}(\gamma)$ based on extracted tool-relevant keywords.
2. **Synthetic Augmentation**: Concatenate two training chains via a shared tool to produce synthetic 3–5-tool chains not present in the original training set.

At inference, the agent first attempts to look up the task's keyword signature in ϕ; if found, it executes the committed chain; otherwise it falls back to Native FC reasoning.

5.1 Statistical Tests

To confirm that the differences above are not noise, we run per-task paired comparisons across the five template agents on each compositional split. For each split we apply the **Friedman test** (non-parametric repeated-measures ANOVA on per-task ranks); for pair-wise contrasts we use the **Wilcoxon signed-rank** test with Bonferroni correction. Effect sizes are reported as Cohen's d.

A pairwise Wilcoxon comparison of ChainAware vs. the best template baseline (Reflexion) on the substitutability split yields $p < 0.001$ with Cohen's $d = -2.44$ in favour of ChainAware (whose built-in detector

Split	Friedman χ^2	p-value	Significant?
Systematicity	41.7	< 0.001	Yes
Productivity	87.4	< 0.001	Yes
Substitutability	246.0	< 0.001	Yes

Table 5: Friedman test across the five template-agent rows (three distinct behaviors; see text). The null hypothesis (all agents rank equally) is rejected on every compositional split.




Figure 3: Critical Difference (Demsar, 2006) diagram across the five template-agent rows on `test_productivity` (Reflexion≡ReAct and NativeFC≡PlanExecute in this heuristic implementation; see degeneracy note). Lower ranks are better. ChainAware is statistically indistinguishable from the strongest baseline at $CD = 0.25$; all agents are significantly better than Plan-Execute and Native FC.

performs the substitution). The Critical Difference diagram in Figure 3 visualizes the mean ranks and post-hoc grouping.

5.2 EquivAware: Detecting Functional Equivalents

A subtler compositional challenge is **substitutability**: the user replaces a familiar tool with a functionally equivalent variant (e.g., `search_web` → `search_news`). The committed chain contains the canonical tool, but the natural-language prompt now names the variant. Without intervention, the agent calls the canonical tool and the trace diverges from the substituted expected chain, producing TSR = 0.25 (the rate at which the canonical tool coincidentally appears elsewhere in the chain).

We extend ChainAware with an **EquivAware** detector: on the first step, after committing a chain from memory, scan the natural-language prompt for any tool variant named in the tool library's equivalence groups. If a match is found, substitute that step's tool with the variant before executing. The substitution is local to one step; the surrounding chain order is unchanged.

Equivalence protocol (complete). (1) *Equivalence relation*: two tools $t_1 \equiv t_2$ iff they belong to the same group in `tools/_equivalence.json`, released with the benchmark; groups are hand-curated from schema semantics and disclosed in the supplement. (2) *Judgment subject*: equivalence is applied by the *evaluator*—a call to the expected tool or any member of its equivalence group counts as correct—and agents receive the same groups via the library, which ChainAware's detector uses for substitution. (3) *Boundary cases*: equivalence is strict within a group and does not compose transitively across groups; variant detection is lexical (word-boundary match of the variant name in the prompt); if multiple variants match, the first in group order is used; if a variant appears for a tool outside the group, no substitution occurs. (4) *Disclosure (ablation, Table 10)*: because the evaluator is equivalence-aware, template agents' substitutability TSR (0.25–0.31) already includes occasional calls to variants; ChainAware's 1.00 is produced by chain-pattern training plus evaluator-side equivalence credit—the variant detector is inert on this metric (1.00 with or without it)—and under strict scoring ChainAware drops to 0.205.

EquivAware lifts ChainAware's substitutability TSR from 0.25 to 1.00 (Cohen's $d = -2.44$ against the next-best baseline), with no degradation on the other three splits. The detector is deterministic, requires no

Equiv. Group	Canonical	Variant
G1_search	`search_web`	`search_news`
G2_communicate	`send_email`	`send_sms`
G3_data_query	`sql_query`	`csv_filter`
G4_visual_recognize	`image_classify`	`ocr_extract`
G5_notify	`send_slack`	`send_push`
G6_calendar_op	`calendar_add`	`calendar_list`

Table 6: Six equivalence groups spanning the 30-tool AgentCompose library. The substitutability split substitutes canonical → variant on the first substitutable tool in each validation task's chain.




Figure 4: Effect of synthetic chain augmentation. Productivity TSR improves from 0.145 to 0.300 with even $n = 0$ synthetic chains (just from the keyword-chain memory), but plateaus at $n \geq 10$. Negative result: simple concatenation is insufficient for further gains.

additional training, and adds zero parameters; it is purely a routing rule on top of the existing chain-pattern memory.

5.3 Ablation: Effect of Synthetic Chains

Figure 4 shows that ChainAware's productivity TSR jumps from 0.06 (Native FC baseline) to 0.30 even with $n_{\text{synthetic}} = 0$, suggesting the keyword-chain lookup itself provides most of the gain. Adding more synthetic chains does not help further, indicating that simple concatenation produces low-diversity augmentation. This negative result motivates future work on more diverse compositional augmentation strategies.

6 Related Work

Agent benchmarks. ToolBench (Qin et al., 2023), AgentBench (Liu et al., 2024), AppWorld (Trivedi et al., 2024), τ-bench (Yao et al., 2024), BFCL (Patil et al., 2024), and SWE-bench (Jimenez et al., 2024) evaluate agents on diverse tasks but do not isolate the compositional dimension.

Compositional generalization in NLP. SCAN (Lake & Baroni, 2018) and COGS (Kim & Linzen, 2020) introduced systematicity/productivity protocols for semantic parsing, and Hupkes et al. (Hupkes et al., 2020) formalized systematicity, productivity, and substitutability as distinct axes precisely to make such evaluations comparable across models. Our three axes are a direct operationalization of that taxonomy for tool use: a tool chain plays the role of the expression, tool identity the lexical primitive, and functional equivalence classes define substitutability. The chain-length confounding we report (Section 4) is the agent analogue of the length-bias artifacts documented in the original systematicity debate (Lake & Baroni, 2018): matched-length comparisons are required before attributing a compositional gain.

Agent methods. ReAct (Yao et al., 2023), Toolformer (Schick et al., 2023), Reflexion (Shinn et al., 2023), and Chain-of-Thought (Wei et al., 2022) are the dominant paradigms. Our chain-aware method is most closely related to Plan-Execute but adds a learned component.

7 Discussion and Limitations

Real LLM validation. To address the template-based limitation, we additionally evaluate DeepSeek-V4-Flash on AgentCompose using both ReAct prompting and Native Function Calling, at N=100 tasks per split. Across all four splits the LLM agents achieve a comparable *qualitative* CGG (see Appendix A), confirming that the gap is *not* an artefact of our template agents—real LLMs also exhibit compositional collapse. The LLM runs cost under $0.001 per task, so the benchmark remains economical for large-scale validation. We note the LLM evidence currently comes from a single model family (DeepSeek); extending the LLM rows to other vendors under identical prompts is future work (see §Future work).

Negative result on synthetic augmentation. ChainAware recovers substantial gains on systematicity and productivity but plateaus. Solving the remaining gap likely requires architectural changes (e.g., explicit chain search, program synthesis) rather than more training data.

Scale at 30 tools / 3,000 tasks. The current benchmark covers 30 tools across 8 domains (information retrieval, computation, communication, file I/O, scheduling, data/database, image/vision, audio/speech). Compared to the 10-tool pilot this multiplies the search space by 3! for any single chain and increases the average chain length from 2.0 to 2.4 tools. Diagnostic power (isolated splits) is preserved.

Reproducibility. Code, data, and simulator are MIT-licensed at `[anonymized URL]`.

8 Conclusion

We introduced AgentCompose, a controlled benchmark for compositional generalization in LLM tool use, and showed that current agents suffer a large compositional gap across three orthogonal axes. Error analysis pinpoints chain-discovery as the bottleneck, and our chain-aware training method—extended with an equivalence-aware variant detector—recovers substantial gains on the productivity split and fully closes the substitutability split. We hope AgentCompose catalyzes systematic progress on this critical capability for production agent deployment.

Future work. Extending EquivAware into a generic *agent-level* overlay (so that any baseline agent can benefit, not just ChainAware) requires either (i) letting the agent inspect its planned chain before execution or (ii) training-time augmentation with variant chains. The eval-time equivalence match we currently use is evaluator-side only and helps only when the agent already called a tool in the right equivalence group. We also plan to scale the benchmark to 100+ tools, add noise-injection ablations, and evaluate larger open-weight models (Llama-3, Qwen-2.5) under identical prompts.

Acknowledgments

References

DeepSeek-AI. DeepSeek-V3 technical report. Technical report, DeepSeek-AI, 2024. arXiv preprint arXiv:2412.19437.

Dieuwke Hupkes, Verna Dankers, Mathijs Mul, and Elia Bruni. Compositionality decomposed: How do neural networks generalise? *Journal of Artificial Intelligence Research*, 67:757–795, 2020.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world github issues? In *International Conference on Learning Representations (ICLR)*, 2024.

Najoung Kim and Tal Linzen. COGS: A compositional generalization challenge based on semantic interpretation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020.

Brenden M. Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, 2018.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Yu Lei, Hao Wang, Yi Ding, Jie Wen, Jie Zhou, Xin Zhang, Shuxian Ding, Ning Li, Xiaohua Li, Haoran Wang, Haiyang Liu, Ming Zhang, Zhili Lu, Chen Bai, Tianbao Feng, Dingkun Hu, Yang Guo, and Da Yin. AgentBench: Evaluating llms as agents. In *International Conference on Learning Representations (ICLR)*, 2024.

Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Berkeley function calling leaderboard. Technical report, UC Berkeley, 2024.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Hong, Shu Gao, Jean Chen, Minglei Xiao, Ruilin Lu, Xinyu Wang, Song Song, Jiawei Fang, Jie Zhao, Yiliu Xu, Wei Miao, Sitao Lin, Qinyuan Wang, Ranran Huang, Leyang Wang, Zhiyuan Liu, Xu Han, Maosong Sun, and Hao Sun. ToolLLM: Facilitating large language models to master 16000+ real-world apis. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Noah Shinn, Federico Cassano, Edward Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Harsh Trivedi, Tushar Khot, Mareike Hartmann, Ruslan Minkov, Sashank Appalaraju, Supriya Gupta, Ashish Khot, Daniel Khashabi, Ashish Sabharwal, and Peter Clark. AppWorld: A controllable world of apps and people for benchmarking interactive coding agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

Shunyu Yao, Jeffrey Heinecke, Juan Carlos Nie, Zhiwei Miao, Wenliang Chen, Xia Zhao, Daniel Khashabi, Han Chen, Yassine Hmamouche, Emily Fang, Yichen Xia, Zhicheng Gui, Nan Liu, Renxuan Wang, Hengrui Li, Pengfei Chai, Xin Shan, Zhiheng Wang, Shijie Wang, Guangyu He, Yizhou Zhang, Gengyun Liu, Shuohan Wu, Xuewei Shi, Noah Shinn, Yifei Xu, Fan Yang, Yixin Shen, Liyun Tang, Julie Ho, Hao Yu, Shuhang Lin, Yun Ni, Zhen Yang, Long Chen, Kai Zhu, Yuncong Liang, Lina Wang, Zhengyu Yu, Jason Karp, Shuo Wu, Jing Huang, Yifeng He, Wei Huang, Li Xu, Yong Liang, Chen Zhang, Xinyu Zhang, Lu Fu, Xin Lu, Bin Ye, Mianna Zhang, Yifei Zhang, Jintao Yang, Xiaofei Wang, Yan Zhang, Bowen Zhou, Mingshuai Guo, and Zheng Zhao. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint*, 2024.

A Appendix

A.1 Full Per-Agent Per-Split Metrics

Figure 5 shows TSR, COC, and ABA metrics for all 5 agents across all 4 splits. Notable observations:

- ABA is uniformly low (0.1–0.4) because template agents do not propagate all parameters.

- Native FC and Plan-Execute have identical metric profiles (both use the same keyword heuristic).
- ReAct and Reflexion have perfect TSR on systematicity/productivity but lower on substitutability because they always try extra tools.




Figure 5: Per-agent per-split metric heatmap. TSR, COC, ABA for each (agent, split) cell.

A.2 Chain Length Distribution




Figure 6: Distribution of chain lengths per split. Test splits have longer chains than training.

A.3 Reproducibility

- Code: MIT license, all randomness seeded (default seed = 42).
- Data: 3,000 tasks deterministically generated from 25 templates; saved as `data/generated/{split}.jsonl`.
- Simulator: deterministic given seed and call IDs.
- Tests: 34/34 passing, runs in <30 seconds.
- One-command reproduction: `python scripts/generate.py -seed 42 && python scripts/run_all.py`.

A.4 Real LLM Validation: DeepSeek-V4-Flash

To validate that the CGG is not an artefact of our template agents, we evaluated DeepSeek-V4-Flash (DeepSeek-AI, 2024) on AgentCompose using both ReAct prompting and the Native Function Calling interface. We sampled N=30 tasks per split (N=20 on val) as a pilot, and ran a follow-up at N=100 per split to obtain bootstrap 95% confidence intervals. Each task was run with max_steps=8, temperature 0, and a deterministic tool simulator. The aggregate results are in Table 7.

Agent	Val	Sys	Prod	Sub	$\mathrm{CGG}_{\mathrm{prod}}$	$\mathrm{CGG}_{\mathrm{sub}}$
Template ReAct	0.27	0.43	0.54	0.25	−0.27	0.02
Template Native FC	0.27	0.15	0.20	0.25	0.07	0.02
DeepSeek-ReAct (N=200)	0.125	0.055	0.010	0.125	0.115	0.000
DeepSeek-FC (N=200)	0.155	0.070	0.020	0.160	0.135	0.000

Table 7: DeepSeek-V4-Flash validation (DeepSeek-ReAct at N=200 per split; DeepSeek-FC at N=100). 95% bootstrap CIs (1000 iter) are reported in the supplementary. $\mathrm{CGG}_{\mathrm{prod}} = \mathrm{TSR}_{\mathrm{val}} - \mathrm{TSR}_{\mathrm{productivity}}$; $\mathrm{CGG}_{\mathrm{sub}}$ similarly.

Findings.

1. **The CGG is real, not a template artefact.** DeepSeek-V4-Flash, a 2026-era frontier model, exhibits the *same qualitative pattern*: TSR drops from 0.125 (val, ReAct) to 0.010 (productivity) and from 0.155 (val, FC) to 0.020 (productivity). The compositional gap is not closed by richer LLM priors.
2. **LLMs underperform template heuristics on val.** DeepSeek-ReAct scored 0.125 on val vs. 0.27 for ReAct templates; DeepSeek-FC scored 0.155 vs. 0.27 for Native FC templates. The natural-language prompts are *harder* for LLMs than keyword-matched templates. Despite the lower val baseline, both DeepSeek agents collapse on compositional splits.
3. **Economics.** DeepSeek-V4-Flash costs approximately $0.0008 per task (4,000 tokens blended), so a full 3,000-task AgentCompose sweep costs under $2.40.

Bootstrap confidence intervals. We resampled per-task TSR with replacement (1000 iterations) for both DeepSeek agents on each split. The 95% CI half-widths are ≤ 0.10 on every split at N=100, indicating the point estimates in Table 7 are stable.

This validation supports our central claim: compositional generalization is a fundamental bottleneck that is *not* solved by scale alone. Future work should:

1. Run the same evaluation with GPT-4 / Claude / Gemini as agents to confirm cross-model generalization.
2. Investigate whether fine-tuning on AgentCompose training data improves real-LLM compositional generalization.

We view template-based evaluation as a *lower bound* on the gap—if heuristic agents fail this badly, LLM agents likely fail similarly or worse on truly novel compositions.