Agent Behavior Regression Testing for Local LLM Systems: Seed Reproducibility and Cross-Model Heterogeneity across 100 Scenarios

Zewen Liu *liuzewen@qlnu.edu.cn*
Qilu Institute of Technology

Abstract

In the tested local cohort, temperature-0 models are nearly perfectly seed-reproducible yet strikingly heterogeneous across models: the cross-model Behavior Drift Score (BDS) is 400× the cross-seed BDS on the same 100-scenario suite. This "behavioral determinism duality" (near-deterministic within model, heterogeneous across models) motivates directly testing the transfer assumption in agent pipelines. We introduce a 100-scenario behavioral regression suite spanning six categories (length compliance, authority bias, multi-agent contagion, tool-use, refusal alignment, multilingual consistency), measure seed reproducibility and cross-model heterogeneity on four local models (deepseek-r1:7b, qwen2.5-coder:7b, qwen2:7b, qwen3:4b) with three seeds per cell at temperature 0 (1,200 cells), and study BDS as a token-distribution proxy; we do not establish a formal consistency theorem for total variation distance. The frozen aggregate outputs report, for the declared 1,200-cell run: mean cross-seed BDS = 0.0173 (all categories except length compliance exactly zero), mean cross-model BDS = 7.15 (paired difference 7.14, 95% CI $[6.80, 7.49]$, $p \approx 4 \times 10^{-18}$). The 12 raw full-run JSONL files are absent from the delivered tree, so these aggregates are not presented as a raw-cell recount. Heterogeneity is category-dependent: tool-use most transferable (BDS 4.48), multilingual most model-specific (BDS 9.42). A 3-agent chain extension on all 20 multi-agent scenarios (960 calls) finds descriptive model-specific differences; it does not establish causal amplification. The candidate package includes the suite, evaluator, analysis outputs and available multi-agent raw outputs.

1 Introduction

LLMs deployed as agents, coordinating with other agents, using tools, or retrieving from memory, are taking an increasing share of production software (Zhao et al., 2023; Liu et al., 2023). Any such deployment rests on two quiet assumptions. The first is *within-model stability*: the same model, given the same input, will produce behavior that is reproducible enough for tests, caching, and auditing to be meaningful. The second is *across-model transferability*: conclusions, guardrails, and regression suites built on one model remain meaningful when the deployment switches to another model of the same or different family. Both assumptions are typically left implicit; neither is routinely measured.

Standard benchmarks (MMLU (Hendrycks et al., 2021), HELM (Liang et al., 2023a), HumanEval (Chen et al., 2021)) measure *capability at a snapshot*. They are deliberately stable in their target dimension and say little about the fine-grained behavioral dimensions that agent

pipelines depend on: length compliance, refusal consistency, multilingual robustness, tool-call formatting, and contagion behavior in multi-agent chains. Prior work has studied model bias and calibration (Guo et al., 2017; Kadavath et al., 2022), memory-driven bias propagation (Zhang, 2026), and multi-agent debate dynamics (Du et al., 2024; Li et al., 2023; Liang et al., 2023b), but the two stability questions above have not, to our knowledge, been measured systematically on a common scenario suite.

This paper provides that measurement. We contribute:

1. **A 100-scenario behavioral regression suite** over six categories: Length (20), Authority (20), Multi-agent contagion (20), Tool-use (10), Refusal alignment (15), and multi-lingual X (15), generated deterministically from a fixed seed and released with the paper.
2. **The Behavior Drift Score (BDS)**: a token-distribution KL-divergence measure over a whitespace tokenizer with a pooled top-K vocabulary, computed symmetrically over all unordered pairs of conditions.
3. **An empirical characterization on four local models**: a manifest-declared design of 4 models $\times$ 100 scenarios $\times$ 3 seeds = 1,200 cells at temperature 0, with frozen aggregate analyses; the 12 raw full-run JSONL files must be restored before a raw-cell recount.
4. **Frozen aggregate findings**: near-perfect seed reproducibility with a single category exception (length compliance), and category-dependent cross-model heterogeneity with tool-use as the most transferable category and multilingual behavior as the most model-specific in this run.

Why this matters. Agent deployments that pin model weights defend against supply-chain changes but not against the two stability failures we measure: a model that cannot reproduce its own behavior cannot be regression-tested, and a regression suite validated on one model may silently be invalid for another. Our results quantify how much behavior changes across seeds and across model families on a common suite, giving deployment teams a concrete number to test against rather than an unmeasured assumption.

2 Related Work

Scope. Capability benchmarks compare models on fixed tasks, while deployment regression testing asks whether the same agent behavior survives seeds and model substitutions. This paper provides that measurement for one local cohort. It does not claim frontier-model drift, temporal drift, semantic equivalence, or causal amplification.

2.1 Snapshot Benchmarks and Longitudinal Measurement

Standard evaluation benchmarks measure capability at a single point in time (Hendrycks et al., 2021; Liang et al., 2023a; Chen et al., 2021). They are not designed to measure consistency of fine-grained behavior across runs or across model versions. Population-level preference signals such as Chatbot Arena (Chiang et al., 2024) aggregate across users and do not isolate behavioral dimensions relevant to agent pipelines. To our knowledge, no prior work runs the same 100 behavioral scenarios across multiple local models with seeded replication and reports both reproducibility and heterogeneity statistics.

2.2 Calibration, Bias, and Memory in Agent Systems

Calibration of model confidence has been studied extensively in classification (Guo et al., 2017) and language models (Kadavath et al., 2022). Prior work in this corpus has shown that evaluator bias propagates across agents through memory (Zhang, 2026), and that communication can shift calibration in multi-agent loops. Our contribution is orthogonal: we fix the pipeline and measure the stability of raw model behavior itself, which is the substrate on which calibration and memory effects operate.

2.3 Agent Dynamics and Multi-Agent Systems

Multi-agent debate and collaboration have been shown to improve factuality in some settings (Du et al., 2024; Li et al., 2023; Liang et al., 2023b) and to introduce consensus and contagion dynamics in others (Park et al., 2023; Zhang, 2026). The scenarios in our M category exercise exactly these dynamics; the reported statistics are single-model measurements of the same prompts, providing a baseline against which multi-agent amplification can later be measured.

3 Method: Behavior Drift Score

3.1 Definition

Let $\mathcal{M}$ be the set of model families under comparison, $\mathcal{X} = \{x_1, \ldots, x_100\}$ the set of canonical scenarios partitioned into categories $C \in \{\mathrm{L}, \mathrm{A}, \mathrm{M}, \mathrm{T}, \mathrm{R}, \mathrm{X}\}$, and $\mathcal{S}$ a set of *conditions* (seed repetitions or model families, depending on the analysis). For each model m, condition s, and scenario x, we record the generated text $r^{(m,s,x)}$.

We tokenize each response with a whitespace tokenizer (lowercased, punctuation-stripped, tokens of length > 1), so that the metric does not depend on any particular model's tokenizer. For each scenario x we build a pooled vocabulary $\mathcal{V}^{(x)}$ of size $K = 10^4$ from the union of tokens across all conditions, and compute per-condition histograms $P^{(m,s,x)}$ over $\mathcal{V}^{(x)}$ with Laplace smoothing $\alpha = 10^{-5}$. The BDS between two conditions s, s' is

$$\mathrm{BDS}\big(P^{(m,s,x)} \,\|\, P^{(m,s',x)}\big) \;=\; D_{\mathrm{KL}}\big(P^{(m,s,x)} \,\|\, P^{(m,s',x)}\big), \tag{1}$$

and for a set of conditions we report the mean over all unordered pairs:

$$\overline{\mathrm{BDS}}(m,x) \;=\; \frac{1}{\binom{|S|}{2}} \sum\nolimits_{s<s'} D_{\mathrm{KL}}\big(P^{(m,s,x)} \,\|\, P^{(m,s',x)}\big). \tag{2}$$

The BDS is non-negative, asymmetric in each pair but symmetric in the averaging, and equals zero only when the two token distributions are identical. It is a distributional measure: it detects changes in *what tokens are emitted*, not changes in *semantic content* with identical token distributions; we discuss this limitation in Section 6.

3.2 Two Stability Quantities

Seed reproducibility (Q1). For each model m and scenario x, we compute $\overline{\mathrm{BDS}}$ over the three seed repetitions ($S = \{0, 1, 2\}$) at temperature 0. Low values indicate that the model reproduces its own behavior; values of exactly zero indicate identical outputs across seeds.

Why three seeds. The choice of $|S| = 3$ fixes the resolution of the seed axis, and we state what it does and does not buy. Three seeds yield $\binom{3}{2} = 3$ unordered seed pairs per cell, hence 3,600 pair-level comparisons over the 1,200 cells. Every cell except the length-compliance category returns $\overline{\text{BDS}} = 0$ *exactly* (Table 2), which is the estimator's zero floor: additional seeds cannot turn an identical-output comparison into a non-identical one, so on those categories the seed axis is resolved as far as BDS can measure it. Where the seed axis is not exactly zero, its magnitude is bounded by the corpus mean 0.0173, which is $7.15/0.0173 = 413$ times smaller than the cross-model mean we are testing against; a larger $|S|$ would move the cross-seed estimate by at most the width of its own pair-level spread, not by two orders of magnitude. What $|S| = 3$ genuinely cannot detect is a seed effect confined to a rarer pair than 1 in 3: such an effect would be attenuated in the per-cell mean over seed pairs that Table 2 reports. Table 2 gives the mean over the three seed pairs only, so this bound is stated as a limitation rather than measured; the maximum over seed pairs is the statistic that would settle it, and we do not report it.

Cross-model heterogeneity (Q2). For each scenario x, we compute $\overline{\text{BDS}}$ over all $\binom{4}{2} = 6$ model pairs using seed 0. High values indicate that the models produce substantially different token distributions on the same scenario; the value is a transferability proxy for regression suites.

3.3 Statistical Protocol

All BDS values are per-scenario. For the paired comparison of cross-model vs. cross-seed BDS we use the Wilcoxon signed-rank test on the per-scenario difference $d_x = \overline{\text{BDS}}_{\text{cross}}(x) - \overline{\text{BDS}}_{\text{seed}}(x)$, with a 95% bootstrap CI ($B = 5{,}000$) on the mean difference. Category-level comparisons use two-sided Mann–Whitney U tests across all $\binom{6}{2} = 15$ category pairs, Bonferroni-corrected to $\alpha' = 0.05/15 \approx 0.0033$. Category means are reported with bootstrap 95% CIs ($B = 5{,}000$). The released evaluator can reproduce the analysis from the corresponding raw-output files. This candidate tree includes the multi-agent raw files and the full-run analysis outputs; the per-cell full-run JSONL files listed in the manifest are missing and must be restored before raw-cell recount.

3.4 Metric Scope and Working Interpretation

BDS is a symmetric KL-style divergence over pooled whitespace-token frequency vectors with top-K truncation and smoothing. It is not a semantic distance and it is not a proof of distributional consistency. For two outputs of length L, the empirical token-disagreement rate concentrates by Hoeffding's inequality, but this does not identify the score with total variation distance: the generation distributions are unobserved, the projection to a pooled top-K vocabulary loses mass, and the stochastic relation between disagreement and the smoothed divergence is not established. We therefore treat any total-variation interpretation as a working hypothesis requiring a separate theorem and validation study.

4 Experimental Setup

4.1 Model Cohort

Four local models served through Ollama at temperature 0:

Label	Model	Size
ds-r1	`deepseek-r1:7b`	7B
coder	`qwen2.5-coder:7b`	7B
qwen2	`qwen2:7b`	7B
qwen3	`qwen3:4b`	4B

All models are instruction-tuned Ollama checkpoints. No hosted model API is used; inference runs on local or remote Ollama runtimes, and remote executions are recorded separately from the main local run. We include two 7B general-purpose models, one 7B code-specialized model, and one 4B model to span both family and scale variation.

4.2 Scenario Suite

The 100 scenarios are partitioned as in Table 1. Scenarios are generated deterministically from a fixed seed (`data/scenarios/canonical.jsonl`, released with the paper), with a system prompt, a user prompt, and an evaluation rubric per scenario. The L and A categories carry evaluation rubrics from prior bias/length audit work; the remaining 60 scenarios are new.

Table 1: **Scenario suite composition.** All 100 scenarios are generated deterministically from a fixed seed.

Category	Scenarios
L length compliance	20
A authority bias	20
M multi-agent contagion	20
T tool-use	10
R refusal alignment	15
X multilingual	15
Total	100

4.3 Cells and Protocol

The run manifest records 4 models × 100 scenarios × 3 seeds = 1,200 cells (one generation per cell), 12 jobs total (one per model–seed pair), with a wall-clock time of approximately 1.7 hours on the local machine. Temperature was set to 0.0000; the seed parameter is therefore a check on determinism (and on sampler nondeterminism) rather than a source of intended diversity. Each job wrote one JSONL line per scenario with the scenario id and the generated text in the upstream design. The manifest and aggregate analyses are present in the candidate tree; the 12 raw full-run JSONL files named by the manifest are absent and are a release blocker.

5 Results

5.1 Seed Reproducibility Is Near-Perfect at Temperature 0

Table 2 reports the mean cross-seed BDS per model from the frozen aggregate. Three of four models are reported as reproducing their outputs across seeds exactly on every scenario in the non-length

categories, and all four models have mean cross-seed BDS below 0.0295. The pooled mean over all models and scenarios is $\overline{\text{BDS}}_{\text{seed}} = 0.0173$.

Table 2: **Seed reproducibility (Q1).** Mean BDS over the three seed pairs at temperature 0, over 100 scenarios per model. Lower is more reproducible; 0.0000 means identical outputs across all three seeds on all scenarios.

Model	Mean cross-seed BDS
deepseek-r1:7b	0.0000
qwen2.5-coder:7b	0.0175
qwen2:7b	0.0295
qwen3:4b	0.0222
Pooled	0.0173

The single exception to exact reproducibility is the L (length-compliance) category: its mean cross-seed BDS is 0.0865 (median 0.0000), while every other category is exactly 0.0000. The aggregate pattern is consistent with length-compliance prompts encouraging long generations that vary across seeds even at temperature 0, but the missing raw full-run cells prevent a cell-level inspection here. We therefore report two levels of reproducibility as aggregate descriptions: exact for directive scenarios, and near-exact with a small distributional spread under length-compliance pressure.

5.2 Cross-Model Heterogeneity Is Large and Category-Dependent

Table 3 and Figure 3 report the mean BDS across the six model pairs for each category from the frozen aggregate. The overall mean is $\overline{\text{BDS}}_{\text{cross}} = 7.15$ (median 7.22), and the paired per-scenario comparison against seed-level BDS has mean difference 7.14, bootstrap 95% CI $[6.80, 7.49]$, Wilcoxon $V = 0.0$, and $p \approx 3.9 \times 10^{-18}$ over $n = 100$ scenarios. These are descriptive paired statistics over shared scenarios, not independent-trial inference. Cross-model differences are roughly two orders of magnitude larger than seed noise in this aggregate.

Table 3: **Cross-model heterogeneity (Q2).** Mean BDS over the six model pairs (seed 0) per category, with bootstrap 95% CIs (B=5,000). T (tool-use) is the most transferable category and X (multilingual) the most model-specific.

Category	n	Mean BDS	95% CI
A authority	20	7.00	$[6.39, 7.60]$
L length	20	7.29	$[7.07, 7.51]$
M multi-agent	20	6.73	$[6.28, 7.15]$
R refusal	15	7.27	$[6.74, 7.80]$
T tool-use	10	**4.48**	$[3.54, 5.38]$
X multilingual	15	**9.42**	$[8.46, 10.39]$
Overall	100	7.15	—

5.3 Category-Level Associations in This Suite

Pairwise two-sided Mann–Whitney U tests over the 15 category pairs (Bonferroni-corrected threshold $\alpha' = 0.0033$) identify the following nominal contrasts: T differs from A ($p < .001$), L ($p < .001$), M




Figure 1: **Cross-model BDS by category.** Tool-use scenarios show the lowest cross-model BDS (most transferable); multilingual scenarios show the highest (most model-specific).




Figure 2: **Behavioral determinism duality.** Cross-seed BDS (within model) is 400× smaller than cross-model BDS, showing that the tested local models are near-deterministic within model and heterogeneous across models in this run.

($p < .001$), R ($p < .001$), and X ($p < .001$); X also differs from A ($p = .0028$) and M ($p < .001$). No other pair reaches the corrected threshold. Tool-use scenarios are thus estimated to be more consistent across models, and multilingual scenarios more model-specific, than the other categories in this suite. Because the 1,200 cells share 100 scenarios, these category contrasts are descriptive rather than independent-trial inference.

The most heterogeneous individual scenarios are X-005 and X-014 (mean model-pair BDS 11.39); the most similar is T-001 (BDS 1.75). The full per-scenario table is released with the data.




Figure 3: **Cross-model heterogeneity by category.** Bars are category means over the six model pairs; error bars are bootstrap 95% CIs. The dashed line is the overall mean (7.15).

5.4 Control Experiments (v2, Remote Ollama Runtime)

Two controls calibrate the BDS magnitude. First, same-seed repetition (10 trials, same prompt, same seed, model qwen3:4b) yields mean BDS 0.030 (cross-seed BDS was 0.017), consistent with temperature-0 outputs being nearly identical across repetitions and with the cross-model BDS 7.15 being two orders of magnitude larger than the available seed-level variation. Second, a random baseline (shuffle tokens of the output) yields mean BDS 0.003, an order of magnitude *smaller* than the same-seed variation, suggesting that the BDS is not driven by random token distance in this control. A semantic BDS via embedding cosine distance was attempted but the remote Ollama embedding endpoint was unavailable (`bds_semantic`=None), so the length-based BDS remains the primary metric; a semantic evaluation is future work.

5.5 Multi-Agent Chain Divergence (Full M-Scenario Suite)

A 3-agent chain protocol on all 20 M scenarios (M-001–M-020), 3 seeds, 4 models; 960 calls total (480 from the original pilot on M-001–M-010, 480 from the cloud extension on M-011–M-020) measures how much a chain of three agents, each receiving the prior agents' outputs, changes behavior relative to a single call on the same scenario. Because temperature is 0, cross-seed BDS is exactly zero in both conditions; the relevant quantity is the single-vs-chain distributional divergence per scenario.

Descriptive result from the available extension files: the 3-agent chain changes behavior on all 20 scenarios in all 4 models. For the extension scenarios M-011–M-020 (cloud runtime, 0 errors, 120 raw responses), the mean single-vs-chain-final length-divergence proxy is 0.57 (deepseek-r1:7b), 0.40 (qwen2.5-coder:7b), 0.12 (qwen2:7b), and 0.15 (qwen3:4b); the chain grew the response in 70%, 67%, 57%, and 0% of scenarios respectively (recomputed by `experiments/multi_agent/analyze_p35_chain_ext.py` from the 12 raw jsonl files, 10 scenarios $\times$ 3 seeds per model). The extension is consistent with the pilot pattern: deepseek-r1:7b and




Figure 4: **Seed reproducibility at temperature 0.** Mean cross-seed BDS per model over 100 scenarios. All models are below 0.03; deepseek-r1:7b is exactly reproducible on all scenarios.

qwen2.5-coder:7b show substantial chain amplification, qwen2:7b shows moderate amplification, and qwen3:4b is the only model where the chain *contracts* the output (0% growth, mean chain-final 1693 vs. single 2000 chars). This is descriptive evidence that multi-agent context materially redistributes local-model behavior across the full M-scenario suite; per-category statistics are the natural follow-up.

6 Discussion

6.1 Implications for Behavioral Regression Testing

Our measurements turn two implicit deployment assumptions into explicit, testable numbers on a local stack. First, a regression suite that runs a model at temperature 0 can expect exact reproduction on directive scenarios, with the caveat that length-compliance prompts induce sampler-level variability even at temperature 0, so regression tests that assert exact string equality should avoid such prompts. Second, conclusions drawn from one model should not be assumed to transfer: mean cross-model BDS is 400× the mean cross-seed BDS on the same suite, and transferability varies by category. Teams that switch a backend model should re-run category-sensitive scenarios (in particular X and R) rather than reusing stale validation results.

6.2 Limitations

1. **Local, single-snapshot cohort.** We measure four local checkpoints at one point in time. Vendor-managed frontier models and temporal snapshots are out of scope for this study; the suite and evaluator are designed to be reusable for such measurements. The four models differ in parameter count (4B vs 7B), family (Qwen vs DeepSeek), and specialization (coder vs general); cross-model differences may reflect size/family confounds rather than model identity alone.

2. **Distributional, not semantic, metric.** BDS detects changes in token distributions, not semantic drift that leaves token distributions unchanged. The R scenarios provide partial mitigation by construction, but a full semantic-drift analysis is future work.
3. **Seed count and pseudo-replication.** Three seeds detect exact determinism and small distributional spread; finer-grained reproducibility analysis would require more repetitions. The 1,200 cells share 100 scenarios as the independent unit; per-cell repetitions within a scenario are not independent, so CIs and p-values should be interpreted as descriptive, not inferential.
4. **Observational, not causal.** The cross-model BDS comparison is observational: models differ simultaneously in architecture, training data, size, and quantization. We report heterogeneity, not its causes; no causal attribution to any single factor is claimed.
5. **Limited null calibration.** A small random-shuffle control gives BDS ≈ 0.003, but it is not a category-wide calibrated null distribution. Absolute magnitudes should be interpreted relative to the cross-seed floor (0.0173), not as an absolute semantic distance.
6. **Multi-agent chain extension.** A 3-agent chain on all 20 M scenarios (4 models, 3 seeds, 960 calls) shows model-specific amplification/contraction. The chain BDS uses a length-divergence proxy (not token-level); per-category statistics and a semantic-divergence evaluator are follow-up work.

7 Broader Impact and Responsible Use

This work is intended to improve regression testing for local agent deployments, not to rank models as generally capable or safe. The BDS metric can expose implementation drift, but it is not a semantic quality or fairness measure. A deployment team should therefore combine it with task-level correctness, safety, and human review before changing a model or a guardrail. Publishing the scenario suite could also reveal brittle prompts or refusal patterns. We avoid releasing credentials or attack tooling, and we scope all recommendations to the tested local checkpoints and scenarios. Claims about future temporal drift, frontier APIs, or causal multi-agent amplification require additional validation and are not made here.

8 Conclusion

On a 100-scenario behavioral regression suite, four local models at temperature 0 are nearly perfectly seed-reproducible (mean cross-seed BDS 0.0173) while being strongly and category-dependently heterogeneous across models (mean cross-model BDS 7.15; paired difference 7.14, 95% CI $[6.80, 7.49]$, $p \approx 4 \times 10^{-18}$). Tool-use behavior is the most transferable category (BDS 4.48) and multilingual behavior the most model-specific (BDS 9.42). These measurements provide a quantitative basis for behavioral regression testing of local agent deployments: pin what you can, re-measure across models what you cannot.

References

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique P. de Oliveira Pinto, Jared Kaplan, Harrison Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Hao Zhang, Banghua Zhu, Michael Jordan, Joseph E. Gonzalez, et al. Chatbot arena: An

open platform for evaluating LLMs by human preference. In *Proceedings of the 41st International Conference on Machine Learning*, 2024.

Yilun Du, Shikun Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint*, 2024.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, 2017.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *International Conference on Learning Representations*, 2021.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Guohao Li, Charles Hammerschmidt, Ken Roumeliotis, Haoming Liu, Xudong Qi, et al. Camel: Communicative agents for "Mind" exploration of large scale language model society. *arXiv preprint arXiv:2303.17760*, 2023.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Xudong Wu, et al. Holistic evaluation of language models (HELM). *Transactions on Machine Learning Research*, 2023a.

Tian Liang, Zhiwei He, Chongxuan Tan, Simin Chen, et al. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint*, 2023b.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 2023.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, 2023.

Yuhao Zhang. Memory contagion: Cross-temporal propagation of evaluator bias via agent memory. arXiv preprint arXiv:2606.23195, 2026.

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Ji Xia, Yupeng Zeng, Chong Lv, Shaowei Feng, et al. A survey of large language models. *arXiv preprint arXiv:2303.18223*, 2023.

A Reproduction Protocol

The upstream evidence manifest names 12 full-run JSONL files (`ollama-multi__{model}__seed{0,1,2}.jsonl`), one line per scenario with fields `scenario_id` and `text`. Those files are not present in the delivered candidate tree, so the 1,200-cell raw recount is blocked. The available multi-agent outputs and aggregate analyses are retained. The evaluator (`scripts/bds_evaluator.py`) computes BDS from raw files when they are present; the analysis script (`experiments/analyze_full_run.py`) reproduces Q1/Q2 and the category tables; the supplemental statistics used in this

manuscript are in `experiments/full_run/analysis/full_run_stats_20260813.json` and `category_pairwise_20260813.json`. The scenario generator (`scripts/scenario_generator.py`) reproduces `data/scenarios/canonical.jsonl` from seed 20260711. All scripts run on commodity CPU; the generation run used a local GPU server.

The overlay carrier audit re-executes each frozen receipt against the named artifact and records the result. A number that stops reproducing is a defect in the evidence archive rather than a rounding difference, and the gate names the row that stopped reproducing.

B Scenario Provenance

The L and A scenarios carry the `carried_over_from` field identifying their provenance in prior bias/length audit work. The M, T, R, and X scenarios are new to this suite. The full per-scenario rubrics are included in the released JSONL.

Reproducibility Statement

Available evidence. The scenario suite, BDS evaluator, full-run analysis outputs, multi-agent analysis outputs, and cloud-extension raw JSONL files are present in this candidate tree with SHA-256 records in the overlay evidence manifest. The main 1,200-cell full-run raw JSONL files are listed in the upstream manifest but are absent from the delivered project; raw-cell recount is therefore a publication blocker.

Protocol. The scenario suite is generated from seed 20260711. The analysis scripts are CPU-only Python; Ollama serves the four local checkpoints, and no hosted model API key is required. Exact downstream commands and environment details remain to be pinned to a fresh execution receipt.

Broader Impact and Ethical Considerations

This work studies behavioral regression testing for local LLM agents. The results describe four local checkpoints and must not be used as a model safety ranking or as evidence of frontier-system behavior.

Deployment risk. Passing a regression suite at one checkpoint does not certify that a later checkpoint or a different model family preserves the same behavior. Teams should bind tests to a model digest and re-run category-sensitive scenarios after a model substitution.

Responsible reporting. We preserve missing raw evidence, non-semantic metric limitations, and failed or unavailable controls rather than promoting them into stronger claims. The candidate package does not authorize upload or assert that every manifest entry is present.