

---

# CS2030 Lecture 5

## Generics and Variance of Types

Henry Chia (hchia@comp.nus.edu.sg)

Semester 2 2019 / 2020

# Lecture Outline

---

- Generics
  - Generic type, classes and methods
  - Auto-boxing and unboxing
  - Sub-typing and variance of types
    - ▷ Covariant, contravariant and invariant
  - Wildcards
    - ▷ Upper-bounded and lower-bounded
- Java Collections Framework
  - `Collection` / `List` interfaces
  - `Comparator` interface
- Type erasure

# Creating a Generic Box

---

- Create a `Box` to contain *any* type of object
  - a `static of(..)` method that takes an object as argument and puts it into the box
  - a `get()` method to return the object
- How to define a “generic” `Box` class to hold any object?
  - **abstraction principle**: avoid defining similar classes with duplicate code: `StringBox`, `PointBox`, ...
  - consider declaring the internal object with type `Object` since every other object is an `Object`?
- *Keep in mind this notion of a “box”, as it will come in very handy when discussing certain FP concepts later...*

# A “Generic” Box using Object

```
class Box {  
    private final Object t;  
  
    private Box(Object t) {  
        this.t = t;  
    }  
  
    static Box of(Object t) {  
        return new Box(t);  
    }  
  
    Object get() {  
        return t;  
    }  
  
    @Override  
    public String toString() {  
        return "[" + t + "];"  
    }  
}
```

```
jshell> Box.of("chocolate")
```

```
$.. ==> [chocolate]
```

```
jshell> Box.of("chocolate").get()
```

```
$.. ==> "chocolate"
```

```
jshell> Box.of("chocolate").get().length()
```

```
| Error:
```

```
| cannot find symbol
```

```
|     symbol:   method length()
```

```
| Box.of("chocolate").get().length()
```

```
| ^-----^
```

- Calling method `get()` on a `Box` returns an `Object` type
  - requires an explicitly cast to a “known” compile-time type

```
jshell> ((String) Box.of("chocolate").get()).length()
```

```
$.. ==> 9
```

# Generic Type

*“allows a type or method to operate on objects of various types while providing compile-time type safety”*

- Since Java 5, generics has been added to eliminate the “drudgery of casting”
- Class/interface or method definitions can now include a type parameter section consisting of type parameters  $T_i$  enclosed with angle brackets (e.g.  $< T_1, T_2, T_3, \dots >$ )
- Type parameters can then be used anywhere within the class/interface or method
- Generic typing is also known as **parametric polymorphism**
  - a means to replace type parameters with concrete types when needed

# Generic Classes

- Declare the class **Box<T>** with a generic type parameter T to support parametric polymorphism, e.g. objects of type `Box<String>`, `Box<Object>`, ...

```
class Box<T> {  
    private final T t;  
  
    Box(T t) {  
        this.t = t;  
    }  
  
    T get() {  
        return t;  
    }  
  
    @Override  
    public String toString() {  
        return "[" + t + "];"  
    }  
}  
  
jshell> Box<String> box = new Box<String>("abc")  
box ==> [abc]  
  
jshell> box.get()  
$.. ==> "abc"  
  
jshell> box.get().length()  
$.. ==> 3
```

# Generic Method

- Can also define generic methods with its own type parameter

```
jshell> <T> Box<T> of(T t) { return new Box<T>(t); }  
| created method of(T)
```

```
jshell> Box<String> box = of("abc")  
box ==> [abc]
```

- The scope of type parameter T is within the method
- Use the same idea to define a static method in class Box<T>

```
class Box<T> {  
    private final T t;  
    ...  
    static <T> Box<T> of(T t) { // can replace <T> with <U> also  
        return new Box<>(t);    new Box<T>(t)  
    }
```

- declaration of two type parameters T: one within the class enclosing scope, the other within an inner method scope

# Generic Box Class

```
class Box<T> {  
    private final T t;  
  
    private Box(T t) {  
        this.t = t;  
    }  
  
    T get() {  
        return t;  
    }  
  
    static <T> Box<T> of(T t) {  
        return new Box<>(t);  
    }  
  
    @Override  
    public String toString() {  
        return "[" + t + "];"  
    }  
}
```

```
jshell> Box<String> box = Box.of("abc")  
box ==> [abc]  
  
jshell> box.get()  
$.. ==> "abc"  
  
jshell> box.get().length()  
$.. ==> 3
```



# Auto-boxing and Unboxing

- Only reference types are allowed as type arguments; primitives are auto-boxed/unboxed, e.g. in the case of `Box<Integer>`

```
jshell> Box<Integer> box = Box.of(123)
box ==> [123]
```

```
jshell> Integer x = Box.of(123).get()
x ==> 123
```

```
jshell> int y = Box.of(123).get()
y ==> 123
```

- Placing an **int** value into `Box<Integer>` causes it to be **auto-boxed** into an `Integer` type
- Getting an `Integer` value out of `Box<Integer>` and assigning to an **int** primitive type variable causes the `Integer` return value to be **(auto-)unboxed**

# Variance of Types

- **LSP** re-defined:  $S$  is a **sub-type** of  $T$  (denoted  $S <: T$ ) if a piece of code written for variables of type  $T$  can be used on variables of type  $S$  while ensuring type-safety
- Let  $S <: T$  with simple types  $S, T$  denoting classes/interfaces
  - **covariance**: when subtype relation is preserved in complex types, e.g. **Java arrays are covariant**  $S[] <: T[]$   
Shape  $s = \text{new Circle}(1)$ ; Shape[] shapes = **new** Circle[10];
  - **contravariant**: when subtype relation is reversed for complex types (*more on this later..*)
  - **invariant**: when its neither covariant nor contravariant, e.g. **Java generics are invariant**  
Box<Shape> shapes = **new** Box<Circle>(); // error  
Box<Circle> circles = **new** Box<Circle>(); // ok

# Wildcards

- Due to invariance in generics, the parameterized type can be inferred from the type declaration of the variable, i.e.  
`Box<Integer> box = new Box<Integer>(10);` can simply be  
`Box<Integer> box = new Box<>(10);`
- How do we then sub-type among generic types, in the spirit of  

```
jshell> Box<Integer> box = Box.of(10)
box ==> [10]

jshell> Box<Object> anybox = box
| Error:
| incompatible types: Box<Integer> cannot be converted to Box<Object>
| Box<Object> anybox = box;
```
- Use the wildcard `?`, i.e. `Box<?> anyBox = new Box<Integer>();`
- `?` is not the `Object` type;
  - see what happens when we try: `new Box<?>()` error

- Suppose we have the following classes:

```
jshell> class FastFood { }  
| created class FastFood
```

```
jshell> class Burger extends FastFood { }  
| created class Burger
```

```
jshell> class CheeseBurger extends Burger { }  
| created class CheeseBurger
```

- Define a method to return a Burger from a Box<Burger>

```
jshell> Burger getBurger(Box<Burger> box) { return box.get(); }  
| created method getBurger(Box<Burger>)
```

```
jshell> Box<Burger> box = Box.of(new Burger())  
box ==> [Burger@6093dd95]
```

```
jshell> Burger burger = getBurger(box)  
burger ==> Burger@6093dd95
```

# Upper-Bounded Wildcards

- What other food can be boxed and passed to `getBurger`, `Box.of(new CheeseBurger())` or `Box.of(new FastFood())`?
  - the former since `CheeseBurger` is a `Burger`; however

```
jshell> Box<CheeseBurger> box = Box.of(new CheeseBurger())
box ==> [CheeseBurger@6093dd95]

jshell> getBurger(box)
| Error:
| incompatible types: Box<CheeseBurger> cannot be converted to Box<Burger>
| getBurger(box)
|      ^_^
```

- Let `Burger` form an upper bound of the wildcard — change parameterized type of the argument to `<? extends Burger>`

```
jshell> Burger getBurger(Box<? extends Burger> box) { return box.get(); }
| replaced method getBurger(Box<? extends Burger>)
```

```
jshell> Box<CheeseBurger> box = Box.of(new CheeseBurger())
box ==> [CheeseBurger@5622fdf]
```

```
jshell> Burger burger = getBurger(box)
burger ==> CheeseBurger@5622fdf
```

# Putting Burgers into Empty Boxes

- Now modify the Box class to include the following:

```
class Box<T> {  
    ...  
    private boolean isEmpty() {  
        return this.t == null;  
    }  
  
    static <T> Box<T> empty() {  
        return new Box<>(null);  
    }  
  
    Box<T> add(T t) {  
        return isEmpty() ? new Box<>(t) : this;  
    }  
  
    @Override  
    public String toString() {  
        return "[" + (isEmpty() ? "empty" : t) + "];"  
    }  
}
```

# Putting Burgers into Empty Boxes

- Define a method to put a Burger into a `Burger<Box>`

```
jshell> Box<Burger> putBurger(Box<Burger> box) {  
    ...> return box.add(new Burger());  
    ...> }  
| created method putBurger(Box<Burger>)
```

```
jshell> Box<Burger> emptybox = Box.empty()  
emptybox ==> [empty]
```

```
jshell> Box<Burger> fullbox = putBurger(emptybox)  
fullbox ==> [Burger@53b32d7]
```

- What other types of box can a Burger be added into, `Box<CheeseBurger>` or `Box<FastFood>`?

- the latter, since `Burger` is a `FastFood`; however

```
jshell> Box<FastFood> emptybox = Box.empty()  
emptybox ==> [empty]
```

```
jshell> putBurger(emptybox)  
| Error:  
| incompatible types: Box<FastFood> cannot be converted to Box<Burger>  
| putBurger(emptybox)  
|      ^-----^
```

# Lower-Bounded Wildcards

- Burger now forms a lower bound of the wildcard — change parameterized type of the argument to `<? super Burger>`

```
jshell> Box<? super Burger> putBurger(Box<? super Burger> box) {  
    ...> return box.add(new Burger());  
    ...> }
```

| replaced method putBurger(Box<? **super** Burger>)

```
jshell> Box<FastFood> emptybox = Box.empty()  
emptybox ==> [empty]
```

```
jshell> Box<? super Burger> fullbox = putBurger(emptybox)  
fullbox ==> [Burger@39c0f4a]
```

- Notice that the return type is also `<? super Burger>` since a Burger can also be added to any box that holds food more general than a Burger



# Covariance versus Contravariance

- Let the **complex-type**  $C<T>$  be a class/interface having a simple-type parameter  $T$
- Covariance:
  - **? extends** is covariant since sub-type relation is **preserved** between simple and complex types
  - if  $S <: T$ , then  $C<S> <: C<? \text{ extends } T>$   
 $\text{CheeseBurger} <: \text{Burger} \implies \text{Box}<\text{CheeseBurger}> <: \text{Box}<? \text{ extends Burger}>$
- Contravariance:
  - **? super** is contravariant since the sub-type relation is **reversed** between simple and complex types
  - if  $S <: T$ , then  $C<T> <: C<? \text{ super } S>$   
 $\text{Burger} <: \text{FastFood} \implies \text{Box}<\text{FastFood}> <: \text{Box}<? \text{ super Burger}>$

# Java Collections Framework

- ❑ The Java API provides **collections** to store related objects
- ❑ Interfaces specified as part of the Collections Framework declare common operations that can be performed *generically* on various type of collections

Interface	Description
Collection	The root interface in the collections hierarchy from which interfaces Set, Queue and List are derived.
Set	A collection that does not contain duplicates.
List	An ordered collection that can contain duplicate elements.
Map	A collection that associates keys to values and cannot contain duplicate keys.
Queue	Typically a first-in, first-out collection that models a waiting line; other orders can be specified.

void	<b>add</b> (int index, E element)	Inserts the specified element at the specified position in this list.
boolean	<b>add</b> (E e)	Appends the specified element to the end of this list.
void	<b>clear</b> ()	Removes all of the elements from this list.
boolean	<b>contains</b> (Object o)	Returns true if this list contains the specified element.
E	<b>get</b> (int index)	Returns the element at the specified position in this list.
int	<b>indexOf</b> (Object o)	Returns the index of the first occurrence of the specified element in this list, or -1 if this list does not contain the element.
boolean	<b>isEmpty</b> ()	Returns true if this list contains no elements.
E	<b>remove</b> (int index)	Removes the element at the specified position in this list.
boolean	<b>remove</b> (Object o)	Removes the first occurrence of the specified element from this list, if it is present.
E	<b>set</b> (int index, E element)	Replaces the element at the specified position in this list with the specified element.
int	<b>size</b> ()	Returns the number of elements in this list.
void	<b>trimToSize</b> ()	Trims the capacity of this ArrayList instance to be the list's current size.

- Examples of methods specified in interface `Collection<E>`
  - size, isEmpty, contains, add(E), remove(Object), clear
- Examples of methods specified in interface `List<E>`
  - indexOf, get, set, add(int, E), remove(int),

# The Collection<E> Interface

the values exists in its original form in the list

- **Generic interface** parameterized with a **type parameter E**
- **toArray(T[])** is a **generic method**; the caller is responsible for passing the right type\*
- **containsAll**, **removeAll**, and **retainAll** has parameter type **Collection<?>**, **we can pass in a Collection of any reference type to check for equality**
- **addAll** has parameter declared as **Collection <? extends E>**; **we can only add elements that are upper-bounded by E**

```
public interface Collection<E>
    extends Iterable<E> {
    boolean add(E e);
    boolean contains(Object o);
    boolean remove(Object o);
    void clear();
    boolean isEmpty();
    int size();
    Object[] toArray();
    <T> T[] toArray(T[] a);
    boolean addAll(Collection<? extends E> c);
    boolean containsAll(Collection<?> c);
    boolean removeAll(Collection<?> c);
    boolean retainAll(Collection<?> c);
    :
}
```

*\*otherwise, an ArrayStoreException will be thrown*

# The List<E> Interface

- List<E> interface extends Collection<E>
  - for ordered collections of possibly duplicate objects
  - Classes that implement List<E> include ArrayList and LinkedList, e.g.  
  
List<Circle> circles = new ArrayList<>();  
  
▷ **covariance**:  $S <: T \implies S<E> <: T<E>$
- List<E> specifies a sort method with a default implementation  
**default void** sort(Comparator<? **super** E> c)
- sort method takes as argument an object with a generic interface Comparator<? **super** E> (*why super?*)

# The Comparator<T> Interface

- An implementation of the Comparator<T> interface is required to define the `int compare(T o1, o2)` method
  - `compare(o1, o2)` returns 0 if the two elements are equal, < 0 if o1 is “less than” o2, or > 0 otherwise

```
import java.util.Comparator;
```

```
class NumberComparator implements Comparator<Integer> {  
    @Override  
    public int compare(Integer s1, Integer s2) {  
        return s1 - s2;  
    }  
}
```

```
jshell> List<Integer> nums = Arrays.asList(3, 1, 2);  
nums ==> [3, 1, 2]
```

```
jshell> nums.sort(new NumberComparator())
```

```
jshell> nums  
nums ==> [1, 2, 3]
```

# Type Erasure

- Compiler performs type checking/inference, and generates non-generic bytecode (erasure) for backward compatibility

- type parameters are replaced with either `Object` if it is unbounded, or the bound if it is bounded

```
class Box { // bytecode generated from this "type-erased" version
    private final Object t;
    private Box(Object t) { this.t = t; }
    Object get() { return t; }
    static Box of(Object t) { return new Box(t); }
```

- type arguments are erased during compile time; generics allow the creation of raw types (should be avoided)

```
jshell> Box raw = Box.of("abc") // possible, but bad practice
raw ==> [abc]
```

```
jshell> Box<Integer> box = raw // erasure becomes: Box box = raw
| Warning: unchecked conversion // warning ensues but still compilable
| required: Box<java.lang.Integer>
| found: Box
box ==> [abc] // still runs
```

# Lecture Summary

---

- Appreciate the use of Java generics in classes and methods
- Understand autoboxing and unboxing involving primitives and its wrapper classes
- Understand parametric polymorphism and the sub-typing mechanism, e.g. given `Burger <: FastFood`
  - covariant: `Burger[] <: FastFood[]`
  - covariant: `ArrayList<Burger> <: List<Burger>`
  - covariant: `Box<Burger> <: Box <? extends FastFood>`
  - contravariant: `Box<FastFood> <: Box<? super Burger>`
  - invariant: Neither `Box<Burger> <: Box<FastFood>` nor `Box<FastFood> <: Box<Burger>`
- Familiarity with usage of the Java Collections Framework