

# Style Transferring



UNIVERSITAT POLITÈCNICA  
DE CATALUNYA  
BARCELONATECH



Mireia Gartzia



Cristina González



Itziar Sagastiberri




Carolina Fernández-Pedraza

## Motivation

### Style transferring



### General approaches:




Desired attributes that these do not have:

**Fast (able to work in real time)**      **Arbitrary**

## Characteristics

### Fast and Arbitrary style transfer:



- It takes as inputs of the feed forward network content and style images
- Our network extracts the features from the style images and applies them to the content images

### Tested attributes:


- **Arbitrariness -> Tested**

Trained several styles at the same time and apply them to content images **Arbitrariness tested**

- **Fastness -> Not tested**

Stylization of images rather than real time video from webcam.

## Architecture



- Encoding of content and style images: VGG-19 model layers (up to relu4.1).
- An AdaIN layer is used to perform style transfer in the feature space.
- A decoder is learned (content and style loss computed) to invert the AdaIN output to the image spaces.
- The decoder mostly mirrors the encoder, with all pooling layers replaced by nearest up-sampling to reduce checkerboard effects.

## Results

### Increasing the number of epochs:

2000



7000



### Increasing the style weight:

Content weight: 1  
Style weight: 1e-2




Content weight: 0.7  
Style weight: 0.1




### Changing the training dataset size (2000 epochs)

Datset: 250 images



Datset: 50000 images



(Overfitting)