


Outline of Assignment 4, Part I

Deadlock-free communication



Where?

2 in atom_copy()
2 in atom_move()

} 4 code segments in total

Computation (ns)/communication (μ s-ms) overlap

```
MPI_Irecv()
?
MPI_Send()
MPI_Wait()
```

[discovery ~]\$ ping hpc-transfer.usc.edu
time=0.074 ms
...

Bash Programming

pmd_irecv.sl

```
mpicc -O -o pmd_irecv pmd_irecv.c -lm
counter=0
while [ $counter -lt 3 ]; do
    echo "***** Asynchronous *****"
    mpirun -n $SLURM_NTASKS ./pmd_irecv
    echo "***** Synchronous *****"
    mpirun -n $SLURM_NTASKS ./pmd
    let counter+=1
done
```

Value of a variable

Print to terminal

Input-parameter file `pmd.in` should be in the same directory

mpicc -O -o pmd pmd.c -lm

Evaluate a mathematical expression & stores its result into a variable

See "Bash scripting tutorial for beginners"

<https://linuxconfig.org/bash-scripting-tutorial-for-beginners>

Start programming scripts for your research!

Runtime Fluctuation

- Due to (1) network interference & (2) shared access to computing nodes, measured runtimes will fluctuate
- The latter could be avoided by exclusive access (#SBATCH --exclusive), but **please do not use this** since it will cause very low utilization of computing resources & slow down other users' work

```
***** Asynchronous *****
CPU & COMT = 4.626476e-01 1.115105e-01
***** Synchronous *****
CPU & COMT = 5.080977e-01 1.547345e-01

***** Asynchronous *****
CPU & COMT = 4.822192e-01 1.280804e-01
***** Synchronous *****
CPU & COMT = 4.952592e-01 1.424449e-01

***** Asynchronous *****
CPU & COMT = 4.679100e-01 1.141893e-01
***** Synchronous *****
CPU & COMT = 4.906234e-01 1.389465e-01
```

pmd_irecv.c

pmd.c

Run time:

pmd_irecv

0.471 ± 0.010 s

pmd

0.498 ± 0.010 s

CPU & COMT reports total run time & communication time, respectively


Removing Barrier

Q. Are MPI_Barrier() calls necessary in atom_copy() & atom_move()?

A. Not necessarily. To remove it, however, message tag needs be made unique across neighbors so that messages won't interfere.

- Message passing of *nsd* & *nrc* can be eliminated by enquiring the received message size.**

Receive up to the array size
Neighbor-specific tag
`MPI_Irecv(dbufr, NDBUF, MPI_DOUBLE, MPI_ANY_SOURCE, 120+ku, MPI_COMM_WORLD, &request);`
`MPI_Get_count(&status, MPI_DOUBLE, &doublesReceived);` *Enquire the count of received doubles*
 $3|6 \times nrc$ in atom_copy|move()



**Average 67% reduction
of communication time**

Resource Usage (1)

- Start interactive job on discovery & start a MPI program on one of the allocated computing nodes

```
[anakano@discovery cs596]$ salloc --nodes=4 --ntasks-per-node=4 -t 30
salloc: Nodes d05-[33-36] are ready for job
[anakano@d05-33 cs596]$ mpirun -n 16 ./pmd_irecv
...
```

- In another terminal, log in to another allocated node & type 'top' to see running processes

```
[anakano@discovery cs596]$ ssh d05-34
[anakano@d05-34 ~]$ top
top - 07:42:03 up 47 days, 18:34,  2 users,  load average: 4.37, 3.33, 3.15
Tasks: 315 total,   8 running, 307 sleeping,   0 stopped,   0 zombie

  PID USER      PR  NI    VIRT    RES    SHR S  %CPU  %MEM    TIME+  COMMAND
  3262 rvandamm  20   0 1168000    1.0g  25228 R 100.0   0.5   1090:38 rna_denovo.stat
  3263 rvandamm  20   0 1344840    1.2g  25228 R  99.7   0.6   1090:38 rna_denovo.stat
 23608 anakano   20   0  432324 110840   8660 R  99.7   0.1    0:26.48 pmd_irecv
 23609 anakano   20   0  432332 108808   8672 R  99.7   0.1    0:26.41 pmd_irecv
 23610 anakano   20   0  432324 110856   8676 R  99.7   0.1    0:26.51 pmd_irecv
 23607 anakano   20   0  432328 108732   8604 R  99.3   0.1    0:26.43 pmd_irecv
15225 sgopalan  20   0   11.4g  11.2g   7576 R  99.0   5.9   2072:59 R
19675 telegraf  20   0 1507240  49764  18380 S    0.3   0.0   14:08.81 telegraf
23588 anakano   20   0  164372   2508   1612 R    0.3   0.0    0:00.12 top
     1 root     20   0    43572   3956   2528 S    0.0   0.0    2:02.10 systemd
```

4 instances (ranks) of pmd_irecv are running per node

Resource Usage (2)

- Type '1' (toggle to show detailed core usage): several users (including myself) are not making full use of cores; let others utilize the unused resources by avoiding exclusive access

```
%Cpu0 : 0.0 us, 0.0 sy, 0.0 ni, 99.7 id, 0.0 wa, 0.0 hi, 0.3 si, 0.0 st
%Cpu1 :100.0 us, 0.0 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu2 :100.0 us, 0.0 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu3 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu4 : 76.3 us, 23.0 sy, 0.0 ni, 0.7 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu5 :100.0 us, 0.0 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu6 :100.0 us, 0.0 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu7 : 99.7 us, 0.3 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu8 : 99.7 us, 0.3 sy, 0.0 ni, 0.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu9 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu10 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu11 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu12 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu13 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu14 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu15 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu16 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu17 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu18 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu19 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu20 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu21 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu22 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
%Cpu23 : 0.0 us, 0.0 sy, 0.0 ni,100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
```

17 out of 24 cores unused

Note on Assignment 4, Part II

- Hands-on experience in a common situation of adding new analysis functionality to an existing MPI simulation code, *via* minimally invasive surgery of the code
- Note the header, `pmd.h`, in the homework package, `csci596-as04`, was set for **Part I**:

```
int vproc[3] = {2,2,4}, nproc = 16;
```

The number of MPI ranks should match `nproc` in `pmd.h`:

```
mpirun -n 16 ./pmd (also ./pmd_irecv)
```

- Due to ‘shadow’ analysis ranks, the total number of ranks to be spawned by `mpirun` in **Part II** should instead be twice the number of spatial subsystems, `nproc`, in `pmd_split.c`:

In `pmd_split.h`:

```
int vproc[3] = {2,2,2}, nproc = 8;
```

Run:

```
#SBATCH --nodes=2
```

```
#SBATCH --ntasks-per-node=8
```

```
mpirun -n $SLURM_NTASKS ./pmd_split // $SLURM_NTASKS = 16
```

Note on Assignment 4, Part II

- Input-parameter file, `pmd.in`, needs be edited for part II

```
pmd.in for part I
3 3 3 InitUcell[0|1[2]
0.8
1.0
0.005
1000 StepLimit
1001 StepAvg
```

To measure run time only for
simulation itself, but not for
calculating other quantities

```
pmd.in for part II
5 5 5 InitUcell[0|1[2]
0.8
1.0
0.005
30 StepLimit
10 StepAvg
```

To compute rapidly equilibrating
velocity probability density at
every 10th time steps

Message Composition

- **Multidimensional arrays are sent as one-dimensional arrays**

```
double rv[NMAX][3];  
double dbuf[NDBUF], dbufr[NDBUF];
```

	0	1	2	3	4	5	
dbuf	rv[0][0]	rv[0][1]	rv[0][2]	rv[1][0]	rv[1][1]	rv[1][2]	...

MD world ($md = 1$)

$dbuf[3*i+a] \leftarrow rv[i][a] \ (i = 0, \dots, n-1; a = 0,1,2)$

Send $dbuf[]$

Analysis world ($md = 0$)

Receive $dbufr[]$

$rv[i][a] \leftarrow dbufr[3*i+a] \ (i = 0, \dots, n-1; a = 0,1,2)$

Which Communicator to Use

- Message is sent to a destination rank in a communicator to which the sender also belongs

